



INTERNATIONAL STANDARD ISO/IEC 8613-6:1994
TECHNICAL CORRIGENDUM 1

Published 1998-12-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION
INTERNATIONAL ELECTROTECHNICAL COMMISSION • МЕЖДУНАРОДНАЯ ЭЛЕКТРОТЕХНИЧЕСКАЯ КОМИССИЯ • COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

Information technology — Open Document Architecture (ODA) and Interchange Format: Character content architectures

TECHNICAL CORRIGENDUM 1

Technologies de l'information — Architecture de document ouverte (ODA) et format de transfert: Architecture de contenu de type caractères

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO/IEC 8613-6:1994 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY –
OPEN DOCUMENT ARCHITECTURE (ODA) AND INTERCHANGE FORMAT:
CHARACTER CONTENT ARCHITECTURES**

TECHNICAL CORRIGENDUM 1

1) General

- a) *Replace Line Position Relative by Line Position Forward in clause 4, and in subclauses 8.3, 13.1.11, 13.1.15, 13.1.16, 14.2.1.3.1.6 (two occurrences), 14.2.3, clause 16, and in Tables 3, 8 and C.1.*
- b) *Replace Graphic Character Composition by Graphic Character Combination in clause 4, and in subclauses 8.4, 13.1.2 and 14.2.1.3.1.8, and in Tables 3, 8 and C.1.*
- c) *Replace Partial Line Up by Partial Line Backward in clause 4, and in subclauses 8.3, 13.1.5, 13.1.6, 13.1.11, 14.2.1.2 and 14.2.3, and in clause 16, and in Tables 3, 8 and C.1.*
- d) *Replace Partial Line Down by Partial Line Forward in clause 4, and in subclauses 8.3, 13.1.5, 13.1.6, 13.1.11 and 14.2.3, and in clause 16, and in Tables 3, 8 and C.1.*
- e) *Replace Substitute Character by Substitute in clause 4, and in subclause 13.1.13, and in Table 3.*
- f) *Replace Character Position Relative by Character Position Forward in clause 4, and in subclauses 8.1.7, 13.2.3, 14.2.1.3.1, 14.2.1.3.1.1, 14.2.1.3.1.2, 14.2.1.3.1.3, 14.2.1.3.1.4, 14.2.1.3.1.5 and 14.2.1.3.1.6 (two occurrences), and in Tables 3, 8 and C.1.*

2) Clause 4

Add the following Note at the end of the clause:

NOTE – For historical reasons the acronyms of some control functions do not correspond to their names.

3) Subclause 6.6

Reword the first paragraph as follows:

The graphic character SPACE has a graphical representation consisting of the absence of a graphic symbol. It also indicates a potential line break point (see 14.2.1.3.2).

4) Subclause 6.8.2

In the last sentence of the third paragraph, replace the character SPACE is regarded both as a graphic character and as a control function that indicates by the graphic character SPACE indicates.

5) Clause 6

Add a new clause 6.9 as follows:

6.9 Implementation dependent features

The real effects of presentation features specified by character content architecture attributes are implementation dependent and not defined in ITU-T Rec. T.410-Series | ISO/IEC 8613.

In interchange, if an originator specifies a particular attribute there is no guarantee that the corresponding feature will be presented correctly by the recipient system. The specification of character content attributes is intended to provide capable recipient systems with sufficient information to achieve the correct presentation of corresponding features.

Document application profiles may specify additional support requirements for character presentation attributes defined in this Specification.

NOTE – How an implementation represents a particular imaging feature, or an alternative fall-back feature, is a local matter and is out of the scope of this Specification. Some examples are:

- use of font selection for achieving some forms of emphasis (e.g. ‘weight’, ‘posture’, ‘image inversion’);
- use of an alternative rendition for representing the ‘blinking’ feature in printed text;
- replacement of underlining by a suitable emphasis in those writing systems which do not use a horizontal writing direction;
- selection of a replacement font when the font specified by the originator is not available to the recipient system.

6) Clause 8

Remove Note 1 and replace current Note 2 by:

NOTE – Document application profiles may define additional restrictions on the use of the character features defined in this clause.

7) Subclause 8.1

Remove the Note.

8) Subclause 8.1.3

Remove the Note.

9) Subclause 8.1.4

Remove the Note.

10) Subclause 8.1.5

Remove the Note.

11) Subclause 8.2.2

Remove Note 1, and renumber current Note 2 to 1 and current Note 3 to 2.

12) Subclause 9.2.1

a) *Replace the last paragraph before the Note by:*

The specification of formatting indicator cannot be altered within the content of a basic component.

b) *Replace the Note by:*

NOTE – In interchange, a recipient system can take advantage of this attribute only if it has a character font with the same character width for each character and the same pairwise kerning for each pair of characters.

13) Subclause 13.1.1

Replace the first paragraph by:

A control function which specifies that the active position be moved to the line home position but not be moved in the direction of line progression.

14) Subclause 13.1.3

Replace the first sentence by:

A control function with one optional selective parameter which specifies a subrepertoire of the graphic character repertoire of ISO/IEC 6937.

15) Subclause 13.1.4

Replace the first sentence by:

A control function which specifies that the active position be advanced in the direction of line progression but not be moved in the direction of the character path.

16) Subclause 13.1.5

Replace the first paragraph by:

A control function which specifies either the start of subscript rendition or the end of superscript rendition of graphic characters.

17) Subclause 13.1.6

Replace the first paragraph by:

A control function which specifies either the start of superscript rendition or the end of subscript rendition of graphic characters.

18) Subclause 13.1.11

Replace the first paragraph by:

A control function with one optional selective parameter which specifies either the start or end of a string of graphic characters that are to be imaged in the direction opposite to that of the immediately preceding text (see 7.2.4).

19) Subclause 13.1.12

Replace the first paragraph by:

A control function with one optional selective parameter which specifies a reference to a tabulation stop position in an associated "line layout table" (see 9.1.13).

20) Subclause 13.1.13

Replace the paragraph by:

A control function which specifies the occurrence of a character that has been found invalid or in error.

21) Subclause 13.1.15

Replace the first paragraph by:

A control function with one optional numeric parameter which specifies that the active position be moved in the opposite direction to the line progression the number of SMUs specified by the parameter.

22) Subclause 13.1.16

Replace the first paragraph by:

A control function with one optional numeric parameter which specifies that the active position be moved in the direction of line progression the number of SMUs specified by the parameter.

23) Subclause 13.1.17

Replace the paragraph by:

This is a category of control functions which specify the designation and invocation of graphic character sets. The control functions are defined in ISO/IEC 6429 and their use is defined in ISO/IEC 2022.

24) Subclause 13.2.1

Replace the first sentence by:

A control function which specifies that the active position be moved, in the direction opposite to the character path, a distance specified by the most recent occurrence of either of the control functions Select Character Spacing (SHS) or Set Character Spacing (SCS), if any, or otherwise by the presentation attribute "character spacing".

25) Subclause 13.2.2

Replace the first paragraph by:

A control function with one optional numeric parameter which specifies that the active position be moved in the opposite direction to the character path the number of SMUs specified by the parameter.

26) Subclause 13.2.3

Replace the first paragraph by:

A control function with one optional numeric parameter which specifies that the active position be moved in the direction of the character path the number of SMUs specified by the parameter.

27) Subclause 13.2.4

Replace the first sentence by:

A control function with one optional selective parameter which is placed at the beginning of a line to specify that the line shall not be justified.