

INTERNATIONAL
STANDARD

ISO/IEC
8650-1

Second edition
1996-10-15

AMENDMENT 2
1998-09-15

**Information technology — Open Systems
Interconnection — Connection-oriented
protocol for the Association Control
Service Element: Protocol specification**

AMENDMENT 2: Fast-associate mechanism

*Technologies de l'information — Interconnexion de systèmes ouverts
(OSI) — Protocole en mode connexion applicable à l'élément de service de
contrôle d'association: Spécification du protocole*

AMENDEMENT 2: Mécanisme d'association rapide



Reference number
ISO/IEC 8650-1:1996/Amd.2:1998(E)

Contents

	<i>Page</i>
1) Introduction	1
2) Subclause 2.1	1
3) Subclause 6.3	1
4) New subclause 6.4 <i>bis</i>	1
5) Subclause 7.1.3	2
6) Subclause 7.1.3.1	2
7) Subclause 7.1.3.2	2
8) Subclause 7.1.3.3	2
9) Subclause 7.1.3.4	2
10) Subclause 8.1.2	3
11) Subclause 8.1.3	3
12) Clause 12	3

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Amendment 2 to ISO/IEC 8650-1:1996 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 33, *Distributed application services*, in collaboration with ITU-T. The identical text is published as ITU-T Rec. X.227/Amd.2.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8650-1:1996/Amd.2:1998

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 8650-1:1996/AMD2:1998

INTERNATIONAL STANDARD

ITU-T RECOMMENDATION

**INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
CONNECTION-ORIENTED PROTOCOL FOR THE ASSOCIATION CONTROL SERVICE
ELEMENT: PROTOCOL SPECIFICATION**

**AMENDMENT 2
Fast-associate mechanism**

1) Introduction

Add the following paragraphs:

The fast-associate mechanism allows a session connection, including its embedded presentation connection and application association, to be established using a compressed form of the information that would otherwise be sent on the S-CONNECT exchange. The compressed form, called the upper-layer context identifier, is a reference to an upper-layer context specification, which is a definition of the fields of the application ACSE, presentation and session protocols that would be sent on the full-form connect messages. The upper-layer context identifier may be parameterized to include values for variable fields allowed by the full form protocols for the upper-layers.

Within the ACSE protocol, the addition is the definition of the construction of the User-summary parameter of the P-CONNECT primitives from the semantics of the AARQ fields and the User-summary parameter of the corresponding A-ASSOCIATE primitive.

2) Subclause 2.1

Insert the following references by numerical order:

- ITU-T Rec. X.216 (1994)/Amd.1 (1997) | ISO/IEC 8822:1994/Amd.1:1998, *Information technology – Open Systems Interconnection – Presentation service definition – Amendment 1: Efficiency enhancements.*
- ITU-T Rec. X.217 (1995)/Amd.2 (1997) | ISO/IEC 8649:1996/Amd.2:1998, *Information technology – Open Systems Interconnection – Service definition for the association control service element – Amendment 2: Fast-associate mechanism.*

3) Subclause 6.3

In Table 2, add User Summary to the list of parameters for A-ASSOCIATE request after User Information.

4) New subclause 6.4 bis

Add a new subclause after 6.4:

6.4 bis User summary mechanism

If the fast-associate mechanism is used during association establishment, the initiating ACPM as well as forming an AARQ APDU to be passed to the Presentation service-provider in the User-Data parameter of a P-CONNECT request, also passes the semantic content of the AARQ in the User Summary parameter of the P-CONNECT request. The User

Summary parameter references an Upper-Layer Context specification and is a purely abstract parameter. If the A-ASSOCIATE request User Information parameter was present, the semantic content of this will have been supplied to the ACPM in the User Summary parameter of the A-ASSOCIATE request, and is conceptually included in the User Summary parameter of the P-CONNECT request.

If the Presentation provider (via the Session service and protocol) makes use of the fast-associate mechanism, the responding ACPM will receive only the User Summary parameter on the P-CONNECT indication, and not the User-Data. The responding implementation will reconstruct the semantic content of the AARQ that would have been present in the P-CONNECT User-Data, and issue an A-ASSOCIATE indication with a User Summary parameter in place of its User-Data.

Similarly, the responding ACPM will form a User Summary parameter on the P-CONNECT response from the AARE APDU, including the semantic content of the User Summary parameter of the A-ASSOCIATE response (if present) by reference to the same Upper-Layer Context specification. The initiating ACPM reconstructs the AARE.

NOTE – The passing of the User Summary parameters and reconstruction of the ACSE APDUs from the Presentation User Summary parameters is abstract. There is no requirement for a real implementation to perform these actions.

5) Subclause 7.1.3

Add in b):

... User-Data or a User Summary parameter on a P-CONNECT ...

Add at the end of d):

or have a User Summary parameter)

6) Subclause 7.1.3.1

Add after the first paragraph:

If the fast-associate mechanism is supported, the requesting ACPM identifies the semantic content of the AARQ, including the User-Data, in the User Summary parameter of the P-CONNECT request.

7) Subclause 7.1.3.2

Add at the end of the first paragraph:

or reconstructs an AARQ APDU from the User Summary parameter of the P-CONNECT indication primitive.

8) Subclause 7.1.3.3

Add after the first paragraph:

If the fast-associate mechanism is supported, the accepting ACPM identifies the semantic content of the AARE, including the User-Data, in the User Summary parameter of the P-CONNECT response, by reference to the Upper-Layer Context specification identified by the User Summary parameter of the received P-CONNECT indication.

9) Subclause 7.1.3.4

Replace the second sentence of the second paragraph with the following:

Either the User-Data parameter contains an AARE APDU or the User Summary parameter is a value from which the requesting ACPM can reconstruct the AARE APDU.