INTERNATIONAL STANDARD ISO/IEC 8825-7:2015

TECHNICAL CORRIGENDUM 2

Published 2017-11

Information technology — ASN.1 encoding rules —

Part 7:
Specification of Octet Encoding Rules (OER)

TECHNICAL CORRIGENDUM 2

Technologies de l'information — Règles de codage ASN.1

Partie 7: Spécification des règles de codage des octets (OER)

RECTIFICATIF TECHNIQUE 2

Technical Corrigendum 2 to ISO/IEC 8825-7:2015 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*, in collaboration with ITU-T. The identical text is published as Rec. ITU-T Rec.X696 (2015)/Cor.1 (2017).

Technical Corrigendum 2 to ISO/IEC 8825-7:2015 cancels and replaces ISO/IEC 8825-7:2015/Cor.1:2017, which did not contain the correct document reference number.

———————

ICS 35.100.70

Ref. No. ISO/IEC 8825-7:2015/Cor.2:2017(E)

Published in Switzerland

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – ASN.1 encoding rules: Specification of Octet Encoding Rules (OER)

Technical Corrigendum 2

Conventions used in this corrigendum: Original, unchanged, text is in normal font. *Deleted text is struck-through, thus:* ~~deleted text~~. *Inserted text is underlined, thus:* <u>inserted text</u>.

1   Clause 12.2

Replace clause 12.2 with the following:

If all of the following are true:

   a)   the lower bound of the effective value constraint of the mantissa is greater than or equal to $-2^{24} + 1$ (-16777215) and its upper bound is less than or equal to $2^{24} - 1$ (16777215);

   b)   the effective value constraint of the base is the fixed value 2; and

   c)   the lower bound of the effective value constraint of the exponent is greater than or equal to $-\underline{323}\text{~~126~~}$ and its upper bound is less than or equal to $\underline{292}\text{~~127~~}$,

then the real value shall be encoded in the binary32 (single precision) floating-point format specified in IEEE 754.

2   Clause 12.3

Replace clause 12.3 with the following:

12.3   Otherwise, if all of the following are true:

   a)   the lower bound of the effective value constraint of the mantissa is greater than or equal to $-2^{53} + 1$ (-9007199254740991) and its upper bound is less than or equal to $2^{53} - 1$ (9007199254740991);

   b)   the effective value constraint of the base is the fixed value 2; and

   c)   the lower bound of the effective value constraint of the exponent is greater than or equal to $-\underline{1074}\text{~~1022~~}$ and its upper bound is less than or equal to $\underline{971}\text{~~1023~~}$,

then the real value shall be encoded in the binary64 (double precision) floating-point format specified in IEEE 754.

3   Clause 16.1

Replace clause 16.1 with:

16.1   The encoding of a sequence value shall consist~~s~~ of the following parts, in order:

   a)   preamble;

   b)   encodings of the components in the extension root;

   c)   extension addition presence bitmap (optional); and

   d)   encodings of the extension additions (optional).

NOTE – Each of these parts occupies a whole number of octets.

4   Clause 18.1

Replace clause 18.1 with:

18.1   The value of a set type shall be encoded as if the type had been declared a sequence type, except that the components in the "RootComponentTypeList" of the set type <u>(as well as the preamble bits)</u> shall be encoded in the order specified in 18.2.