



Information technology – Telecommunications and information exchange between systems – Use of X.25 to provide the OSI Connection-mode Network Service

TECHNICAL CORRIGENDUM 2

Technologies de l'information – Télécommunications et échange d'informations entre systèmes – Utilisation du protocole X.25 pour fournir le service de réseau OSI en mode connexion

RECTIFICATIF TECHNIQUE 2

Technical corrigendum 2 to International Standard ISO/IEC 8878:1992 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

Page 4

Subclause 5.1

Item a) 4), replace "facility used" with "facility used if operating in a packet-switched network environment".

Page 7

Table 2

Add a superscript 3) following "Transit Delay Selection And Indication Facility" in the FIELDS column.

Add a new footnote 3 which reads "The Transit Delay Selection And Indication Facility shall be used only in a packet-switched network environment."

Change the superscript on "Fast Select Facility" in the FIELDS column to 4) and renumber the corresponding footnote.

Page 12

Subclause 6.2.5.2.1

Item d), change the text to read as follows:

"when operating in a DTE/DCE environment: if the target transit delay... calling end system, otherwise, the TDSAI... Standard); when operating in a DTE/DTE environment: the TDSAI Facility shall not be used."