

---

---

**Information technology — Database  
languages — SQL —**

**Part 3:  
Call-Level Interface (SQL/CLI)**

*Technologies de l'information — Langages de base de données — SQL —  
Partie 3: Interface de niveau d'appel (SQL/CLI)*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

© ISO/IEC 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## Contents

Page

Foreword .....	ix
Introduction .....	xi
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>3</b>
<b>3 Definitions, notations, and conventions</b> .....	<b>5</b>
3.1 Definitions .....	5
3.1.1 Definitions provided in Part 3 .....	5
3.2 Notations .....	5
3.3 Conventions .....	5
3.3.1 Specification of routine definitions .....	5
3.3.2 Relationships to other parts of ISO/IEC 9075 .....	6
3.3.2.1 Clause, Subclause, and Table relationships .....	6
3.4 Object identifier for Database Language SQL .....	13
<b>4 Concepts</b> .....	<b>15</b>
4.1 Introduction to SQL/CLI .....	15
4.2 Return codes .....	18
4.3 Diagnostics areas in SQL/CLI .....	19
4.3.1 Setting of ROW_NUMBER and COLUMN_NUMBER fields .....	22
4.4 Miscellaneous characteristics .....	22
4.4.1 Handles .....	22
4.4.2 Null terminated strings .....	23
4.4.3 Null pointers .....	23
4.4.4 Environment attributes .....	23
4.4.5 Connection attributes .....	24
4.4.6 Statement attributes .....	24
4.4.7 CLI descriptor areas .....	25
4.4.8 Obtaining diagnostics during multi-row fetch .....	26
4.5 Client-server operation .....	26

<b>5</b>	<b>Call-Level Interface specifications</b>	27
5.1	<CLI routine>	27
5.2	<CLI routine> invocation	34
5.3	Implicit set connection	37
5.4	Implicit cursor	38
5.5	Implicit DESCRIBE USING clause	40
5.6	Implicit EXECUTE USING and OPEN USING clauses	46
5.7	Implicit CALL USING clause	52
5.8	Implicit FETCH USING clause	56
5.9	Character string retrieval	62
5.10	Binary large object string retrieval	63
5.11	Deferred parameter check	64
5.12	CLI-specific status codes	65
5.13	Description of CLI item descriptor areas	67
5.14	Other tables associated with CLI	77
5.15	Data type correspondences	100
<b>6</b>	<b>SQL/CLI routines</b>	109
6.1	AllocConnect	109
6.2	AllocEnv	110
6.3	AllocHandle	111
6.4	AllocStmt	114
6.5	BindCol	115
6.6	BindParameter	117
6.7	Cancel	122
6.8	CloseCursor	124
6.9	ColAttribute	125
6.10	ColumnPrivileges	127
6.11	Columns	133
6.12	Connect	143
6.13	CopyDesc	147
6.14	DataSources	148
6.15	DescribeCol	150
6.16	Disconnect	152
6.17	EndTran	154
6.18	Error	159
6.19	ExecDirect	161
6.20	Execute	164
6.21	Fetch	166
6.22	FetchScroll	169
6.23	ForeignKeys	173
6.24	FreeConnect	186
6.25	FreeEnv	187
6.26	FreeHandle	188
6.27	FreeStmt	191
6.28	GetConnectAttr	193

6.29	GetCursorName	195
6.30	GetData	196
6.31	GetDescField	203
6.32	GetDescRec	205
6.33	GetDiagField	207
6.34	GetDiagRec	216
6.35	GetEnvAttr	218
6.36	GetFeatureInfo	220
6.37	GetFunctions	223
6.38	GetInfo	224
6.39	GetLength	232
6.40	GetParamData	234
6.41	GetPosition	240
6.42	GetSessionInfo	242
6.43	GetStmtAttr	244
6.44	GetSubString	247
6.45	GetTypeInfo	249
6.46	MoreResults	253
6.47	NextResult	254
6.48	NumResultCols	255
6.49	ParamData	256
6.50	Prepare	262
6.51	PrimaryKeys	264
6.52	PutData	269
6.53	RowCount	272
6.54	SetConnectAttr	273
6.55	SetCursorName	275
6.56	SetDescField	277
6.57	SetDescRec	282
6.58	SetEnvAttr	284
6.59	SetStmtAttr	286
6.60	SpecialColumns	290
6.61	StartTran	297
6.62	TablePrivileges	299
6.63	Tables	304
<b>7</b>	<b>Definition Schema</b>	<b>311</b>
7.1	SQL_IMPLEMENTATION_INFO base table	311
7.2	SQL_SIZING base table	313
7.3	SQL_LANGUAGES base table	315
<b>8</b>	<b>Conformance</b>	<b>317</b>
8.1	Conformance to SQL/CLI	317
8.2	Claims of conformance	317

8.3	Extensions and options .....	318
<b>Annex A</b>	<b>Typical header files .....</b>	<b>319</b>
A.1	C header file SQLCLI.H .....	319
A.2	COBOL library item SQLCLI .....	333
<b>Annex B</b>	<b>Sample C programs .....</b>	<b>343</b>
B.1	Create table, insert, select .....	343
B.2	Interactive Query .....	346
B.3	Providing long dynamic arguments at Execute time .....	350
<b>Annex C</b>	<b>Implementation-defined elements .....</b>	<b>355</b>
<b>Annex D</b>	<b>Implementation-dependent elements .....</b>	<b>369</b>
<b>Annex E</b>	<b>Incompatibilities with ISO/IEC 9075-3:1995 .....</b>	<b>375</b>
<b>Annex F</b>	<b>Deprecated features .....</b>	<b>377</b>
<b>Annex G</b>	<b>SQL feature and package taxonomy .....</b>	<b>379</b>
<b>Index</b>	.....	<b>381</b>

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## TABLES

<b>Tables</b>	<b>Page</b>
1	Clause, Subclause, and Table relationships . . . . . 6
2	Fields in SQL/CLI diagnostics areas . . . . . 20
3	Supported calling conventions of SQL/CLI routines by language . . . . . 30
4	Abbreviated SQL/CLI generic names . . . . . 30
5	SQLSTATE class and subclass values for SQL/CLI-specific conditions . . . . . 65
6	Fields in SQL/CLI row and parameter descriptor areas . . . . . 72
7	Codes used for implementation data types in SQL/CLI . . . . . 74
8	Codes used for application data types in SQL/CLI . . . . . 75
9	Codes associated with datetime data types in SQL/CLI . . . . . 76
10	Codes associated with <interval qualifier> in SQL/CLI . . . . . 76
11	Codes associated with <parameter mode> in SQL/CLI . . . . . 76
12	Codes used for diagnostic fields . . . . . 77
13	Codes used for handle types . . . . . 78
14	Codes used for transaction termination . . . . . 78
15	Codes used for environment attributes . . . . . 79
16	Codes used for connection attributes . . . . . 79
17	Codes used for statement attributes . . . . . 79
18	Codes used for FreeStmt options . . . . . 80
19	Data types of attributes . . . . . 80
20	Codes used for descriptor fields . . . . . 81
21	Ability to set SQL/CLI descriptor fields . . . . . 83
22	Ability to retrieve SQL/CLI descriptor fields . . . . . 85
23	SQL/CLI descriptor field default values . . . . . 87
24	Codes used for fetch orientation . . . . . 89
25	Multi-row fetch status codes . . . . . 89
26	Miscellaneous codes used in CLI . . . . . 90
27	Codes used to identify SQL/CLI routines . . . . . 90
28	Codes and data types for implementation information . . . . . 92
29	Codes and data types for session implementation information . . . . . 94
30	Values for ALTER TABLE with GetInfo . . . . . 94
31	Values for FETCH DIRECTION with GetInfo . . . . . 95
32	Values for GETDATA EXTENSIONS with GetInfo . . . . . 95
33	Values for OUTER JOIN CAPABILITIES with GetInfo . . . . . 95
34	Values for SCROLL CONCURRENCY with GetInfo . . . . . 95
35	Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran . . . . . 95
36	Values for TRANSACTION ACCESS MODE with StartTran . . . . . 96
37	Codes used for concise data types . . . . . 96
38	Codes used with concise datetime data types in SQL/CLI . . . . . 97

39	Codes used with concise interval data types in SQL/CLI .....	97
40	Concise codes used with datetime data types in SQL/CLI .....	98
41	Concise codes used with interval data types in SQL/CLI .....	98
42	Special parameter values .....	99
43	Column types and scopes used with SpecialColumns .....	99
44	Data type correspondences for Ada .....	100
45	Data type correspondences for C .....	102
46	Data type correspondences for COBOL .....	103
47	Data type correspondences for Fortran .....	105
48	Data type correspondences for MUMPS .....	106
49	Data type correspondences for Pascal .....	107
50	Data type correspondences for PL/I .....	108
51	SQL/CLI feature taxonomy .....	379

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

International Standard ISO/IEC 9075-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 32, *Data management and interchange*.

This second edition of this part of ISO/IEC 9075 cancels and replaces the first edition, ISO/IEC 9075-3:1995.

ISO/IEC 9075 comprises the following parts, under the general title *Information technology — Database languages — SQL*:

- *Part 1: Framework (SQL/Framework)*
- *Part 2: Foundation (SQL/Foundation)*
- *Part 3: Call-Level Interface (SQL/CLI)*
- *Part 4: Persistent Stored Modules (SQL/PSM)*
- *Part 5: Host Language Bindings (SQL/Bindings)*

Annexes A, B, C, D, E, F, and G of this part of ISO/IEC 9075 are for information only.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## Introduction

The organization of this part of ISO/IEC 9075 is as follows:

- 1) Clause 1, "Scope", specifies the scope of this part of ISO/IEC 9075.
- 2) Clause 2, "Normative references", identifies additional standards that, through reference in this part of ISO/IEC 9075, constitute provisions of this part of ISO/IEC 9075.
- 3) Clause 3, "Definitions, notations, and conventions", defines the notations and conventions used in this part of ISO/IEC 9075.
- 4) Clause 4, "Concepts", presents concepts used in the definition of the Call-Level Interface.
- 5) Clause 5, "Call-Level Interface specifications", defines facilities for using SQL through a Call-Level Interface.
- 6) Clause 6, "SQL/CLI routines", defines each of the routines that comprise the Call-Level Interface.
- 7) Clause 7, "Definition Schema", specifies extensions to the Definition Schema required for support of the Call-Level Interface.
- 8) Clause 8, "Conformance", defines the criteria for conformance to this part of ISO/IEC 9075.
- 9) Annex A, "Typical header files", is an informative Annex. It provides examples of typical definition files for application programs using the SQL Call-Level Interface.
- 10) Annex B, "Sample C programs", is an informative Annex. It provides examples of using the SQL Call-Level Interface from the C programming language.
- 11) Annex C, "Implementation-defined elements", is an informative Annex. It lists those features for which the body of this part of ISO/IEC 9075 states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or any other behavior is partly or wholly implementation-defined.
- 12) Annex D, "Implementation-dependent elements", is an informative Annex. It lists those features for which the body of this part of ISO/IEC 9075 states that the syntax, the meaning, the returned results, the effect on SQL-data and/or schemas, or any other behavior is partly or wholly implementation-dependent.
- 13) Annex E, "Incompatibilities with ISO/IEC 9075-3:1995", is an informative Annex. It identifies incompatibilities with ISO/IEC 9075-3:1995.
- 14) Annex F, "Deprecated features", is an informative Annex. It lists features that the responsible Technical Committee intends will not appear in a future revised version of ISO/IEC 9075.
- 15) Annex G, "SQL feature and package taxonomy", is an informative Annex. It contains a taxonomy of features of the SQL language that are specified in this part of ISO/IEC 9075.

In the text of this part of ISO/IEC 9075, Clauses begin a new odd-numbered page, and in Clause 5, “Call-Level Interface specifications”, through Clause 8, “Conformance”, Subclauses begin a new page. Any resulting blank space is not significant.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

# Information technology — Database languages — SQL — Part 3: Call-Level Interface (SQL/CLI)

## 1 Scope

This part of ISO/IEC 9075 defines the structures and procedures that may be used to execute statements of the database language SQL from within an application written in a standard programming language in such a way that procedures used are independent of the SQL statements to be executed.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 2 Normative references

The following standards contain provisions that, through reference in this text, constitute provisions of this part of ISO/IEC 9075. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO/IEC 9075 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid international Standards.

ISO/IEC 1539:1991, *Information technology — Programming languages — FORTRAN*.

ISO 1989:1985, *Programming languages — COBOL*.

ISO 6160:1979, *Programming languages — PL/I*.

ISO/IEC 7185:1990, *Information technology — Programming languages — Pascal*.

ISO/IEC 8652:1995, *Information technology — Programming languages — Ada*.

ISO/IEC 9075-1:1999, *Information technology — Database languages — SQL — Part 1: Framework (SQL/Framework)*.

ISO/IEC 9075-2:1999, *Information technology — Database languages — SQL — Part 2: Foundation (SQL/Foundation)*.

ISO/IEC 9075-4:1999, *Information technology — Database languages — SQL — Part 4: Persistent Stored Modules (SQL/PSM)*.

ISO/IEC 9075-5:1999, *Information technology — Database languages — SQL — Part 5: Host Language Bindings (SQL/Bindings)*.

ISO/IEC 9899:1990, *Programming languages — C*.

ISO/IEC 10206:1991, *Information technology — Programming languages — Extended Pascal*.

ISO/IEC 11756:1992, *Information technology — Programming languages — MUMPS*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 3 Definitions, notations, and conventions

### 3.1 Definitions

#### 3.1.1 Definitions provided in Part 3

Insert this paragraph For the purposes of this part of ISO/IEC 9075, the definitions given in ISO/IEC 9075-1, ISO/IEC 9075-2, and ISO/IEC 9075-5 and the following definitions apply.

- a) **handle**: A CLI object returned by an SQL/CLI implementation when a CLI resource is allocated and used by an SQL/CLI application to reference that CLI resource.
- b) **inner table**: The second operand of a left outer join or the first operand of a right outer join.
- c) **pseudo-column**: A column in a table that is not part of the descriptor for that table. An example of such a pseudo-column is an implementation-defined row identifier.

### 3.2 Notations

Insert this paragraph The syntax notation used in this part of ISO/IEC 9075 is an extended version of BNF ("Backus Normal Form" or "Backus Naur Form"). This version of BNF is fully described in Subclause 6.1, "Notation", of ISO/IEC 9075-1.

### 3.3 Conventions

Insert this paragraph Except as otherwise specified in this part of ISO/IEC 9075, the conventions used in this part of ISO/IEC 9075 are identical to those described in ISO/IEC 9075-1 and ISO/IEC 9075-2.

#### 3.3.1 Specification of routine definitions

The routines in this part of ISO/IEC 9075 are specified in terms of:

- **Function**: A short statement of the purpose of the routine.
- **Definition**: The name of the routine and the names, modes, and data types of its parameters.
- **General Rules**: A specification of the run-time effect of the routine. Where more than one General Rule is used to specify the effect of a routine, the required effect is that which would be obtained by beginning with the first General Rule and applying the Rules in numeric sequence until a Rule is applied that specifies or implies a change in sequence or termination of the application of the Rules. Unless otherwise specified or implied by a specific Rule that is applied, application of General Rules terminates when the last in the sequence has been applied.

## 3.3 Conventions

## 3.3.2 Relationships to other parts of ISO/IEC 9075

## 3.3.2.1 Clause, Subclause, and Table relationships

Table 1—Clause, Subclause, and Table relationships

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Clause 1, "Scope"	Clause 1, "Scope"	ISO/IEC 9075-2
Clause 2, "Normative references"	Clause 2, "Normative references"	ISO/IEC 9075-2
Clause 3, "Definitions, notations, and conventions"	Clause 3, "Definitions, notations, and conventions"	ISO/IEC 9075-2
Subclause 3.1, "Definitions"	Subclause 3.1, "Definitions"	ISO/IEC 9075-2
Subclause 3.1.1, "Definitions provided in Part 3"	Subclause 3.1.5, "Definitions provided in Part 2"	ISO/IEC 9075-2
Subclause 3.2, "Notations"	Subclause 3.2, "Notation"	ISO/IEC 9075-2
Subclause 3.3, "Conventions"	Subclause 3.3, "Conventions"	ISO/IEC 9075-2
Subclause 3.3.1, "Specification of routine definitions"	<i>(none)</i>	<i>(none)</i>
Subclause 3.3.2, "Relationships to other parts of ISO/IEC 9075"	<i>(none)</i>	<i>(none)</i>
Subclause 3.3.2.1, "Clause, Subclause, and Table relationships"	<i>(none)</i>	<i>(none)</i>
Subclause 3.4, "Object identifier for Database Language SQL"	<i>none</i>	<i>none</i>
Clause 4, "Concepts"	Clause 4, "Concepts"	ISO/IEC 9075-2
Subclause 4.1, "Introduction to SQL/CLI"	<i>none</i>	<i>none</i>
Subclause 4.2, "Return codes"	<i>none</i>	<i>none</i>
Subclause 4.3, "Diagnostics areas in SQL/CLI"	<i>none</i>	<i>none</i>
Subclause 4.3.1, "Setting of ROW_NUMBER and COLUMN_NUMBER fields"	<i>none</i>	<i>none</i>
Subclause 4.4, "Miscellaneous characteristics"	<i>none</i>	<i>none</i>
Subclause 4.4.1, "Handles"	<i>none</i>	<i>none</i>
Subclause 4.4.2, "Null terminated strings"	<i>none</i>	<i>none</i>
Subclause 4.4.3, "Null pointers"	<i>none</i>	<i>none</i>
Subclause 4.4.4, "Environment attributes"	<i>none</i>	<i>none</i>

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Subclause 4.4.5, "Connection attributes"	<i>none</i>	<i>none</i>
Subclause 4.4.6, "Statement attributes"	<i>none</i>	<i>none</i>
Subclause 4.4.7, "CLI descriptor areas"	<i>none</i>	<i>none</i>
Subclause 4.4.8, "Obtaining diagnostics during multi-row fetch"	<i>none</i>	<i>none</i>
Subclause 4.5, "Client-server operation"	Subclause 4.36, "Client-server operation"	ISO/IEC 9075-2
Clause 5, "Call-Level Interface specifications"	<i>none</i>	<i>none</i>
Subclause 5.1, "<CLI routine>"	<i>none</i>	<i>none</i>
Subclause 5.2, "<CLI routine> invocation"	<i>none</i>	<i>none</i>
Subclause 5.3, "Implicit set connection"	<i>none</i>	<i>none</i>
Subclause 5.4, "Implicit cursor"	<i>none</i>	<i>none</i>
Subclause 5.5, "Implicit DESCRIBE USING clause"	<i>none</i>	<i>none</i>
Subclause 5.6, "Implicit EXECUTE USING and OPEN USING clauses"	<i>none</i>	<i>none</i>
Subclause 5.7, "Implicit CALL USING clause"	<i>none</i>	<i>none</i>
Subclause 5.8, "Implicit FETCH USING clause"	<i>none</i>	<i>none</i>
Subclause 5.9, "Character string retrieval"	<i>none</i>	<i>none</i>
Subclause 5.10, "Binary large object string retrieval"	<i>none</i>	<i>none</i>
Subclause 5.11, "Deferred parameter check"	<i>none</i>	<i>none</i>
Subclause 5.12, "CLI-specific status codes"	<i>none</i>	<i>none</i>
Subclause 5.13, "Description of CLI item descriptor areas"	<i>none</i>	<i>none</i>
Subclause 5.14, "Other tables associated with CLI"	<i>none</i>	<i>none</i>
Subclause 5.15, "Data type correspondences"	Subclause 13.6, "Data type correspondences"	ISO/IEC 9075-2
Clause 6, "SQL/CLI routines"	<i>none</i>	<i>none</i>
Subclause 6.1, "AllocConnect"	<i>none</i>	<i>none</i>

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Subclause 6.2, “AllocEnv”	<i>none</i>	<i>none</i>
Subclause 6.3, “AllocHandle”	<i>none</i>	<i>none</i>
Subclause 6.4, “AllocStmt”	<i>none</i>	<i>none</i>
Subclause 6.5, “BindCol”	<i>none</i>	<i>none</i>
Subclause 6.6, “BindParameter”	<i>none</i>	<i>none</i>
Subclause 6.7, “Cancel”	<i>none</i>	<i>none</i>
Subclause 6.8, “CloseCursor”	<i>none</i>	<i>none</i>
Subclause 6.9, “ColAttribute”	<i>none</i>	<i>none</i>
Subclause 6.10, “ColumnPrivileges”	<i>none</i>	<i>none</i>
Subclause 6.11, “Columns”	<i>none</i>	<i>none</i>
Subclause 6.12, “Connect”	<i>none</i>	<i>none</i>
Subclause 6.13, “CopyDesc”	<i>none</i>	<i>none</i>
Subclause 6.14, “DataSources”	<i>none</i>	<i>none</i>
Subclause 6.15, “DescribeCol”	<i>none</i>	<i>none</i>
Subclause 6.16, “Disconnect”	<i>none</i>	<i>none</i>
Subclause 6.17, “EndTran”	<i>none</i>	<i>none</i>
Subclause 6.18, “Error”	<i>none</i>	<i>none</i>
Subclause 6.19, “ExecDirect”	<i>none</i>	<i>none</i>
Subclause 6.20, “Execute”	<i>none</i>	<i>none</i>
Subclause 6.21, “Fetch”	<i>none</i>	<i>none</i>
Subclause 6.22, “FetchScroll”	<i>none</i>	<i>none</i>
Subclause 6.23, “ForeignKeys”	<i>none</i>	<i>none</i>
Subclause 6.24, “FreeConnect”	<i>none</i>	<i>none</i>
Subclause 6.25, “FreeEnv”	<i>none</i>	<i>none</i>
Subclause 6.26, “FreeHandle”	<i>none</i>	<i>none</i>
Subclause 6.27, “FreeStmt”	<i>none</i>	<i>none</i>
Subclause 6.28, “GetConnectAttr”	<i>none</i>	<i>none</i>
Subclause 6.29, “GetCursorName”	<i>none</i>	<i>none</i>
Subclause 6.30, “GetData”	<i>none</i>	<i>none</i>
Subclause 6.31, “GetDescField”	<i>none</i>	<i>none</i>
Subclause 6.32, “GetDescRec”	<i>none</i>	<i>none</i>
Subclause 6.33, “GetDiagField”	<i>none</i>	<i>none</i>
Subclause 6.34, “GetDiagRec”	<i>none</i>	<i>none</i>

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Subclause 6.35, "GetEnvAttr"	<i>none</i>	<i>none</i>
Subclause 6.36, "GetFeatureInfo"	<i>none</i>	<i>none</i>
Subclause 6.37, "GetFunctions"	<i>none</i>	<i>none</i>
Subclause 6.38, "GetInfo"	<i>none</i>	<i>none</i>
Subclause 6.39, "GetLength"	<i>none</i>	<i>none</i>
Subclause 6.40, "GetParamData"	<i>none</i>	<i>none</i>
Subclause 6.41, "GetPosition"	<i>none</i>	<i>none</i>
Subclause 6.42, "GetSessionInfo"	<i>none</i>	<i>none</i>
Subclause 6.43, "GetStmtAttr"	<i>none</i>	<i>none</i>
Subclause 6.44, "GetSubString"	<i>none</i>	<i>none</i>
Subclause 6.45, "GetTypeInfo"	<i>none</i>	<i>none</i>
Subclause 6.46, "MoreResults"	<i>none</i>	<i>none</i>
Subclause 6.47, "NextResult"	<i>none</i>	<i>none</i>
Subclause 6.48, "NumResultCols"	<i>none</i>	<i>none</i>
Subclause 6.49, "ParamData"	<i>none</i>	<i>none</i>
Subclause 6.50, "Prepare"	<i>none</i>	<i>none</i>
Subclause 6.51, "PrimaryKeys"	<i>none</i>	<i>none</i>
Subclause 6.52, "PutData"	<i>none</i>	<i>none</i>
Subclause 6.53, "RowCount"	<i>none</i>	<i>none</i>
Subclause 6.54, "SetConnectAttr"	<i>none</i>	<i>none</i>
Subclause 6.55, "SetCursorName"	<i>none</i>	<i>none</i>
Subclause 6.56, "SetDescField"	<i>none</i>	<i>none</i>
Subclause 6.57, "SetDescRec"	<i>none</i>	<i>none</i>
Subclause 6.58, "SetEnvAttr"	<i>none</i>	<i>none</i>
Subclause 6.59, "SetStmtAttr"	<i>none</i>	<i>none</i>
Subclause 6.60, "SpecialColumns"	<i>none</i>	<i>none</i>
Subclause 6.61, "StartTran"	<i>none</i>	<i>none</i>
Subclause 6.62, "TablePrivileges"	<i>none</i>	<i>none</i>
Subclause 6.63, "Tables"	<i>none</i>	<i>none</i>
Clause 7, "Definition Schema"	Clause 21, "Definition Schema"	ISO/IEC 9075-2
Subclause 7.1, "SQL_IMPLEMENTATION_INFO base table"	Subclause 21.36, "SQL_IMPLEMENTATION_INFO base table"	ISO/IEC 9075-2
Subclause 7.2, "SQL_SIZING base table"	Subclause 21.38, "SQL_SIZING base table"	ISO/IEC 9075-2

## 3.3 Conventions

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Subclause 7.3, "SQL_LANGUAGES base table"	Subclause 21.37, "SQL_LANGUAGES base table"	ISO/IEC 9075-2
Clause 8, "Conformance"	Clause 8, "Conformance"	ISO/IEC 9075-1
Subclause 8.1, "Conformance to SQL/CLI"	<i>none</i>	<i>none</i>
Subclause 8.2, "Claims of conformance"	Subclause 8.1.5, "Claims of conformance"	ISO/IEC 9075-1
Subclause 8.3, "Extensions and options"	<i>none</i>	<i>none</i>
Annex A, "Typical header files"	<i>none</i>	<i>none</i>
Subclause A.1, "C header file SQLCLI.H"	<i>none</i>	<i>none</i>
Subclause A.2, "COBOL library item SQLCLI"	<i>none</i>	<i>none</i>
Annex B, "Sample C programs"	<i>none</i>	<i>none</i>
Subclause B.1, "Create table, insert, select"	<i>none</i>	<i>none</i>
Subclause B.2, "Interactive Query"	<i>none</i>	<i>none</i>
Subclause B.3, "Providing long dynamic arguments at Execute time"	<i>none</i>	<i>none</i>
Annex C, "Implementation-defined elements"	Appendix B, "Implementation-defined elements"	ISO/IEC 9075-2
Annex D, "Implementation-dependent elements"	Appendix C, "Implementation-dependent elements"	ISO/IEC 9075-2
Annex E, "Incompatibilities with ISO/IEC 9075-3:1995"	Appendix E, "Incompatibilities with ISO/IEC 9075:1992 and ISO/IEC 9075-4:1996"	ISO/IEC 9075-2
Annex F, "Deprecated features"	Appendix D, "Deprecated features"	ISO/IEC 9075-2
Annex G, "SQL feature and package taxonomy"	<i>none</i>	<i>none</i>
Table 1, "Clause, Subclause, and Table relationships"	<i>none</i>	<i>none</i>
Table 2, "Fields in SQL/CLI diagnostics areas"	<i>none</i>	<i>none</i>
Table 3, "Supported calling conventions of SQL/CLI routines by language"	<i>none</i>	<i>none</i>
Table 4, "Abbreviated SQL/CLI generic names"	<i>none</i>	<i>none</i>
Table 5, "SQLSTATE class and subclass values for SQL/CLI-specific conditions"	<i>none</i>	<i>none</i>

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Table 6, "Fields in SQL/CLI row and parameter descriptor areas"	<i>none</i>	<i>none</i>
Table 7, "Codes used for implementation data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 8, "Codes used for application data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 9, "Codes associated with date-time data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 10, "Codes associated with <interval qualifier> in SQL/CLI"	<i>none</i>	<i>none</i>
Table 11, "Codes associated with <parameter mode> in SQL/CLI"	<i>none</i>	<i>none</i>
Table 12, "Codes used for diagnostic fields"	<i>none</i>	<i>none</i>
Table 13, "Codes used for handle types"	<i>none</i>	<i>none</i>
Table 14, "Codes used for transaction termination"	<i>none</i>	<i>none</i>
Table 15, "Codes used for environment attributes"	<i>none</i>	<i>none</i>
Table 16, "Codes used for connection attributes"	<i>none</i>	<i>none</i>
Table 17, "Codes used for statement attributes"	<i>none</i>	<i>none</i>
Table 18, "Codes used for FreeStmt options"	<i>none</i>	<i>none</i>
Table 19, "Data types of attributes"	<i>none</i>	<i>none</i>
Table 20, "Codes used for descriptor fields"	<i>none</i>	<i>none</i>
Table 21, "Ability to set SQL/CLI descriptor fields"	<i>none</i>	<i>none</i>
Table 22, "Ability to retrieve SQL/CLI descriptor fields"	<i>none</i>	<i>none</i>
Table 23, "SQL/CLI descriptor field default values"	<i>none</i>	<i>none</i>
Table 24, "Codes used for fetch orientation"	<i>none</i>	<i>none</i>
Table 25, "Multi-row fetch status codes"	<i>none</i>	<i>none</i>
Table 26, "Miscellaneous codes used in CLI"	<i>none</i>	<i>none</i>

## 3.3 Conventions

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Table 27, "Codes used to identify SQL/CLI routines"	<i>none</i>	<i>none</i>
Table 28, "Codes and data types for implementation information"	<i>none</i>	<i>none</i>
Table 29, "Codes and data types for session implementation information"	<i>none</i>	<i>none</i>
Table 30, "Values for ALTER TABLE with GetInfo"	<i>none</i>	<i>none</i>
Table 31, "Values for FETCH DIRECTION with GetInfo"	<i>none</i>	<i>none</i>
Table 32, "Values for GETDATA EXTENSIONS with GetInfo"	<i>none</i>	<i>none</i>
Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo"	<i>none</i>	<i>none</i>
Table 34, "Values for SCROLL CONCURRENCY with GetInfo"	<i>none</i>	<i>none</i>
Table 35, "Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran"	<i>none</i>	<i>none</i>
Table 36, "Values for TRANSACTION ACCESS MODE with StartTran"	<i>none</i>	<i>none</i>
Table 37, "Codes used for concise data types"	<i>none</i>	<i>none</i>
Table 38, "Codes used with concise datetime data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 39, "Codes used with concise interval data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 40, "Concise codes used with datetime data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 41, "Concise codes used with interval data types in SQL/CLI"	<i>none</i>	<i>none</i>
Table 42, "Special parameter values"	<i>none</i>	<i>none</i>
Table 43, "Column types and scopes used with SpecialColumns"	<i>none</i>	<i>none</i>
Table 44, "Data type correspondences for Ada"	Table 18, "Data type correspondences for Ada"	ISO/IEC 9075-2
Table 45, "Data type correspondences for C"	Table 19, "Data type correspondences for C"	ISO/IEC 9075-2
Table 46, "Data type correspondences for COBOL"	Table 20, "Data type correspondences for COBOL"	ISO/IEC 9075-2

Table 1—Clause, Subclause, and Table relationships (Cont.)

Clause, Subclause, or Table in this part of ISO/IEC 9075	Corresponding Clause, Subclause, or Table from another part	Part containing correspondence
Table 47, "Data type correspondences for Fortran"	Table 21, "Data type correspondences for Fortran"	ISO/IEC 9075-2
Table 48, "Data type correspondences for MUMPS"	Table 22, "Data type correspondences for MUMPS"	ISO/IEC 9075-2
Table 49, "Data type correspondences for Pascal"	Table 23, "Data type correspondences for Pascal"	ISO/IEC 9075-2
Table 50, "Data type correspondences for PL/I"	Table 24, "Data type correspondences for PL/I"	ISO/IEC 9075-2
Table 51, "SQL/CLI feature taxonomy"	Table 32, "SQL/Foundation feature taxonomy for features outside Core SQL"	ISO/IEC 9075-2

### 3.4 Object identifier for Database Language SQL

The object identifier for Database Language SQL is defined in ISO/IEC 9075-1 in Subclause 6.3, "Object identifier for Database Language SQL", with the following additions:

#### Format

<Part 3 yes> ::= <Part 3 conformance>

<Part 3 conformance> ::= 3 | sqlcli1999 <left paren> 3 <right paren>

#### Syntax Rules

None.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 4 Concepts

### 4.1 Introduction to SQL/CLI

The Call-Level Interface (SQL/CLI) is a binding style for executing SQL statements. SQL/CLI comprises routines that:

- Allocate and deallocate resources.
- Control connections to SQL-servers.
- Execute SQL statements using mechanisms similar to dynamic SQL.
- Obtain diagnostic information.
- Control transaction termination.
- Obtain information about the implementation.

A *handle* is a CLI object returned by an SQL/CLI implementation when a CLI resource is allocated and used by an SQL/CLI application to reference that CLI resource. The *AllocHandle* routine allocates the resources to manage an SQL-environment, an SQL-connection, a CLI descriptor area, or SQL-statement processing and returns an environment handle, a connection handle, a descriptor handle, or a statement handle, respectively. An SQL-connection is allocated in the context of an allocated SQL-environment. A CLI descriptor area and an SQL-statement are allocated in the context of an allocated SQL-connection. The *FreeHandle* routine deallocates a specified resource. The *AllocConnect*, *AllocEnv*, and *AllocStmt* routines can be used to allocate the resources to manage an SQL-connection, an SQL-environment, and SQL-statement processing, respectively, instead of using the *AllocHandle* routine. The *FreeConnect*, *FreeEnv*, and *FreeStmt* routines can be used to deallocate the specific resource instead of using *FreeHandle*.

Each allocated SQL-environment has an attribute that determines whether output character strings are null terminated by the implementation. The application can set the value of this attribute by using the routine *SetEnvAttr* and can retrieve the current value of the attribute by using the routine *GetEnvAttr*.

The *Connect* routine establishes an SQL-connection. The *Disconnect* routine terminates an established SQL-connection. Switching between established SQL-connections occurs automatically whenever the application switches processing to a dormant SQL-connection.

The *ExecDirect* routine is used for a one-time execution of an SQL-statement. The *Prepare* routine is used to prepare an SQL-statement for subsequent execution using the *Execute* routine. In each case, the executed SQL-statement can contain dynamic parameters.

The interface for a description of dynamic parameters, dynamic parameter values, the resultant columns of a <dynamic select statement> or <dynamic single row select statement>, and the target specifications for the resultant columns is a CLI descriptor area. A CLI descriptor area for each type of interface is automatically allocated when an SQL-statement is allocated. The application may allocate additional CLI descriptor areas and nominate them for use as the interface for the description of dynamic parameter values or the description of target specifications by using the

routine `SetStmtAttr`. The application can determine the handle value of the CLI descriptor area currently being used for a specific interface by using the routine `GetStmtAttr`. The `GetDescField` and `GetDescRec` routines enable information to be retrieved from a CLI descriptor area. The `CopyDesc` routine enables the contents of a CLI descriptor area to be copied to another CLI descriptor area.

When a `<dynamic select statement>` or `<dynamic single row select statement>` is prepared or executed immediately, a description of the resultant columns is automatically provided in the applicable CLI implementation descriptor area. In this case, the application may additionally retrieve information by using the `DescribeCol` and/or the `ColAttribute` routine to obtain a description of a single resultant column and by using the `NumResultCols` routine to obtain a count of the number of resultant columns. The application sets values in the CLI application descriptor area for the description of the corresponding target specifications either explicitly using the routines `SetDescField` and `SetDescRec` or implicitly using the routine `BindCol`.

When an SQL-statement is prepared or executed immediately, a description of the dynamic parameters is automatically provided in the applicable CLI implementation descriptor area if this facility is supported by the current SQL-connection. An attribute associated with the allocated SQL-connection indicates whether this facility is supported. The value of the attribute may be retrieved using the routine `GetConnectAttr`. Regardless of whether automatic description is supported, all dynamic input and input/output parameters must be defined in the CLI application descriptor area before SQL-statement execution. This can be done either explicitly using the routines `SetDescField` and `SetDescRec` or implicitly using the routine `BindParameter`. The value of a dynamic input or input/output parameter may be established before SQL-statement execution (immediate parameter value) or may be provided during SQL-statement execution (deferred parameter value). Its description in the CLI descriptor area determines which method is in use. The `ParamData` routine is used to cycle through and process deferred input and input/output parameter values. The `PutData` routine is used to provide the deferred values. The `PutData` routine also enables the values of character string input and input/output parameters to be provided in pieces.

Before a `<call statement>` is prepared or executed immediately, the application may choose whether or not to bind any dynamic output parameters in the CLI application descriptor area. This can be done either explicitly using the routines `SetDescField` and `SetDescRec` or implicitly using the routine `BindParameter`. After execution of the statement, values of unbound output and input/output parameters can be individually retrieved using the `GetParamData` routine. The `GetParamData` routine also enables the retrieval of the values of character and binary string output and input/output parameters to be accomplished piece by piece.

When a `<dynamic select statement>` or `<dynamic single row select statement>` is executed, a cursor is implicitly declared and opened. The cursor name can be supplied by the application by using the routine `SetCursorName`. If a cursor name is not supplied by the application, an implementation-dependent cursor name is generated. The cursor name can be retrieved by using the `GetCursorName` routine.

The `Fetch` and `FetchScroll` routines are used to position an open cursor on a row and to retrieve the values of bound columns for that row. A bound column is one whose target specification in the specified CLI descriptor area defines a location for the target value. The `Fetch` routine always positions the open cursor on the next row, whereas the `FetchScroll` routine may be used to position the open cursor on any of its rows. The value of the `CURSOR SCROLLABLE` statement attribute must be `SCROLLABLE` at the time that the cursor is implicitly declared in order to use `FetchScroll` with a `FetchOrientation` other than `NEXT`. The application can set the value of this attribute by using the `SetStmtAttr` routine and can retrieve the current value of the attribute by using the `GetStmtAttr` routine. The `Fetch` and `FetchScroll` routines can also retrieve multiple rows in a single call; the set of rows thus retrieved is called a *rowset*. This is accomplished by setting the `ARRAY_SIZE` field of the applicable CLI application row descriptor to the desired number of rows. Note that the single row fetch is just a special case of multi-row fetch, where the rowset size is one.

Values for unbound columns can be individually retrieved by using the GetData routine. The GetData routine also enables the retrieval of the values of character and binary string columns to be accomplished piece by piece. The current row of a cursor can be deleted or updated by executing a <preparable dynamic delete statement: positioned> or a <preparable dynamic update statement: positioned>, respectively, for that cursor under a different allocated SQL-statement to the one under which the cursor was opened. The CloseCursor routine enables a cursor to be closed.

Result sets can be returned to the application as a result of issuing an Execute or ExecDirect routine against a statement handle whose current statement is a <call statement>. Such result sets are described and processed in the same way as outlined above for the result sets produced by the execution of a <dynamic select statement>. Multiple result sets may result from the execution of a single <call statement>. These result sets are returned as an ordered set of result sets that can be processed one at a time or in parallel. To process the result sets one at a time, once the processing of a given result set is complete, the MoreResults routine is used to determine whether there are any additional result sets and, if there are, to position the cursor before the first row in the next result set. To process the result sets in parallel, the NextResult routine is used to determine whether there are any additional result sets and, if there are, to position a cursor before the first row in the next result set.

Special routines, called *catalog routines* are available to return result sets from the information schemas. These routines are:

- ColumnPrivileges: Returns a list of the privileges held on the columns whose names adhere to the requested pattern(s) within a single specified table. Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the COLUMN\_PRIVILEGES view of the Information Schema.
- Columns: Returns the column names and attributes for all columns that adhere to the requested pattern(s). Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the COLUMNS view of the Information Schema.
- ForeignKeys: Returns either the primary key of a single specified table together with the foreign keys in all other tables that reference that primary key or the foreign keys of a single specified table together with all the primary and unique keys in all other tables that reference those foreign keys. Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the TABLE\_CONSTRAINTS view and the REFERENTIAL\_CONSTRAINTS view of the Information Schema.
- PrimaryKeys: Returns a list of the columns that constitute the primary key of a single specified table. Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the TABLE\_CONSTRAINTS view and the KEY\_COLUMN\_USAGE view of the Information Schema.
- SpecialColumns: Returns a list of the columns which can uniquely identify any row within a single specified table. Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the COLUMNS view of the Information Schema.
- Tables: Returns information about the tables that adhere to the requested pattern(s) and type(s). Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the TABLES view of the Information Schema.
- TablePrivileges: Returns a list of the privileges held on tables that adhere to the requested pattern(s). Most of this information can also be obtained by using the ExecDirect routine to issue an appropriate query on the TABLE\_PRIVILEGES view of the Information Schema.

These special routines are only available for a small portion of the metadata that is available in the Information Schema. Other metadata (for example, that about SQL-invoked routines, triggers, and user-defined types) must be obtained by issuing appropriate queries on the views of the Information Schema.

The `GetPosition`, `GetLength`, and `GetSubString` routines can be used with their own independent statement handle to access a string value at the server that is represented by a Large Object locator in order to do any of the following:

- The `GetPosition` routine may be used determine whether a given substring exists within that string and, if it does, to obtain an integer value that indicates the starting position of that substring.
- The `GetLength` routine may be used to obtain an integer value that contains the length of the string.
- The `GetSubString` routine may be used to retrieve a portion of a string, or alternatively, to create a new Large Object value at the server which is a portion of the string and to return a Large Object locator that represents that value.

The `Error`, `GetDiagField`, and `GetDiagRec` routines obtain diagnostic information about the most recent routine operating on a particular resource. The `Error` routine always retrieves information from the next status record, whereas the `GetDiagField` and `GetDiagRec` routines may be used to retrieve information from any status record.

Information on the number of rows affected by the last executed SQL-statement can be obtained by using the `RowCount` or `GetDiagField` routine.

An SQL-transaction is terminated by using the `EndTran` routine. An SQL-transaction is implicitly initiated whenever a CLI routine is invoked that requires the context of an SQL-transaction and no SQL-transaction is active. An SQL-transaction is explicitly started and its characteristics set by using the `StartTran` routine.

NOTE 1 – Neither a `<start transaction statement>`, a `<commit statement>`, a `<rollback statement>`, nor a `<release savepoint statement>` may be executed using the `ExecDirect` or `Execute` routines.

The `Cancel` routine is used to cancel the execution of a concurrently executing SQL/CLI routine or to terminate the processing of deferred parameter values and the execution of the associated SQL-statement.

The `GetFeatureInfo`, `GetFunctions`, `GetInfo`, `GetSessionInfo`, and `GetTypeInfo` routines are used to obtain information about the implementation. The `DataSources` routine returns a list of names that identify SQL-servers to which the application may be able to connect and returns a description of each such SQL-server.

## 4.2 Return codes

The execution of a CLI routine causes one or more conditions to be raised. The status of the execution is indicated by a code that is returned either as the result of a CLI routine that is a CLI function or as the value of the `ReturnCode` argument of a CLI routine that is a CLI procedure.

The values and meanings of the return codes are as follows. If more than one return code is possible, then the one appearing later in the list is the one returned.

- A value of 0 (zero) indicates **Success**. The CLI routine executed successfully.

- A value of 1 (one) indicates **Success with information**. The CLI routine executed successfully but a completion condition was raised: *warning*.
- A value of 100 indicates **No data found**. The CLI routine executed successfully but a completion condition was raised: *no data*.
- A value of 99 indicates **Data needed**. The CLI routine did not complete its execution because additional data is needed. An exception condition was raised: *CLI-specific condition — dynamic parameter value needed*.
- A value of –1 indicates **Error**. The CLI routine did not execute successfully. An exception condition other than *CLI-specific condition — invalid handle* or *CLI-specific condition — dynamic parameter value needed* was raised.
- A value of –2 indicates **Invalid handle**. The CLI routine did not execute successfully because an exception condition was raised: *CLI-specific condition — invalid handle*.

After the execution of a CLI routine, the values of all output arguments not explicitly defined by this part of ISO/IEC 9075 are implementation-dependent.

In addition to providing the return code, for all CLI routines other than Error, GetDiagField, and GetDiagRec, the implementation records information about completion conditions and about exception conditions other than *CLI-specific condition — invalid handle* in the diagnostics area associated with the resource being utilized.

The resource being utilized by a routine is the resource identified by its input handle. In the case of CopyDesc, which has two input handles, the resource being utilized is deemed to be the one identified by TargetDescHandle.

### 4.3 Diagnostics areas in SQL/CLI

Each diagnostics area comprises header fields that contain general information relating to the routine that was executed and zero or more status records containing information about individual conditions that occurred during the execution of the CLI routine. A condition that causes a status record to be generated is referred to as a *status condition*.

At the beginning of the execution of any CLI routine other than Error, GetDiagField, and GetDiagRec, the diagnostics area for the resource being utilized is emptied. If the execution of such a routine does not result in the exception condition *CLI-specific condition — invalid handle* or the exception condition *CLI-specific condition — dynamic parameter value needed*, then:

- Header information is generated in the diagnostics area.
- If the routine's return code indicates **Success**, then no status records are generated.
- If the routine's return code indicates **Success with information** or **Error**, then one or more status records are generated.
- If the routine's return code indicates **No data found**, then no status record is generated corresponding to SQLSTATE value '02000' but there may be status records generated corresponding to SQLSTATE value '02nnn', where 'nnn' is an implementation-defined subclass value.

### 4.3 Diagnostics areas in SQL/CLI

When Fetch or FetchScroll is called to fetch a rowset and there are exceptions or warnings generated when fetching one or more rows, then the corresponding records in the diagnostics area have the ROW\_NUMBER field set to the appropriate row number in the rowset. If a status record does not correspond to any row in the rowset, or the record is generated as a result of calling a routine other than Fetch or FetchScroll, the ROW\_NUMBER field is set to zero. The COLUMN\_NUMBER field of the diagnostic record contains the column number (if any) to which this diagnostic applies. If the diagnostic record does not apply to any column, then COLUMN\_NUMBER is set to zero.

Status records in the diagnostics area are ordered by ROW\_NUMBER. If multiple status records are generated for the same ROW\_NUMBER value, then the order in which status records are placed in a diagnostics area is implementation-dependent except that:

- For the purpose of choosing the first status record, status records corresponding to *transaction rollback* have precedence over status records corresponding to other exceptions, which in turn have precedence over status records corresponding to the completion condition *no data*, which in turn have precedence over status records corresponding to the completion condition *warning*.
- Apart from any status records corresponding to an implementation-specified *no data*, any status record corresponding to an implementation-specified condition that duplicates, in whole or in part, a condition defined in this part of ISO/IEC 9075 shall not be the first status record.

The routines GetDiagField and GetDiagRec retrieve information from a diagnostics area. The application identifies which diagnostics area is to be accessed by providing the handle of the relevant resource as an input argument. The routines return a result code but do not modify the identified diagnostics area.

The Error routine also retrieves information from a diagnostics area. The Error routine retrieves the status records in the identified diagnostics area one at a time but does not permit already processed status records to be retrieved. Error returns a result code but does not modify the identified diagnostics area.

The RowCount routine retrieves the ROW\_COUNT field from the diagnostics area for the specified statement handle. RowCount returns a result code and may cause exception or completion conditions to be raised which cause status records to be generated.

A CLI diagnostics area comprises the fields specified in Table 2, "Fields in SQL/CLI diagnostics areas".

Table 2—Fields in SQL/CLI diagnostics areas

Field	Data type
<b>Header fields</b>	
DYNAMIC_FUNCTION	CHARACTER VARYING ( <i>L</i> )
DYNAMIC_FUNCTION_CODE	INTEGER
MORE	INTEGER
NUMBER	INTEGER
RETURNCODE	SMALLINT
ROW_COUNT	INTEGER
<p><b>Where</b> <i>L</i> is an implementation-defined integer not less than 128 and <i>L1</i> is an implementation-defined integer not less than 254.</p>	

Table 2—Fields in SQL/CLI diagnostics areas (Cont.)

Field	Data type
<b>Header fields</b>	
TRANSACTIONS_COMMITTED	INTEGER
TRANSACTIONS_ROLLED_BACK	INTEGER
TRANSACTION_ACTIVE	INTEGER
Implementation-defined header field	Implementation-defined
<b>Fields in status records</b>	
CATALOG_NAME	CHARACTER VARYING ( <i>L</i> )
CLASS_ORIGIN	CHARACTER VARYING ( <i>LI</i> )
COLUMN_NAME	CHARACTER VARYING ( <i>L</i> )
COLUMN_NUMBER	INTEGER
CONDITION_IDENTIFIER	CHARACTER VARYING ( <i>L</i> )
CONDITION_NUMBER	INTEGER
CONNECTION_NAME	CHARACTER VARYING ( <i>L</i> )
CONSTRAINT_CATALOG	CHARACTER VARYING ( <i>L</i> )
CONSTRAINT_NAME	CHARACTER VARYING ( <i>L</i> )
CONSTRAINT_SCHEMA	CHARACTER VARYING ( <i>L</i> )
CURSOR_NAME	CHARACTER VARYING ( <i>L</i> )
MESSAGE_LENGTH	INTEGER
MESSAGE_OCTET_LENGTH	INTEGER
MESSAGE_TEXT	CHARACTER VARYING ( <i>LI</i> )
NATIVE_CODE	INTEGER
PARAMETER_MODE	CHARACTER VARYING ( <i>L</i> )
PARAMETER_NAME	CHARACTER VARYING ( <i>L</i> )
PARAMETER_ORDINAL_POSITION	INTEGER
ROUTINE_CATALOG	CHARACTER VARYING ( <i>L</i> )
ROUTINE_NAME	CHARACTER VARYING ( <i>L</i> )
ROUTINE_SCHEMA	CHARACTER VARYING ( <i>L</i> )
ROW_NUMBER	INTEGER
SCHEMA_NAME	CHARACTER VARYING ( <i>L</i> )
SERVER_NAME	CHARACTER VARYING ( <i>L</i> )
<b>Where</b> <i>L</i> is an implementation-defined integer not less than 128 and <i>LI</i> is an implementation-defined integer not less than 254.	

(Continued on next page)

Table 2—Fields in SQL/CLI diagnostics areas (Cont.)

Field	Data type
<b>Fields in status records</b>	
SQLSTATE	CHARACTER (5)
SPECIFIC_NAME	CHARACTER VARYING ( <i>L</i> )
SUBCLASS_ORIGIN	CHARACTER VARYING ( <i>LI</i> )
TABLE_NAME	CHARACTER VARYING ( <i>L</i> )
TRIGGER_CATALOG	CHARACTER VARYING ( <i>L</i> )
TRIGGER_NAME	CHARACTER VARYING ( <i>L</i> )
TRIGGER_SCHEMA	CHARACTER VARYING ( <i>L</i> )
Implementation-defined status field	Implementation-defined
<p><b>Where</b> <i>L</i> is an implementation-defined integer not less than 128 and <i>LI</i> is an implementation-defined integer not less than 254.</p>	

All diagnostics area fields specified in other parts of ISO/IEC 9075 that are not included in this table are not applicable to SQL/CLI.

### 4.3.1 Setting of ROW\_NUMBER and COLUMN\_NUMBER fields

Unless explicitly set to a different value in this part of ISO/IEC 9075, the ROW\_NUMBER and COLUMN\_NUMBER fields in a diagnostic record are always 0 (zero).

## 4.4 Miscellaneous characteristics

### 4.4.1 Handles

The AllocHandle routine returns a handle, that uniquely identifies the allocated resource. Although the data type for a handle parameter is INTEGER, its value has no meaning in any other context and should not be used as a numeric operand or modified in any way.

In general, if the related resource cannot be allocated, then a handle value of zero is returned. However, even if a resource has been successfully allocated, processing of that resource can subsequently fail due to memory constraints as follows:

- If additional memory is required but is not available, then an exception condition is raised: *CLI-specific condition — memory allocation error.*
- If previously allocated memory cannot be accessed, then an exception condition is raised: *CLI-specific condition — memory management error.*

NOTE 2 – No diagnostic information is generated in this case.

The validity of a handle in a compilation unit other than the one in which the identified resource was allocated is implementation-defined.

Specifying (the address of) a valid handle as the output handle of AllocHandle does not have the effect of reinitializing the identified resource. Instead, a new resource is allocated and a new handle value overwrites the old one.

#### 4.4.2 Null terminated strings

An input character string provided by the application may be terminated by the implementation-defined null character that terminates C character strings. If this technique is used, the application may set the associated length argument to either the length of the string excluding the null terminator or to  $-3$ , indicating NULL TERMINATED.

If the NULL TERMINATION attribute for the SQL-environment is *true*, then all output character strings returned by the implementation are terminated by the implementation-defined null character that terminates C character strings. If the NULL TERMINATION attribute is *false*, then output character strings are not null terminated.

#### 4.4.3 Null pointers

If the standard programming language of the invoking host program supports pointers, then the host program may provide a zero-valued pointer, referred to as a null pointer, in the following circumstances:

- In lieu of an output argument that is to receive the length of a returned character string. This indicates that the application wishes to prohibit the return of this information.
- In lieu of other output arguments where specifically allowed by this part of ISO/IEC 9075. This indicates that the application wishes to prohibit the return of this information.
- In lieu of input arguments where specifically allowed by this part of ISO/IEC 9075. The semantics of such a specification depend on the context.

If the host program provides a null pointer in any other circumstances, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.

If the NULL TERMINATION attribute for the SQL-environment is *false*, then specifying a zero buffer size for an output argument is equivalent to specifying a null pointer for that output argument.

#### 4.4.4 Environment attributes

Environment attributes are associated with each allocated SQL-environment and affect the behavior of CLI functions in that SQL-environment.

The GetEnvAttr routine enables the application to determine the current value of a specific attribute. For attributes that may be set by the user, the SetEnvAttr routine enables the application to set the value of a specific attribute. Attribute values may be set by the application whenever there are no SQL-connections allocated within the SQL-environment.

Table 15, “Codes used for environment attributes”, and Table 19, “Data types of attributes”, in Subclause 5.14, “Other tables associated with CLI”, indicate for each attribute its name, code value, data type, possible values, and whether the attribute may be set using SetEnvAttr.

The NULL TERMINATION attribute determines whether output character strings are null terminated by the implementation. The attribute is set to *true* when an SQL-environment is allocated.

## 4.4 Miscellaneous characteristics

### 4.4.5 Connection attributes

Connection attributes are associated with each allocated SQL-connection and affect the behavior of CLI functions operating in the context of that allocated SQL-connection.

The GetConnectAttr routine enables the application to determine the current value of a specific attribute. For attributes that may be set by the user, the SetConnectAttr routine enables the application to set the value of a specific attribute.

Table 16, “Codes used for connection attributes”, and Table 19, “Data types of attributes”, in Subclause 5.14, “Other tables associated with CLI”, indicate for each attribute its name, code value, data type, possible values and whether the attribute may be set using SetConnectAttr.

The POPULATE IPD attribute determines whether the implementation will populate the implementation parameter descriptor with a descriptor for the <dynamic parameter specification>s when an SQL-statement is prepared or executed immediately. The attribute is automatically set each time an SQL-connection is established for the allocated SQL-connection.

The SAVEPOINT NAME and SAVEPOINT NUMBER connection attributes specify the savepoint to be referenced in an invocation of the EndTran routine that uses the SAVEPOINT NAME COMMIT, SAVEPOINT NAME RELEASE, or SAVEPOINT NUMBER COMMIT, SAVEPOINT NUMBER RELEASE CompletionType, respectively. The SAVEPOINT NAME attribute is set to a zero-length string and the SAVEPOINT NUMBER attribute is set to 0 (zero) when the SQL-connection is allocated.

### 4.4.6 Statement attributes

Statement attributes are associated with each allocated SQL-statement and affect the processing of SQL-statements under that allocated SQL-statement.

The GetStmtAttr routine enables the application to determine the current value of a specific attribute. For attributes that may be set by the user, the SetStmtAttr routine enables the application to set the value of a specific attribute.

Table 17, “Codes used for statement attributes”, and Table 19, “Data types of attributes”, in Subclause 5.14, “Other tables associated with CLI”, indicate for each attribute its name, code value, data type, possible values, and whether the attribute may be set by using SetStmtAttr.

The APD HANDLE attribute is the value of the handle of the current application parameter descriptor for the allocated SQL-statement. The attribute is set to the value of the handle of the automatically allocated application parameter descriptor when the SQL-statement is allocated.

The ARD HANDLE attribute is the value of the handle of the current application row descriptor for the allocated SQL-statement. The attribute is set to the value of the handle of the automatically allocated application row descriptor when the SQL-statement is allocated.

The IPD HANDLE attribute is the value of the handle of the implementation parameter descriptor associated with the allocated SQL-statement. The attribute is set to the value of the handle of the automatically allocated implementation parameter descriptor when the SQL-statement is allocated.

The IRD HANDLE attribute is the value of the handle of the implementation row descriptor associated with the allocated SQL-statement. The attribute is set to the value of the handle of the automatically allocated implementation row descriptor when the SQL-statement is allocated.

The CURSOR SCROLLABLE attribute determines the *scrollability* implicitly declared when Execute or ExecDirect are invoked. The attribute is set to NONSCROLLABLE when the statement is allocated. The CURSOR SENSITIVITY attribute determines the *sensitivity* to changes of the cursor implicitly declared when Execute or ExecDirect are invoked. The attribute is set to ASENSITIVE when the statement is allocated.

The CURSOR HOLDABLE attribute determines the *holdability* of the cursor implicitly declared when Execute or ExecDirect are invoked. The attribute is set to HOLDABLE or NONHOLDABLE when the statement is allocated, depending on the values of the CURSOR COMMIT BEHAVIOR item used by the GetInfo routine.

The statement attribute CURRENT OF POSITION identifies the row in the rowset to which a positioned update or delete operation applies. This is set to 1 (one) when a statement is initially allocated. It is reset to 1 (one) whenever Fetch or FetchScroll are successfully executed.

The NEST DESCRIPTOR attribute determines whether nested descriptor items are permitted in a CLI descriptor. Nested descriptor items are used to describe ROW and ARRAY data types. The attribute is set to FALSE when the statement is allocated.

#### 4.4.7 CLI descriptor areas

A CLI descriptor area provides an interface for a description of <dynamic parameter specification>s, <dynamic parameter specification> values, resultant columns of a <dynamic select statement> or <dynamic single row select statement>, or the <target specification>s for the resultant columns.

Each descriptor area comprises header fields and zero or more item descriptor areas. The header fields are specified in Table 6, "Fields in SQL/CLI row and parameter descriptor areas". The header fields include a COUNT fields that indicates the number of item descriptor areas and an ALLOC\_TYPE field that indicated whether the CLI descriptor area was allocated by the user or automatically allocated by the implementation.

The header fields include ARRAY\_SIZE, ARRAY\_STATUS\_POINTER, and ROWS\_PROCESSED\_POINTER. These three fields are used to support the fetching of multiple rows with one invocation of Fetch or FetchScroll.

Each CLI item descriptor area consists of the fields specified in Table 6, "Fields in SQL/CLI row and parameter descriptor areas", in Subclause 5.13, "Description of CLI item descriptor areas".

The CLI descriptor areas for the four interface types are referred to as an implementation parameter descriptor (IPD), an application parameter descriptor (APD), an implementation row descriptor (IRD), and an application row descriptor (ARD), respectively.

When an SQL-statement is allocated, a CLI descriptor area of each type is automatically allocated by the implementation. The ALLOC\_TYPE fields for these CLI descriptor areas are set to indicate AUTOMATIC. CLI descriptor areas allocated by the user have their ALLOC\_TYPE fields set to indicate USER, and can only be used as an APD or ARD. The handle values of the IPD, IRD, current APD, and current ARD are attributes of the allocated SQL-statement. The application can determine the current values of these attributes by using the routine GetStmtAttr. The current APD and ARD are initially the automatically-allocated APD and ARD, respectively, but can subsequently be changed by changing the corresponding attribute value using the routine SetStmtAttr.

The routines GetDescField and GetDescRec enable information to be retrieved from any CLI descriptor area. The routines SetDescField and SetDescRec enable information to be set in any CLI descriptor area except an IRD. The routine BindCol implicitly sets information in the current ARD. The routine BindParameter implicitly sets information in the current APD and the current IPD. The CopyDesc routine enables the contents of any CLI descriptor area to be copied to any CLI descriptor area except an IRD.

#### 4.4 Miscellaneous characteristics

NOTE 3 – Although there is no need to set a DATA\_POINTER field in the IPD, to align with the consistency check that applies in the case of an APD or ARD, setting this field causes the item descriptor area to be validated.

#### 4.4.8 Obtaining diagnostics during multi-row fetch

When Fetch or FetchScroll is used to fetch a rowset, exceptions or warnings may be raised during the retrieval of one or more rows in the rowset. The status of each row (that is, information about whether each row in the rowset was successfully retrieved or not) is available in the array addressed by the ARRAY\_STATUS\_POINTER field of the applicable IRD. The cardinality of this array is the same as the ARRAY\_SIZE field of the corresponding ARD; for each row in the rowset, the corresponding element of this array has one of the following values:

- A value of 0 (zero), indicates **Row success**, meaning that the row was fetched successfully.
- A value of 6, indicates **Row success with information**, meaning that the row was fetched successfully, but a completion condition was raised: *warning*.
- A value of 3, indicates **No row**, meaning that there is no row at this position in the rowset. This condition occurs when a partial rowset is retrieved because the result set ended.
- A value of 5, indicates **Row error**, meaning that the row was not fetched successfully and an exception condition was raised.

Each **Row success with information** or **Row Error** generates one or more status records in the diagnostics area. The ROW\_NUMBER field for each status record has the value of the row position within the rowset to which this status record corresponds.

#### 4.5 Client-server operation

New paragraph If the execution of a CLI routine causes the implicit or explicit execution of an <SQL procedure statement> by an SQL-server, diagnostic information is passed in an implementation-dependent manner to the SQL-client and then into the appropriate diagnostics area. The effect on diagnostic information of incompatibilities between the character repertoires supported by the SQL-client and the SQL-server is implementation-dependent.

## 5 Call-Level Interface specifications

### 5.1 <CLI routine>

#### Function

Describe SQL/CLI routines in a generic fashion.

#### Format

```

<CLI routine> ::=
    <CLI routine name>
    <CLI parameter list>
    [ <CLI returns clause> ]

<CLI routine name> ::= <CLI name prefix><CLI generic name>

<CLI name prefix> ::=
    <CLI by-reference prefix>
    | <CLI by-value prefix>

<CLI by-reference prefix> ::= SQLR

<CLI by-value prefix> ::= SQL

<CLI generic name> ::=
    AllocConnect
    | AllocEnv
    | AllocHandle
    | AllocStmt
    | BindCol
    | BindParameter
    | Cancel
    | CloseCursor
    | ColAttribute
    | ColumnPrivileges
    | Columns
    | Connect
    | CopyDesc
    | DataSources
    | DescribeCol
    | Disconnect
    | EndTran
    | Error
    | ExecDirect
    | Execute
    | Fetch
    | FetchScroll
    | ForeignKeys
    | FreeConnect
    | FreeEnv
    | FreeHandle
    | FreeStmt
    | GetConnectAttr
    | GetCursorName

```

## 5.1 &lt;CLI routine&gt;

| GetData  
 | GetDescField  
 | GetDescRec  
 | GetDiagField  
 | GetDiagRec  
 | GetEnvAttr  
 | GetFeatureInfo  
 | GetFunctions  
 | GetInfo  
 | GetLength  
 | GetParamData  
 | GetPosition  
 | GetSessionInfo  
 | GetStmtAttr  
 | GetSubString  
 | GetTypeInfo  
 | MoreResults  
 | NextResult  
 | NumResultCols  
 | ParamData  
 | Prepare  
 | PrimaryKeys  
 | PutData  
 | RowCount  
 | SetConnectAttr  
 | SetCursorName  
 | SetDescField  
 | SetDescRec  
 | SetEnvAttr  
 | SetStmtAttr  
 | SpecialColumns  
 | StartTran  
 | TablePrivileges  
 | Tables  
 | <implementation-defined CLI generic name>

<CLI parameter list> ::=  
 <left paren> <CLI parameter declaration>  
 [ { <comma> <CLI parameter declaration> }... ] <right paren>

<CLI parameter declaration> ::=  
 <CLI parameter name> <CLI parameter mode> <CLI parameter data type>

<CLI parameter name> ::= !! See the individual CLI routine definitions

<CLI parameter mode> ::=  
 IN  
 | OUT  
 | DEFIN  
 | DEFOUT  
 | DEF

<CLI parameter data type> ::=  
 INTEGER  
 | SMALLINT  
 | ANY  
 | CHARACTER <left paren> <length> <right paren>

<CLI returns clause> ::= RETURNS SMALLINT

<implementation-defined CLI generic name> ::= !! See the Syntax Rules

## Syntax Rules

- 1) <CLI routine> is a pre-defined routine written in a standard programming language that is invoked by a compilation unit of the same standard programming language. Let *HL* be that standard programming language. *HL* shall be one of Ada, C, COBOL, Fortran, MUMPS, Pascal, or PL/I.
- 2) <CLI routine> that contains a <CLI returns clause> is called a *CLI function*. A <CLI routine> that does not contain a <CLI returns clause> is called a *CLI procedure*.
- 3) For each CLI function *CF*, there is a corresponding CLI procedure *CP*, with the same <CLI routine name>. The <CLI parameter list> for *CP* is the same as the <CLI parameter list> for *CF* but with the following additional <CLI parameter declaration>:

```
ReturnCode OUT SMALLINT
```

- 4) *HL* shall support either the invocation of *CF* or the invocation of *CP*. It is implementation-defined which is supported.
- 5) Case:
  - a) If <CLI parameter mode> is IN, then the parameter is an *input parameter*. The value of an input argument is established when a CLI routine is invoked.
  - b) If <CLI parameter mode> is OUT, then the parameter is an *output parameter*. The value of an output argument is established when a CLI routine is executed.
  - c) If <CLI parameter mode> is DEFIN, then the parameter is a *deferred input parameter*. The value of a deferred input argument for a CLI routine *R* is not established when *R* is invoked, but subsequently during the execution of a related CLI routine.
  - d) If <CLI parameter mode> is DEFOUT, then the parameter is a *deferred output parameter*. The value of a deferred output argument for a CLI routine *R* is not established by the execution of *R* but subsequently by the execution of a related CLI routine.
  - e) If <CLI parameter mode> is DEF, then the parameter is a *deferred parameter*. The value of a deferred argument for a CLI routine *R* is not established by the execution of *R* but subsequently by the execution of a related CLI routine.
- 6) The value of an output, deferred output, deferred input, or deferred parameter is an address. It is either a non-pointer host variable passed by reference or a pointer host variable passed by value.
- 7) A *by-value version* of a CLI routine is a version that expects each of its non-character input parameters to be provided as actual values. A *by-reference version* of a CLI routine is a version that expects each of its input parameters to be provided as an address. By-value and by-reference versions of the CLI routines shall be supported according to Table 3, "Supported calling conventions of SQL/CLI routines by language".

## 5.1 &lt;CLI routine&gt;

Table 3—Supported calling conventions of SQL/CLI routines by language

Language	By-value	By-reference
Ada (ISO 8652)	Optional	Required
C (ISO/IEC 9899)	Required	Optional
COBOL (ISO 1989)	Optional	Required
Fortran (ISO/IEC 1539)	Not supported	Required
MUMPS (ISO/IEC 11756)	Optional	Required
Pascal (ISO/IEC 7185 and ISO/IEC 10206)	Optional	Required
PL/I (ISO 6160)	Optional	Required

- 8) If a <CLI routine> is a by-reference routine, then its <CLI routine name> shall contain a <CLI by-reference prefix>. Otherwise, its <CLI routine name> shall contain a <CLI by-value prefix>.
- 9) The <implementation-defined CLI generic name> for an implementation-defined CLI function shall be different from the <CLI generic name> of any other CLI function. The <implementation-defined CLI generic name> for an implementation-defined CLI procedure shall be different from the <CLI generic name> of any other CLI procedure.
- 10) Any <CLI routine name> that cannot be used by an implementation because of its length or because it is made identical to some other <CLI routine name> by truncation is effectively replaced with an abbreviated name according to the following rules:
  - a) Any <CLI by-value prefix> remains unchanged.
  - b) Any <CLI by-reference prefix> is replaced by SQR.
  - c) The <CLI generic name> is replaced by an abbreviated version according to Table 4, "Abbreviated SQL/CLI generic names".

Table 4—Abbreviated SQL/CLI generic names

Generic Name	Abbreviation
AllocConnect	AC
AllocEnv	AE
AllocHandle	AH
AllocStmt	AS
BindCol	BC
BindParameter	BP
Cancel	CAN
CloseCursor	CC
ColAttribute	CO
ColumnPrivileges	CP

Table 4—Abbreviated SQL/CLI generic names (Cont.)

Generic Name	Abbreviation
Columns	COL
Connect	CON
CopyDesc	CD
DataSources	DS
DescribeCol	DC
Disconnect	DIS
EndTran	ET
Error	ER
ExecDirect	ED
Execute	EX
Fetch	FT
FetchScroll	FTS
ForeignKeys	FK
FreeConnect	FC
FreeEnv	FE
FreeHandle	FH
FreeStmt	FS
GetConnectAttr	GCA
GetCursorName	GCN
GetData	GDA
GetDescField	GDF
GetDescRec	GDR
GetDiagField	GXF
GetDiagRec	GXR
GetEnvAttr	GEA
GetFeatureInfo	GFI
GetFunctions	GFU
GetInfo	GI
GetLength	GLN
GetParamData	GPD
GetPosition	GPO
GetSessionInfo	GSI
GetStmtAttr	GSA
GetSubString	GSB

## 5.1 &lt;CLI routine&gt;

Table 4—Abbreviated SQL/CLI generic names (Cont.)

Generic Name	Abbreviation
GetTypeInfo	GTI
MoreResults	MR
NextResult	NR
NumResultCols	NRC
ParamData	PRD
Prepare	PR
PrimaryKeys	PK
PutData	PTD
RowCount	RC
SetConnectAttr	SCA
SetCursorName	SCN
SetDescField	SDF
SetDescRec	SDR
SetEnvAttr	SEA
SetStmtAttr	SSA
SpecialColumns	SC
StartTran	STN
TablePrivileges	TP
Tables	TAB
Implementation-defined CLI routine	Implementation-defined abbreviation

- 11) Let  $CR$  be a <CLI routine> and let  $RN$  be its <CLI routine name>. Let  $RNU$  be the value of  $UPPER(RN)$ .
- Case:
- If  $HL$  supports case sensitive routine names, then the name used for the invocation of  $CR$  shall be  $RN$ .
  - If  $HL$  does not support <simple Latin lower case letter>s, then the name used for the invocation of  $CR$  shall be  $RNU$ .
  - If  $HL$  does not support case sensitive routine names, then the name used for the invocation of  $CR$  shall be  $RN$  or  $RNU$ .
- 12) Let *operative data type correspondence table* be the data type correspondence table for  $HL$  as specified in Subclause 5.15, "Data type correspondences". Refer to the two columns of the operative data type correspondence table as the "SQL data type column" and the "host data type column".

- 13) Let  $TI$ ,  $TS$ ,  $TC$ , and  $TV$  be the types listed in the host data type column for the rows that contains INTEGER, SMALLINT, CHARACTER( $L$ ) and CHARACTER VARYING( $L$ ), respectively, in the SQL data type column.
- a) If  $TS$  is “None”, then let  $TS = TI$ .
  - b) If  $TC$  is “None”, then let  $TC = TV$ .
  - c) For each parameter  $P$ ,  
Case:
    - i) If the CLI parameter data type is INTEGER, then the type of the corresponding argument shall be  $TI$ .
    - ii) If the CLI parameter data type is SMALLINT, then the type of the corresponding argument shall be  $TS$ .
    - iii) If the CLI parameter data type is CHARACTER( $L$ ), then the type of the corresponding argument shall be  $TC$ .
    - iv) If the CLI parameter data type is ANY, then  
Case:
      - 1) If  $HL$  is  $C$ , then the type of the corresponding argument shall be “void \*”.
      - 2) Otherwise, the type of the corresponding argument shall be any type (other than “None”) listed in the host data type column.
  - d) If the CLI routine is a CLI function, then the type of the returned value is  $TS$ .

### Access Rules

None.

### General Rules

- 1) The rules for invocation of a <CLI routine> are specified in Subclause 5.2, “<CLI routine> invocation”.

## 5.2 <CLI routine> invocation

### Function

Specify the rules for invocation of a <CLI routine>.

### Syntax Rules

- 1) Let *HL* be the standard programming language of the invoking host program.
- 2) A CLI function or CLI procedure is invoked by the *HL* mechanism for invoking functions or procedures, respectively.
- 3) Let *RN* be the <CLI routine name> of the <CLI routine> invoked by the host program. The number of arguments provided in the invocation shall be the same as the number of <CLI parameter declaration>s for *RN*.
- 4) Let *DA* be the data type of the *i*-th argument in the invocation and let *DP* be the <CLI parameter data type> of the *i*-th <CLI parameter declaration> of *RN*. *DA* shall be the *HL* equivalent of *DP* as specified by the rules of Subclause 5.1, “<CLI routine>”.

### General Rules

- 1) If the value of any input argument provided by the host program falls outside the set of allowed values of the data type of the parameter, or if the value of any output argument resulting from the execution of the <CLI routine> falls outside the set of values supported by the host program for that parameter, then the effect is implementation-defined.
- 2) Let *GRN* be the <CLI generic name> of *RN*.
- 3) When the <CLI routine> is called by the host program:
  - a) The values of all input arguments to *RN* are established.
  - b) Case:
    - i) If *RN* is a CLI routine with a statement handle as an input parameter, *RN* has no accompanying handle type parameter, and *GRN* is not 'Error', then:
      - 1) If the statement handle does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*. Otherwise, let *S* be the allocated SQL-statement identified by the statement handle.
      - 2) If *GRN* is not 'Cancel', then the diagnostics area associated with *S* is emptied.
      - 3) Let *C* be the allocated SQL-connection with which *S* is associated.
      - 4) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*. Otherwise, let *EC* be the established SQL-connection associated with *C*.
      - 5) If *EC* is not the current connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant connection.

- 6) If *GRN* is neither 'Cancel' nor 'ParamData' nor 'PutData' and there is a deferred parameter number associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 7) *RN* is invoked.
- ii) If *RN* is a CLI routine with a descriptor handle as an input parameter and *RN* has no accompanying handle type parameter and *GRN* is not 'CopyDesc', then:
- 1) If the descriptor handle does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*. Otherwise, let *D* be the allocated CLI descriptor area identified by the descriptor handle.
  - 2) The diagnostics area associated with *D* is emptied.
  - 3) Let *C* be the allocated SQL-connection with which *D* is associated.
  - 4) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*. Otherwise, let *EC* be the established SQL-connection associated with *C*.
  - 5) If *EC* is not the current connection, then the General Rules of Subclause 5.3, "Implicit set connection", are applied to *EC* as the dormant connection.
  - 6) *RN* is invoked.
- iii) Otherwise, *RN* is invoked.
- 4) Case:
- a) If the <CLI routine> is a CLI function, then:
    - i) The values of all output arguments are established.
    - ii) Let *RC* be the return value.
  - b) If the <CLI routine> is a CLI procedure, then:
    - i) The values of all output arguments are established except for the argument associated with the ReturnCode parameter.
    - ii) Let *RC* be the argument associated with the ReturnCode parameter.
- 5) Case:
- a) If *RN* did not complete execution because it requires more input data, then:
    - i) *RC* is set to indicate **Data needed**.
    - ii) An exception condition is raised: *CLI-specific condition — dynamic parameter value needed*.
  - b) If *RN* executed successfully, then:
    - i) Either a completion condition is raised: *successful completion*, or a completion condition is raised: *warning*, or a completion condition is raised: *no data*.

- ii) Case:
  - 1) If a completion condition is raised: *successful completion*, then *RC* is set to indicate **Success**.
  - 2) If a completion condition is raised: *warning*, then *RC* is set to indicate **Success with information**.
  - 3) If a completion condition is raised: *no data*, then *RC* is set to indicate **No data found**.
- c) If *RN* did not execute successfully, then:
  - i) All changes made to SQL-data or schemas by the execution of *RN* are canceled.
  - ii) One or more exception conditions are raised as determined by the General Rules of this and other Subclauses of this part of ISO/IEC 9075 or by implementation-defined rules.
- iii) Case:
  - 1) If an exception condition is raised: *CLI-specific condition — invalid handle*, then *RC* is set to indicate **Invalid handle**.
  - 2) Otherwise, *RC* is set to indicate **Error**.
- 6) Case:
  - a) If *GRN* is neither 'Error', 'GetDiagField', nor 'GetDiagRec' and *RC* indicates neither **Invalid handle** nor **Data needed**, then diagnostic information resulting from the execution of *RN* is placed into the appropriate diagnostics area as specified in Subclause 4.2, "Return codes", and Subclause 4.3, "Diagnostics areas in SQL/CLI".
  - b) Otherwise, no diagnostics area is updated.

## 5.3 Implicit set connection

### Function

Specify the rules for an implicit SET CONNECTION statement.

### General Rules

- 1) Let *DC* be a dormant SQL-connection specified in an application of this Subclause.
- 2) If an SQL-transaction is active for the current SQL-connection and the implementation does not support transactions that affect more than one SQL-server, then an exception condition is raised: *feature not supported — multiple server transactions*.
- 3) If *DC* cannot be selected, then an exception condition is raised: *connection exception — connection failure*.
- 4) The current SQL-connection and current SQL-session become a dormant SQL-connection and a dormant SQL-session, respectively. The SQL-session context information is preserved and is not affected in any way by operations performed over the selected SQL-connection.  
NOTE 4 – The SQL-session context information is defined in Subclause 4.34, "SQL-sessions", in ISO/IEC 9075-2.
- 5) *DC* becomes the current SQL-connection and the SQL-session associated with *DC* becomes the current SQL-session. All SQL-session context information is restored to the same state as at the time *DC* became dormant.  
NOTE 5 – The SQL-session context information is defined in Subclause 4.34, "SQL-sessions", in ISO/IEC 9075-2.
- 6) The SQL-server for the subsequent execution of SQL-statements via CLI routine invocations is set to that of the current SQL-connection.

## 5.4 Implicit cursor

## 5.4 Implicit cursor

## Function

Specify the rules for an implicit DECLARE CURSOR and OPEN statement.

## General Rules

- 1) Let *SS* and *AS* be a *SELECT SOURCE* and *ALLOCATED STATEMENT* specified in an application of this Subclause.
- 2) If there is no cursor associated with *AS*, then a cursor is associated with *AS* and the cursor name associated with *AS* becomes the name of the cursor.
- 3) The General Rules of Subclause 5.6, "Implicit EXECUTE USING and OPEN USING clauses", are applied to 'OPEN', *SS*, and *AS* as *TYPE*, *SOURCE*, and *ALLOCATED STATEMENT*, respectively.
- 4) If the value of the CURSOR SCROLLABLE attribute of *AS* is SCROLLABLE, then let *CT* be 'SCROLL'; otherwise, let *CT* be an empty string.
- 5) Case:
  - a) If the value of the CURSOR SENSITIVITY attribute of *AS* is INSENSITIVE, then let *CS* be 'INSENSITIVE'.
  - b) If the value of the CURSOR SENSITIVITY attribute of *AS* is SENSITIVE, then let *CS* be 'SENSITIVE'.
  - c) Otherwise, let *CS* be 'ASENSITIVE'.
- 6) If the value of the CURSOR HOLDABLE attribute of *AS* is HOLDABLE, then let *CH* be 'WITH HOLD'; otherwise, let *CH* be an empty string.
- 7) Let *CN* be the name of the cursor associated with *AS* and let *CR* be the following <declare cursor>:
 

```
DECLARE CN CS CT CURSOR CH FOR SS
```
- 8) Cursor *CN* is opened in the following steps:
  - a) A copy of *SS* is effectively created in which:
    - i) Each <dynamic parameter specification> is replaced by the value of the corresponding dynamic parameter.
    - ii) Each <value specification> generally contained in *SS* that is CURRENT\_USER, CURRENT\_ROLE, SESSION\_USER or SYSTEM\_USER is replaced by the value resulting from evaluation of CURRENT\_USER, CURRENT\_ROLE, SESSION\_USER, or SYSTEM\_USER, respectively, with all such evaluations effectively done at the same instant in time.
    - iii) Each <datetime value function> generally contained in *SS* is replaced by the value resulting from evaluation of that <datetime value function>, with all such evaluations effectively done at the same instant in time.

- iv) Each <value specification> generally contained in *S* that is CURRENT\_PATH is replaced by the value resulting from evaluation of CURRENT\_PATH, with all such evaluations effectively done at the same instant in time.
- b) Let *T* be the table specified by the copy of *SS*.
- c) A table descriptor for *T* is effectively created.
- d) The General Rules of Subclause 14.1, "<declare cursor>", in ISO/IEC 9075-2 are applied to *CR*.
- e) Case:
  - i) If *CR* specifies INSENSITIVE, then a copy of *T* is effectively created and cursor *CN* is placed in the open state and its position is before the first row of the copy of *T*.
  - ii) Otherwise, cursor *CN* is placed in the open state and its position is before the first row of *T*.
- 9) If *CR* specifies INSENSITIVE, and the implementation is unable to guarantee that significant changes will be invisible through *CR* during the SQL-transaction in which *CR* is opened and every subsequent SQL-transaction during which it may be held open, then an exception condition is raised: *cursor sensitivity exception — request rejected*.
- 10) If *CR* specifies SENSITIVE, and the implementation is unable to guarantee that significant changes will be visible through *CR* during the SQL-transaction in which *CR* is opened, then an exception condition is raised: *cursor sensitivity exception — request rejected*.  
NOTE 6 – The visibility of significant changes through a sensitive holdable cursor during a subsequent SQL-transaction is implementation-defined.
- 11) Whether an implementation is able to disallow significant changes that would not be visible through a currently open cursor is implementation-defined.

## 5.5 Implicit DESCRIBE USING clause

## 5.5 Implicit DESCRIBE USING clause

**Function**

Specify the rules for an implicit DESCRIBE USING clause.

**General Rules**

- 1) Let *S* and *AS* be a *SOURCE* and an *ALLOCATED STATEMENT* specified in the rules of this Subclause.
- 2) Let *IRD* and *IPD* be the implementation row descriptor and implementation parameter descriptor, respectively, associated with *AS*.
- 3) Let *HL* be the standard programming language of the invoking host program.
- 4) The value of *DYNAMIC\_FUNCTION* and *DYNAMIC\_FUNCTION\_CODE* in the *IRD* and *IPD* are respectively a character string representation of the prepared statement and a numeric code that identifies the prepared statement.
- 5) A representation of the column descriptors of the <select list> columns for the prepared statement is stored in *IRD* as follows:
  - a) Case:
    - i) If there is a select source associated with *AS*, then:
      - 1) Let *TBL* be the table defined by *S* and let *D* be the degree of *TBL*.
 

Case:

        - A) If the value of the statement attribute *NEST\_DESCRIPTOR* is *true*, then let  $NS_i$ ,  $1 \text{ (one)} \leq i \leq D$ , be the number of subordinate descriptors of the descriptor for the *i*-th column of *T*.
        - B) Otherwise, let  $NS_i$ ,  $1 \text{ (one)} \leq i \leq D$ , be 0 (zero).
      - 2) *TOP\_LEVEL\_COUNT* is set to *D*. If *D* is 0 (zero), then let *TD* be 0 (zero); otherwise, let *TD* be  $D + \sum_{i=1}^D (NS_i)$ . *COUNT* is set to *TD*.
      - 3) Let *SL* be the collection of <select list> columns of *TBL*.
      - 4) Case:
        - A) If some subset of *SL* is the primary key of *TBL*, then *KEY\_TYPE* is set to 1 (one).
        - B) If some subset of *SL* is the preferred key of *TBL*, then *KEY\_TYPE* is set to 2.
        - C) Otherwise, *KEY\_TYPE* is set to 0 (zero).
    - ii) Otherwise:
      - 1) Let *D* be 0 (zero). Let *TD* be 0 (zero).
      - 2) *KEY\_TYPE* is set to 0 (zero).

- b) If  $TD$  is zero, then no item descriptor areas are set. Otherwise, the first  $TD$  item descriptor areas are set so that the  $i$ -th item descriptor area contains the descriptor of the  $j$ -th column of  $TBL$  such that:
- i) The descriptor for the first such column is assigned to the first descriptor area.
  - ii) The descriptor for the  $j+1$ -th column is assigned to the  $i+NS_{j+1}$ -th item descriptor area.
  - iii) If the value of the statement attribute NEST DESCRIPTOR is *true*, then the implicitly ordered subordinate descriptors for the  $j$ -th column are assigned to contiguous item descriptor areas starting at the  $i+1$ -th item descriptor area.
- c) The descriptor of a column consists of values for LEVEL, TYPE, NULLABLE, NAME, UNNAMED, KEY\_MEMBER, and other fields depending on the value of TYPE as described below. Those fields and fields that are not applicable for a particular value of TYPE are set to implementation-dependent values. The DATA\_POINTER, INDICATOR\_POINTER, and OCTET\_LENGTH\_POINTER fields are not relevant in this case.
- i) If the item descriptor area is set to a descriptor that is immediately subordinate to another whose LEVEL value is some value  $k$ , then LEVEL is set to  $k+1$ ; otherwise, LEVEL is set to 0 (zero).
  - ii) TYPE is set to a code as shown in Table 7, "Codes used for implementation data types in SQL/CLI", indicating the data type of the column or subordinate descriptor.
  - iii) Case:
    - 1) If the value of LEVEL is 0 (zero), then:
      - A) If the resulting column is possibly nullable, then NULLABLE is set to 1 (one); otherwise NULLABLE is set to 0 (zero).
      - B) If the column name is implementation-dependent, then NAME is set to the implementation-dependent name of the column and UNNAMED is set to 1 (one); otherwise, NAME is set to the <derived column> name for the column and UNNAMED is set to 0 (zero).
      - C) Case:
        - I) If a <select list> column  $C$  is a member of a primary or preferred key of  $TBL$ , then KEY\_MEMBER is set to 1 (one).
        - II) Otherwise, KEY\_MEMBER is set to 0 (zero).
    - 2) Otherwise:
      - A) NULLABLE is set to 1 (one).
      - B) Case:
        - I) If the item descriptor area describes a field of a row, then

## 5.5 Implicit DESCRIBE USING clause

Case:

- 1) If the name of the field is implementation-dependent, then NAME is set to the implementation-dependent name of the field and UNNAMED is set to 1 (one).
  - 2) Otherwise, NAME is set to the name of the field and UNNAMED is set to 0 (zero).
- II) Otherwise, UNNAMED is set to 1 (one) and NAME is set to an implementation-dependent value.
- C) KEY\_MEMBER is set to 0 (zero).
- iv) Case:
- 1) If TYPE indicates a <character string type>, then LENGTH is set to the length or maximum length in characters of the character string. OCTET\_LENGTH is set the maximum possible length in octets of the character string. If HL is C, then the lengths specified in LENGTH and OCTET\_LENGTH do not include the implementation-defined null character that terminates a C character string. CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, and CHARACTER\_SET\_NAME are set to the <character set name> of the character string's character set. COLLATION\_CATALOG, COLLATION\_SCHEMA, and COLLATION\_NAME are set to the <collation name> of the character string's collation.
  - 2) If TYPE indicates a <bit string type>, then LENGTH is set to the length or maximum length in bits of the bit string and OCTET\_LENGTH is set to the maximum possible length in octets of the bit string.
  - 3) If TYPE indicates a <binary large object string type>, then LENGTH and OCTET\_LENGTH are both set to the maximum length in octets of the binary large object string.
  - 4) If TYPE indicates an <exact numeric type>, then PRECISION and SCALE are set to the precision and scale of the exact numeric.
  - 5) If TYPE indicates an <approximate numeric type>, then PRECISION is set to the precision of the approximate numeric.
  - 6) If TYPE indicates a <datetime type>, then LENGTH is set to the length in positions of the datetime type, DATETIME\_INTERVAL\_CODE is set to a code as specified in Table 9, "Codes associated with datetime data types in SQL/CLI", to indicate the specific datetime data type and PRECISION is set to the <time precision> or <timestamp precision> if either is applicable.
  - 7) If TYPE indicates INTERVAL, then LENGTH is set to the length in positions of the interval type, DATETIME\_INTERVAL\_CODE is set to a code as specified in Table 10, "Codes associated with <interval qualifier> in SQL/CLI", to indicate the specific <interval qualifier>, DATETIME\_INTERVAL\_PRECISION is set to the <interval leading field precision>, and PRECISION is set to the <interval fractional seconds precision>, if applicable.

- 8) If TYPE indicates REF, then LENGTH and OCTET\_LENGTH are set to the length in octets of the <reference type>, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME are set to the <user-defined type name> of the <reference type>, and SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME are set to the qualified name of the referenceable base table.
- 9) If TYPE indicates USER-DEFINED TYPE, then USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME are set to the <user-defined type name> of the user-defined type. SPECIFIC\_TYPE\_CATALOG, SPECIFIC\_TYPE\_SCHEMA, and SPECIFIC\_TYPE\_NAME are set to the <user-defined type name> of the user-defined type and CURRENT\_TRANSFORM\_GROUP is set to the CURRENT\_TRANSFORM\_GROUP\_FOR\_TYPE for the user-defined type.
- 10) If TYPE indicates ROW, then DEGREE is set to the degree of the row type.
- 11) If TYPE indicates ARRAY, then CARDINALITY is set to the cardinality of the array type.
- 6) Let  $C$  be the allocated SQL-connection with which  $AS$  is associated.
- 7) If POPULATE IPD for  $C$  is false, then no further rules of this Subclause are applied.
- 8) If POPULATE IPD for  $C$  is true, then a descriptor for the <dynamic parameter specification> for the prepared statement is stored in  $IPD$  as follows:
- a) Let  $D$  be the number of <dynamic parameter specification>s in  $S$ .  
Case:
- i) If the value of the statement attribute NEST DESCRIPTOR is true, then let  $NS_i$ ,  $1 \text{ (one)} \leq i \leq D$ , be the number of subordinate descriptors of the descriptor for the  $i$ -th input dynamic parameter.
- ii) Otherwise, let  $NS_i$ ,  $1 \text{ (one)} \leq i \leq D$ , be 0 (zero).
- b) TOP\_LEVEL\_COUNT is set to  $D$ . If  $D$  is 0 (zero), then let  $TD$  be 0 (zero); otherwise, let  $TD$  be  $D + \sum_{i=1}^D (NS_i)$ . COUNT is set to  $TD$ .  
NOTE 7 – The KEY\_TYPE field is not relevant in this case.
- c) If  $TD$  is zero, then no item descriptor areas are set. Otherwise, the first  $TD$  item descriptor areas are set so that the  $i$ -th item descriptor area contains a descriptor of the  $j$ -th <dynamic parameter specification> such that:
- i) The descriptor for the first such <dynamic parameter specification> is assigned to the first descriptor area.
- ii) The descriptor for the  $j+1$ -th <dynamic parameter specification> is assigned to the  $i+NS_j+1$ -th item descriptor area.
- iii) If the value of the statement attribute NEST DESCRIPTOR is true, then the implicitly ordered subordinate descriptors for the  $j$ -th <dynamic parameter specification> are assigned to contiguous item descriptor areas starting at the  $i+1$ -th item descriptor area.

## 5.5 Implicit DESCRIBE USING clause

- d) The descriptor of a <dynamic parameter specification> consists of values for LEVEL, TYPE, NULLABLE, NAME, UNNAMED, PARAMETER\_MODE, PARAMETER\_ORDINAL\_POSITION, PARAMETER\_SPECIFIC\_CATALOG, PARAMETER\_SPECIFIC\_SCHEMA, PARAMETER\_SPECIFIC\_NAME, and other fields depending on the value of TYPE as described below. Those fields and fields that are not applicable for a particular value of TYPE are set to implementation-dependent values. The DATA\_POINTER, INDICATOR\_POINTER, OCTET\_LENGTH\_POINTER, RETURNED\_CARDINALITY\_POINTER, and KEY\_MEMBER fields are not relevant in this case.
- i) If the item descriptor area is set to a descriptor that is immediately subordinate to another whose LEVEL value is some value  $k$ , then LEVEL is set to  $k+1$ ; otherwise, LEVEL is set to 0 (zero).
  - ii) TYPE is set to a code as shown in Table 7, "Codes used for implementation data types in SQL/CLI", indicating the data type of the <dynamic parameter specification> or subordinate descriptor.
  - iii) NULLABLE is set to 1 (one).  
NOTE 8 – This indicates that the <dynamic parameter specification> can have the null value.
  - iv) KEY\_MEMBER is set to 0 (zero).
  - v) UNNAMED is set to 1 (one) and NAME is set to an implementation-dependent value.
  - vi) Case:
    - 1) If TYPE indicates a <character string type>, then LENGTH is set to the length or maximum length in characters of the character string. OCTET\_LENGTH is set the maximum possible length in octets of the character string. If HL is C, then the lengths specified in LENGTH and OCTET\_LENGTH do not include the implementation-defined null character that terminates a C character string. CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, and CHARACTER\_SET\_NAME are set to the <character set name> of the character string's character set. COLLATION\_CATALOG, COLLATION\_SCHEMA, and COLLATION\_NAME are set to the <collation name> of the character string's collation.
    - 2) If TYPE indicates a <bit string type>, then LENGTH is set to the length or maximum length in bits of the bit string and OCTET\_LENGTH is set to the maximum possible length in octets of the bit string.
    - 3) If TYPE indicates a <binary string type>, then LENGTH is set to the maximum length in octets of the binary string.
    - 4) If TYPE indicates an <exact numeric type>, then PRECISION and SCALE are set to the precision and scale of the exact numeric.
    - 5) If TYPE indicates an <approximate numeric type>, then PRECISION is set to the precision of the approximate numeric.
    - 6) If TYPE indicates a <datetime type>, then LENGTH is set to the length in positions of the datetime type, DATETIME\_INTERVAL\_CODE is set to a code as specified in Table 9, "Codes associated with datetime data types in SQL/CLI", to indicate the specific datetime data type and PRECISION is set to the <time precision> or <timestamp precision> if either is applicable.

- 7) If TYPE indicates INTERVAL, then LENGTH is set to the length in positions of the interval type, DATETIME\_INTERVAL\_CODE is set to a code as specified in Table 10, "Codes associated with <interval qualifier> in SQL/CLI", to indicate the specific <interval qualifier>, DATETIME\_INTERVAL\_PRECISION is set to the <interval leading field precision>, and PRECISION is set to the <interval fractional seconds precision>, if applicable.
- 8) If TYPE indicates REF, then LENGTH and OCTET\_LENGTH are set to the length in octets of the <reference type>, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME are set to the <user-defined type name> of the <reference type>, and SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME are set to the qualified name of the referenceable base table.
- 9) If TYPE indicates USER-DEFINED TYPE, then USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME are set to the <user-defined type name> of the user-defined type. SPECIFIC\_TYPE\_CATALOG, SPECIFIC\_TYPE\_SCHEMA, and SPECIFIC\_TYPE\_NAME are set to the <user-defined type name> of the user-defined type and CURRENT\_TRANSFORM\_GROUP is set to the CURRENT\_TRANSFORM\_GROUP\_FOR\_TYPE <user-defined type name>.
- 10) If TYPE indicates ROW, then DEGREE is set to the degree of the row type.
- 11) If TYPE indicates ARRAY, then CARDINALITY is set to the cardinality of the array type.
- 9) If LEVEL is 0 (zero) and the prepared statement being described is a <call statement>, then:
- Let  $SR$  be the subject routine for the <routine invocation> of the <call statement>.
  - Let  $D_x$  be the  $x$ -th <dynamic parameter specification> simply contained in an SQL argument  $A_y$  of the <call statement>.
  - Let  $P_y$  be the  $y$ -th SQL parameter of  $SR$ .  
NOTE 9 – A  $P$  whose <SQL parameter mode> is IN can be a <value expression> that contains zero, one, or more <dynamic parameter specification>s. Thus:
    - Every  $D_x$  maps to one and only one  $P_y$ .
    - Several  $D_x$  instances can map to the same  $P_y$ .
    - There can be  $P_y$  instances that have no  $D_x$  instances that map to them.
  - The PARAMETER\_MODE value in the descriptor for each  $D_x$  is set to the value from Table 11, "Codes associated with <parameter mode> in SQL/CLI", that indicates the <SQL parameter mode> of  $P_y$ .
  - The PARAMETER\_ORDINAL\_POSITION value in the descriptor for each  $D_x$  is set to the ordinal position of  $P_y$ .
  - The PARAMETER\_SPECIFIC\_CATALOG, PARAMETER\_SPECIFIC\_SCHEMA, and PARAMETER\_SPECIFIC\_NAME values in the descriptor for each  $D_x$  is set to the values that identify the catalog, schema, and specific name of  $SR$ .

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

**Function**

Specify the rules for an implicit EXECUTE USING clause and an implicit OPEN USING clause.

**General Rules**

- 1) Let *T*, *S*, and *AS* be a *TYPE*, *SOURCE*, and *ALLOCATED STATEMENT* specified in the rules of this Subclause.
- 2) Let *IPD*, *ARD*, and *APD* be the current implementation parameter descriptor, current application row descriptor, and current application parameter descriptor, respectively, for *AS*.
- 3) Let *C* be the allocated SQL-connection with which *S* is associated.
- 4) *IPD* and *APD* describe the <dynamic parameter specification>s and <dynamic parameter specification> values, respectively, for the statement being executed. Let *D* be the number of <dynamic parameter specification>s in *S*. Let *NAPD* be the value of COUNT for *APD* and let *NIPD* be the value of COUNT for *IPD*.
  - a) If *NAPD* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
  - b) If *NIPD* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
  - c) If *NIPD* is less than *D*, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
  - d) Let *NIDAL* be the number of item descriptor areas in the *IPD* for which LEVEL is 0 (zero). If *NIDAL* is greater than *D*, then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
  - e) If the first *NIPD* item descriptor areas of *IPD* are not valid as specified in Subclause 5.13, “Description of CLI item descriptor areas”, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
  - f) Let *AD* be the minimum of *NAPD* and *NIPD*.
  - g) For each of the first *AD* item descriptor areas of *APD*, if TYPE indicates DEFAULT, then:
    - i) Let *TP*, *P*, and *SC* be the values of the TYPE, PRECISION, and SCALE fields, respectively, for the corresponding item descriptor area of *IPD*.
    - ii) The data type, precision, and scale of the described <dynamic parameter specification> value (or part thereof, if the item descriptor area is a subordinate descriptor) are set to *TP*, *P*, and *SC*, respectively, for the purposes of this invocation only.
  - h) If the first *AD* item descriptor areas of *APD* are not valid as specified in Subclause 5.13, “Description of CLI item descriptor areas”, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

- i) For the first *AD* item descriptor areas in the APD:
- i) If the number of item descriptor areas in which the value of LEVEL is 0 (zero) is not *D*, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
  - ii) If all of the following are true, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
    - 1) The value of the host variable addressed by INDICATOR\_POINTER is not negative.
    - 2) Either of the following is true:
      - A) TYPE does not indicate ROW and the item descriptor area is not subordinate to an item descriptor area for which the value of the host variable addressed by the INDICATOR\_POINTER is not negative.
      - B) TYPE indicates ARRAY or ARRAY LOCATOR.
    - 3) The value of the host variable addressed by DATA\_POINTER is not a valid value of the data type represented by the item descriptor area.
- j) If all of the following are true for any item descriptor area in the first *AD* item descriptor areas of APD, then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications*.
- i) DEFERRED is true for the item descriptor area.
  - ii) Either of the following is true:
    - 1) The value of LEVEL is zero and TYPE indicates ROW or ARRAY.
    - 2) LEVEL is greater than 0 (zero).

NOTE 10 – This rule states that a parameter whose type is ROW or ARRAY must be bound; it cannot be a deferred parameter.
- k) For each item descriptor area whose LEVEL is 0 (zero) and for each of its subordinate descriptor areas, if any, for which DEFERRED is false in the first *AD* item descriptor areas of APD and whose corresponding <dynamic parameter specification> has a <parameter mode> of PARAM MODE IN or PARAM MODE INOUT, refer to the corresponding <dynamic parameter specification> value as an *immediate parameter value* and refer to the corresponding <dynamic parameter specification> as an *immediate parameter*.
- l) Let *IDA* be the *i*-th item descriptor area of the APD whose LEVEL value is 0 (zero). Let *SDT* be the data type represented by *IDA*. The *associated value* of *IDA* denoted by *SV*, is defined as follows.
- Case:
- i) If NULL is true for *IDA*, then *SV* is the null value.
  - ii) If TYPE indicates ROW, then *SV* is a row whose type is *SDT* and whose field values are the associated values of the immediately subordinate descriptor areas of *IDA*.
  - iii) Otherwise:
    - 1) Let *V* be the value of the host variable addressed by DATA\_POINTER.

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

- 2) Case:
- A) If TYPE indicates CHARACTER, then
- Case:
- I) If OCTET\_LENGTH\_POINTER is zero or if OCTET\_LENGTH\_POINTER is not zero and the value of the host variable addressed by OCTET\_LENGTH\_POINTER indicates NULL TERMINATED, then let  $L$  be the number of characters of  $V$  that precede the implementation-defined null character that terminates a C character string.
- II) Otherwise, let  $Q$  be the value of the host variable addressed by OCTET\_LENGTH\_POINTER and let  $L$  be the number of characters wholly contained in the first  $Q$  octets of  $V$ .
- B) Otherwise, let  $L$  be zero.
- 3) Let  $SV$  be  $V$  with effective data type  $SDT$ , as represented by the length value  $L$  and by the values of the TYPE, PRECISION, and SCALE fields.
- m) Let  $TDT$  be the effective data type of the  $i$ -th immediate parameter as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the  $i$ -th item descriptor area of the IPD for which the LEVEL value is 0 (zero), and all its subordinate descriptor areas.
- n) Let  $SDT$  be the effective data type of the  $i$ -th bound parameter as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the corresponding item descriptor area of the APD for which the LEVEL is 0 (zero), and all its subordinate descriptor areas.
- o) Case:
- i) If  $SDT$  is a locator type, then let  $TV$  be the value  $SV$ .
- ii) If  $SDT$  and  $TDT$  are predefined data types, then:
- 1) Case:
- A) If the <cast specification>
- ```
CAST ( SV AS TDT )
```
- does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type  $SDT$  to type  $TDT$ , then that implementation-defined conversion is effectively performed, converting  $SV$  to type  $TDT$ , and the result is the value  $TV$  of the  $i$ -th bound target.

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

B) Otherwise:

I) If the <cast specification>

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

II) If the <cast specification>

```
CAST ( SV AS TDT )
```

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

III) The <cast specification>

```
CAST ( SV AS TDT )
```

is effectively performed and the result is the value *TV* of the *i*-th bound target.

2) Let *UDT* be the effective data type of the actual *i*-th immediate parameter, defined to be the data type represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields that would automatically be set in the corresponding item descriptor area of *IPD* if POPULATE IPD was true for *C*.

3) Case:

A) If the <cast specification>

```
CAST ( TV AS UDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SdT* to type *UDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *UDT* and the result is the value *TV* of the *i*-th immediate parameter.

B) Otherwise:

I) If the <cast specification>

```
CAST ( TV AS UDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

II) If the <cast specification>

```
CAST ( TV AS UDT )
```

## 5.6 Implicit EXECUTE USING and OPEN USING clauses

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

## III) The &lt;cast specification&gt;

CAST ( *TV* AS *UDT* )

is effectively performed and is the value of the *i*-th immediate parameter.

iii) If *SDT* is a predefined data type and *TDT* is a user-defined type, then:

- 1) Let *DT* be the data type identified by *TDT*.
- 2) If the current SQL-session has a group name corresponding to the user-defined name of *DT*, then let *GN* be that group name; otherwise, let *GN* be the default transform group name associated with the current SQL-session.
- 3) The Syntax Rules of Subclause 10.17, "Determination of a to-sql function", in ISO/IEC 9075-2, are applied with *DT* and *GN* as *TYPE* and *GROUP*, respectively.

Case:

- A) If there is an applicable to-sql function, then let *TSF* be that to-sql function. If *TSF* is an SQL-invoked method, then let *TSFPT* be the declared type of the second SQL parameter of *TSF*; otherwise, let *TSFPT* be the declared type of the first SQL parameter of *TSF*.

Case:

- I) If *TSFPT* is compatible with *SDT*, then

Case:

- 1) If *TSF* is an SQL-invoked method, then *TSF* is effectively invoked with the value returned by the function invocation:

*DT* ( )

as the first parameter and *SV* as the second parameter. The <return value> is the value of the *i*-th immediate parameter.

- 2) Otherwise, *TSF* is effectively invoked with *SV* as the first parameter. The <return value> is the value of the *i*-th immediate parameter.

- II) Otherwise, an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

- B) Otherwise, an exception condition is raised: *dynamic SQL error — data type transform function violation*.

- p) If DEFERRED is true for at least one of the first *AD* item descriptor areas of *APD*, then:
  - i) Let *PN* be the parameter number associated with the first such item descriptor area.
  - ii) *PN* becomes the deferred parameter number associated with *AS*.
  - iii) If *T* is 'EXECUTE', then *S* becomes the statement source associated with *AS*.

**5.6 Implicit EXECUTE USING and OPEN USING clauses**

- iv) An exception condition is raised: *CLI-specific condition — dynamic parameter value needed.*

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 5.7 Implicit CALL USING clause

### Function

Specify the rules for an implicit CALL USING clause.

### General Rules

- 1) Let *S* and *AS* be a *SOURCE* and an *ALLOCATED STATEMENT* specified in the rules of this Subclause.
- 2) Let *IPD* and *APD* be the current implementation parameter descriptor and current application row descriptor, respectively, for *AS*.
- 3) *IPD* and *APD* describe the <dynamic parameter specification>s and <dynamic parameter specification> values, respectively, for the <call statement> being executed. Let *D* be the number of <dynamic parameter specification>s in *S*.
  - a) Let *AD* be the value of the COUNT field of *APD*. If *AD* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
  - b) For each item descriptor area in the *APD* whose LEVEL is 0 (zero) in the first *AD* item descriptor areas of *APD*, and for all of their subordinate descriptor areas, refer to a <dynamic parameter specification> value whose corresponding item descriptor areas have a non-zero DATA\_POINTER value and whose corresponding <dynamic parameter specification> has a <parameter mode> of PARAM MODE OUT or PARAM MODE INOUT as a *bound target* and refer to the corresponding <dynamic parameter specification> as a *bound parameter*.
  - c) If any item descriptor area corresponding to a bound target in the first *AD* item descriptor areas of *APD* is not valid as specified in Subclause 5.13, "Description of CLI item descriptor areas", then an exception condition is raised: *dynamic SQL error — using clause does not match target specifications*.
  - d) Let *SDT* be the effective data type of the *i*-th bound parameter as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the *i*-th item descriptor area of the *IPD* for which the LEVEL is 0 (zero) and all of its subordinate descriptor areas. Let *SV* be the value of the output parameter, with data type *SDT*.
  - e) If TYPE indicates USER-DEFINED TYPE, then let the most specific type of the *i*-th bound parameter whose value is *SV* be represented by the values of the SPECIFIC\_TYPE\_CATALOG, SPECIFIC\_TYPE\_SCHEMA, and SPECIFIC\_TYPE\_NAME fields in the corresponding item descriptor area of *IPD*.
  - f) Let *TYPE*, *OL*, *DP*, *IP*, and *LP* be the values of the TYPE, OCTET\_LENGTH, DATA\_POINTER, INDICATOR\_POINTER, and OCTET\_LENGTH\_POINTER fields, respectively, in the item descriptor area of the *APD* corresponding to the *i*-th bound target (or part thereof, if the item descriptor area is a subordinate descriptor).

- g) Case:
- i) If *TYPE* indicates CHARACTER, then:
    - 1) Let *UT* be the code value corresponding to CHARACTER VARYING as specified in Table 7, "Codes used for implementation data types in SQL/CLI".
    - 2) Let *LV* be the implementation-defined maximum length for a CHARACTER VARYING data type.
  - ii) Otherwise, let *UT* be *TYPE* and let *LV* be 0 (zero).
- h) Let *TDT* be the effective data type of the *i*-th bound target as represented by the type *UT*, the length value *LV*, and the values of the PRECISION, SCALE, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the corresponding item descriptor area of the APD for which the LEVEL is 0 (zero) and all its subordinate descriptor areas.
- i) Case:
- i) If *TDT* is a locator type, then:
    - 1) If *SV* is not the null value, then a locator *L* that uniquely identifies *SV* is generated and the value *TV* of the *i*-th bound target is set to an implementation-dependent four-octet value that represents *L*.
    - 2) Otherwise, the value *TV* of the *i*-th bound target is the null value.
  - ii) If *SDT* and *TDT* are predefined data types, then
 

Case:

    - 1) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

 does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *TDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *TDT*, and the result is the value *TV* of the *i*-th bound target.
    - 2) Otherwise:
      - A) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

 does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
      - B) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

- C) The <cast specification>

CAST ( *SV* AS *TDT* )

is effectively performed and the result is the value *TV* of the *i*-th bound target.

- iii) If *SDT* is a user-defined type and *TDT* is a predefined data type, then:

- 1) Let *DT* be the data type identified by *SDT*.
- 2) If the current SQL-session has a group name corresponding to the user-defined name of *DT*, then let *GN* be that group name; otherwise, let *GN* be the default transform group name associated with the current SQL-session.
- 3) The Syntax Rules of Subclause 10.15, "Determination of a from-sql function", in ISO/IEC 9075-2, are applied with *DT* and *GN* as *TYPE* and *GROUP*, respectively.

Case:

- A) If there is an applicable from-sql function, then let *FSF* be that from-sql function and let *FSFRT* be the <returns data type> of *FSF*.

Case:

- I) If *FSFRT* is compatible with *TDT*, then the from-sql function *TSF* is effectively invoked with *SV* as its input parameter and the <return value> is the value *TV* of the *i*-th bound target.
- II) Otherwise, an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

- B) Otherwise, an exception condition is raised: *dynamic SQL error — data type transform function violation*.

- j) Let *IDA* be the top-level item descriptor area corresponding to the *i*-th output parameter.

- k) Case:

- i) If *TYPE* indicates ROW, then

Case:

- 1) If *TV* is the null value, then

Case:

- A) If *IP* is a null pointer for *IDA* or for any of the subordinate descriptor areas of *IDA* that are not subordinate to an item descriptor area whose type indicates ARRAY or ARRAY\_LOCATOR, then an exception condition is raised: *data exception — null value, no indicator parameter*.

- B) Otherwise, the value of the host variable addressed by *IP* for *IDA*, and that in all subordinate descriptor areas of *IDA* that are not subordinate to an item descriptor area whose *TYPE* indicates ARRAY or ARRAY\_LOCATOR, is set to the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous

codes used in CLI”, and the values of variables addressed by *DP* and *LP* are implementation-dependent.

- 2) Otherwise, the *i*-th subordinate descriptor area of *IDA* is set to reflect the value of the *i*-th field of *TV* by applying General Rule 3)k) to the *i*-th subordinate descriptor area of *IDA* as *IDA*, the value of *i*-th field of *TV* as *TV*, the value of the *i*-th field of *SV* as *SV*, and the data type of the *i*-th field of *SV* as *SDT*.
- ii) Otherwise,
- Case:
- 1) If *TV* is the null value, then
 

Case:

    - A) If *IP* is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
    - B) Otherwise, the value of the host variable addressed by *IP* is set to the appropriate 'Code' for SQL NULL DATA in Table 26, “Miscellaneous codes used in CLI”, and the values of the host variables addressed by *DP* and *LP* are implementation-dependent.
  - 2) Otherwise:
    - A) If *IP* is not a null pointer, then the value of the host variable addressed by *IP* is set to 0 (zero).
    - B) Case:
      - I) If *TYPE* indicates CHARACTER or CHARACTER LARGE OBJECT, then:
        - A) If *TV* is a zero-length character string, then it is implementation-defined whether or not an exception condition is raised: *data exception — zero-length character string*.
        - B) The General Rules of Subclause 5.9, “Character string retrieval”, are applied with *DP*, *TV*, *OL*, and *LP* as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.
      - II) If *TYPE* indicates BINARY LARGE OBJECT, then the General Rules of Subclause 5.10, “Binary large object string retrieval”, are applied with *DP*, *TV*, *OL*, and *LP* as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.
      - III) If *TYPE* indicates ARRAY or ARRAY LOCATOR, and if *RETURNED\_CARDINALITY\_POINTER* is not 0 (zero), then the value of the host variable addressed by *RETURNED\_CARDINALITY\_POINTER* is set to the cardinality of *TV*.
      - IV) Otherwise, the value of the host variable addressed by *DP* is set to *TV*.

## 5.8 Implicit FETCH USING clause

### Function

Specify the rules for an implicit FETCH USING clause.

### General Rules

- 1) Let *S*, *RS*, *RP*, and *AS* be a *SOURCE*, *ROWS*, *ROWS PROCESSED*, and an *ALLOCATED STATEMENT* specified in the rules of this Subclause.
- 2) Let *IRD* and *ARD* be the current implementation row descriptor and current application row descriptor, respectively, associated with *AS*.
- 3) *IRD* and *ARD* describe the <select list> columns and <target specification>s, respectively, for the column values that are to be retrieved. Let *D* be the degree of the table defined by *S*.
  - a) Let *AD* be the value of the COUNT field of *ARD*. If *AD* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
  - b) For each item descriptor area in *ARD* whose LEVEL is 0 (zero) in the first *AD* item descriptor areas of *ARD*, and for all of their subordinate descriptor areas, refer to a <target specification> whose corresponding item descriptor areas have a non-zero DATA\_POINTER as a *bound target* and refer to the corresponding <select list> column as a *bound column*.
  - c) If any item descriptor area corresponding to a bound target in the first *AD* item descriptor areas of *ARD* is not valid as specified in Subclause 5.13, "Description of CLI item descriptor areas", then an exception condition is raised: *dynamic SQL error — using clause does not match target specifications*.
  - d) Let *SDT* be the effective data type of the *i*-th bound column as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the *i*-th item descriptor area of the *IRD* whose LEVEL is 0 (zero) and all of its subordinate descriptor areas.
  - e) If TYPE indicates USER-DEFINED TYPE, then let the most specific type of the *i*-th bound column whose value is *SV* be represented by the values of the SPECIFIC\_TYPE\_CATALOG, SPECIFIC\_TYPE\_SCHEMA, and SPECIFIC\_TYPE\_NAME fields in the corresponding item descriptor area of *IRD*.
  - f) Let *TYPE*, *OL*, *DP*, *IP*, and *LP* be the values of the TYPE, OCTET\_LENGTH, DATA\_POINTER, INDICATOR\_POINTER, and OCTET\_LENGTH\_POINTER fields, respectively, in the item descriptor area of the *ARD* corresponding to the *i*-th bound target (or part thereof, if the item descriptor area is a subordinate descriptor).
  - g) Let *ASP* be the value of the ARRAY\_STATUS\_POINTER field in the *IRD*.
  - h) For *RN* ranging from 1 (one) through *RS*, if the *RN*-th row of the rowset has been fetched, then:
    - i) Let *SV* be the value of the <select list> column, with data type *SDT*.

- ii) Let *DPE*, *IPE*, and *LPE* be the addresses of the *RN*-th element of the arrays addressed by *DP*, *IP*, and *LP*, respectively.
- iii) Case:
- 1) If *TYPE* indicates CHARACTER, then:
    - A) Let *UT* be the code value corresponding to CHARACTER VARYING as specified in Table 7, "Codes used for implementation data types in SQL/CLI".
    - B) Let *LV* be the implementation-defined maximum length for a CHARACTER VARYING data type.
  - 2) Otherwise, let *UT* be *TYPE* and let *LV* be 0 (zero).
- iv) Let *TDT* be the effective data type of the *i*-th bound target as represented by the type *UT*, the length value *LV*, and the values of the PRECISION, SCALE, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the item descriptor area of the ARD whose LEVEL is 0 (zero) and all of its subordinate descriptor areas.
- v) Let *LTDT* be the data type on the last fetch of the *i*-th bound target, if any. If any of the following is true, then is implementation-defined whether or not an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
- 1) If *LTDT* and *TDT* both identify a binary large object type and only one of *LTDT* and *TDT* is a binary large object locator.
  - 2) If *LTDT* and *TDT* both identify a character large object type and only one of *LTDT* and *TDT* is a character large object locator.
  - 3) If *LTDT* and *TDT* both identify an array type and only one of *LTDT* and *TDT* is an array locator.
  - 4) If *LTDT* and *TDT* both identify a user-defined type and only one of *LTDT* and *TDT* is a user-defined type locator.
- vi) Case:
- 1) If *TDT* is a locator type, then;
    - A) If *SV* is not the null value, then a locator *L* that uniquely identifies *SV* is generated and the value *TV* of the *i*-th bound target is set to an implementation-dependent four-octet value that represents *L*.
    - B) Otherwise, the value *TV* of the *i*-th bound target is the null value.
  - 2) If *SdT* and *TDT* are predefined data types, then
 

Case:

    - A) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *TDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *TDT*, and the result is the value *TV* of the *i*-th bound target.

B) Otherwise:

I) If the <cast specification>

CAST ( *SV* AS *TDT* )

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

II) If the <cast specification>

CAST ( *SV* AS *TDT* )

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

For every status record that results from the application of this Rule, the *ROW\_NUMBER* field is set to *RN* and the *COLUMN\_NUMBER* field is set to *i*. If *ASP* is not a null pointer, then the *RN*-th element of the array addressed by *ASP* is set to:

- 1) If there were completion conditions: *warning* raised during the application of this Rule, then 6 (indicating **Row success with information**).
- 2) If there were exception conditions raised during the application of this Rule, then 5 (indicating **Row error**).

III) The <cast specification>

CAST ( *SV* AS *TDT* )

is effectively performed and the result is the value *TV* of the *i*-th bound target.

3) If *SDT* is a user-defined type and *TDT* is a predefined data type, then:

- A) Let *DT* be the data type identified by *SDT*.
- B) If the current SQL-session has a group name corresponding to the user-defined name of *DT*, then let *GN* be that group name; otherwise, let *GN* be the default transform group name associated with the current SQL-session.
- C) The Syntax Rules of Subclause 10.15, "Determination of a from-sql function", in ISO/IEC 9075-2, are applied with *DT* and *GN* as *TYPE* and *GROUP*, respectively.

Case:

- I) If there is an applicable from-sql function, then let *FSF* be that from-sql function and let *FSFRT* be the <returns data type> of *FSF*.

Case:

- 1) If *FSFRT* is compatible with *TDT*, then the from-sql function *TSF* is effectively invoked with *SV* as its input parameter and the <return value> is the value *TV* of the *i*-th bound target.
- 2) Otherwise, an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

II) Otherwise, an exception condition is raised: *dynamic SQL error — data type transform function violation*.

vii) Let *IDA* be the top-level item descriptor area corresponding to the *i*-th bound column.

viii) Case:

1) If TYPE indicates ROW, then

Case:

A) If *TV* is the null value, then

Case:

- I) If *IPE* is a null pointer for *IDA* or for any of the subordinate descriptor areas of *IDA* that are not subordinate to an item descriptor area whose type indicates ARRAY or ARRAY\_LOCATOR, then an exception condition is raised: *data exception — null value, no indicator parameter*.
- II) Otherwise, the value of the host variable addressed by *IPE* for *IDA*, and that in all subordinate descriptor areas of *IDA* that are not subordinate to an item descriptor area whose TYPE indicates ARRAY or ARRAY\_LOCATOR, is set to the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", and the values of variables addressed by *DPE* and *LPE* are implementation-dependent.

B) Otherwise, the *i*-th subordinate descriptor area of *IDA* is set to reflect the value of the *i*-th field of *TV* by applying General Rule 3)h)viii) to the *i*-th subordinate descriptor area of *IDA* as *IDA*, the value of *i*-th field of *TV* as *TV*, the value of the *i*-th field of *SV* as *SV*, and the data type of the *i*-th field of *SV* as *SDT*.

2) Otherwise,

Case:

A) If *TV* is the null value, then

Case:

- I) If *IPE* is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
- II) Otherwise, the value of the host variable addressed by *IPE* is set to the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", and the values of the host variables addressed by *DPE* and *LPE* are implementation-dependent.

B) Otherwise:

I) If *IPE* is not a null pointer, then the value of the host variable addressed by *IPE* is set to 0 (zero).

II) Case:

1) If *TYPE* indicates CHARACTER or CHARACTER LARGE OBJECT, then:

- a) If *TV* is a zero-length character string, then it is implementation-defined whether or not an exception condition is raised: *data exception — zero-length character string*.
- b) The General Rules of Subclause 5.9, “Character string retrieval”, are applied with *DPE*, *TV*, *OL*, and *LPE* as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

2) For every status record that results from the application of the preceding Rule, the *ROW\_NUMBER* field is set to *RN* and the *COLUMN\_NUMBER* field is set to *i*. If *ASP* is not a null pointer, then the *RN*-th element of the array addressed by *ASP* is set to:

- a) If there were completion conditions: *warning* raised during the application of the preceding Rule, then 6 (indicating **Row success with information**).
- b) If there were exception conditions raised during the application of the preceding Rule, then 5 (indicating **Row error**).

3) If *TYPE* indicates BINARY LARGE OBJECT, then the General Rules of Subclause 5.10, “Binary large object string retrieval”, are applied with *DPE*, *TV*, *OL*, and *LPE* as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

For every status record that results from the application of this Rule, the *ROW\_NUMBER* field is set to *RN* and the *COLUMN\_NUMBER* field is set to *i*. If *ASP* is not a null pointer, then the *RN*-th element of the array addressed by *ASP* is set to:

- a) If there were completion conditions: *warning* raised during the application of this Rule, then 6 (indicating **Row success with information**).
- b) If there were exception conditions raised during the application of this Rule, then 5 (indicating **Row error**).

4) If *TYPE* indicates ARRAY or ARRAY LOCATOR, and if *RETURNED\_CARDINALITY\_POINTER* is not a null pointer, then the value of the host variable addressed by *RETURNED\_CARDINALITY\_POINTER* is set to the cardinality of *TV*.

5) Otherwise, the value of the host variable addressed by *DPE* is set to *TV* and the value of the host variable addressed by *LPE* is implementation-dependent.

- 3) If there were no exception conditions raised during the application of this Rule, then:
  - A) Increment *RP* by 1 (one).
  - B) If *ASP* is not a null pointer, then set the *RN*-th element of the array pointed to by *ASP* to 0 (zero, indicating **Row success**).

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 5.9 Character string retrieval

### Function

Specify the rules for retrieving character string values.

### General Rules

- 1) Let  $T$ ,  $V$ ,  $TL$ , and  $RL$  be a *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH* specified in an application of this Subclause.
- 2) If  $TL$  is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 3) Let  $L$  be the length in octets of  $V$ .
- 4) If  $RL$  is not a null pointer, then the value of the host variable addressed by  $RL$  is set to  $L$ .
- 5) Case:
  - a) If null termination is *false* for the current SQL-environment, then:
    - i) If  $L$  is not greater than  $TL$ , then the first  $L$  octets of  $T$  are set to  $V$  and the values of the remaining octets of  $T$  are implementation-dependent.
    - ii) Otherwise,  $T$  is set to the first  $TL$  octets of  $V$  and a completion condition is raised: *warning — string data, right truncation*.
  - b) Otherwise, let  $NB$  be the length in octets of a null terminator in the character set of  $T$ .  
Case:
    - i) If  $L$  is not greater than  $(TL - NB)$ , then the first  $(L + NB)$  octets of  $T$  are set to  $V$  concatenated with a single implementation-defined null character that terminates a C character string. The values of the remaining characters of  $T$  are implementation-dependent.
    - ii) Otherwise,  $T$  is set to the first  $(TL - NB)$  octets of  $V$  concatenated with a single implementation-defined null character that terminates a C character string and a completion condition is raised: *warning — string data, right truncation*.

## 5.10 Binary large object string retrieval

### Function

Specify the rules for retrieving BINARY LARGE OBJECT string values.

### General Rules

- 1) Let *T*, *V*, *TL*, and *RL* be a *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH* specified in an application of this Subclause.
- 2) If *TL* is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 3) Let *L* be the length in octets of *V*.
- 4) If *RL* is not a null pointer, then *RL* is set to *L*.
- 5) Case:
  - a) If *L* is not greater than *TL*, then the first *L* octets of *T* are set to *V* and the values of the remaining octets of *T* are implementation-dependent.
  - b) Otherwise, *T* is set to the first *TL* octets of *V* and a completion condition is raised: *warning — string data, right truncation*.

## 5.11 Deferred parameter check

### Function

Check for the existence of deferred dynamic parameters when accessing a CLI descriptor.

### General Rules

- 1) Let  $DA$  be a DESCRIPTOR AREA specified in an application of this Subclause.
- 2) Let  $C$  be the allocated SQL-connection with which  $DA$  is associated.
- 3) Let  $L1$  be the set of all allocated SQL-statements associated with  $C$ .
- 4) Let  $L2$  be the set of all allocated SQL-statements in  $L1$  which have an associated deferred parameter number.
- 5) Let  $L3$  be the set of all CLI descriptor areas that are either the current application parameter descriptor for, or the implementation parameter descriptor associated with, an allocated SQL-statement in  $L2$ .
- 6) If  $DA$  is contained in  $L3$ , then an exception condition is raised: *CLI-specific condition — function sequence error*.

## 5.12 CLI-specific status codes

Some of the conditions that can occur during the execution of CLI routines are CLI-specific. The corresponding status codes are listed in Table 5, “SQLSTATE class and subclass values for SQL/CLI-specific conditions”.

Table 5—SQLSTATE class and subclass values for SQL/CLI-specific conditions

| Category                                                 | Condition              | Class | Subcondition                                | Subclass                               |
|----------------------------------------------------------|------------------------|-------|---------------------------------------------|----------------------------------------|
| X                                                        | CLI-specific condition | HY    | (no subclass)                               | 000                                    |
|                                                          |                        |       | associated statement is not prepared        | 007                                    |
|                                                          |                        |       | attempt to concatenate a null value         | 020                                    |
|                                                          |                        |       | attribute cannot be set now                 | 011                                    |
|                                                          |                        |       | column type out of range                    | 097                                    |
|                                                          |                        |       | dynamic parameter value needed              | (See the Note at the end of the table) |
|                                                          |                        |       | function sequence error                     | 010                                    |
|                                                          |                        |       | inconsistent descriptor information         | 021                                    |
|                                                          |                        |       | invalid attribute identifier                | 092                                    |
|                                                          |                        |       | invalid attribute value                     | 024                                    |
|                                                          |                        |       | invalid cursor position                     | 109                                    |
|                                                          |                        |       | invalid data type                           | 004                                    |
|                                                          |                        |       | invalid data type in application descriptor | 003                                    |
|                                                          |                        |       | invalid descriptor field identifier         | 091                                    |
|                                                          |                        |       | invalid fetch orientation                   | 106                                    |
|                                                          |                        |       | invalid FunctionId specified                | 095                                    |
|                                                          |                        |       | invalid handle                              | (See the Note at the end of the table) |
|                                                          |                        |       | invalid information type                    | 096                                    |
|                                                          |                        |       | invalid LengthPrecision value               | 104                                    |
|                                                          |                        |       | invalid parameter mode                      | 105                                    |
|                                                          |                        |       | invalid retrieval code                      | 103                                    |
|                                                          |                        |       | invalid string length or buffer length      | 090                                    |
|                                                          |                        |       | invalid transaction operation code          | 012                                    |
| invalid use of automatically-allocated descriptor handle | 017                    |       |                                             |                                        |
| invalid use of null pointer                              | 009                    |       |                                             |                                        |
| limit on number of handles exceeded                      | 014                    |       |                                             |                                        |

Table 5—SQLSTATE class and subclass values for SQL/CLI-specific conditions (Cont.)

| Category | Condition | Class | Subcondition                                       | Subclass |
|----------|-----------|-------|----------------------------------------------------|----------|
|          |           |       | memory allocation error                            | 001      |
|          |           |       | memory management error                            | 013      |
|          |           |       | non-string data cannot be sent in pieces           | 019      |
|          |           |       | non-string data cannot be used with string routine | 055      |
|          |           |       | nullable type out of range                         | 099      |
|          |           |       | operation canceled                                 | 008      |
|          |           |       | optional feature not implemented                   | C00      |
|          |           |       | row value out of range                             | 107      |
|          |           |       | scope out of range                                 | 098      |
|          |           |       | server declined the cancellation request           | 018      |

NOTE 11 – No subclass value is defined for the subcondition *invalid handle* since no diagnostic information can be generated in this case or for the subcondition *dynamic parameter value needed*, since no diagnostic information is generated in this case.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 5.13 Description of CLI item descriptor areas

### Function

Specify the identifiers, data types and codes for fields used in CLI item descriptor areas.

### Syntax Rules

- 1) A CLI item descriptor area comprises the fields specified in Table 6, "Fields in SQL/CLI row and parameter descriptor areas".
- 2) Given a CLI item descriptor area *IDA* in which the value of LEVEL is some value *N*, the *immediately subordinate* descriptor areas of *IDA* are those CLI item descriptor areas in which the value of LEVEL is *N+1* and whose position in the CLI descriptor area follows that of *IDA* and precedes that of any CLI item descriptor area in which the value of LEVEL is less than *N+1*. The subordinate descriptor areas of *IDA* are those CLI item descriptor areas that are immediately subordinate descriptor areas of *IDA* or that are subordinate descriptor areas of an CLI item descriptor area that is immediately subordinate to *IDA*.
- 3) Given a data type *DT* and its descriptor *DE*, the immediately subordinate descriptors of *DE* are defined to be
 

Case:

  - a) If *DT* is ROW, then the field descriptors of the fields of *DT*. The *i*-th immediately subordinate descriptor is the descriptor of the *i*-th field of *DT*.
  - b) If *DT* is ARRAY, then the descriptor of the associated element type of *DT*. The subordinate descriptors of *DE* are those descriptors that are immediately subordinate descriptors of *DE* or that are subordinate descriptors of a descriptor that is immediately subordinate to *DE*.
- 4) Given a descriptor *DE*, let *SDE<sub>j</sub>* represent its *j*-th immediately subordinate descriptor. There is an implied ordering of the subordinate descriptors of *DE*, such that:
  - a) *SDE<sub>1</sub>* is in the first ordinal position.
  - b) The ordinal position of *SDE<sub>j+1</sub>* is  $K+NS+1$ , where *K* is the ordinal position of *SDE<sub>j</sub>* and *NS* is the number of subordinate descriptors of *SDE<sub>j</sub>*. The implicitly ordered subordinate descriptors of *SDE<sub>j</sub>* occupy contiguous ordinal positions starting at position *K+1*.
- 5) Let *IDA* be an item descriptor area in an implementation parameter descriptor. *IDA* is *valid* if and only if all of the following are true:
  - a) TYPE is one of the code values in Table 7, "Codes used for implementation data types in SQL/CLI".
  - b) If LEVEL is 0 (zero) for *IDA*, then let *TLC* be the value of TOP\_LEVEL\_COUNT of the implementation parameter descriptor associated with *IDA*. *IDA* shall be one of exactly *TLC* item descriptor areas in the implementation parameter descriptor.
  - c) Exactly one of the following is true:
 

Case:

    - i) TYPE indicates NUMERIC and PRECISION and SCALE are valid precision and scale values for the NUMERIC data type.

## 5.13 Description of CLI item descriptor areas

- ii) TYPE indicates DECIMAL and PRECISION and SCALE are valid precision and scale values for the DECIMAL data type.
  - iii) TYPE indicates FLOAT and PRECISION is a valid precision value for the FLOAT data type.
  - iv) TYPE indicates INTEGER, SMALLINT, REAL, or DOUBLE PRECISION.
  - v) TYPE indicates CHARACTER or CHARACTER VARYING, or CHARACTER LARGE OBJECT and LENGTH is a valid length value for a <character string type>.
  - vi) TYPE indicates BIT or BIT VARYING and LENGTH is a valid length value for <bit string type>.
  - vii) TYPE indicates BINARY LARGE OBJECT and LENGTH is a valid value for a <binary string type>.
  - viii) TYPE indicates a <datetime type>, DATETIME\_INTERVAL\_CODE is one of the code values in Table 9, "Codes associated with datetime data types in SQL/CLI", and PRECISION is a valid value for the <time precision> or <timestamp precision> of the indicated datetime data type.
  - ix) TYPE indicates an <interval type>, DATETIME\_INTERVAL\_CODE is one of the code values in Table 10, "Codes associated with <interval qualifier> in SQL/CLI", to indicate the <interval qualifier> of the interval data type, DATETIME\_INTERVAL\_PRECISION is a valid <interval leading field precision>, and PRECISION is a valid value for <interval fractional seconds precision>, if applicable.
  - x) TYPE indicates REF.
  - xi) TYPE indicates USER-DEFINED TYPE.
  - xii) TYPE indicates BOOLEAN.
  - xiii) TYPE indicates ROW, the value *N* of DEGREE is a valid value for the degree of a row type, there are exactly *N* immediately subordinate descriptor areas of *IDA*, and those item descriptor areas are valid.
  - xiv) TYPE indicates ARRAY or ARRAY CARDINALITY is a valid value for the cardinality of an array, there is LOCATOR, the value of exactly one immediately subordinate descriptor area of *IDA*, and that item descriptor area is valid.
  - xv) TYPE indicates an implementation-defined data type.
- 6) Let *HL* be the standard programming language of the invoking host program. Let *operative data type correspondence table* be the data type correspondence table for *HL* as specified in Subclause 5.15, "Data type correspondences". Refer to the two columns of the operative data type correspondence table as the *SQL data type column* and the *host data type column*.
- 7) A CLI item descriptor area in a CLI descriptor area that is not an implementation row descriptor is *consistent* if and only if all of the following are true:
- a) TYPE indicates DEFAULT or is one of the code values in Table 8, "Codes used for application data types in SQL/CLI".

## 5.13 Description of CLI item descriptor areas

- b) All of the following are true:
- i) TYPE is one of the code values in Table 8, "Codes used for application data types in SQL/CLI".
  - ii) TYPE is neither ROW nor ARRAY.
  - iii) The row that contains the SQL data type corresponding to TYPE in the SQL data type column of the operative data type correspondence table does not contain "None" in the host data type column.
- c) Exactly one of the following is true:
- i) TYPE indicates NUMERIC and PRECISION and SCALE are valid precision and scale values for the NUMERIC data type.
  - ii) TYPE indicates DECIMAL and PRECISION and SCALE are valid precision and scale values for the DECIMAL data type.
  - iii) TYPE indicates FLOAT and PRECISION is a valid precision value for the FLOAT data type.
  - iv) TYPE indicates DEFAULT, CHARACTER, CHARACTER LARGE OBJECT, BINARY LARGE OBJECT, CHARACTER LARGE OBJECT LOCATOR, BINARY LARGE OBJECT LOCATOR, USER-DEFINED TYPE LOCATOR, REF, INTEGER, SMALLINT, REAL, or DOUBLE PRECISION.
  - v) TYPE indicates ROW and, where  $N$  is the value of the DEGREE field in the corresponding item descriptor area in the implementation parameter descriptor, there are exactly  $N$  immediately subordinate descriptor areas of  $IDA$ , and those item descriptor areas are valid.
  - vi) TYPE indicates ARRAY or ARRAY LOCATOR, there is exactly 1 (one) immediately subordinate descriptor area of  $IDA$ , and that item descriptor area is valid.
  - vii) TYPE indicates an implementation-defined data type.
- 8) Let  $IDA$  be a CLI item descriptor area in an application parameter descriptor. Let  $IDA1$  be the corresponding item descriptor area in the implementation parameter descriptor.
- 9) If the OCTET\_LENGTH\_POINTER field of  $IDA$  has the same non-zero value as the INDICATOR\_POINTER field of  $IDA$ , then SHARE is true for  $IDA$ ; otherwise SHARE is false for  $IDA$ .
- 10) Case:
- a) If SHARE is true and the value of the commonly addressed host variable is the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", then NULL is true for  $IDA$ .
  - b) If SHARE is false, INDICATOR\_POINTER is not zero, and the value of the host variable addressed by INDICATOR\_POINTER is the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", then NULL is true for  $IDA$ .
  - c) Otherwise, NULL is false for  $IDA$ .

### 5.13 Description of CLI item descriptor areas

- 11) If NULL is false, OCTET\_LENGTH\_POINTER is not zero, and the value of the host variable addressed by OCTET\_LENGTH\_POINTER the appropriate 'Code' for DATA AT EXEC in Table 26, "Miscellaneous codes used in CLI", then DEFERRED is true for *IDA*; otherwise DEFERRED is false for *IDA*.
- 12) *IDA* is *valid* if and only if:
- a) TYPE is one of the code values in Table 8, "Codes used for application data types in SQL/CLI", and at least one of the following is true:
    - i) TYPE is ROW or ARRAY.
    - ii) The row of the operative data type correspondences table that contains the SQL data type corresponding to the value of TYPE in the SQL data type column does not contain 'None' in the host data type column.
  - b) If LEVEL is 0 (zero) for *IDA*, then let *TLC* be the value of TOP\_LEVEL\_COUNT in the application parameter descriptor associated with *IDA*. *IDA* shall be one of exactly *TLC* item descriptor areas in the implementation parameter descriptor.
  - c) One of the following is true:
 

Case:

    - i) TYPE indicates NUMERIC and PRECISION and SCALE are valid precision and scale values for the NUMERIC data type.
    - ii) TYPE indicates DECIMAL and PRECISION and SCALE are valid precision and scale values for the DECIMAL data type.
    - iii) TYPE indicates FLOAT and PRECISION is a valid precision value for the FLOAT data type.
    - iv) TYPE indicates INTEGER, SMALLINT, REAL, or DOUBLE PRECISION.
    - v) TYPE indicates CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, and one of the following is true:
      - 1) NULL is true.
      - 2) DEFERRED is true.
      - 3) OCTET\_LENGTH\_POINTER is not zero, PARAMETER\_MODE in *IDA1* is PARAM MODE IN or PARAM MODE INOUT, the value *V* of the host variable addressed by OCTET\_LENGTH\_POINTER is greater than zero, and the number of characters wholly contained in the first *V* octets of the host variable addressed by DATA\_POINTER is a valid length value for a CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT data type, as indicated by TYPE.
      - 4) OCTET\_LENGTH\_POINTER is not zero, PARAMETER\_MODE in *IDA1* is PARAM MODE IN or PARAM MODE INOUT, the value of the host variable addressed by OCTET\_LENGTH\_POINTER indicates NULL TERMINATED, and the number of characters of the value of the host variable addressed by DATA\_POINTER that precede the implementation-defined null character that terminates a C character string is a valid length value for a CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT data type, as indicated by TYPE.

## 5.13 Description of CLI item descriptor areas

- 5) OCTET\_LENGTH\_POINTER is zero, PARAMETER\_MODE in *IDA1* is PARAM MODE IN or PARAM MODE INOUT, and the number of characters of the value of the host variable addressed by DATA\_POINTER that precede the implementation-defined null character that terminates a C character string is a valid length value for a CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT data type, as indicated by TYPE.
- 6) PARAMETER\_MODE in *IDA1* is PARAM MODE OUT.
- vi) TYPE indicates REF and one of the following is true:
- 1) NULL is true.
  - 2) DEFERRED is true.
- vii) TYPE indicates CHARACTER LARGE OBJECT LOCATOR, BINARY LARGE OBJECT LOCATOR, or USER-DEFINED TYPE LOCATOR and one of the following is true:
- 1) NULL is true.
  - 2) DEFERRED is true.
- viii) TYPE indicates ROW and, where *N* is the value of the DEGREE field in the corresponding item descriptor area in the implementation parameter descriptor, there are exactly *N* immediately subordinate descriptor areas of *IDA*, and those item descriptor areas are valid.
- ix) TYPE indicates ARRAY or ARRAY LOCATOR, there is exactly 1 (one) immediately subordinate descriptor area of *IDA*, and that item descriptor area is valid.
- x) TYPE indicates an implementation-defined data type.
- d) One of the following is true:
- i) DATA\_POINTER is zero and NULL is true.
  - ii) DATA\_POINTER is zero and DEFERRED is true.
  - iii) DATA\_POINTER is not zero and exactly one of the following is true:
    - 1) NULL is true.
    - 2) DEFERRED is true.
    - 3) PARAMETER\_MODE in *IDA1* is PARAM MODE IN or PARAM MODE INOUT and the value of the host variable addressed by DATA\_POINTER is a valid value of the data type indicated by TYPE.
    - 4) PARAMETER\_MODE in *IDA1* is PARAM MODE OUT.
- 13) A CLI item descriptor area in an application row descriptor is *valid* if and only if:
- a) TYPE is one of the code values in Table 8, "Codes used for application data types in SQL/CLI", and at least one of the following is true:
    - i) TYPE is ROW or ARRAY.

5.13 Description of CLI item descriptor areas

- ii) The row of the operative data type correspondences table that contains the SQL data type corresponding to the value of TYPE in the SQL data type column does not contain 'None' in the host data type column.
- b) If LEVEL is 0 (zero) for IDA, then let TLC be the value of TOP\_LEVEL\_COUNT in the application parameter descriptor associated with IDA. IDA shall be one of exactly TLC item descriptor areas in the implementation parameter descriptor.
- c) One of the following is true:
 

Case:

  - i) TYPE indicates NUMERIC and PRECISION and SCALE are valid precision and scale values for the NUMERIC data type.
  - ii) TYPE indicates DECIMAL and PRECISION and SCALE are valid precision and scale values for the DECIMAL data type.
  - iii) TYPE indicates FLOAT and PRECISION is a valid precision value for the FLOAT data type.
  - iv) TYPE indicates CHARACTER, CHARACTER LARGE OBJECT, BINARY LARGE OBJECT, CHARACTER LARGE OBJECT LOCATOR, BINARY LARGE OBJECT LOCATOR, USER-DEFINED TYPE LOCATOR, REF, INTEGER, SMALLINT, REAL, or DOUBLE PRECISION.
  - v) TYPE indicates ROW and, where N is the value of the DEGREE field in the corresponding item descriptor area in the implementation parameter descriptor, there are exactly N immediately subordinate descriptor areas of IDA, and those item descriptor areas are valid.
  - vi) TYPE indicates ARRAY or ARRAY LOCATOR, there is exactly 1 (one) immediately subordinate descriptor area of IDA, and that item descriptor area is valid.
  - vii) TYPE indicates an implementation-defined data type.

Table 6—Fields in SQL/CLI row and parameter descriptor areas

| Field                                                                                                                                                                                                           | Data Type                        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>Header fields</b>                                                                                                                                                                                            |                                  |
| ALLOC_TYPE                                                                                                                                                                                                      | SMALLINT                         |
| ARRAY_SIZE                                                                                                                                                                                                      | INTEGER                          |
| ARRAY_STATUS_POINTER                                                                                                                                                                                            | host variable address of INTEGER |
| DYNAMIC_FUNCTION                                                                                                                                                                                                | CHARACTER VARYING(L)             |
| DYNAMIC_FUNCTION_CODE                                                                                                                                                                                           | INTEGER                          |
| KEY_TYPE                                                                                                                                                                                                        | SMALLINT                         |
| ROWS_PROCESSED_POINTER                                                                                                                                                                                          | host variable address of INTEGER |
| TOP_LEVEL_COUNT                                                                                                                                                                                                 | SMALLINT                         |
| <p><b>Where</b> L is an implementation-defined integer not less than 128, and LI is the implementation-defined maximum length for the &lt;general value specification&gt; CURRENT_TRANSFORM_GROUP_FOR_TYPE.</p> |                                  |

Table 6—Fields in SQL/CLI row and parameter descriptor areas (Cont.)

| Field                                                                                                                                                                                                                         | Data Type                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>Header fields</b>                                                                                                                                                                                                          |                                  |
| Implementation-defined header field                                                                                                                                                                                           | Implementation-defined           |
| <b>Fields in item descriptor areas</b>                                                                                                                                                                                        |                                  |
| CARDINALITY                                                                                                                                                                                                                   | INTEGER                          |
| CHARACTER_SET_CATALOG                                                                                                                                                                                                         | CHARACTER VARYING( <i>L</i> )    |
| CHARACTER_SET_NAME                                                                                                                                                                                                            | CHARACTER VARYING( <i>L</i> )    |
| CHARACTER_SET_SCHEMA                                                                                                                                                                                                          | CHARACTER VARYING( <i>L</i> )    |
| COLLATION_CATALOG                                                                                                                                                                                                             | CHARACTER VARYING( <i>L</i> )    |
| COLLATION_NAME                                                                                                                                                                                                                | CHARACTER VARYING( <i>L</i> )    |
| COLLATION_SCHEMA                                                                                                                                                                                                              | CHARACTER VARYING( <i>L</i> )    |
| COUNT                                                                                                                                                                                                                         | SMALLINT                         |
| CURRENT_TRANSFORM_GROUP                                                                                                                                                                                                       | CHARACTER VARYING( <i>L1</i> )   |
| DATA_POINTER                                                                                                                                                                                                                  | host variable address            |
| DATETIME_INTERVAL_CODE                                                                                                                                                                                                        | SMALLINT                         |
| DATETIME_INTERVAL_PRECISION                                                                                                                                                                                                   | SMALLINT                         |
| DEGREE                                                                                                                                                                                                                        | INTEGER                          |
| INDICATOR_POINTER                                                                                                                                                                                                             | host variable address of INTEGER |
| KEY_MEMBER                                                                                                                                                                                                                    | SMALLINT                         |
| LENGTH                                                                                                                                                                                                                        | INTEGER                          |
| LEVEL                                                                                                                                                                                                                         | INTEGER                          |
| NAME                                                                                                                                                                                                                          | CHARACTER VARYING( <i>L</i> )    |
| NULLABLE                                                                                                                                                                                                                      | SMALLINT                         |
| OCTET_LENGTH                                                                                                                                                                                                                  | INTEGER                          |
| OCTET_LENGTH_POINTER                                                                                                                                                                                                          | host variable address of INTEGER |
| PARAMETER_MODE                                                                                                                                                                                                                | SMALLINT                         |
| PARAMETER_ORDINAL_POSITION                                                                                                                                                                                                    | SMALLINT                         |
| PARAMETER_SPECIFIC_CATALOG                                                                                                                                                                                                    | CHARACTER VARYING( <i>L</i> )    |
| PARAMETER_SPECIFIC_NAME                                                                                                                                                                                                       | CHARACTER VARYING( <i>L</i> )    |
| PARAMETER_SPECIFIC_SCHEMA                                                                                                                                                                                                     | CHARACTER VARYING( <i>L</i> )    |
| PRECISION                                                                                                                                                                                                                     | SMALLINT                         |
| RETURNED_CARDINALITY_POINTER                                                                                                                                                                                                  | host variable address of INTEGER |
| SCALE                                                                                                                                                                                                                         | SMALLINT                         |
| <p><b>Where</b> <i>L</i> is an implementation-defined integer not less than 128, and <i>L1</i> is the implementation-defined maximum length for the &lt;general value specification&gt; CURRENT_TRANSFORM_GROUP_FOR_TYPE.</p> |                                  |

(Continued on next page)

## 5.13 Description of CLI item descriptor areas

Table 6—Fields in SQL/CLI row and parameter descriptor areas (Cont.)

| Field                                                                                                                                                                                                                         | Data Type                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| <b>Fields in item descriptor areas</b>                                                                                                                                                                                        |                               |
| SCOPE_CATALOG                                                                                                                                                                                                                 | CHARACTER VARYING( <i>L</i> ) |
| SCOPE_NAME                                                                                                                                                                                                                    | CHARACTER VARYING( <i>L</i> ) |
| SCOPE_SCHEMA                                                                                                                                                                                                                  | CHARACTER VARYING( <i>L</i> ) |
| SPECIFIC_TYPE_CATALOG                                                                                                                                                                                                         | CHARACTER VARYING( <i>L</i> ) |
| SPECIFIC_TYPE_NAME                                                                                                                                                                                                            | CHARACTER VARYING( <i>L</i> ) |
| SPECIFIC_TYPE_SCHEMA                                                                                                                                                                                                          | CHARACTER VARYING( <i>L</i> ) |
| TYPE                                                                                                                                                                                                                          | SMALLINT                      |
| UNNAMED                                                                                                                                                                                                                       | SMALLINT                      |
| USER_DEFINED_TYPE_CATALOG                                                                                                                                                                                                     | CHARACTER VARYING( <i>L</i> ) |
| USER_DEFINED_TYPE_NAME                                                                                                                                                                                                        | CHARACTER VARYING( <i>L</i> ) |
| USER_DEFINED_TYPE_SCHEMA                                                                                                                                                                                                      | CHARACTER VARYING( <i>L</i> ) |
| Implementation-defined item field                                                                                                                                                                                             | Implementation-defined        |
| <p><b>Where</b> <i>L</i> is an implementation-defined integer not less than 128, and <i>L1</i> is the implementation-defined maximum length for the &lt;general value specification&gt; CURRENT_TRANSFORM_GROUP_FOR_TYPE.</p> |                               |

**General Rules**

- 1) Table 7, “Codes used for implementation data types in SQL/CLI”, specifies the codes associated with the SQL data types used in implementation descriptor areas.

Table 7—Codes used for implementation data types in SQL/CLI

| Data Type                                                               | Code |
|-------------------------------------------------------------------------|------|
| ARRAY                                                                   | 50   |
| BINARY LARGE OBJECT                                                     | 30   |
| BIT                                                                     | 14   |
| BIT VARYING                                                             | 15   |
| BOOLEAN                                                                 | 16   |
| CHARACTER                                                               | 1    |
| CHARACTER LARGE OBJECT                                                  | 40   |
| CHARACTER VARYING                                                       | 12   |
| DATE, TIME, TIME WITH TIME ZONE, TIMESTAMP, or TIMESTAMP WITH TIME ZONE | 9    |
| DECIMAL                                                                 | 3    |
| DOUBLE PRECISION                                                        | 8    |

Table 7—Codes used for implementation data types in SQL/CLI (Cont.)

| Data Type                        | Code |
|----------------------------------|------|
| FLOAT                            | 6    |
| INTEGER                          | 4    |
| INTERVAL                         | 10   |
| NUMERIC                          | 2    |
| REAL                             | 7    |
| REF                              | 20   |
| ROW                              | 19   |
| SMALLINT                         | 5    |
| USER-DEFINED TYPE                | 17   |
| Implementation-defined data type | <0   |

- 2) Table 8, “Codes used for application data types in SQL/CLI”, specifies the codes associated with the SQL data types used in application descriptor areas.

Table 8—Codes used for application data types in SQL/CLI

| Data Type                        | Code |
|----------------------------------|------|
| Implementation-defined data type | <0   |
| ARRAY LOCATOR                    | 51   |
| BINARY LARGE OBJECT              | 30   |
| BINARY LARGE OBJECT LOCATOR      | 31   |
| CHARACTER                        | 1    |
| CHARACTER LARGE OBJECT           | 40   |
| CHARACTER LARGE OBJECT LOCATOR   | 41   |
| DECIMAL                          | 3    |
| DOUBLE PRECISION                 | 8    |
| FLOAT                            | 6    |
| INTEGER                          | 4    |
| NUMERIC                          | 2    |
| REAL                             | 7    |
| REF                              | 20   |
| SMALLINT                         | 5    |
| USER-DEFINED TYPE LOCATOR        | 18   |

- 3) Table 9, “Codes associated with datetime data types in SQL/CLI”, specifies the codes associated with the datetime data types allowed in SQL/CLI.

## 5.13 Description of CLI item descriptor areas

Table 9—Codes associated with datetime data types in SQL/CLI

| Datetime Data Type       | Code |
|--------------------------|------|
| DATE                     | 1    |
| TIME                     | 2    |
| TIME WITH TIME ZONE      | 4    |
| TIMESTAMP                | 3    |
| TIMESTAMP WITH TIME ZONE | 5    |

- 4) Table 10, “Codes associated with <interval qualifier> in SQL/CLI”, specifies the codes associated with <interval qualifier>s for interval data types in SQL/CLI.

Table 10—Codes associated with &lt;interval qualifier&gt; in SQL/CLI

| Interval qualifier | Code |
|--------------------|------|
| DAY                | 3    |
| DAY TO HOUR        | 8    |
| DAY TO MINUTE      | 9    |
| DAY TO SECOND      | 10   |
| HOUR               | 4    |
| HOUR TO MINUTE     | 11   |
| HOUR TO SECOND     | 12   |
| MINUTE             | 5    |
| MINUTE TO SECOND   | 13   |
| MONTH              | 2    |
| SECOND             | 6    |
| YEAR               | 1    |
| YEAR TO MONTH      | 7    |

- 5) Table 11, “Codes associated with <parameter mode> in SQL/CLI”, specifies the codes associated with the SQL parameter modes.

Table 11—Codes associated with &lt;parameter mode&gt; in SQL/CLI

| Parameter mode   | Code |
|------------------|------|
| PARAM MODE IN    | 1    |
| PARAM MODE INOUT | 2    |
| PARAM MODE OUT   | 4    |

## 5.14 Other tables associated with CLI

The tables contained in this Subclause are used to specify the codes used by the various CLI routines.

Table 12—Codes used for diagnostic fields

| Field                      | Code  | Type   |
|----------------------------|-------|--------|
| CATALOG_NAME               | 18    | Status |
| CLASS_ORIGIN               | 8     | Status |
| COLUMN_NAME                | 21    | Status |
| COLUMN_NUMBER              | -1247 | Status |
| CONDITION_IDENTIFIER       | 25    | Status |
| CONDITION_NUMBER           | 14    | Status |
| CONNECTION_NAME            | 10    | Status |
| CONSTRAINT_CATALOG         | 15    | Status |
| CONSTRAINT_NAME            | 17    | Status |
| CONSTRAINT_SCHEMA          | 16    | Status |
| CURSOR_NAME                | 22    | Status |
| DYNAMIC_FUNCTION           | 7     | Header |
| DYNAMIC_FUNCTION_CODE      | 12    | Header |
| MESSAGE_LENGTH             | 23    | Status |
| MESSAGE_OCTET_LENGTH       | 24    | Status |
| MESSAGE_TEXT               | 6     | Status |
| MORE                       | 13    | Header |
| NATIVE_CODE                | 5     | Status |
| NUMBER                     | 2     | Header |
| PARAMETER_MODE             | 37    | Status |
| PARAMETER_NAME             | 26    | Status |
| PARAMETER_ORDINAL_POSITION | 38    | Status |
| RETURNCODE                 | 1     | Header |
| ROUTINE_CATALOG            | 27    | Status |
| ROUTINE_NAME               | 29    | Status |
| ROUTINE_SCHEMA             | 28    | Status |
| ROW_COUNT                  | 3     | Header |
| ROW_NUMBER                 | -1248 | Status |
| SCHEMA_NAME                | 19    | Status |

## 5.14 Other tables associated with CLI

Table 12—Codes used for diagnostic fields (Cont.)

| Field                                           | Code             | Type   |
|-------------------------------------------------|------------------|--------|
| SERVER_NAME                                     | 11               | Status |
| SPECIFIC_NAME                                   | 30               | Status |
| SQLSTATE                                        | 4                | Status |
| SUBCLASS_ORIGIN                                 | 9                | Status |
| TABLE_NAME                                      | 20               | Status |
| TRANSACTION_ACTIVE                              | 36               | Header |
| TRANSACTIONS_COMMITTED                          | 34               | Header |
| TRANSACTIONS_ROLLED_BACK                        | 35               | Header |
| TRIGGER_CATALOG                                 | 31               | Status |
| TRIGGER_NAME                                    | 33               | Status |
| TRIGGER_SCHEMA                                  | 32               | Status |
| Implementation-defined diagnostics header field | < 0 <sup>1</sup> | Header |
| Implementation-defined diagnostics status field | < 0 <sup>1</sup> | Status |

<sup>1</sup>Except for values in this table that are less than 0 (zero).

Table 13—Codes used for handle types

| Handle type                        | Code         |
|------------------------------------|--------------|
| CONNECTION HANDLE                  | 2            |
| DESCRIPTOR HANDLE                  | 4            |
| ENVIRONMENT HANDLE                 | 1            |
| STATEMENT HANDLE                   | 3            |
| Implementation-defined handle type | < 1 or > 100 |

Table 14—Codes used for transaction termination

| Termination type         | Code |
|--------------------------|------|
| COMMIT                   | 0    |
| ROLLBACK                 | 1    |
| SAVEPOINT NAME COMMIT    | 2    |
| SAVEPOINT NUMBER COMMIT  | 3    |
| SAVEPOINT NAME RELEASE   | 4    |
| SAVEPOINT NUMBER RELEASE | 5    |
| COMMIT AND CHAIN         | 6    |

Table 14—Codes used for transaction termination (Cont.)

| Termination type                        | Code |
|-----------------------------------------|------|
| ROLLBACK AND CHAIN                      | 7    |
| Implementation-defined termination type | <0   |

Table 15—Codes used for environment attributes

| Attribute                                    | Code                                             | May be set             |
|----------------------------------------------|--------------------------------------------------|------------------------|
| NULL TERMINATION                             | 10001                                            | Yes                    |
| Implementation-defined environment attribute | $\geq 0$ ,<br>except<br>values<br>given<br>above | Implementation-defined |

Table 16—Codes used for connection attributes

| Attribute                                   | Code                                             | May be set             |
|---------------------------------------------|--------------------------------------------------|------------------------|
| POPULATE IPD                                | 10001                                            | No                     |
| SAVEPOINT NAME                              | 10027                                            | Yes                    |
| SAVEPOINT NUMBER                            | 10028                                            | Yes                    |
| Implementation-defined connection attribute | $\geq 0$ ,<br>except<br>values<br>given<br>above | Implementation-defined |

Table 17—Codes used for statement attributes

| Attribute           | Code  | May be set |
|---------------------|-------|------------|
| APD HANDLE          | 10011 | Yes        |
| ARD HANDLE          | 10010 | Yes        |
| IPD HANDLE          | 10013 | No         |
| IRD HANDLE          | 10012 | No         |
| CURRENT OF POSITION | 10027 | Yes        |
| CURSOR HOLDABLE     | -3    | Yes        |
| CURSOR SCROLLABLE   | -1    | Yes        |
| CURSOR SENSITIVITY  | -2    | Yes        |
| METADATA ID         | 10014 | Yes        |
| NEST DESCRIPTOR     | 10029 | Yes        |

## 5.14 Other tables associated with CLI

Table 17—Codes used for statement attributes (Cont.)

| Attribute                                  | Code                                             | May be set             |
|--------------------------------------------|--------------------------------------------------|------------------------|
| Implementation-defined statement attribute | $\geq 0$ ,<br>except<br>values<br>given<br>above | Implementation-defined |

Table 18—Codes used for FreeStmt options

| Option            | Code |
|-------------------|------|
| CLOSE CURSOR      | 0    |
| FREE HANDLE       | 1    |
| UNBIND COLUMNS    | 2    |
| UNBIND PARAMETERS | 3    |
| REALLOCATE        | 4    |

Table 19—Data types of attributes

| Attribute                     | Data type | Values                                               |
|-------------------------------|-----------|------------------------------------------------------|
| <b>Environment attributes</b> |           |                                                      |
| NULL TERMINATION              | INTEGER   | 0 ( <i>false</i> )<br>1 ( <i>true</i> )              |
| <b>Connection attributes</b>  |           |                                                      |
| POPULATE IPD                  | INTEGER   | 0 ( <i>false</i> )<br>1 ( <i>true</i> )              |
| <b>Statement attributes</b>   |           |                                                      |
| APD HANDLE                    | INTEGER   | Handle value                                         |
| ARD HANDLE                    | INTEGER   | Handle value                                         |
| IPD HANDLE                    | INTEGER   | Handle value                                         |
| IRD HANDLE                    | INTEGER   | Handle value                                         |
| CURRENT OF POSITION           | INTEGER   | Integer value denoting the current row in the rowset |
| CURSOR HOLDABLE               | INTEGER   | 0 (NONHOLDABLE)<br>1 (HOLDABLE)                      |
| CURSOR SCROLLABLE             | INTEGER   | 0 (NONSCROLLABLE)<br>1 (SCROLLABLE)                  |
| CURSOR SENSITIVITY            | INTEGER   | 0 (ASENSITIVE)<br>1 (INSENSITIVE)<br>2 (SENSITIVE)   |
| METADATA ID                   | INTEGER   | 0 (FALSE)<br>1 (TRUE)                                |
| NEST DESCRIPTOR               | INTEGER   | 0 (FALSE)<br>1 (TRUE)                                |
| SAVEPOINT NAME                | CHARACTER | Not specified                                        |
| SAVEPOINT NUMBER              | INTEGER   | Not specified                                        |

Table 20—Codes used for descriptor fields

| Field                 | Code | SQL Item Descriptor Name  | Type   |
|-----------------------|------|---------------------------|--------|
| ALLOC_TYPE            | 1099 | ( <i>Not applicable</i> ) | Header |
| ARRAY_SIZE            | 20   | ( <i>Not applicable</i> ) | Header |
| ARRAY_STATUS_POINTER  | 21   | ( <i>Not applicable</i> ) | Header |
| CARDINALITY           | 1040 | CARDINALITY               | Status |
| CHARACTER_SET_CATALOG | 1018 | CHARACTER_SET_CATALOG     | Item   |
| CHARACTER_SET_NAME    | 1020 | CHARACTER_SET_NAME        | Item   |
| CHARACTER_SET_SCHEMA  | 1019 | CHARACTER_SET_SCHEMA      | Item   |
| COLLATION_CATALOG     | 1015 | COLLATION_CATALOG         | Item   |

## 5.14 Other tables associated with CLI

Table 20—Codes used for descriptor fields (Cont.)

| Field                        | Code | SQL Item Descriptor Name                                     | Type   |
|------------------------------|------|--------------------------------------------------------------|--------|
| COLLATION_NAME               | 1017 | COLLATION_NAME                                               | Item   |
| COLLATION_SCHEMA             | 1016 | COLLATION_SCHEMA                                             | Item   |
| COUNT                        | 1001 | COUNT                                                        | Header |
| CURRENT_TRANSFORM_GROUP      | 1039 | <i>(Not applicable)</i>                                      | Status |
| DATA_POINTER                 | 1010 | DATA                                                         | Item   |
| DATETIME_INTERVAL_CODE       | 1007 | DATETIME_INTERVAL_CODE                                       | Item   |
| DATETIME_INTERVAL_PRECISION  | 26   | DATETIME_INTERVAL_PRECISION                                  | Item   |
| DEGREE                       | 1041 | DEGREE                                                       | Status |
| DYNAMIC_FUNCTION             | 1031 | DYNAMIC_FUNCTION                                             | Header |
| DYNAMIC_FUNCTION_CODE        | 1032 | DYNAMIC_FUNCTION_CODE                                        | Header |
| INDICATOR_POINTER            | 1009 | INDICATOR                                                    | Item   |
| KEY_MEMBER                   | 1030 | KEY_MEMBER                                                   | Item   |
| KEY_TYPE                     | 1029 | KEY_TYPE                                                     | Header |
| LENGTH                       | 1003 | LENGTH                                                       | Item   |
| LEVEL                        | 1042 | LEVEL                                                        | Item   |
| NAME                         | 1011 | NAME                                                         | Item   |
| NULLABLE                     | 1008 | NULLABLE                                                     | Item   |
| OCTET_LENGTH                 | 1013 | OCTET_LENGTH                                                 | Item   |
| OCTET_LENGTH_POINTER         | 1004 | Both OCTET_LENGTH (input) and RETURNED_OCTET_LENGTH (output) | Item   |
| PARAMETER_MODE               | 1021 | PARAMETER_MODE                                               | Item   |
| PARAMETER_ORDINAL_POSITION   | 1022 | PARAMETER_ORDINAL_POSITION                                   | Item   |
| PARAMETER_SPECIFIC_CATALOG   | 1023 | PARAMETER_SPECIFIC_CATALOG                                   | Item   |
| PARAMETER_SPECIFIC_NAME      | 1025 | PARAMETER_SPECIFIC_NAME                                      | Item   |
| PARAMETER_SPECIFIC_SCHEMA    | 1024 | PARAMETER_SPECIFIC_SCHEMA                                    | Item   |
| PRECISION                    | 1005 | PRECISION                                                    | Item   |
| RETURNED_CARDINALITY_POINTER | 1043 | RETURNED_CARDINALITY                                         | Status |
| ROW_PROCESSED_POINTER        | 34   | <i>(Not applicable)</i>                                      | Header |
| SCALE                        | 1006 | SCALE                                                        | Item   |
| SCOPE_CATALOG                | 1033 | SCOPE_CATALOG                                                | Status |
| SCOPE_NAME                   | 1035 | SCOPE_NAME                                                   | Status |
| SCOPE_SCHEMA                 | 1034 | SCOPE_SCHEMA                                                 | Status |
| SPECIFIC_TYPE_CATALOG        | 1036 | <i>(Not applicable)</i>                                      | Status |

Table 20—Codes used for descriptor fields (Cont.)

| Field                                          | Code                                                                                                                      | SQL Item Descriptor Name                       | Type   |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|--------|
| SPECIFIC_TYPE_NAME                             | 1038                                                                                                                      | (Not applicable)                               | Status |
| SPECIFIC_TYPE_SCHEMA                           | 1037                                                                                                                      | (Not applicable)                               | Status |
| TOP_LEVEL_COUNT                                | 1044                                                                                                                      | TOP_LEVEL_COUNT                                | Header |
| TYPE                                           | 1002                                                                                                                      | TYPE                                           | Item   |
| UNNAMED                                        | 1012                                                                                                                      | UNNAMED                                        | Item   |
| USER_DEFINED_TYPE_CATALOG                      | 1026                                                                                                                      | USER_DEFINED_TYPE_CATALOG                      | Item   |
| USER_DEFINED_TYPE_NAME                         | 1028                                                                                                                      | USER_DEFINED_TYPE_NAME                         | Item   |
| USER_DEFINED_TYPE_SCHEMA                       | 1027                                                                                                                      | USER_DEFINED_TYPE_SCHEMA                       | Item   |
| Implementation-defined descriptor header field | 0<br>(zero)<br>through<br>999,<br>or $\geq$<br>1200,<br>ex-<br>clud-<br>ing<br>values<br>de-<br>fined<br>in this<br>table | Implementation-defined descriptor header field | Header |
| Implementation-defined descriptor item field   | 0<br>(zero)<br>through<br>999,<br>or $\geq$<br>1200,<br>ex-<br>clud-<br>ing<br>values<br>de-<br>fined<br>in this<br>table | Implementation-defined descriptor item field   | Item   |

Table 21—Ability to set SQL/CLI descriptor fields

| Field      | May be set |     |     |     |
|------------|------------|-----|-----|-----|
|            | ARD        | IRD | APD | IPD |
| ALLOC_TYPE | No         | No  | No  | No  |

**Where** “No” means that the descriptor field is not settable, “ID” means that it is implementation-defined whether or not the descriptor field is settable, and the absence of any notation means that the descriptor field is settable.

(Continued on next page)

Table 21—Ability to set SQL/CLI descriptor fields (Cont.)

| Field                       | May be set |     |     |     |
|-----------------------------|------------|-----|-----|-----|
|                             | ARD        | IRD | APD | IPD |
| ARRAY_SIZE                  |            | No  |     | No  |
| ARRAY_STATUS_POINTER        |            |     |     |     |
| CARDINALITY                 | No         | No  | No  |     |
| CHARACTER_SET_CATALOG       |            | No  |     |     |
| CHARACTER_SET_NAME          |            | No  |     |     |
| CHARACTER_SET_SCHEMA        |            | No  |     |     |
| COLLATION_CATALOG           |            | No  |     |     |
| COLLATION_NAME              |            | No  |     |     |
| COLLATION_SCHEMA            |            | No  |     |     |
| COUNT                       |            | No  |     |     |
| CURRENT_TRANSFORM_GROUP     | No         | No  | No  | No  |
| DATA_POINTER                |            | No  |     |     |
| DATETIME_INTERVAL_CODE      |            | No  |     |     |
| DATETIME_INTERVAL_PRECISION |            | No  |     |     |
| DEGREE                      | No         | No  | No  |     |
| DYNAMIC_FUNCTION            | No         | No  | No  | No  |
| DYNAMIC_FUNCTION_CODE       | No         | No  | No  | No  |
| INDICATOR_POINTER           |            | No  |     | No  |
| KEY_MEMBER                  | No         | No  | No  | No  |
| KEY_TYPE                    | No         | No  | No  | No  |
| LENGTH                      |            | No  |     |     |
| LEVEL                       |            | No  |     |     |
| NAME                        |            | No  |     |     |
| NULLABLE                    |            | No  |     |     |
| OCTET_LENGTH                |            | No  |     |     |
| OCTET_LENGTH_POINTER        |            | No  |     | No  |
| PARAMETER_MODE              | No         | No  | No  |     |
| PARAMETER_ORDINAL_POSITION  | No         | No  | No  |     |
| PARAMETER_SPECIFIC_CATALOG  | No         | No  | No  |     |
| PARAMETER_SPECIFIC_NAME     | No         | No  | No  |     |
| PARAMETER_SPECIFIC_SCHEMA   | No         | No  | No  |     |
| PRECISION                   |            | No  |     |     |

Table 21—Ability to set SQL/CLI descriptor fields (Cont.)

| Field                                          | May be set |     |     |     |
|------------------------------------------------|------------|-----|-----|-----|
|                                                | ARD        | IRD | APD | IPD |
| RETURNED_CARDINALITY_POINTER                   |            | No  |     | No  |
| ROWS_PROCESSED_POINTER                         | No         |     | No  |     |
| SCALE                                          |            | No  |     |     |
| SCOPE_CATALOG                                  |            | No  |     |     |
| SCOPE_NAME                                     |            | No  |     |     |
| SCOPE_SCHEMA                                   |            | No  |     |     |
| SPECIFIC_TYPE_CATALOG                          | No         | No  | No  | No  |
| SPECIFIC_TYPE_NAME                             | No         | No  | No  | No  |
| SPECIFIC_TYPE_SCHEMA                           | No         | No  | No  | No  |
| TOP_LEVEL_COUNT                                |            | No  |     |     |
| TYPE                                           |            | No  |     |     |
| UNNAMED                                        |            | No  |     |     |
| USER_DEFINED_TYPE_CATALOG                      |            | No  |     |     |
| USER_DEFINED_TYPE_NAME                         |            | No  |     |     |
| USER_DEFINED_TYPE_SCHEMA                       |            | No  |     |     |
| Implementation-defined descriptor header field | ID         | ID  | ID  | ID  |
| Implementation-defined descriptor item field   | ID         | ID  | ID  | ID  |

Table 22—Ability to retrieve SQL/CLI descriptor fields

| Field                 | May be retrieved |     |     |     |
|-----------------------|------------------|-----|-----|-----|
|                       | ARD              | IRD | APD | IPD |
| ALLOC_TYPE            |                  | PS  |     |     |
| ARRAY_SIZE            |                  | No  |     | No  |
| ARRAY_STATUS_POINTER  |                  |     |     |     |
| CARDINALITY           | No               | PS  | No  |     |
| CHARACTER_SET_CATALOG |                  | PS  |     |     |
| CHARACTER_SET_NAME    |                  | PS  |     |     |
| CHARACTER_SET_SCHEMA  |                  | PS  |     |     |
| COLLATION_CATALOG     |                  | PS  |     |     |
| COLLATION_NAME        |                  | PS  |     |     |

Table 22—Ability to retrieve SQL/CLI descriptor fields (Cont.)

| Field                        | May be retrieved |     |     |     |
|------------------------------|------------------|-----|-----|-----|
|                              | ARD              | IRD | APD | IPD |
| COLLATION_SCHEMA             |                  | PS  |     |     |
| COUNT                        |                  | PS  |     |     |
| CURRENT_TRANSFORM_GROUP      |                  | PS  |     |     |
| DATA_POINTER                 |                  | No  |     | No  |
| DATETIME_INTERVAL_CODE       |                  | PS  |     |     |
| DATETIME_INTERVAL_PRECISION  |                  | PS  |     |     |
| DEGREE                       | No               | PS  | No  |     |
| DYNAMIC_FUNCTION             | No               |     | No  |     |
| DYNAMIC_FUNCTION_CODE        | No               |     | No  |     |
| INDICATOR_POINTER            |                  | No  |     | No  |
| KEY_MEMBER                   | No               | PS  | No  | No  |
| KEY_TYPE                     | No               | PS  | No  | No  |
| LENGTH                       |                  | PS  |     |     |
| LEVEL                        |                  | PS  |     |     |
| NAME                         |                  | PS  |     |     |
| NULLABLE                     |                  | PS  |     |     |
| OCTET_LENGTH                 |                  | PS  |     |     |
| OCTET_LENGTH_POINTER         |                  | No  |     | No  |
| PARAMETER_MODE               | No               | PS  | No  | No  |
| PARAMETER_ORDINAL_POSITION   | No               | PS  | No  | No  |
| PARAMETER_SPECIFIC_CATALOG   | No               | PS  | No  | No  |
| PARAMETER_SPECIFIC_NAME      | No               | PS  | No  | No  |
| PARAMETER_SPECIFIC_SCHEMA    | No               | PS  | No  | No  |
| PRECISION                    |                  | PS  |     |     |
| RETURNED_CARDINALITY_POINTER |                  | No  |     | No  |
| ROWS_PROCESSED_POINTER       | No               |     | No  |     |
| SCALE                        |                  | PS  |     |     |
| SCOPE_CATALOG                |                  | PS  |     |     |
| SCOPE_NAME                   |                  | PS  |     |     |
| SCOPE_SCHEMA                 |                  | PS  |     |     |

**Where** “No” means that the descriptor field is not retrievable, *PS* means that the descriptor field is retrievable from the IRD only when a prepared or executed statement is associated with the IRD, the absence of any notation means that the descriptor field is retrievable, and “ID” means that it is implementation-defined whether or not the descriptor field is retrievable.

Table 22—Ability to retrieve SQL/CLI descriptor fields (Cont.)

| Field                                          | May be retrieved |     |     |     |
|------------------------------------------------|------------------|-----|-----|-----|
|                                                | ARD              | IRD | APD | IPD |
| SPECIFIC_TYPE_CATALOG                          |                  | PS  |     |     |
| SPECIFIC_TYPE_NAME                             |                  | PS  |     |     |
| SPECIFIC_TYPE_SCHEMA                           |                  | PS  |     |     |
| TOP_LEVEL_COUNT                                |                  | PS  |     |     |
| TYPE                                           |                  | PS  |     |     |
| UNNAMED                                        |                  | PS  |     |     |
| USER_DEFINED_TYPE_CATALOG                      |                  | PS  |     |     |
| USER_DEFINED_TYPE_NAME                         |                  | PS  |     |     |
| USER_DEFINED_TYPE_SCHEMA                       |                  | PS  |     |     |
| Implementation-defined descriptor header field | ID               | ID  | ID  | ID  |
| Implementation-defined descriptor item field   | ID               | ID  | ID  | ID  |

Table 23—SQL/CLI descriptor field default values

| Field                   | Default values    |           |                   |           |
|-------------------------|-------------------|-----------|-------------------|-----------|
|                         | ARD               | IRD       | APD               | IPD       |
| ALLOC_TYPE              | AUTOMATIC or USER | AUTOMATIC | AUTOMATIC or USER | AUTOMATIC |
| ARRAY_SIZE              | 1 (one)           |           | 1 (one)           |           |
| ARRAY_STATUS_POINTER    | Null              | Null      | Null              | Null      |
| CARDINALITY             |                   |           |                   |           |
| CHARACTER_SET_CATALOG   |                   |           |                   |           |
| CHARACTER_SET_NAME      |                   |           |                   |           |
| CHARACTER_SET_SCHEMA    |                   |           |                   |           |
| COLLATION_CATALOG       |                   |           |                   |           |
| COLLATION_NAME          |                   |           |                   |           |
| COLLATION_SCHEMA        |                   |           |                   |           |
| COUNT                   | 0 (zero)          |           | 0 (zero)          |           |
| CURRENT_TRANSFORM_GROUP |                   |           |                   |           |

**Where** "Null" means that the descriptor field's default value is a null pointer, the absence of any notation means that the descriptor field's default value is initially undefined, "ID" means that the descriptor field's default value is implementation-defined, and any other value specifies the descriptor field's default value.

(Continued on next page)

Table 23—SQL/CLI descriptor field default values (Cont.)

| Field                        | Default values |      |          |      |
|------------------------------|----------------|------|----------|------|
|                              | ARD            | IRD  | APD      | IPD  |
| DATA_POINTER                 | Null           |      | Null     |      |
| DATETIME_INTERVAL_CODE       |                |      |          |      |
| DATETIME_INTERVAL_PRECISION  |                |      |          |      |
| DEGREE                       |                |      |          |      |
| DYNAMIC_FUNCTION             |                |      |          |      |
| DYNAMIC_FUNCTION_CODE        |                |      |          |      |
| INDICATOR_POINTER            | Null           |      | Null     |      |
| KEY_MEMBER                   |                |      |          |      |
| KEY_TYPE                     |                |      |          |      |
| LENGTH                       |                |      |          |      |
| LEVEL                        | 0 (zero)       |      | 0 (zero) |      |
| NAME                         |                |      |          |      |
| NULLABLE                     |                |      |          |      |
| OCTET_LENGTH                 |                |      |          |      |
| OCTET_LENGTH_POINTER         | Null           |      | Null     |      |
| PARAMETER_MODE               |                |      |          |      |
| PARAMETER_ORDINAL_POSITION   |                |      |          |      |
| PARAMETER_SPECIFIC_CATALOG   |                |      |          |      |
| PARAMETER_SPECIFIC_NAME      |                |      |          |      |
| PARAMETER_SPECIFIC_SCHEMA    |                |      |          |      |
| PRECISION                    |                |      |          |      |
| RETURNED_CARDINALITY_POINTER | Null           |      | Null     |      |
| ROWS_PROCESSED_POINTER       |                | Null |          | Null |
| SCALE                        |                |      |          |      |
| SCOPE_CATALOG                |                |      |          |      |
| SCOPE_NAME                   |                |      |          |      |
| SCOPE_SCHEMA                 |                |      |          |      |
| SPECIFIC_TYPE_CATALOG        |                |      |          |      |
| SPECIFIC_TYPE_NAME           |                |      |          |      |

Table 23—SQL/CLI descriptor field default values (Cont.)

| Field                                          | Default values |     |          |     |
|------------------------------------------------|----------------|-----|----------|-----|
|                                                | ARD            | IRD | APD      | IPD |
| SPECIFIC_TYPE_SCHEMA                           |                |     |          |     |
| TOP_LEVEL_COUNT                                | 0 (zero)       |     | 0 (zero) |     |
| TYPE                                           | DEFAULT        |     | DEFAULT  |     |
| UNNAMED                                        |                |     |          |     |
| USER_DEFINED_TYPE_CATALOG                      |                |     |          |     |
| USER_DEFINED_TYPE_NAME                         |                |     |          |     |
| USER_DEFINED_TYPE_SCHEMA                       |                |     |          |     |
| Implementation-defined descriptor header field | ID             | ID  | ID       | ID  |
| Implementation-defined descriptor item field   | ID             | ID  | ID       | ID  |

Table 24—Codes used for fetch orientation

| Fetch Orientation | Code |
|-------------------|------|
| NEXT              | 1    |
| FIRST             | 2    |
| LAST              | 3    |
| PRIOR             | 4    |
| ABSOLUTE          | 5    |
| RELATIVE          | 6    |

Table 25—Multi-row fetch status codes

| Return code meaning          | Return code |
|------------------------------|-------------|
| Row success                  | 0 (zero)    |
| Row success with information | 6           |
| Row error                    | 5           |
| No row                       | 3           |

## 5.14 Other tables associated with CLI

Table 26—Miscellaneous codes used in CLI

| Context                | Code | Indicates                                               |
|------------------------|------|---------------------------------------------------------|
| Allocation type        | 1    | AUTOMATIC                                               |
| Allocation type        | 2    | USER                                                    |
| Attribute value        | 0    | FALSE, NONSCROLLABLE, ASENSITIVE, NO NULLS, NONHOLDABLE |
| Attribute value        | 1    | TRUE, SCROLLABLE, INSENSITIVE, NULLABLE, HOLDABLE       |
| Attribute value        | 2    | SENSITIVE                                               |
| Data type              | 0    | ALL TYPES                                               |
| Data type              | -99  | APD TYPE                                                |
| Data type              | -99  | ARD TYPE                                                |
| Data type              | 99   | DEFAULT                                                 |
| Deferrable constraints | 5    | INITIALLY DEFERRED                                      |
| Deferrable constraints | 6    | INITIALLY IMMEDIATE                                     |
| Deferrable constraints | 7    | NOT DEFERRABLE                                          |
| Input string length    | -3   | NULL TERMINATED                                         |
| Input or output data   | -1   | SQL NULL DATA                                           |
| Parameter length       | -2   | DATA AT EXEC                                            |
| Referential Constraint | 0    | CASCADE                                                 |
| Referential Constraint | 1    | RESTRICT                                                |
| Referential Constraint | 4    | SET DEFAULT                                             |
| Referential Constraint | 2    | SET NULL                                                |
| Referential Constraint | 3    | NO ACTION                                               |

Table 27—Codes used to identify SQL/CLI routines

| Generic Name     | Code |
|------------------|------|
| AllocConnect     | 1    |
| AllocEnv         | 2    |
| AllocHandle      | 1001 |
| AllocStmt        | 3    |
| BindCol          | 4    |
| BindParameter    | 72   |
| Cancel           | 5    |
| CloseCursor      | 1003 |
| ColAttribute     | 6    |
| ColumnPrivileges | 56   |

Table 27—Codes used to identify SQL/CLI routines (Cont.)

| Generic Name   | Code |
|----------------|------|
| Columns        | 40   |
| Connect        | 7    |
| CopyDesc       | 1004 |
| DataSources    | 57   |
| DescribeCol    | 8    |
| Disconnect     | 9    |
| EndTran        | 1005 |
| Error          | 10   |
| ExecDirect     | 11   |
| Execute        | 12   |
| Fetch          | 13   |
| FetchScroll    | 1021 |
| ForeignKeys    | 60   |
| FreeConnect    | 14   |
| FreeEnv        | 15   |
| FreeHandle     | 1006 |
| FreeStmt       | 16   |
| GetConnectAttr | 1007 |
| GetCursorName  | 17   |
| GetData        | 43   |
| GetDescField   | 1008 |
| GetDescRec     | 1009 |
| GetDiagField   | 1010 |
| GetDiagRec     | 1011 |
| GetEnvAttr     | 1012 |
| GetFeatureInfo | 1027 |
| GetFunctions   | 44   |
| GetInfo        | 45   |
| GetLength      | 1022 |
| GetParamData   | 1025 |
| GetPosition    | 1023 |
| GetSessionInfo | 1028 |
| GetStmtAttr    | 1014 |
| GetSubString   | 1024 |

## 5.14 Other tables associated with CLI

Table 27—Codes used to identify SQL/CLI routines (Cont.)

| Generic Name                                  | Code                                            |
|-----------------------------------------------|-------------------------------------------------|
| GetTypeInfo                                   | 47                                              |
| MoreResults                                   | 61                                              |
| NextResult                                    | 73                                              |
| NumResultCols                                 | 18                                              |
| ParamData                                     | 48                                              |
| Prepare                                       | 19                                              |
| PrimaryKeys                                   | 65                                              |
| PutData                                       | 49                                              |
| RowCount                                      | 20                                              |
| SetConnectAttr                                | 1016                                            |
| SetCursorName                                 | 21                                              |
| SetDescField                                  | 1017                                            |
| SetDescRec                                    | 1018                                            |
| SetEnvAttr                                    | 1019                                            |
| SetStmtAttr                                   | 1020                                            |
| SpecialColumns                                | 52                                              |
| StartTran                                     | 74                                              |
| TablePrivileges                               | 70                                              |
| Tables                                        | 54                                              |
| <i>Implementation-defined<br/>CLI routine</i> | < 0 (zero), or 400 through 1299, or $\geq$ 2000 |

Table 28—Codes and data types for implementation information

| Information Type              | Code  | Data Type      |
|-------------------------------|-------|----------------|
| ALTER TABLE                   | 86    | INTEGER        |
| CATALOG NAME                  | 10003 | CHARACTER(1)   |
| COLLATING SEQUENCE            | 10004 | CHARACTER(254) |
| CURSOR COMMIT BEHAVIOR        | 23    | SMALLINT       |
| CURSOR SENSITIVITY            | 10001 | INTEGER        |
| DATA SOURCE NAME              | 2     | CHARACTER(128) |
| DATA SOURCE READ ONLY         | 25    | CHARACTER(1)   |
| DBMS NAME                     | 17    | CHARACTER(254) |
| DBMS VERSION                  | 18    | CHARACTER(254) |
| DEFAULT TRANSACTION ISOLATION | 26    | INTEGER        |

Table 28—Codes and data types for implementation information (Cont.)

| Information Type                | Code  | Data Type      |
|---------------------------------|-------|----------------|
| DESCRIBE PARAMETER              | 10002 | CHARACTER(1)   |
| FETCH DIRECTION                 | 8     | INTEGER        |
| GETDATA EXTENSIONS              | 81    | INTEGER        |
| IDENTIFIER CASE                 | 28    | SMALLINT       |
| INTEGRITY                       | 73    | CHARACTER(1)   |
| MAXIMUM CATALOG NAME LENGTH     | 34    | SMALLINT       |
| MAXIMUM COLUMN NAME LENGTH      | 30    | SMALLINT       |
| MAXIMUM COLUMNS IN GROUP BY     | 97    | SMALLINT       |
| MAXIMUM COLUMNS IN ORDER BY     | 99    | SMALLINT       |
| MAXIMUM COLUMNS IN SELECT       | 100   | SMALLINT       |
| MAXIMUM COLUMNS IN TABLE        | 101   | SMALLINT       |
| MAXIMUM CONCURRENT ACTIVITIES   | 1     | SMALLINT       |
| MAXIMUM CURSOR NAME LENGTH      | 31    | SMALLINT       |
| MAXIMUM DRIVER CONNECTIONS      | 0     | SMALLINT       |
| MAXIMUM IDENTIFIER LENGTH       | 10005 | SMALLINT       |
| MAXIMUM SCHEMA NAME LENGTH      | 32    | SMALLINT       |
| MAXIMUM STATEMENT OCTETS        | 20000 | SMALLINT       |
| MAXIMUM STATEMENT OCTETS DATA   | 20001 | SMALLINT       |
| MAXIMUM STATEMENT OCTETS SCHEMA | 20002 | SMALLINT       |
| MAXIMUM TABLE NAME LENGTH       | 35    | SMALLINT       |
| MAXIMUM TABLES IN SELECT        | 106   | SMALLINT       |
| MAXIMUM USER NAME LENGTH        | 107   | SMALLINT       |
| NULL COLLATION                  | 85    | SMALLINT       |
| OUTER JOIN CAPABILITIES         | 115   | INTEGER        |
| ORDER BY COLUMNS IN SELECT      | 90    | CHARACTER(1)   |
| SCROLL CONCURRENCY              | 43    | INTEGER        |
| SEARCH PATTERN ESCAPE           | 14    | CHARACTER(1)   |
| SERVER NAME                     | 13    | CHARACTER(128) |
| SPECIAL CHARACTERS              | 94    | CHARACTER(254) |
| TRANSACTION CAPABLE             | 46    | SMALLINT       |
| TRANSACTION ISOLATION OPTION    | 72    | INTEGER        |
| USER NAME                       | 47    | CHARACTER(128) |

## 5.14 Other tables associated with CLI

Table 28—Codes and data types for implementation information (Cont.)

| Information Type                                  | Code                   | Data Type                     |
|---------------------------------------------------|------------------------|-------------------------------|
| Implementation-defined information type           | Implementation-defined | Implementation-defined        |
| SQL implementation information                    | 21000 through 24999    | CHARACTER( $L^1$ ) or INTEGER |
| SQL sizing information                            | 25000 through 29999    | INTEGER                       |
| Implementation-defined implementation information | 11000 through 14999    | CHARACTER( $L^1$ ) or INTEGER |
| Implementation-defined sizing information         | 15000 through 19999    | INTEGER                       |

<sup>1</sup> $L$  is the implementation-defined maximum length of a variable-length character string.

NOTE 12 – Additional implementation information items are defined in Subclause 21.36, "SQL\_IMPLEMENTATION\_INFO base table", in ISO/IEC 9075-2.

Additional sizing items are defined in Subclause 21.38, "SQL\_SIZING base table", in ISO/IEC 9075-2.

Table 29—Codes and data types for session implementation information

| Information Type                | Code  | Data Type        | <general value specification>   |
|---------------------------------|-------|------------------|---------------------------------|
| CURRENT USER                    | 47    | CHARACTER( $L$ ) | USER and CURRENT_USER           |
| CURRENT DEFAULT TRANSFORM GROUP | 20004 | CHARACTER( $L$ ) | CURRENT_DEFAULT_TRANSFORM_GROUP |
| CURRENT PATH                    | 20005 | CHARACTER( $L$ ) | CURRENT_PATH                    |
| CURRENT ROLE                    | 20006 | CHARACTER( $L$ ) | CURRENT_ROLE                    |
| SESSION USER                    | 20007 | CHARACTER( $L$ ) | SESSION_USER                    |
| SYSTEM USER                     | 20008 | CHARACTER( $L$ ) | SYSTEM_USER                     |

**Where**  $L$  is the implementation-defined maximum length of the corresponding <general value specification>.

Table 30—Values for ALTER TABLE with GetInfo

| Information Type | Value |
|------------------|-------|
| ADD COLUMN       | 1     |
| DROP COLUMN      | 2     |
| ALTER COLUMN     | 4     |
| ADD CONSTRAINT   | 8     |
| DROP CONSTRAINT  | 16    |

Table 31—Values for FETCH DIRECTION with GetInfo

| Information Type | Value |
|------------------|-------|
| FETCH NEXT       | 1     |
| FETCH FIRST      | 2     |
| FETCH LAST       | 4     |
| FETCH PRIOR      | 8     |
| FETCH ABSOLUTE   | 16    |
| FETCH RELATIVE   | 32    |

Table 32—Values for GETDATA EXTENSIONS with GetInfo

| Information Type | Value |
|------------------|-------|
| ANY COLUMN       | 1     |
| ANY ORDER        | 2     |

Table 33—Values for OUTER JOIN CAPABILITIES with GetInfo

| Information Type   | Value |
|--------------------|-------|
| LEFT               | 1     |
| RIGHT              | 2     |
| FULL               | 4     |
| NESTED             | 8     |
| NOT ORDERED        | 16    |
| INNER              | 32    |
| ALL COMPARISON OPS | 64    |

Table 34—Values for SCROLL CONCURRENCY with GetInfo

| Information Type | Value |
|------------------|-------|
| READ ONLY        | 1     |
| LOCK             | 2     |
| OPT ROWVER       | 4     |
| OPT VALUES       | 8     |

Table 35—Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran

| Information Type | Value |
|------------------|-------|
| READ UNCOMMITTED | 1     |
| READ COMMITTED   | 2     |

## 5.14 Other tables associated with CLI

Table 35—Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran (Cont.)

| Information Type | Value |
|------------------|-------|
| REPEATABLE READ  | 4     |
| SERIALIZABLE     | 8     |

Table 36—Values for TRANSACTION ACCESS MODE with StartTran

| Information Type | Value |
|------------------|-------|
| READ ONLY        | 1     |
| READ WRITE       | 2     |

Table 37—Codes used for concise data types

| Data Type                        | Code |
|----------------------------------|------|
| Implementation-defined data type | <0   |
| CHARACTER                        | 1    |
| CHAR                             | 1    |
| NUMERIC                          | 2    |
| DECIMAL                          | 3    |
| DEC                              | 3    |
| INTEGER                          | 4    |
| INT                              | 4    |
| SMALLINT                         | 5    |
| FLOAT                            | 6    |
| REAL                             | 7    |
| DOUBLE                           | 8    |
| CHARACTER VARYING                | 12   |
| CHAR VARYING                     | 12   |
| VARCHAR                          | 12   |
| BIT                              | 14   |
| BIT VARYING                      | 15   |
| BOOLEAN                          | 16   |
| REF                              | 20   |
| BINARY LARGE OBJECT              | 30   |
| BLOB                             | 30   |
| CHARACTER LARGE OBJECT           | 40   |
| CLOB                             | 40   |

Table 37—Codes used for concise data types (Cont.)

| Data Type                 | Code |
|---------------------------|------|
| DATE                      | 91   |
| TIME                      | 92   |
| TIMESTAMP                 | 93   |
| TIME WITH TIME ZONE       | 94   |
| TIMESTAMP WITH TIME ZONE  | 95   |
| INTERVAL YEAR             | 101  |
| INTERVAL MONTH            | 102  |
| INTERVAL DAY              | 103  |
| INTERVAL HOUR             | 104  |
| INTERVAL MINUTE           | 105  |
| INTERVAL SECOND           | 106  |
| INTERVAL YEAR TO MONTH    | 107  |
| INTERVAL DAY TO HOUR      | 108  |
| INTERVAL DAY TO MINUTE    | 109  |
| INTERVAL DAY TO SECOND    | 110  |
| INTERVAL HOUR TO MINUTE   | 111  |
| INTERVAL HOUR TO SECOND   | 112  |
| INTERVAL MINUTE TO SECOND | 113  |

Table 38—Codes used with concise datetime data types in SQL/CLI

| Concise Data Type Code | Data Type Code | Datetime Interval Code |
|------------------------|----------------|------------------------|
| 91                     | 9              | 1                      |
| 92                     | 9              | 2                      |
| 93                     | 9              | 3                      |
| 94                     | 9              | 4                      |
| 95                     | 9              | 5                      |

Table 39—Codes used with concise interval data types in SQL/CLI

| Concise Data Type Code | Data Type Code | Datetime Interval Code |
|------------------------|----------------|------------------------|
| 101                    | 10             | 1                      |
| 102                    | 10             | 2                      |
| 103                    | 10             | 3                      |
| 104                    | 10             | 4                      |

## 5.14 Other tables associated with CLI

Table 39—Codes used with concise interval data types in SQL/CLI (Cont.)

| Concise Data Type Code | Data Type Code | Datetime Interval Code |
|------------------------|----------------|------------------------|
| 105                    | 10             | 5                      |
| 106                    | 10             | 6                      |
| 107                    | 10             | 7                      |
| 108                    | 10             | 8                      |
| 109                    | 10             | 9                      |
| 110                    | 10             | 10                     |
| 111                    | 10             | 11                     |
| 112                    | 10             | 12                     |
| 113                    | 10             | 13                     |

Table 40—Concise codes used with datetime data types in SQL/CLI

| Datetime Interval Code | Concise Code |
|------------------------|--------------|
| 1                      | 91           |
| 2                      | 92           |
| 3                      | 93           |
| 4                      | 94           |
| 5                      | 95           |

Table 41—Concise codes used with interval data types in SQL/CLI

| Datetime Interval Code | Code |
|------------------------|------|
| 1                      | 101  |
| 2                      | 102  |
| 3                      | 103  |
| 4                      | 104  |
| 5                      | 105  |
| 6                      | 106  |
| 7                      | 107  |
| 8                      | 108  |
| 9                      | 109  |
| 10                     | 110  |
| 11                     | 111  |
| 12                     | 112  |
| 13                     | 113  |

Table 42—Special parameter values

| Value Name   | Value | Data Type    |
|--------------|-------|--------------|
| ALL CATALOGS | '%'   | CHARACTER(1) |
| ALL SCHEMAS  | '%'   | CHARACTER(1) |
| ALL TYPES    | '%'   | CHARACTER(1) |

Table 43—Column types and scopes used with SpecialColumns

| Context             | Code | Indicates         |
|---------------------|------|-------------------|
| Special Column Type | 1    | BEST ROWID        |
| Scope of Row Id     | 0    | SCOPE CURRENT ROW |
| Scope of Row Id     | 1    | SCOPE TRANSACTION |
| Scope of Row Id     | 2    | SCOPE SESSION     |
| Pseudo Column Flag  | 0    | PSEUDO UNKNOWN    |
| Pseudo Column Flag  | 1    | NOT PSEUDO        |
| Pseudo Column Flag  | 2    | PSEUDO            |

## 5.15 Data type correspondences

### Function

Replaces first paragraph Specify the data type correspondences for SQL data types and host language types associated with the required parameter mechanisms, as shown in Table 3, “Supported calling conventions of SQL/CLI routines by language”.

Replaces second paragraph In the following tables, let  $P$  be <precision>,  $S$  be <scale>,  $L$  be <length>,  $T$  be <time fractional seconds precision>, and  $Q$  be <interval qualifier>.

### Tables

Table 44—Data type correspondences for Ada

| SQL Data Type                  | Ada Data Type                           |
|--------------------------------|-----------------------------------------|
| ARRAY                          | <i>None</i>                             |
| ARRAY LOCATOR                  | SQL_STANDARD.INT                        |
| BINARY LARGE OBJECT ( $L$ )    | SQL_STANDARD.CHAR, with P'LENGTH of $L$ |
| BINARY LARGE OBJECT LOCATOR    | SQL_STANDARD.INT                        |
| BIT ( $L$ )                    | SQL_STANDARD.BIT, with P'LENGTH of $L$  |
| BIT VARYING ( $L$ )            | <i>None</i>                             |
| BOOLEAN                        | SQL_STANDARD.BOOLEAN                    |
| CHARACTER ( $L$ )              | SQL_STANDARD.CHAR, with P'LENGTH of $L$ |
| CHARACTER LARGE OBJECT ( $L$ ) | SQL_STANDARD.CHAR, with P'LENGTH of $L$ |
| CHARACTER LARGE OBJECT LOCATOR | SQL_STANDARD.INT                        |
| CHARACTER VARYING ( $L$ )      | <i>None</i>                             |
| DATE                           | <i>None</i>                             |
| DECIMAL( $P,S$ )               | <i>None</i>                             |
| DOUBLE PRECISION               | SQL_STANDARD.DOUBLE_PRECISION           |
| FLOAT( $P$ )                   | <i>None</i>                             |
| INTEGER                        | SQL_STANDARD.INT                        |
| INTERVAL( $Q$ )                | <i>None</i>                             |
| NUMERIC( $P,S$ )               | <i>None</i>                             |
| REAL                           | SQL_STANDARD.REAL                       |
| REF                            | SQL_STANDARD.CHAR with P'LENGTH of $L$  |
| ROW                            | <i>None</i>                             |
| SMALLINT                       | SQL_STANDARD.SMALLINT                   |
| TIME( $T$ )                    | <i>None</i>                             |
| TIMESTAMP( $T$ )               | <i>None</i>                             |

Table 44—Data type correspondences for Ada (Cont.)

| SQL Data Type             | Ada Data Type    |
|---------------------------|------------------|
| USER-DEFINED TYPE         | <i>None</i>      |
| USER-DEFINED TYPE LOCATOR | SQL_STANDARD.INT |

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

Table 45—Data type correspondences for C

| SQL Data Type                       | C Data Type                   |
|-------------------------------------|-------------------------------|
| ARRAY                               | <i>None</i>                   |
| ARRAY LOCATOR                       | long                          |
| BINARY LARGE OBJECT ( <i>L</i> )    | char, with length <i>L</i>    |
| BINARY LARGE OBJECT LOCATOR         | long                          |
| BIT ( <i>L</i> )                    | char, with length $X^2$       |
| BIT VARYING ( <i>L</i> )            | <i>None</i>                   |
| BOOLEAN                             | short                         |
| CHARACTER ( <i>L</i> )              | char, with length $(L+1)*k^1$ |
| CHARACTER LARGE OBJECT ( <i>L</i> ) | char, with length $(L+1)*k^1$ |
| CHARACTER LARGE OBJECT LOCATOR      | long                          |
| CHARACTER VARYING ( <i>L</i> )      | char, with length $(L+1)*k^1$ |
| DATE                                | <i>None</i>                   |
| DECIMAL( <i>P,S</i> )               | <i>None</i>                   |
| DOUBLE PRECISION                    | double                        |
| FLOAT( <i>P</i> )                   | <i>None</i>                   |
| INTEGER                             | long                          |
| INTERVAL( <i>Q</i> )                | <i>None</i>                   |
| NUMERIC( <i>P,S</i> )               | <i>None</i>                   |
| REAL                                | float                         |
| REF                                 | char, with length <i>L</i>    |
| ROW                                 | <i>None</i>                   |
| SMALLINT                            | short                         |
| TIME( <i>T</i> )                    | <i>None</i>                   |
| TIMESTAMP( <i>T</i> )               | <i>None</i>                   |
| USER-DEFINED TYPE                   | <i>None</i>                   |
| USER-DEFINED TYPE LOCATOR           | long                          |

<sup>1</sup> *k* is the length in units of C **char** of the largest character in the character set associated with the SQL data type.

<sup>2</sup> The length *X* of the character data type corresponding with SQL data type BIT(*L*) is the smallest integer not less than the quotient of the division  $L/B$ , where *B* is the implementation-defined number of bits contained in a character of the host language.

Table 46—Data type correspondences for COBOL

| SQL Data Type                       | COBOL Data Type                                                                   |
|-------------------------------------|-----------------------------------------------------------------------------------|
| ARRAY                               | <i>None</i>                                                                       |
| ARRAY LOCATOR                       | PICTURE S9( <i>PI</i> ) USAGE BINARY, where <i>PI</i> is implementation-defined   |
| BINARY LARGE OBJECT ( <i>L</i> )    | alphanumeric, with length <i>L</i>                                                |
| BINARY LARGE OBJECT LOCATOR         | PICTURE S9( <i>PI</i> ) USAGE BINARY, where <i>PI</i> is implementation-defined   |
| BIT ( <i>L</i> )                    | alphanumeric, with length $X^1$                                                   |
| BIT VARYING ( <i>L</i> )            | <i>None</i>                                                                       |
| BOOLEAN                             | PICTURE X                                                                         |
| CHARACTER ( <i>L</i> )              | alphanumeric, with length <i>L</i>                                                |
| CHARACTER LARGE OBJECT ( <i>L</i> ) | alphanumeric, with length <i>L</i>                                                |
| CHARACTER LARGE OBJECT LOCATOR      | PICTURE S9( <i>PI</i> ) USAGE BINARY, where <i>PI</i> is implementation-defined   |
| CHARACTER VARYING ( <i>L</i> )      | <i>None</i>                                                                       |
| DATE                                | <i>None</i>                                                                       |
| DECIMAL( <i>P,S</i> )               | <i>None</i>                                                                       |
| DOUBLE PRECISION                    | <i>None</i>                                                                       |
| FLOAT( <i>P</i> )                   | <i>None</i>                                                                       |
| INTEGER                             | PICTURE S9( <i>PI</i> ) USAGE BINARY, where <i>PI</i> is implementation-defined   |
| INTERVAL( <i>Q</i> )                | <i>None</i>                                                                       |
| NUMERIC( <i>P,S</i> )               | USAGE DISPLAY SIGN LEADING SEPARATE, with PICTURE as specified <sup>2</sup>       |
| REAL                                | <i>None</i>                                                                       |
| REF                                 | alphanumeric, with length <i>L</i>                                                |
| ROW                                 | <i>None</i>                                                                       |
| SMALLINT                            | PICTURE S9( <i>SPI</i> ) USAGE BINARY, where <i>SPI</i> is implementation-defined |
| TIME( <i>T</i> )                    | <i>None</i>                                                                       |
| TIMESTAMP( <i>T</i> )               | <i>None</i>                                                                       |
| USER-DEFINED TYPE                   | <i>None</i>                                                                       |

<sup>1</sup>The length of a character type corresponding with SQL BIT(*L*) is one more than the smallest integer not less than the quotient of the division  $L/B$ , where *B* is the implementation-defined number of bits contained in one character of the host language.

<sup>2</sup>Case:

a) If  $S=P$ , then a PICTURE with an 'S' followed by a 'V' followed by *P* '9's.

b) If  $P>S>0$ , then a PICTURE with an 'S' followed by  $P-S$  '9's followed by a 'V' followed by *S* '9's.

c) If  $S=0$ , then a PICTURE with an 'S' followed by *P* '9's optionally followed by a 'V'.

(Continued on next page)

Table 46—Data type correspondences for COBOL (Cont.)

| SQL Data Type             | COBOL Data Type                                                                 |
|---------------------------|---------------------------------------------------------------------------------|
| USER-DEFINED TYPE LOCATOR | PICTURE S9( <i>PI</i> ) USAGE BINARY, where <i>PI</i> is implementation-defined |

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

Table 47—Data type correspondences for Fortran

| SQL Data Type                       | Fortran Data Type               |
|-------------------------------------|---------------------------------|
| ARRAY                               | <i>None</i>                     |
| ARRAY LOCATOR                       | INTEGER                         |
| BINARY LARGE OBJECT ( <i>L</i> )    | CHARACTER, with length <i>L</i> |
| BINARY LARGE OBJECT LOCATOR         | INTEGER                         |
| BOOLEAN                             | LOGICAL                         |
| BIT ( <i>L</i> )                    | CHARACTER, with length $X^1$    |
| BIT VARYING ( <i>L</i> )            | <i>None</i>                     |
| CHARACTER ( <i>L</i> )              | CHARACTER, with length <i>L</i> |
| CHARACTER LARGE OBJECT ( <i>L</i> ) | CHARACTER, with length <i>L</i> |
| CHARACTER LARGE OBJECT LOCATOR      | INTEGER                         |
| CHARACTER VARYING ( <i>L</i> )      | <i>None</i>                     |
| DATE                                | <i>None</i>                     |
| DECIMAL( <i>P,S</i> )               | <i>None</i>                     |
| DOUBLE PRECISION                    | DOUBLE PRECISION                |
| FLOAT( <i>P</i> )                   | <i>None</i>                     |
| INTEGER                             | INTEGER                         |
| INTERVAL( <i>Q</i> )                | <i>None</i>                     |
| NUMERIC( <i>P,S</i> )               | <i>None</i>                     |
| REAL                                | REAL                            |
| REF                                 | CHARACTER, with length <i>L</i> |
| ROW                                 | <i>None</i>                     |
| SMALLINT                            | <i>None</i>                     |
| TIME( <i>T</i> )                    | <i>None</i>                     |
| TIMESTAMP( <i>T</i> )               | <i>None</i>                     |
| USER-DEFINED TYPE                   | <i>None</i>                     |
| USER-DEFINED TYPE LOCATOR           | INTEGER                         |

<sup>1</sup>The length *X* of the character data type corresponding with SQL data type BIT(*L*) is the smallest integer not less than the quotient of the division  $L/B$ , where *B* is the implementation-defined number of bits contained in a character of the host language.

Table 48—Data type correspondences for MUMPS

| SQL Data Type                       | MUMPS Data Type                        |
|-------------------------------------|----------------------------------------|
| ARRAY                               | <i>None</i>                            |
| ARRAY LOCATOR                       | character                              |
| BINARY LARGE OBJECT ( <i>L</i> )    | character                              |
| BINARY LARGE OBJECT LOCATOR         | character                              |
| BIT ( <i>L</i> )                    | <i>None</i>                            |
| BIT VARYING ( <i>L</i> )            | <i>None</i>                            |
| BOOLEAN                             | <i>None</i>                            |
| CHARACTER ( <i>L</i> )              | <i>None</i>                            |
| CHARACTER LARGE OBJECT ( <i>L</i> ) | character                              |
| CHARACTER LARGE OBJECT LOCATOR      | character                              |
| CHARACTER VARYING ( <i>L</i> )      | character with maximum length <i>L</i> |
| DATE                                | <i>None</i>                            |
| DECIMAL( <i>P,S</i> )               | character                              |
| DOUBLE PRECISION                    | <i>None</i>                            |
| FLOAT( <i>P</i> )                   | <i>None</i>                            |
| INTEGER                             | character                              |
| INTERVAL( <i>Q</i> )                | <i>None</i>                            |
| NUMERIC( <i>P,S</i> )               | character                              |
| REAL                                | character                              |
| REF                                 | character                              |
| ROW                                 | <i>None</i>                            |
| SMALLINT                            | <i>None</i>                            |
| TIME( <i>T</i> )                    | <i>None</i>                            |
| TIMESTAMP( <i>T</i> )               | <i>None</i>                            |
| USER-DEFINED TYPE                   | <i>None</i>                            |
| USER-DEFINED TYPE LOCATOR           | character                              |

Table 49—Data type correspondences for Pascal

| SQL Data Type                           | Pascal Data Type                       |
|-----------------------------------------|----------------------------------------|
| ARRAY                                   | <i>None</i>                            |
| ARRAY LOCATOR                           | INTEGER                                |
| BIT ( $L$ ), $1 \leq L \leq B^1$        | CHAR                                   |
| BIT ( $L$ ), $B^1 < L$                  | PACKED ARRAY[LB <sup>1</sup> ] OF CHAR |
| BIT VARYING ( $L$ )                     | <i>None</i>                            |
| BINARY LARGE OBJECT ( $L$ ), $L > 1$    | PACKED ARRAY[1..L] OF CHAR             |
| BINARY LARGE OBJECT LOCATOR             | INTEGER                                |
| BOOLEAN                                 | BOOLEAN                                |
| CHARACTER (1)                           | CHAR                                   |
| CHARACTER ( $L$ ), $L > 1$              | PACKED ARRAY[1..L] OF CHAR             |
| CHARACTER LARGE OBJECT ( $L$ ), $L > 1$ | PACKED ARRAY[1..L] OF CHAR             |
| CHARACTER LARGE OBJECT LOCATOR          | INTEGER                                |
| CHARACTER VARYING ( $L$ )               | <i>None</i>                            |
| DATE                                    | <i>None</i>                            |
| DECIMAL( $P,S$ )                        | <i>None</i>                            |
| DOUBLE PRECISION                        | <i>None</i>                            |
| FLOAT( $P$ )                            | <i>None</i>                            |
| INTEGER                                 | INTEGER                                |
| INTERVAL( $Q$ )                         | <i>None</i>                            |
| NUMERIC( $P,S$ )                        | <i>None</i>                            |
| REAL                                    | REAL                                   |
| REF, $L > 1$                            | PACKED ARRAY[1..L] OF CHAR             |
| ROW                                     | <i>None</i>                            |
| SMALLINT                                | <i>None</i>                            |
| TIME( $T$ )                             | <i>None</i>                            |
| TIMESTAMP( $T$ )                        | <i>None</i>                            |
| USER-DEFINED TYPE                       | <i>None</i>                            |
| USER-DEFINED TYPE LOCATOR               | INTEGER                                |

<sup>1</sup>The length  $LB$  of the character data type corresponding with SQL data type BIT( $L$ ) is the smallest integer not less than the quotient of the division  $L/B$ , where  $B$  is the implementation-defined number of bits contained in a character of the host language.

Table 50—Data type correspondences for PL/I

| SQL Data Type                       | PL/I Data Type                                                         |
|-------------------------------------|------------------------------------------------------------------------|
| ARRAY                               | <i>None</i>                                                            |
| ARRAY LOCATOR                       | FIXED BINARY( <i>PI</i> ), where <i>PI</i> is implementation-defined   |
| BINARY LARGE OBJECT ( <i>L</i> )    | CHARACTER VARYING( <i>L</i> )                                          |
| BINARY LARGE OBJECT LOCATOR         | FIXED BINARY( <i>PI</i> ), where <i>PI</i> is implementation-defined   |
| BIT ( <i>L</i> )                    | BIT( <i>L</i> )                                                        |
| BIT VARYING ( <i>L</i> )            | BIT VARYING ( <i>L</i> )                                               |
| BOOLEAN                             | BIT(1)                                                                 |
| CHARACTER ( <i>L</i> )              | CHARACTER( <i>L</i> )                                                  |
| CHARACTER LARGE OBJECT ( <i>L</i> ) | CHARACTER VARYING( <i>L</i> )                                          |
| CHARACTER LARGE OBJECT LOCATOR      | FIXED BINARY( <i>PI</i> ), where <i>PI</i> is implementation-defined   |
| CHARACTER VARYING ( <i>L</i> )      | CHARACTER VARYING( <i>L</i> )                                          |
| DATE                                | <i>None</i>                                                            |
| DECIMAL( <i>P,S</i> )               | FIXED DECIMAL( <i>P,S</i> )                                            |
| DOUBLE PRECISION                    | <i>None</i>                                                            |
| FLOAT( <i>P</i> )                   | FLOAT BINARY ( <i>P</i> )                                              |
| INTEGER                             | FIXED BINARY( <i>PI</i> ), where <i>PI</i> is implementation-defined   |
| INTERVAL( <i>Q</i> )                | <i>None</i>                                                            |
| NUMERIC( <i>P,S</i> )               | <i>None</i>                                                            |
| REAL                                | <i>None</i>                                                            |
| REF                                 | CHARACTER VARYING ( <i>L</i> )                                         |
| ROW                                 | <i>None</i>                                                            |
| SMALLINT                            | FIXED BINARY( <i>SPI</i> ), where <i>SPI</i> is implementation-defined |
| TIME( <i>T</i> )                    | <i>None</i>                                                            |
| TIMESTAMP( <i>T</i> )               | <i>None</i>                                                            |
| USER-DEFINED TYPE LOCATOR           | <i>None</i>                                                            |
| USER-DEFINED TYPE                   | FIXED BINARY( <i>PI</i> ), where <i>PI</i> is implementation-defined   |

## 6 SQL/CLI routines

Subclause 5.1, “<CLI routine>”, defines a generic CLI routine. This Subclause describes the individual CLI routines in alphabetical order.

For convenience, the variable <CLI name prefix> is omitted and the <CLI generic name> is used for the descriptions. For presentation purposes (and purely arbitrarily), the routines are presented as functions rather than as procedures.

### 6.1 AllocConnect

#### Function

Allocate an SQL-connection and assign a handle to it.

#### Definition

```
AllocConnect (
    EnvironmentHandle    IN        INTEGER,
    ConnectionHandle    OUT       INTEGER )
    RETURNS SMALLINT
```

#### General Rules

- 1) Let *EH* be the value of EnvironmentHandle.
- 2) AllocHandle is implicitly invoked with HandleType indicating CONNECTION HANDLE, with *EH* as the value of InputHandle and with ConnectionHandle as OutputHandle.

**6.2 AllocEnv****6.2 AllocEnv****Function**

Allocate an SQL-environment and assign a handle to it.

**Definition**

```
AllocEnv (
    EnvironmentHandle    OUT    INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) AllocHandle is implicitly invoked with HandleType indicating ENVIRONMENT HANDLE, with zero as the value of InputHandle, and with EnvironmentHandle as OutputHandle.

## 6.3 AllocHandle

### Function

Allocate a resource and assign a handle to it.

### Definition

```
AllocHandle (
    HandleType      IN      SMALLINT ,
    InputHandle     IN      INTEGER ,
    OutputHandle    OUT     INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let *HT* be the value of HandleType and let *IH* be the value of InputHandle.
- 2) If *HT* is not one of the code values in Table 13, “Codes used for handle types”, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If *HT* indicates ENVIRONMENT HANDLE, then:
    - i) If the maximum number of SQL-environments that can be allocated at one time has already been reached, then an exception condition is raised: *CLI-specific condition — limit on number of handles exceeded*. A skeleton SQL-environment is allocated and is assigned a unique value that is returned in OutputHandle.
    - ii) Case:
      - 1) If the memory requirements to manage an SQL-environment cannot be satisfied, then OutputHandle is set to zero and an exception condition is raised: *CLI-specific condition — memory allocation error*.  
NOTE 13 – No diagnostic information is generated in this case as there is no valid environment handle that can be used in order to obtain diagnostic information.
      - 2) If the resources to manage an SQL-environment cannot be allocated for implementation-defined reasons, then an implementation-defined exception condition is raised. A skeleton SQL-environment is allocated and is assigned a unique value that is returned in OutputHandle.
      - 3) Otherwise, the resources to manage an SQL-environment are allocated and are referred to as an allocated SQL-environment. The allocated SQL-environment is assigned a unique value that is returned in OutputHandle.
  - b) If *HT* indicates CONNECTION HANDLE, then:
    - i) If *IH* does not identify an allocated SQL-environment or if it identifies an allocated skeleton SQL-environment, then OutputHandle is set to zero and an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Let *E* be the allocated SQL-environment identified by *IH*.

**6.3 AllocHandle**

- iii) The diagnostics area associated with *E* is emptied.
- iv) If the maximum number of SQL-connections that can be allocated at one time has already been reached, then *OutputHandle* is set to zero and an exception condition is raised: *CLI-specific condition — limit on number of handles exceeded*.
- v) Case:
  - 1) If the memory requirements to manage an SQL-connection cannot be satisfied, then *OutputHandle* is set to zero and an exception condition is raised: *CLI-specific condition — memory allocation error*.
  - 2) If the resources to manage an SQL-connection cannot be allocated for implementation-defined reasons, then *OutputHandle* is set to zero and an implementation-defined exception condition is raised.
  - 3) Otherwise, the resources to manage an SQL-connection are allocated and are referred to as an allocated SQL-connection. The allocated SQL-connection is associated with *E* and is assigned a unique value that is returned in *OutputHandle*.
- c) If *HT* indicates STATEMENT HANDLE, then:
  - i) If *IH* does not identify an allocated SQL-connection, then *OutputHandle* is set to zero and an exception condition is raised: *CLI-specific condition — invalid handle*.
  - ii) Let *C* be the allocated SQL-connection identified by *IH*.
  - iii) The diagnostics area associated with *C* is emptied.
  - iv) If there is no established SQL-connection associated with *C*, then *OutputHandle* is set to zero and an exception condition is raised: *connection exception — connection does not exist*. Otherwise, let *EC* be the established SQL-connection associated with *C*.
  - v) If the maximum number of SQL-statements that can be allocated at one time has already been reached, then *OutputHandle* is set to zero and an exception condition is raised: *CLI-specific condition — limit on number of handles exceeded*.
  - vi) If *EC* is not the current SQL-connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant SQL-connection.
  - vii) If the memory requirements to manage an SQL-statement cannot be satisfied, then *OutputHandle* is set to zero and an exception condition is raised: *CLI-specific condition — memory allocation error*.
  - viii) If the resources to manage an SQL-statement cannot be allocated for implementation-defined reasons, then *OutputHandle* is set to zero and an implementation-defined exception condition is raised.
  - ix) The resources to manage an SQL-statement are allocated and are referred to as an *allocated SQL-statement*. The allocated SQL-statement is associated with *C* and is assigned a unique value that is returned in *OutputHandle*.
  - x) The following CLI descriptor areas are automatically allocated and associated with the allocated SQL-statement:
    - 1) An implementation parameter descriptor.

- 2) An implementation row descriptor.
- 3) An application parameter descriptor.
- 4) An application row descriptor.

For each of these descriptor areas, the ALLOC\_TYPE field is set to indicate AUTOMATIC. For each of these descriptor areas, fields with non-blank entries in Table 23, "SQL/CLI descriptor field default values", are set to the specified default values. All other fields in the CLI item descriptor areas are initially undefined.

- xi) The automatically allocated application parameter descriptor becomes the current application parameter descriptor for the allocated SQL-statement and the automatically allocated application row descriptor becomes the current application row descriptor for the allocated SQL-statement.
- d) If *HT* indicates DESCRIPTOR HANDLE, then:
- i) If *IH* does not identify an allocated SQL-connection then OutputHandle is set to zero and an exception condition is raised: *CLI-specific condition — invalid handle*.
  - ii) Let *C* be the allocated SQL-connection identified by *IH*.
  - iii) The diagnostics area associated with *C* is emptied.
  - iv) If there is no established SQL-connection associated with *C*, then OutputHandle is set to zero and an exception condition is raised: *connection exception — connection does not exist*. Otherwise, let *EC* be the established SQL-connection associated with *C*.
  - v) If the maximum number of CLI descriptor areas that can be allocated at one time has already been reached, then OutputHandle is set to zero and an exception condition is raised: *CLI-specific condition — limit on number of handles exceeded*.
  - vi) If *EC* is not the current SQL-connection, then the General Rules of Subclause 5.3, "Implicit set connection", are applied to *EC* as the dormant SQL-connection.
  - vii) Case:
    - 1) If the memory requirements to manage a CLI descriptor area cannot be satisfied, then OutputHandle is set to zero and an exception condition is raised: *CLI-specific condition — memory allocation error*.
    - 2) If the resources to manage a CLI descriptor area cannot be allocated for implementation-defined reasons, then OutputHandle is set to zero and an implementation-defined exception condition is raised.
    - 3) Otherwise, the resources to manage a CLI descriptor area are allocated and are referred to as an allocated CLI descriptor area. The allocated CLI descriptor area is associated with *C* and is assigned a unique value that is returned in OutputHandle. The ALLOC\_TYPE field of the allocated CLI descriptor area is set to indicate USER. Other fields of the allocated CLI descriptor area are set to the default values for an ARD specified in Table 23, "SQL/CLI descriptor field default values". Fields in the CLI item descriptor areas not set to a default value are initially undefined.

**6.4 AllocStmt****6.4 AllocStmt****Function**

Allocate an SQL-statement and assign a handle to it.

**Definition**

```
AllocStmt (
    ConnectionHandle    IN    INTEGER,
    StatementHandle     OUT   INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) Let *CH* be the value of ConnectionHandle.
- 2) AllocHandle is implicitly invoked with HandleType indicating STATEMENT HANDLE, with *CH* as the value of InputHandle, and with StatementHandle as OutputHandle.

## 6.5 BindCol

### Function

Describe a target specification or array of target specifications.

### Definition

```
BindCol (
    StatementHandle      IN      INTEGER,
    ColumnNumber         IN      SMALLINT,
    TargetType           IN      SMALLINT,
    TargetValue          DEFOUT  ANY,
    BufferLength          IN      INTEGER,
    StrLen_or_Ind        DEFOUT  INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) Let *HV* be the value of the handle of the current application row descriptor for *S*.
- 3) Let *ARD* be the allocated CLI descriptor area identified by *HV* and let *N* be the value of the *TOP\_LEVEL\_COUNT* field of *ARD*.
- 4) Let *CN* be the value of *ColumnNumber*.
- 5) If *CN* is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 6) If *CN* is greater than *N*, then
 

Case:

  - a) If the memory requirements to manage the larger *ARD* cannot be satisfied, then an exception condition is raised: *CLI-specific condition — memory allocation error*.
  - b) Otherwise, the *TOP\_LEVEL\_COUNT* field of *ARD* is set to *CN* and the *COUNT* field of *ARD* is incremented by 1 (one).
- 7) Let *TT* be the value of *TargetType*.
- 8) Let *HL* be the standard programming language of the invoking host program. Let *operative data type correspondence table* be the data type correspondence table for *HL* as specified in Subclause 5.15, "Data type correspondences". Refer to the two columns of this table as the *SQL data type column* and the *host data type column*.
- 9) If either of the following is true, then an exception condition is raised: *CLI-specific condition — invalid data type in application descriptor*.
  - a) *TT* does not indicate *DEFAULT* and is not one of the code values in Table 8, "Codes used for application data types in SQL/CLI".

**6.5 BindCol**

- b) *TT* is one of the code values in Table 8, “Codes used for application data types in SQL/CLI”, but the row that contains the corresponding SQL data type in the SQL data type column of the operative data type correspondence table contains ‘None’ in the host data type column.
- 10) Let *BL* be the value of BufferLength.
  - 11) If *BL* is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - 12) Let *IDA* be the item descriptor area of *ARD* specified by *CN*.
  - 13) If an exception condition is raised in any of the following General Rules, then the TYPE, OCTET\_LENGTH, LENGTH, DATA\_POINTER, INDICATOR\_POINTER, and OCTET\_LENGTH\_POINTER fields of *IDA* are set to implementation-dependent values and the value of COUNT for *ARD* is unchanged.
  - 14) The data type of the <target specification> described by *IDA* is set to *TT*.
  - 15) The length in octets of the <target specification> described by *IDA* is set to *BL*.
  - 16) The length in characters or positions of the <target specification> described by *IDA* is set to the maximum number of characters or positions that may be represented by the data type *TT*.
  - 17) The address of the host variable or array of host variables that is to receive a value or values for the <target specification> or <target specification>s described by *IDA* is set to the address of TargetValue. If TargetValue is a null pointer, then the address is set to 0 (zero).
  - 18) The address of the <indicator variable> or array of <indicator variable>s associated with the host variable or host variables addressed by the DATA\_POINTER field of *IDA* is set to the address of StrLen\_or\_Ind.
  - 19) The address of the host variable or array of host variables that is to receive the returned length (in characters) of the <target specification> or <target specification>s described by *IDA* is set to the address of StrLen\_or\_Ind.
  - 20) Restrictions on the differences allowed between *ARD* and *IRD* are implementation-defined, except as specified in the General Rules of Subclause 5.8, “Implicit FETCH USING clause”, and the General Rules of Subclause 6.30, “GetData”.

## 6.6 BindParameter

### Function

Describe a dynamic parameter specification and its value.

### Definition

```
BindParameter (
    StatementHandle      IN      INTEGER ,
    ParameterNumber     IN      SMALLINT ,
    InputOutputMode     IN      SMALLINT ,
    ValueType           IN      SMALLINT ,
    ParameterType       IN      SMALLINT ,
    ColumnSize          IN      INTEGER ,
    DecimalDigits       IN      SMALLINT ,
    ParameterValue     DEF     ANY ,
    BufferLength         IN      INTEGER ,
    StrLen_or_Ind       DEF     INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) Let *HV* be the value of the handle of the current application parameter descriptor for *S*.
- 3) Let *APD* be the allocated CLI descriptor area identified by *HV* and let *N2* be the value of the TOP\_LEVEL\_COUNT field of *APD*.
- 4) Let *PN* be the value of ParameterNumber.
- 5) If *PN* is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 6) Let *IOM* be the value of InputOutputMode.
- 7) If *IOM* is not one of the code values in Table 11, “Codes associated with <parameter mode> in SQL/CLI”, then an exception condition is raised: *CLI-specific condition — invalid parameter mode*.
- 8) Let *VT* be the value of ValueType.
- 9) Let *HL* be the standard programming language of the invoking host program. Let *operative data type correspondence table* be the data type correspondence table for *HL* as specified in Subclause 5.15, “Data type correspondences”. Refer to the two columns of the operative data type correspondence table as the *SQL data type column* and the *host data type column*.
- 10) If any of the following are true, then an exception condition is raised: *CLI-specific condition — invalid data type in application descriptor*.
  - a) *VT* does not indicate DEFAULT and is not one of the code values in Table 8, “Codes used for application data types in SQL/CLI”.

**6.6 BindParameter**

- b) *VT* is one of the code values in Table 8, “Codes used for application data types in SQL/CLI”, but the row that contains the corresponding SQL data type in the SQL data type column of the operative data type correspondence table contains ‘None’ in the host data type column.
- 11) Let *PT* be the value of ParameterType.
- 12) If *PT* is not one of the code values in Table 37, “Codes used for concise data types”, then an exception condition is raised: *CLI-specific condition — invalid data type*.
- 13) Let *IPD* be the implementation parameter descriptor associated with *S* and let *N1* be the value of the TOP\_LEVEL\_COUNT field of *IPD*.
- 14) If *PN* is greater than *N1*, then  
Case:
- a) If the memory requirements to manage the larger *IPD* cannot be satisfied, then an exception condition is raised: *CLI-specific condition — memory allocation error*.
- b) Otherwise, the TOP\_LEVEL\_COUNT field of *IPD* is set to *PN* and the COUNT field of *APD* is incremented by 1 (one).
- 15) If *PN* is greater than *N2*, then  
Case:
- a) If the memory requirements to manage the larger *APD* cannot be satisfied, then an exception condition is raised: *CLI-specific condition — memory allocation error*.
- b) Otherwise, the TOP\_LEVEL\_COUNT field of *APD* is set to *PN* and the COUNT field of *APD* is incremented by 1 (one).
- 16) Let *IDA1* be the item descriptor area of *IPD* specified by *PN*.
- 17) Let *CS* be the value of ColumnSize, let *DD* be the value of DecimalDigits, and let *BL* be the value of BufferLength.
- 18) Case:
- a) If *PT* is one of the values listed in Table 38, “Codes used with concise datetime data types in SQL/CLI”, then:
- i) The data type of the <dynamic parameter specification> described by *IDA1* is set to a code shown in the Data Type Code column of Table 38, “Codes used with concise datetime data types in SQL/CLI”, indicating the concise data type code.
- ii) The datetime interval code of the <dynamic parameter specification> described by *IDA1* is set to a code shown in the Datetime Interval Code column in Table 38, “Codes used with concise datetime data types in SQL/CLI”, indicating the concise data type code.
- iii) The length (in positions) of the <dynamic parameter specification> described by *IDA1* is set to *CS*.
- iv) Case:
- 1) If the datetime interval code of the <dynamic parameter specification> indicates DATE, then the time fractional seconds precision of the <dynamic parameter specification> described by *IDA1* is set to zero.

- 2) Otherwise, the time fractional seconds precision of the <dynamic parameter specification> described by *IDA1* is set to *DD*.
- b) If *PT* is one of the values listed in Table 39, “Codes used with concise interval data types in SQL/CLI”, then:
- i) The data type of the <dynamic parameter specification> described by *IDA1* is set to a code shown in the Data Type Code column of Table 39, “Codes used with concise interval data types in SQL/CLI”, indicating the concise data type code.
  - ii) The datetime interval code of the <dynamic parameter specification> described by *IDA1* is set to a code shown in the Datetime Interval Code column in Table 39, “Codes used with concise interval data types in SQL/CLI”, indicating the concise data type code. Let *DIC* be that code.
  - iii) The length (in positions) of the <dynamic parameter specification> described by *IDA1* is set to *CS*.
  - iv) Let *LS* be 0 (zero).
  - v) If *IOM* is PARAM MODE IN or PARAM MODE INOUT, ParameterValue is not a null pointer, and *BL* is greater than zero, then:
    - 1) Let *PV* be the value of ParameterValue.
    - 2) Let *FC* be the value of  

$$\text{SUBSTR} ( PV \text{ FROM } 1 \text{ FOR } 1 )$$
    - 3) If *FC* is <plus sign> or <minus sign>, then let *LS* be 1 (one).
  - vi) Case:
    - 1) If *DIC* indicates SECOND, DAY TO SECOND, HOUR TO SECOND, or MINUTE TO SECOND, then the interval fractional seconds precision of the <dynamic parameter specification> described by *IDA1* is set to *DD*. If *DD* is zero, then let *DP* be zero; otherwise, let *DP* be one.
    - 2) Otherwise, the interval fractional seconds precision of the <dynamic parameter specification> described by *IDA1* is set to zero.
  - vii) Case:
    - 1) If *DIC* indicates YEAR TO MONTH, DAY TO HOUR, HOUR TO MINUTE or MINUTE TO SECOND, then let *IL* be 3.
    - 2) If *DIC* indicates DAY TO MINUTE or HOUR TO SECOND, then let *IL* be 6.
    - 3) If *DIC* indicates DAY TO SECOND, then let *IL* be 9.
    - 4) Otherwise, let *IL* be zero.
  - viii) Case:
    - 1) If *DIC* indicates SECOND, DAY TO SECOND, HOUR TO SECOND, or MINUTE TO SECOND, then the interval leading field precision of the <dynamic parameter specification> described by *IDA1* is set to *CS-IL-DD-DP-LS*.

**6.6 BindParameter**

- 2) Otherwise, the interval leading field precision of the <dynamic parameter specification> described by *IDA1* is set to *CS-IL-LS*.
- c) Otherwise:
- i) The data type of the <dynamic parameter specification> described by *IDA1* is set to *PT*.
  - ii) If *PT* indicates a character string type, then the length (in characters) of the <dynamic parameter specification> described by *IDA1* is set to *CS*.
  - iii) If *PT* indicates a bit type, then the length (in bits) of the <dynamic parameter specification> described by *IDA1* is set to *CS*.
  - iv) If *PT* indicates a numeric type, then the precision of the <dynamic parameter specification> described by *IDA1* is set to *CS*.
  - v) If *PT* indicates a numeric type, then the scale of the <dynamic parameter specification> described by *IDA1* is set to *DD*.
- 19) Let *IDA2* be the item descriptor area of *APD* specified by *PN*.
- 20) If an exception condition is raised in any of the following General Rules, then:
- a) The TYPE, LENGTH, PRECISION, and SCALE fields of *IDA1* are set to implementation-dependent values and the values of the TOP\_LEVEL\_COUNT and COUNT fields of *IPD* are unchanged.
  - b) The TYPE, DATA\_POINTER, INDICATOR\_POINTER, and OCTET\_LENGTH\_POINTER fields of *IDA2* are set to implementation-dependent values and the values of the TOP\_LEVEL\_COUNT and COUNT fields of *APD* are unchanged.
- 21) The parameter mode of the <dynamic parameter specification> described by *IDA2* is set to *IOM*.
- 22) The data type of the <dynamic parameter specification> described by *IDA2* is set to *VT*.
- 23) The address of the host variable that is to provide a value for the <dynamic parameter specification> value described by *IDA2* is set to the address of ParameterValue. If ParameterValue is a null pointer, then the address is set to 0 (zero).
- 24) The address of the <indicator variable> associated with the host variable addressed by the DATA\_POINTER field of *IDA2* is set to the address of StrLen\_or\_Ind.
- 25) The address of the host variable that is to define the length (in octets) of the <dynamic parameter specification> value described by *IDA2* is set to the address of StrLen\_or\_Ind.
- 26) If *IOM* is PARAM MODE OUT or PARAM MODE INOUT and *BL* is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 27) The length in octets of the <dynamic parameter specification> value described by *IDA2* is set to *BL*.
- 28) If *IOM* is PARAM MODE IN or PARAM MODE INOUT, ParameterValue is not a null pointer, and *BL* is greater than 0 (zero), then let *PV* be the value of the <dynamic parameter specification> value described by *IDA2*.

- 29) Restrictions on the differences allowed between *APD* and *IPD* are implementation-defined, except as specified in the General Rules of Subclause 5.6, “Implicit EXECUTE USING and OPEN USING clauses”, Subclause 5.7, “Implicit CALL USING clause”, and the General Rules of Subclause 6.49, “ParamData”.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

**6.7 Cancel****6.7 Cancel****Function**

Attempt to cancel execution of a CLI routine.

**Definition**

```
Cancel (
    StatementHandle IN    INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) Case:
  - a) If there is a CLI routine concurrently operating on *S*, then:
    - i) Let *RN* be the routine name of the concurrent CLI routine.
    - ii) Let *C* be the allocated SQL-connection with which *S* is associated.
    - iii) Let *EC* be the established SQL-connection associated with *C* and let *SS* be the SQL-server associated with *EC*.
    - iv) *SS* is requested to cancel the execution of *RN*.
    - v) If *SS* rejects the cancellation request, then an exception condition is raised: *CLI-specific condition — server declined the cancellation request*.
    - vi) If *SS* accepts the cancellation request, then a completion condition is raised: *successful completion*.  
NOTE 14 – Acceptance of the request does not guarantee that the execution of *RN* will be canceled.
    - vii) If *SS* succeeds in canceling the execution of *RN*, then an exception condition is raised for *RN*: *CLI-specific condition — operation canceled*.  
NOTE 15 – Canceling the execution of *RN* does not destroy any diagnostic information already generated by its execution.  
NOTE 16 – The method of passing control between concurrently operating programs is implementation-dependent.
  - b) If there is a deferred parameter number associated with *S*, then:
    - i) The diagnostics area associated with *S* is emptied.
    - ii) The deferred parameter number is removed from association with *S*.
    - iii) Any statement source associated with *S* is removed from association with *S*.
  - c) Otherwise:
    - i) The diagnostics area associated with *S* is emptied.

- ii) A completion condition is raised: *successful completion*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.8 CloseCursor

### Function

Close a cursor.

### Definition

```
CloseCursor (
    StatementHandle    IN    INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no executed statement associated with *S*, then an exception condition is raised:  
*CLI-specific condition — function sequence error.*
- 3) Case:
  - a) If there is no open cursor associated with *S*, then an exception condition is raised: *invalid cursor state.*
  - b) Otherwise:
    - i) The open cursor associated with *S* is placed in the closed state and its copy of the select source is destroyed.
    - ii) Any fetched row associated with *S* is removed from association with *S*.

## 6.9 ColAttribute

### Function

Get a column attribute.

### Definition

```
ColAttribute (
    StatementHandle      IN    INTEGER,
    ColumnNumber        IN    SMALLINT,
    FieldIdentifier      IN    SMALLINT,
    CharacterAttribute   OUT   CHARACTER(L),
    BufferLength         IN    SMALLINT,
    StringLength        OUT   SMALLINT,
    NumericAttribute    OUT   INTEGER )
RETURNS SMALLINT
```

where *L* is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no prepared or executed statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) Let *IRD* be the implementation row descriptor associated with *S* and let *N* be the value of the TOP\_LEVEL\_COUNT field of *IRD*.
- 4) Let *FI* be the value of FieldIdentifier.
- 5) If *FI* is not one of the code values in Table 20, “Codes used for descriptor fields”, then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.
- 6) Let *CN* be the value of ColumnNumber.
- 7) Let *TYPE* be the value of the Type column in the row of Table 20, “Codes used for descriptor fields”, that contains *FI*.
- 8) Let *FDT* be the value of the Data Type column in the row of Table 6, “Fields in SQL/CLI row and parameter descriptor areas”, whose Field column contains the value of the Field column in the row of Table 20, “Codes used for descriptor fields”, that contains *FI*.
- 9) If *TYPE* is 'ITEM', then:
  - a) If *N* is zero, then an exception condition is raised: *dynamic SQL error — prepared statement not a cursor specification*.
  - b) If *CN* is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
  - c) If *CN* is greater than *N*, then a completion condition is raised: *no data*.

**6.9 ColAttribute**

- d) Let *IDA* be the item descriptor area of *IRD* specified by the *CN*-th descriptor area in *IRD* for which LEVEL is 0 (zero).
  - e) Let *DT* and *DIC* be the values of the TYPE and DATETIME\_INTERVAL\_CODE fields, respectively, for *IDA*.
- 10) If TYPE is 'HEADER', then:
- a) If *CN* is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
  - b) If *CN* is greater than *N*, then a completion condition is raised: *no data*.
  - c) Let *CN* be 0 (zero).
- 11) Let *DH* be the handle that identifies *IRD*.
- 12) Let *RI* be the number of the descriptor record in *IRD* that is the *CN*-th descriptor area for which LEVEL is 0 (zero).

Case:

- a) If *FDT* indicates character string, then let the information be retrieved from *IRD* by implicitly executing GetDescField as follows:

```
GetDescField ( DH, RI, FI,
              CharacterAttribute, BufferLength, StringLength )
```

- b) Otherwise,

Case:

- i) If *FI* indicates TYPE, then:

- 1) If *DT* indicates a <datetime type>, then NumericAttribute is set to the concise code value corresponding to the datetime interval code value *DIC* as defined in Table 40, "Concise codes used with datetime data types in SQL/CLI".
- 2) If *DT* indicates INTERVAL, then NumericAttribute is set to the concise code value corresponding to the datetime interval code value *DIC* as defined in Table 41, "Concise codes used with interval data types in SQL/CLI".
- 3) Otherwise, NumericAttribute is set to *DT*.

- ii) Otherwise, let the information be retrieved from *IRD* by implicitly executing GetDescField as follows:

```
GetDescField ( DH, RI, FI,
              NumericAttribute, BufferLength, StringLength )
```

## 6.10 ColumnPrivileges

### Function

Return a result set that contains a list of the privileges held on the columns whose names adhere to the requested pattern or patterns within a single specified table stored in the information schemas of the connected data source.

### Definition

```
ColumnPrivileges (
    StatementHandle      IN      INTEGER,
    CatalogName         IN      CHARACTER(L1),
    NameLength1         IN      SMALLINT,
    SchemaName          IN      CHARACTER(L2),
    NameLength2         IN      SMALLINT,
    TableName           IN      CHARACTER(L3),
    NameLength3         IN      SMALLINT,
    ColumnName          IN      CHARACTER(L4),
    NameLength4         IN      SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  are determined by the values of NameLength1, NameLength2, NameLength3, and NameLength4, respectively and each of  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $COLUMN\_PRIVILEGES\_QUERY$  be a table, with the definition:

```
CREATE TABLE COLUMN_PRIVILEGES_QUERY (
    TABLE_CAT          CHARACTER VARYING(128),
    TABLE_SCHEM       CHARACTER VARYING(128) NOT NULL,
    TABLE_NAME        CHARACTER VARYING(128) NOT NULL,
    COLUMN_NAME        CHARACTER VARYING(128) NOT NULL,
    GRANTOR            CHARACTER VARYING(128),
    GRANTEE            CHARACTER VARYING(128) NOT NULL,
    PRIVILEGE          CHARACTER VARYING(128) NOT NULL,
    IS_GRANTABLE       CHARACTER VARYING(3) )
```

**6.10 ColumnPrivileges**

- 6) *COLUMN\_PRIVILEGES\_QUERY* contains a row for each privilege in *SS*'s Information Schema *COLUMN\_PRIVILEGES* view where:
- a) Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
  - b) Case:
    - i) If the value of *SUP* is 1 (one), then *COLUMN\_PRIVILEGES\_QUERY* contains a row for each privilege in *SS*'s Information Schema *COLUMN\_PRIVILEGES* view.
    - ii) Otherwise, *COLUMN\_PRIVILEGES\_QUERY* contains a row for each privilege in *SS*'s Information Schema *COLUMN\_PRIVILEGES* view that meets implementation-defined authorization criteria.
- 7) For each row of *COLUMN\_PRIVILEGES\_QUERY*:
- a) If the implementation does not support catalog names, then *TABLE\_CAT* is the null value; otherwise, the value of *TABLE\_CAT* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *TABLE\_CATALOG* column in the *COLUMN\_PRIVILEGES* view in the information schema.
  - b) The value of *TABLE\_SCHEM* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *TABLE\_SCHEMA* column in the *COLUMN\_PRIVILEGES* view.
  - c) The value of *TABLE\_NAME* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *TABLE\_NAME* column in the *COLUMN\_PRIVILEGES* view.
  - d) The value of *COLUMN\_NAME* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *COLUMN\_NAME* column in the *COLUMN\_PRIVILEGES* view.
  - e) The value of *GRANTOR* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *GRANTOR* column in the *COLUMN\_PRIVILEGES* view.
  - f) The value of *GRANTEE* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *GRANTEE* column in the *COLUMN\_PRIVILEGES* view.
  - g) The value of *PRIVILEGE* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *PRIVILEGE\_TYPE* column in the *COLUMN\_PRIVILEGES* view.
  - h) The value of *IS\_GRANTABLE* in *COLUMN\_PRIVILEGES\_QUERY* is the value of the *IS\_GRANTABLE* column in the *COLUMN\_PRIVILEGES* view.
- 8) Let *NL1*, *NL2*, *NL3*, and *NL4* be the values of NameLength1, NameLength2, NameLength3, and NameLength4, respectively.
- 9) Let *CATVAL*, *SCHVAL*, *TBLVAL*, and *COLVAL* be the values of CatalogName, SchemaName, TableName, and ColumnName, respectively.
- 10) If the METADATA ID attribute of *S* is TRUE, then:
- a) If CatalogName is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", is 'Y', then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.

- b) If SchemaName is a null pointer or if ColumnName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer.*
- 11) If TableName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer.*
- 12) If CatalogName is a null pointer, then *NL1* is set to zero. If SchemaName is a null pointer, then *NL2* is set to zero. If TableName is a null pointer, then *NL3* is set to zero. If ColumnName is a null pointer, then *NL4* is set to zero.
- 13) Case:
- a) If *NL1* is not negative, then let *L* be *NL1*.
- b) If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of CatalogName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*
- Let *CATVAL* be the first *L* octets of CatalogName.
- 14) Case:
- a) If *NL2* is not negative, then let *L* be *NL2*.
- b) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of SchemaName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*
- Let *SCHVAL* be the first *L* octets of SchemaName.
- 15) Case:
- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of TableName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*
- Let *TBLVAL* be the first *L* octets of TableName.
- 16) Case:
- a) If *NL4* is not negative, then let *L* be *NL4*.
- b) If *NL4* indicates NULL TERMINATED, then let *L* be the number of octets of ColumnName that precede the implementation-defined null character that terminates a C character string.

- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

Let *COLVAL* be the first *L* octets of *ColumnName*.

17) Case:

a) If the METADATA ID attribute of *S* is TRUE, then:

i) Case:

1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING(TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(CATVAL) FROM CHAR_LENGTH(TRIM(CATVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(CATVAL) FROM 2
FOR CHAR_LENGTH(TRIM(CATVAL)) - 2)
```

and let *CATSTR* be the character string:

```
TABLE_CAT = 'TEMPSTR' AND
```

B) Otherwise, let *CATSTR* be the character string:

```
UPPER(TABLE_CAT) = UPPER('CATVAL') AND
```

ii) Case:

1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(SCHVAL) FROM CHAR_LENGTH(TRIM(SCHVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
a) SUBSTRING(TRIM(SCHVAL) FROM 2
FOR CHAR_LENGTH(TRIM(SCHVAL)) - 2)
```

and let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'TEMPSTR' AND
```

B) Otherwise, let *SCHSTR* be the character string:

```
UPPER(TABLE_SCHEM) = UPPER('SCHVAL') AND
```

iii) Case:

1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

2) Otherwise,

Case:

- A) If `SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(TBLVAL) FROM CHAR_LENGTH(TRIM(TBLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(TBLVAL) FROM 2
FOR CHAR_LENGTH(TRIM(TBLVAL)) - 2)
```

and let *TBLSTR* be the character string:

```
TABLE_NAME = 'TEMPSTR' AND
```

- B) Otherwise, let *TBLSTR* be the character string:

```
UPPER(TABLE_NAME) = UPPER('TBLVAL') AND
```

iv) Case:

- 1) If the value of *NL4* is zero, then let *COLSTR* be a zero-length string.

- 2) Otherwise,

Case:

- A) If `SUBSTRING(TRIM(COLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(COLVAL) FROM CHAR_LENGTH(TRIM(COLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(COLVAL) FROM 2
FOR CHAR_LENGTH(TRIM(COLVAL)) - 2)
```

and let *COLSTR* be the character string:

```
COLUMN_NAME = 'TEMPSTR'
```

- B) Otherwise, let *COLSTR* be the character string:

```
UPPER(COLUMN_NAME) = UPPER('COLVAL')
```

b) Otherwise,

- i) Let *SPC* be the Code value from Table 28, "Codes and data types for implementation information", that corresponds to the Information Type SEARCH PATTERN ESCAPE in that same table.

- ii) Let *ESC* be the value of InfoValue that is returned by the execution of GetInfo() with the value of InfoType set to *SPC*.

- iii) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
TABLE_CAT = 'CATVAL' AND
```

- iv) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'SCHVAL' AND
```

**6.10 ColumnPrivileges**

- v) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string; otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME = 'TBLVAL' AND
```

- vi) If the value of *NL4* is zero, then let *COLSTR* be a zero-length string. Otherwise, let *COLSTR* be the character string:

```
COLUMN_NAME LIKE 'COLVAL' ESCAPE 'ESC' AND
```

- 18) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || COLSTR || ' ' || 1=1
```

- 19) Let *STMT* be the character string:

```
SELECT *
FROM COLUMN_PRIVILEGES_QUERY
WHERE PRED
ORDER BY TABLE_CAT, TABLE_SCHEM, TABLE_NAME, COLUMN_NAME, PRIVILEGE
```

- 20) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

## 6.11 Columns

### Function

Based on the specified selection criteria, return a result set that contains information about columns of tables stored in the information schemas of the connected data source.

### Definition

```
Columns (
    StatementHandle      IN      INTEGER,
    CatalogName         IN      CHARACTER(L1),
    NameLength1         IN      SMALLINT,
    SchemaName          IN      CHARACTER(L2),
    NameLength2         IN      SMALLINT,
    TableName           IN      CHARACTER(L3),
    NameLength3         IN      SMALLINT,
    ColumnName          IN      CHARACTER(L4),
    NameLength4         IN      SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  are determined by the values of NameLength1, NameLength2, NameLength3, and NameLength4, respectively, and each of  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $COLUMNS\_QUERY$  be a table, with the definition:

```
CREATE TABLE COLUMNS_QUERY (
    TABLE_CAT          CHARACTER VARYING(128),
    TABLE_SCHEM       CHARACTER VARYING(128) NOT NULL,
    TABLE_NAME         CHARACTER VARYING(128) NOT NULL,
    COLUMN_NAME         CHARACTER VARYING(128) NOT NULL,
    DATA_TYPE          SMALLINT NOT NULL,
    TYPE_NAME           CHARACTER VARYING(128) NOT NULL,
    COLUMN_SIZE         INTEGER,
    BUFFER_LENGTH       INTEGER,
    DECIMAL_DIGITS      SMALLINT,
    NUM_PREC_RADIX      SMALLINT,
    NULLABLE            SMALLINT NOT NULL,
    REMARKS             CHARACTER VARYING(254),
    COLUMN_DEF          CHARACTER VARYING(254),
    SQL_DATA_TYPE       SMALLINT NOT NULL,
    SQL_DATETIME_SUB    INTEGER,
    CHAR_OCTET_LENGTH  INTEGER,
    ORDINAL_POSITION    INTEGER NOT NULL,
    IS_NULLABLE         CHARACTER VARYING(254),
```

## 6.11 Columns

|                 |                         |
|-----------------|-------------------------|
| CHAR_SET_CAT    | CHARACTER VARYING(128), |
| CHAR_SET_SCHEM  | CHARACTER VARYING(128), |
| CHAR_SET_NAME   | CHARACTER VARYING(128), |
| COLLATION_CAT   | CHARACTER VARYING(128), |
| COLLATION_SCHEM | CHARACTER VARYING(128), |
| COLLATION_NAME  | CHARACTER VARYING(128), |
| UDT_CAT         | CHARACTER VARYING(128), |
| UDT_SCHEM       | CHARACTER VARYING(128), |
| UDT_NAME        | CHARACTER VARYING(128), |
| DOMAIN_CAT      | CHARACTER VARYING(128), |
| DOMAIN_SCHEM    | CHARACTER VARYING(128), |
| DOMAIN_NAME     | CHARACTER VARYING(128), |
| SCOPE_CAT       | CHARACTER VARYING(128), |
| SCOPE_SCHEM     | CHARACTER VARYING(128), |
| SCOPE_NAME      | CHARACTER VARYING(128), |
| MAX_CARDINALITY | INTEGER,                |
| DTD_IDENTIFIER  | CHARACTER VARYING(128), |
| IS_SELF_REF     | CHARACTER VARYING(128), |

UNIQUE (TABLE\_CAT, TABLE\_SCHEM, TABLE\_NAME, COLUMN\_NAME) )

- 6) *COLUMNS\_QUERY* contains a row for each column described by *SS*'s Information Schema *COLUMNS* view where:
- Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
  - Case:
    - If the value of *SUP* is 1 (one), then *COLUMNS\_QUERY* contains a row for each row describing a column in *SS*'s Information Schema *COLUMNS* view.
    - Otherwise, *COLUMNS\_QUERY* contains a row for each row describing a column in *SS*'s Information Schema *COLUMNS* view that meets implementation-defined authorization criteria.
- 7) For each row of *COLUMNS\_QUERY*:
- The value of *TABLE\_CAT* in *COLUMNS\_QUERY* is the value of the *TABLE\_CATALOG* column in the *COLUMNS* view. If *SS* does not support catalog names, then *TABLE\_CAT* is set to the null value.
  - The value of *TABLE\_SCHEM* in *COLUMNS\_QUERY* is the value of the *TABLE\_SCHEMA* column in the *COLUMNS* view.
  - The value of *TABLE\_NAME* in *COLUMNS\_QUERY* is the value of the *TABLE\_NAME* column in the *COLUMNS* view.
  - The value of *COLUMN\_NAME* in *COLUMNS\_QUERY* is the value of the *COLUMN\_NAME* column in the *COLUMNS* view.
  - The value of *DATA\_TYPE* in *COLUMNS\_QUERY* is determined by the values of the *DATA\_TYPE* and *INTERVAL\_TYPE* columns in the *COLUMNS* view.

Case:

- i) If the value of `DATA_TYPE` in the `COLUMNS` view is 'INTERVAL', then the value of `DATA_TYPE` in `COLUMNS_QUERY` is the appropriate 'Code' from Table 37, "Codes used for concise data types", that matches the interval specified in the `INTERVAL_TYPE` column in the `COLUMNS` view.
- ii) Otherwise, the value of `DATA_TYPE` in `COLUMNS_QUERY` is the appropriate 'Code' from Table 37, "Codes used for concise data types", that matches the value specified in the `DATA_TYPE` column in the `COLUMNS` view.
- f) The value of `TYPE_NAME` in `COLUMNS_QUERY` is an implementation-defined value that is the character string by which the data type is known at the data source.
- g) The value of `COLUMN_SIZE` in `COLUMNS_QUERY` is

Case:

- i) If the value of `DATA_TYPE` in the `COLUMNS` view is 'CHARACTER', 'CHARACTER VARYING', 'CHARACTER LARGE OBJECT', or 'BINARY LARGE OBJECT', then the value is that of the `CHARACTER_MAXIMUM_LENGTH` in the same row of the `COLUMNS` view.
- ii) If the value of `DATA_TYPE` in the `COLUMNS` view is 'BIT' or 'BIT VARYING', then the value is that of the `CHARACTER_MAXIMUM_LENGTH` in the same row of the `COLUMNS` view.
- iii) If the value of `DATA_TYPE` in the `COLUMNS` view is 'DECIMAL' or 'NUMERIC', then the value is that of the `NUMERIC_PRECISION` column in the same row of the `COLUMNS` view.
- iv) If the value of `DATA_TYPE` in the `COLUMNS` view is 'SMALLINT', 'INTEGER', 'REAL', 'DOUBLE PRECISION', or 'FLOAT', then the value is implementation-defined.
- v) If the value of `DATA_TYPE` in the `COLUMNS` view is 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE', then the value of `COLUMN_SIZE` is that determined by Syntax Rule 33), in Subclause 6.1, "<data type>", in ISO/IEC 9075-2, where the value of <time fractional seconds precision> is the value of the `DATETIME_PRECISION` column in the same row of the `COLUMNS` view.
- vi) If the value of `DATA_TYPE` in the `COLUMNS` view is 'INTERVAL', then the value of `COLUMN_SIZE` is that determined by the General Rules of Subclause 10.1, "<interval qualifier>", in ISO/IEC 9075-2, where:
  - 1) The value of <interval qualifier> is the value of the `INTERVAL_TYPE` column in the same row of the `COLUMNS` view.
  - 2) The value of <interval leading field precision> is the value of the `INTERVAL_PRECISION` column in the same row of the `COLUMNS` view.
  - 3) The value of <interval fractional seconds precision> is the value of the `NUMERIC_PRECISION` column in the same row of the `COLUMNS` view.
- vii) If the value of `DATA_TYPE` in the `COLUMNS` view is 'REF', then the value is the length in octets of the reference type.
- viii) Otherwise, the value is implementation-dependent.

**6.11 Columns**

- h) The value of `BUFFER_LENGTH` in `COLUMNS_QUERY` is implementation-defined.

NOTE 17 – The purpose of `BUFFER_LENGTH` in `COLUMNS_QUERY` is to record the number of octets transferred for the column with a Fetch routine, a FetchScroll routine, or a GetData routine when the `TYPE` field in the application row descriptor indicates `DEFAULT`. This length excludes any null terminator.

- i) The value of `DECIMAL_DIGITS` in `COLUMNS_QUERY` is

Case:

- i) If the value of `DATA_TYPE` in the `COLUMNS` view is one of 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE', then the value of `DECIMAL_DIGITS` in `COLUMNS_QUERY` is the value of the `DATETIME_PRECISION` column in the `COLUMNS` view.
  - ii) If the value of `DATA_TYPE` in the `COLUMNS` view is one of 'DECIMAL', 'INTEGER', 'NUMERIC', or 'SMALLINT', then the value of `DECIMAL_DIGITS` in `COLUMNS_QUERY` is the value of the `NUMERIC_SCALE` column in the `COLUMNS` view.
  - iii) Otherwise, the value of `DECIMAL_DIGITS` in `COLUMNS_QUERY` is the null value.
- j) The value of `NUM_PREC_RADIX` in `COLUMNS_QUERY` is the value of the `NUMERIC_PRECISION_RADIX` column in the `COLUMNS` view.
- k) If the value of the `IS_NULLABLE` column in the `COLUMNS` view is 'NO', then the value of `NULLABLE` in `COLUMNS_QUERY` is set to the appropriate 'Code' for NO NULLS in Table 26, "Miscellaneous codes used in CLI"; otherwise it is set to the appropriate 'Code' for `NULLABLE` from Table 26, "Miscellaneous codes used in CLI".
- l) The value of `REMARKS` in `COLUMNS_QUERY` is an implementation-defined description of the column.
- m) The value of `COLUMN_DEF` in `COLUMNS_QUERY` is the value of the `COLUMN_DEFAULT` column in the `COLUMNS` view.
- n) The value of `SQL_DATETIME_SUB` in `COLUMNS_QUERY` is determined by the value of the `DATA_TYPE` column in the same row of the `COLUMNS` view.

Case:

- i) If the value of `DATA_TYPE` in the `COLUMNS` view is the appropriate 'Code' for the any of the data types 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE' from Table 37, "Codes used for concise data types", then the value is the matching 'Datetime Interval Code' from Table 37, "Codes used for concise data types".
  - ii) If the value of `DATA_TYPE` in the `COLUMNS` view is the appropriate 'Code' for any of the `INTERVAL` data types from Table 37, "Codes used for concise data types", then the value is the matching 'Datetime Interval Code' from Table 37, "Codes used for concise data types".
  - iii) Otherwise, the value is the null value.
- o) The value of `CHAR_OCTET_LENGTH` in `COLUMNS_QUERY` is the value of the `CHARACTER_OCTET_LENGTH` column in the `COLUMNS` view.

- p) The value of `ORDINAL_POSITION` in `COLUMNS_QUERY` is the value of the `ORDINAL_POSITION` column in the `COLUMNS` view.
- q) The value of `IS_NULLABLE` in `COLUMNS_QUERY` is the value of the `IS_NULLABLE` column in the `COLUMNS` view.
- r) The value of `SQL_DATA_TYPE` in `COLUMNS_QUERY` is determined by the value of the `DATA_TYPE` column in the same row of the `COLUMNS` view.

Case:

- i) If the value of `DATA_TYPE` in the `COLUMNS` view is the appropriate 'Code' for any of the data types 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE', from Table 37, "Codes used for concise data types", then the value is the matching 'Code' from Table 7, "Codes used for implementation data types in SQL/CLI".
- ii) If the value of `DATA_TYPE` in the `COLUMNS` view is the appropriate 'Code' for any of the `INTERVAL` data types from Table 37, "Codes used for concise data types", then the value is the matching 'Code' from Table 7, "Codes used for implementation data types in SQL/CLI".
- iii) Otherwise, the value is the same as the value of `DATA_TYPE` in `COLUMNS_QUERY`.
- s) The value of `CHAR_SET_CAT` in `COLUMNS_QUERY` is the value of the `CHARACTER_SET_CATALOG` column in the `COLUMNS` view. If `SS` does not support catalog names, then `CHAR_SET_CAT` is set to the null value.
- t) The value of `CHAR_SET_SCHEM` in `COLUMNS_QUERY` is the value of the `CHARACTER_SET_SCHEMA` column in the `COLUMNS` view.
- u) The value of `CHAR_SET_NAME` in `COLUMNS_QUERY` is the value of the `CHARACTER_SET_NAME` column in the `COLUMNS` view.
- v) The value of `COLLATION_CAT` in `COLUMNS_QUERY` is the value of the `COLLATION_CATALOG` column in the `COLUMNS` view. If `SS` does not support catalog names, then `COLLATION_CAT` is set to the null value.
- w) The value of `COLLATION_SCHEM` in `COLUMNS_QUERY` is the value of the `COLLATION_SCHEMA` column in the `COLUMNS` view.
- x) The value of `COLLATION_NAME` in `COLUMNS_QUERY` is the value of the `COLLATION_NAME` column in the `COLUMNS` view.
- y) The value of `UDT_CAT` in `COLUMNS_QUERY` is the value of the `USER_DEFINED_TYPE_CATALOG` column in the `COLUMNS` view. If `SS` does not support catalog names, then `UDT_CAT` is set to the null value.
- z) The value of `UDT_SCHEM` in `COLUMNS_QUERY` is the value of the `USER_DEFINED_TYPE_SCHEMA` column in the `COLUMNS` view.
- aa) The value of `UDT_NAME` in `COLUMNS_QUERY` is the value of the `USER_DEFINED_TYPE_NAME` column in the `COLUMNS` view.
- bb) The value of `DOMAIN_CAT` in `COLUMNS_QUERY` is the value of the `DOMAIN_CATALOG` column in the `COLUMNS` view. If `SS` does not support catalog names, then `DOMAIN_CAT` is set to the null value.

**6.11 Columns**

- cc) The value of DOMAIN\_SCHEM in COLUMNS\_QUERY is the value of the DOMAIN\_SCHEMA column in the COLUMNS view.
  - dd) The value of DOMAIN\_NAME in COLUMNS\_QUERY is the value of the DOMAIN\_NAME column in the COLUMNS view.
  - ee) The value of SCOPE\_CAT in COLUMNS\_QUERY is the value of the SCOPE\_CATALOG column in the COLUMNS view. If SS does not support catalog names, then SCOPE\_CAT is set to the null value.
  - ff) The value of SCOPE\_SCHEM in COLUMNS\_QUERY is the value of the SCOPE\_SCHEMA column in the COLUMNS view.
  - gg) The value of SCOPE\_NAME in COLUMNS\_QUERY is the value of the SCOPE\_NAME column in the COLUMNS view.
  - hh) The value of MAX\_CARDINALITY in COLUMNS\_QUERY is the value of the MAXIMUM\_CARDINALITY column in the COLUMNS view.
  - ii) The value of DTD\_IDENTIFIER in COLUMNS\_QUERY is the value of the DTD\_IDENTIFIER column in the COLUMNS view.
  - jj) The value of IS\_SELF\_REF in COLUMNS\_QUERY is the value of the IS\_SELF\_REFERENCING column in the COLUMNS view.
- 8) Let  $NL1$ ,  $NL2$ ,  $NL3$ , and  $NL4$  be the values of NameLength1, NameLength2, NameLength3, and NameLength4, respectively.
- 9) Let  $CATVAL$ ,  $SCHVAL$ ,  $TBLVAL$ , and  $COLVAL$  be the values of CatalogName, SchemaName, TableName, and ColumnName, respectively.
- 10) If the METADATA ID attribute of  $S$  is TRUE, then:
- a) If CatalogName is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", is 'Y', then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - b) If SchemaName is a null pointer, or if TableName is a null pointer, or if ColumnName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- 11) If CatalogName is a null pointer, then  $NL1$  is set to zero. If SchemaName is a null pointer, then  $NL2$  is set to zero. If TableName is a null pointer, then  $NL3$  is set to zero. If ColumnName is a null pointer, then  $NL4$  is set to zero.
- 12) Case:
- a) If  $NL1$  is not negative, then let  $L$  be  $NL1$ .
  - b) If  $NL1$  indicates NULL TERMINATED, then let  $L$  be the number of octets of CatalogName that precede the implementation-defined null character that terminates a C character string.
  - c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let  $CATVAL$  be the first  $L$  octets of CatalogName.

## 13) Case:

- a) If *NL2* is not negative, then let *L* be *NL2*.
- b) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of *SchemaName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *SCHVAL* be the first *L* octets of *SchemaName*.

## 14) Case:

- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of *TableName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TBLVAL* be the first *L* octets of *TableName*.

## 15) Case:

- a) If *NL4* is not negative, then let *L* be *NL4*.
- b) If *NL4* indicates NULL TERMINATED, then let *L* be the number of octets of *ColumnName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *COLVAL* be the first *L* octets of *ColumnName*.

## 16) Case:

- a) If the METADATA ID attribute of *S* is TRUE, then:

- i) Case:

- 1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
- 2) Otherwise,

- Case:

- A) If `SUBSTRING( TRIM( CATVAL ) FROM 1 FOR 1 ) = ' ' and if SUBSTRING( TRIM( CATVAL ) FROM CHAR_LENGTH( TRIM( CATVAL ) ) FOR 1 ) = ' '`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM ( CATVAL ) FROM 2
FOR CHAR_LENGTH ( TRIM( CATVAL ) ) - 2 )
```

## 6.11 Columns

and let *CATSTR* be the character string:

```
TABLE_CAT = 'TEMPSTR' AND
```

B) Otherwise, let *CATSTR* be the character string:

```
UPPER(TABLE_CAT) = UPPER('CATVAL') AND
```

ii) Case:

1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(SCHVAL) FROM CHAR_LENGTH(TRIM(SCHVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(SCHVAL) FROM 2
FOR CHAR_LENGTH ( TRIM(SCHVAL) ) - 2 )
```

and let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'TEMPSTR' AND
```

B) Otherwise, let *SCHSTR* be the character string:

```
UPPER(TABLE_SCHEM) = UPPER('SCHVAL') AND
```

iii) Case:

1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(TBLVAL) FROM CHAR_LENGTH(TRIM(TBLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(TBLVAL) FROM 2
FOR CHAR_LENGTH ( TRIM(TBLVAL) ) - 2 )
```

and let *TBLSTR* be the character string:

```
TABLE_NAME = 'TEMPSTR' AND
```

B) Otherwise, let *TBLSTR* be the character string:

```
UPPER(TABLE_NAME) = UPPER('TBLVAL') AND
```

iv) Case:

1) If the value of *NL4* is zero, then let *COLSTR* be a zero-length string.

2) Otherwise,

Case:

- A) If `SUBSTRING( TRIM(COLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING( TRIM(COLVAL) FROM CHAR_LENGTH( TRIM(COLVAL) ) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(COLVAL) FROM 2
           FOR CHAR_LENGTH ( TRIM(COLVAL) ) - 2 )
```

and let *COLSTR* be the character string:

```
COLUMN_NAME = 'TEMPSTR'
```

- B) Otherwise, let *COLSTR* be the character string:

```
UPPER(COLUMN_NAME) = UPPER('COLVAL')
```

b) Otherwise:

- i) Let *SPC* be the Code value from Table 28, “Codes and data types for implementation information”, that corresponds to the Information Type SEARCH PATTERN ESCAPE in that same table.
- ii) Let *ESC* be the value of InfoValue that is returned by the execution of GetInfo() with the value of InfoType set to *SPC*.
- iii) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
TABLE_CAT = 'CATVAL' AND
```

- iv) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM LIKE 'SCHVAL' ESCAPE 'ESC' AND
```

NOTE 18 – The pattern value specified in the string to the right of LIKE may use the escape character that is indicated by the value of the SEARCH PATTERN ESCAPE information type from Table 28, “Codes and data types for implementation information”.

- v) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string; otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME LIKE 'TBLVAL' ESCAPE 'ESC' AND
```

NOTE 19 – The pattern value specified in the string to the right of LIKE may use the escape character that is indicated by the value of the SEARCH PATTERN ESCAPE information type from Table 28, “Codes and data types for implementation information”.

- vi) If the value of *NL4* is zero, then let *COLSTR* be a zero-length string. Otherwise, let *COLSTR* be the character string:

```
COLUMN_NAME = 'COLVAL' AND
```

17) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || COLSTR || ' ' || 1=1
```

**6.11 Columns**

- 18) Let *STMT* be the character string:

```
SELECT *  
FROM COLUMNS_QUERY  
WHERE PRED  
ORDER BY TABLE_CAT, TABLE_SCHEM, TABLE_NAME, ORDINAL_POSITION
```

- 19) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.12 Connect

### Function

Establish a connection.

### Definition

```

Connect (
    ConnectionHandle    IN    INTEGER,
    ServerName          IN    CHARACTER(L1),
    NameLength1         IN    SMALLINT,
    UserName            IN    CHARACTER(L2),
    NameLength2         IN    SMALLINT,
    Authentication      IN    CHARACTER(L3),
    NameLength3         IN    SMALLINT )
RETURNS SMALLINT

```

where:

- *L1* is determined by the value of *NameLength1* and has a maximum value of 128.
- *L2* is determined by the value of *NameLength2* and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.
- *L3* is determined by the value of *NameLength3* and has an implementation-defined maximum value.

### General Rules

- 1) Case:
  - a) If *ConnectionHandle* does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by *ConnectionHandle*.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) If an SQL-transaction is active for the current SQL-connection and the implementation does not support transactions that affect more than one SQL-server, then an exception condition is raised: *feature not supported — multiple server transactions*.
- 3) If there is an established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection name in use*.
- 4) Case:
  - a) If *ServerName* is a null pointer, then let *NL1* be zero.
  - b) Otherwise, let *NL1* be the value of *NameLength1*.

**6.12 Connect**

- 5) Case:
- If  $NL1$  is not negative, then let  $L1$  be  $NL1$ .
  - If  $NL1$  indicates NULL TERMINATED, then let  $L1$  be the number of octets of `ServerName` that precede the implementation-defined null character that terminates a C character string.
  - Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 6) Case:
- If  $L1$  is zero, then let 'DEFAULT' be the value of  $SN$ .
  - If  $L1$  is greater than 128, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - Otherwise, let  $SN$  be the first  $L1$  octets of `ServerName`.
- 7) Let  $E$  be the allocated SQL-environment with which  $C$  is associated.
- 8) Case:
- If `UserName` is a null pointer, then let  $NL2$  be zero.
  - Otherwise, let  $NL2$  be the value of `NameLength2`.
- 9) Case:
- If  $NL2$  is not negative, then let  $L2$  be  $NL2$ .
  - If  $NL2$  indicates NULL TERMINATED, then let  $L2$  be the number of Octets of `UserName` that precede the implementation-defined null character that terminates a C character string.
  - Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 10) Case:
- If `Authentication` is a null pointer, then let  $NL3$  be zero.
  - Otherwise, let  $NL3$  be the value of `NameLength3`.
- 11) Case:
- If  $NL3$  is not negative, then let  $L3$  be  $NL3$ .
  - If  $NL3$  indicates NULL TERMINATED, then let  $L3$  be the number of octets of `Authentication` that precede the implementation-defined null character that terminates a C character string.
  - Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

## 12) Case:

a) If the value of *SN* is 'DEFAULT', then:

- i) If *L2* is not zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- ii) If *L3* is not zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- iii) If an established default SQL-connection is associated with an allocated SQL-connection associated with *E*, then an exception condition is raised: *connection exception — connection name in use*.

## b) Otherwise:

- i) If *L2* is zero, then let *UN* be an implementation-defined <user identifier>.
- ii) If *L2* is non-zero, then:
  - 1) Let *UV* be the first *L2* octets of *UserName* and let *UN* be the result of  
`TRIM ( BOTH ' ' FROM UV )`
  - 2) If *UN* does not conform to the Format and Syntax Rules of a <user identifier>, then an exception condition is raised: *invalid authorization specification*.
  - 3) If *UN* does not conform to any implementation-defined restrictions on its value, then an exception condition is raised: *invalid authorization specification*.
- iii) Case:
  - 1) If *L3* is not zero, then let *AU* be the first *L3* octets of *Authentication*.
  - 2) Otherwise, let *AU* be an implementation-defined authentication string, whose length may be zero.

## 13) Case:

- a) If the value of *SN* is 'DEFAULT', then the default SQL-session is initiated and associated with the default SQL-server. The method by which the default SQL-server is determined is implementation-defined.
- b) Otherwise, an SQL-session is initiated and associated with the SQL-server identified by *SN*. The method by which *SN* is used to determine the appropriate SQL-server is implementation-defined.

## 14) If an SQL-session is successfully initiated, then:

- a) The current SQL-connection and current SQL-session, if any, become a dormant SQL-connection and a dormant SQL-session respectively. The SQL-session context information is preserved and is not affected in any way by operations performed over the initiated SQL-connection.

NOTE 20 – The SQL-session context information is defined in Subclause 4.34, "SQL-sessions", in ISO/IEC 9075-2.

**6.12 Connect**

- b) The initiated SQL-session becomes the current SQL-session and the SQL-connection established to that SQL-session becomes the current SQL-connection and is associated with *C*.

NOTE 21 – If an SQL-session is not successfully initiated, then the current SQL-connection and current SQL-session, if any, remain unchanged.

- 15) If the SQL-client cannot establish the SQL-connection, then an exception condition is raised: *connection exception — SQL-client unable to establish SQL-connection*.
- 16) If the SQL-server rejects the establishment of the SQL-connection, then an exception condition is raised: *connection exception — SQL-server rejected establishment of SQL-connection*.  
NOTE 22 – *AU* and *UN* are used by the SQL-server, along with other implementation-dependent values, to determine whether to accept or reject the establishment of an SQL-session.
- 17) The SQL-server for the subsequent execution of SQL-statements via CLI routine invocations is set to the SQL-server identified by *SN*.
- 18) The SQL-session user identifier and the current user identifier are set to *UN*. The current role name is set to the null value.

## 6.13 CopyDesc

### Function

Copy a CLI descriptor.

### Definition

```
CopyDesc (
    SourceDescHandle    IN    INTEGER ,
    TargetDescHandle    IN    INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Case:
  - a) If SourceDescHandle does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise, let *SD* be the CLI descriptor area identified by SourceDescHandle.
- 2) Case:
  - a) If TargetDescHandle does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *TD* be the CLI descriptor area identified by TargetDescHandle.
    - ii) The diagnostics area associated with *TD* is emptied.
- 3) The General Rules of Subclause 5.11, “Deferred parameter check”, are applied to *SD* as the DESCRIPTOR AREA.
- 4) The General Rules of Subclause 5.11, “Deferred parameter check”, are applied to *TD* as the DESCRIPTOR AREA.
- 5) If *TD* is an implementation row descriptor, then an exception condition is raised: *CLI-specific condition — cannot modify an implementation row descriptor*.
- 6) Let *AT* be the value of the ALLOC\_TYPE field of *TD*.
- 7) The contents of *TD* are replaced by a copy of the contents of *SD*.
- 8) The ALLOC\_TYPE field of *TD* is set to *AT*.

## 6.14 DataSources

## 6.14 DataSources

## Function

Get server name(s) that the application can connect to, along with description information, if available.

## Definition

```
DataSources (
    EnvironmentHandle    IN        INTEGER,
    Direction            IN        SMALLINT,
    ServerName          OUT       CHARACTER(L1),
    BufferLength1        IN        SMALLINT,
    NameLength1         OUT       SMALLINT,
    Description         OUT       CHARACTER(L2),
    BufferLength2        IN        SMALLINT,
    NameLength2         OUT       SMALLINT )
RETURNS SMALLINT
```

where  $L1$  and  $L2$  are the values of BufferLength1 and BufferLength2, respectively, and have maximum values equal to the implementation-defined maximum length of a variable-length character string.

## General Rules

- 1) Let  $EH$  be the value of EnvironmentHandle.
- 2) If  $EH$  does not identify an allocated SQL-environment or if it identifies an allocated skeleton SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Let  $E$  be the allocated SQL-environment identified by  $EH$ . The diagnostics area associated with  $E$  is emptied.
- 4) Let  $BL1$  and  $BL2$  be the values of BufferLength1 and BufferLength2, respectively.
- 5) Let  $D$  be the value of Direction.
- 6) If  $D$  is not either the code value for NEXT or the code value for FIRST in Table 24, “Codes used for fetch orientation”, then an exception condition is raised: *CLI-specific condition — invalid retrieval code*.
- 7) Let  $SN_1, SN_2, SN_3, etc.$ , be an ordered set of the names of SQL-servers to which the application might be eligible to connect (where the mechanism used to establish this set is implementation-defined).  
NOTE 23 –  $SN_1, SN_2, SN_3, etc.$ , are the names that an application program would use in invocations of Connect, rather than the “actual” names of the SQL-servers.
- 8) Let  $D_1, D_2, D_3, etc.$ , be strings describing the SQL-servers named by  $SN_1, SN_2, SN_3, etc.$  (again provided via an implementation-defined mechanism).

## 9) Case:

- a) If  $D$  indicates FIRST, or if DataSources has never been successfully called on  $EH$ , or if the previous call to DataSources on  $EH$  raised a completion condition: *no data*, then:
  - i) If there are no entries in the set  $SN_1, SN_2, SN_3, \text{ etc.}$ , then a completion condition is raised: *no data* and no further rules for this Subclause are applied.
  - ii) The General Rules of Subclause 5.9, "Character string retrieval", are applied with ServerName,  $SN_1$ ,  $BL1$ , and NameLength1 as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.
  - iii) The General Rules of Subclause 5.9, "Character string retrieval", are applied with Description,  $D_1$ ,  $BL2$ , and NameLength2 as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.
- b) Otherwise,
  - i) Let  $SN_n$  be the ServerName value that was returned on the previous call to DataSources on  $EH$ .
  - ii) If there is no entry in the set after  $SN_n$ , then a completion condition is raised: *no data* and no further rules for this subclause are applied.
  - iii) The General Rules of Subclause 5.9, "Character string retrieval", are applied with ServerName,  $SN_{n+1}$ ,  $BL1$ , and NameLength1 as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.
  - iv) The General Rules of Subclause 5.9, "Character string retrieval", are applied with Description,  $D_{n+1}$ ,  $BL2$ , and NameLength2 as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

## 6.15 DescribeCol

### Function

Get column attributes.

### Definition

```
DescribeCol (
    StatementHandle      IN      INTEGER,
    ColumnNumber         IN      SMALLINT,
    ColumnName           OUT     CHARACTER(L),
    BufferLength          IN      SMALLINT,
    NameLength           OUT     SMALLINT,
    DataType             OUT     SMALLINT,
    ColumnSize           OUT     INTEGER,
    DecimalDigits        OUT     SMALLINT,
    Nullable             OUT     SMALLINT )
RETURNS SMALLINT
```

where  $L$  is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no prepared or executed statement associated with  $S$ , then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) Let  $IRD$  be the implementation row descriptor associated with  $S$  and let  $N$  be the value of the TOP\_LEVEL\_COUNT field of  $IRD$ .
- 4) If  $N$  is zero, then an exception condition is raised: *dynamic SQL error — prepared statement not a cursor specification*.
- 5) Let  $CN$  be the value of ColumnNumber.
- 6) If  $CN$  is less than 1 (one) or greater than  $N$ , then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 7) Let  $RI$  be the number of the descriptor record in  $IRD$  that is the  $CN$ -th descriptor area for which LEVEL is 0 (zero). Let  $C$  be the <select list> column described by the item descriptor area of  $IRD$  specified by  $RI$ .
- 8) Let  $BL$  be the value of BufferLength.
- 9) Information is retrieved from  $IRD$ :
  - a) Case:
    - i) If the data type of  $C$  is datetime, then DataType is set to the value of the Code column from Table 40, “Concise codes used with datetime data types in SQL/CLI”, corresponding to the datetime interval code of  $C$ .

- ii) If the data type of *C* is interval, then *DataType* is set to the value of the *Code* column from Table 41, "Concise codes used with interval data types in SQL/CLI", corresponding to the datetime interval code of *C*.
  - iii) Otherwise, *DataType* is set to the data type of *C*.
- b) Case:
- i) If the data type of *C* is character string, then *ColumnSize* is set to the maximum length in octets of *C*.
  - ii) If the data type of *C* is exact numeric or approximate numeric, then *ColumnSize* is set to the maximum length of *C* in decimal digits.
  - iii) If the data type of *C* is datetime or interval, then *ColumnSize* is set to the length in positions of *C*.
  - iv) If the data type of *C* is bit string, then *ColumnSize* is set to the length in bits of *C*.
  - v) If the data type of *C* is a reference type, then *ColumnSize* is set to the length in octets of that reference type.
  - vi) Otherwise, *ColumnSize* is set to an implementation-dependent value.
- c) Case:
- i) If the data type of *C* is exact numeric, then *DecimalDigits* is set to the scale of *C*.
  - ii) If the data type of *C* is datetime, then *DecimalDigits* is set to the time fractional seconds precision of *C*.
  - iii) If the data type of *C* is interval, then *DecimalDigits* is set to the interval fractional seconds precision of *C*.
  - iv) Otherwise, *DecimalDigits* is set to an implementation-dependent value.
- d) If *C* can have the null value, then *Nullable* is set to 1 (one); otherwise, *Nullable* is set to 0 (zero).
- e) The name associated with *C* is retrieved. If *C* has an implementation-dependent name, then the value retrieved is the implementation-dependent name for *C*; otherwise, the value retrieved is the <derived column> name of *C*. Let *V* be the value retrieved. The General Rules of Subclause 5.9, "Character string retrieval", are applied with *ColumnName*, *V*, *BL*, and *NameLength* as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

**6.16 Disconnect****6.16 Disconnect****Function**

Terminate an established connection.

**Definition**

```
Disconnect (
    ConnectionHandle    IN    INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Case:
  - a) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise, let *EC* be the established SQL-connection associated with *C*.
- 3) Let *L1* be a list of the allocated SQL-statements associated with *C*. Let *L2* be a list of the allocated CLI descriptor areas associated with *C*.
- 4) If *EC* is active, then
 

Case:

  - a) If any allocated SQL-statement in *L1* has a deferred parameter number associated with it, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) Otherwise, an exception condition is raised: *invalid transaction state — active SQL-transaction*.
- 5) For every allocated SQL-statement *AS* in *L1*:
  - a) Let *SH* be the StatementHandle that identifies *AS*.
  - b) FreeHandle is implicitly invoked with HandleType indicating STATEMENT HANDLE and with *SH* as the value of Handle.

NOTE 24 – Any diagnostic information generated by the invocation is associated with *C* and not with *AS*.

- 6) For every allocated CLI descriptor area *AD* in *L2*:
  - a) Let *DH* be the DescriptorHandle that identifies *AD*.
  - b) FreeHandle is implicitly invoked with HandleType indicating DESCRIPTOR HANDLE and with *DH* as the value of Handle.  
NOTE 25 – Any diagnostic information generated by the invocation is associated with *C* and not with *AD*.
- 7) Let *CC* be the current SQL-connection.
- 8) The SQL-session associated with *EC* is terminated. *EC* is terminated, regardless of any exception conditions that might occur during the disconnection process, and is no longer associated with *C*.
- 9) If any error is detected during the disconnection process, then a completion condition is raised: *warning — disconnect error*.
- 10) If *EC* and *CC* were the same SQL-connection, then there is no current SQL-connection. Otherwise, *CC* remains the current SQL-connection.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

**6.17 EndTran****6.17 EndTran****Function**

Terminate an SQL-transaction.

**Definition**

```
EndTran (
    HandleType           IN    SMALLINT ,
    Handle               IN    INTEGER ,
    CompletionType       IN    SMALLINT )
    RETURNS SMALLINT
```

**General Rules**

- 1) Let  $HT$  be the value of HandleType and let  $H$  be the value of Handle.
- 2) If  $HT$  is not one of the code values in Table 13, "Codes used for handle types", then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If  $HT$  indicates STATEMENT HANDLE, then:
    - i) If  $H$  does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
  - b) If  $HT$  indicates DESCRIPTOR HANDLE, then:
    - i) If  $H$  does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
  - c) If  $HT$  indicates CONNECTION HANDLE, then:
    - i) If  $H$  does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise:
      - 1) Let  $C$  be the allocated SQL-connection identified by  $H$ .
      - 2) The diagnostics area associated with  $C$  is emptied.
      - 3) If  $C$  has an associated established SQL-connection that is active, then let  $L1$  be a list containing  $C$ ; otherwise, let  $L1$  be an empty list.

- d) If *HT* indicates ENVIRONMENT HANDLE, then:
- i) If *H* does not identify an allocated SQL-environment or if it identifies an allocated SQL-environment that is a skeleton SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - ii) Otherwise:
    - 1) Let *E* be the allocated SQL-environment identified by *H*.
    - 2) The diagnostics area associated with *E* is emptied.
    - 3) Let *L* be a list of the allocated SQL-connections associated with *E*. Let *L1* be a list of the allocated SQL-connections in *L* that have an associated established SQL-connection that is active.
- 4) Let *CT* be the value of CompletionType.
  - 5) If *CT* is not one of the code values in Table 14, “Codes used for transaction termination”, then an exception condition is raised: *CLI-specific condition — invalid transaction operation code*.
  - 6) If *L1* is empty, then no further rules of this Subclause are applied.
  - 7) If the current SQL-transaction is part of an encompassing transaction that is controlled by an agent other than the SQL-agent, then an exception condition is raised: *invalid transaction termination*.
  - 8) Let *L2* be a list of the allocated SQL-statements associated with allocated SQL-connections in *L1*.
  - 9) If any of the allocated SQL-statements in *L2* has an associated deferred parameter number, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - 10) Let *L3* be a list of the open cursors associated with allocated SQL-statements in *L2*.
  - 11) If *CT* indicates COMMIT, COMMIT AND CHAIN, ROLLBACK, or ROLLBACK AND CHAIN, then:
    - a) Case:
      - i) If *CT* indicates COMMIT or COMMIT AND CHAIN, then let *LOC* be the list of all non-holdable cursors in *L3*.
      - ii) Otherwise, let *LOC* be the list of all cursors in *L3*.
    - b) For *OC* ranging over all cursors in *LOC*:
      - i) Let *S* be the allocated SQL-statement with which *OC* is associated.
      - ii) *OC* is placed in the closed state and its copy of the select source is destroyed.
      - iii) Any fetched row associated with *S* is removed from association with *S*.
  - 12) If *CT* indicates COMMIT or COMMIT AND CHAIN, then:
    - a) If an atomic execution context is active, then an exception condition is raised: *invalid transaction termination*.

**6.17 EndTran**

- b) For every temporary table associated with the current SQL-transaction that specifies the ON COMMIT DELETE option and that was updated by the current SQL-transaction, the invocation of EndTran with *CT* indicating COMMIT is effectively preceded by the execution of a <delete statement: searched> that specifies DELETE FROM *T*, where *T* is the <table name> of that temporary table.
- c) The effects specified in the General Rules of Subclause 16.3, "<set constraints mode statement>", in ISO/IEC 9075-2, occur as if the statement SET CONSTRAINTS ALL IMMEDIATE were executed.
- d) Case:
- i) If any constraint is not satisfied, then any changes to SQL-data or schemas that were made by the current SQL-transaction are canceled and an exception condition is raised: *transaction rollback — integrity constraint violation*.
  - ii) If the execution of any <triggered SQL statement> is unsuccessful, then all changes to SQL-data or schemas that were made by the current SQL-transaction are canceled and an exception condition is raised: *transaction rollback — triggered action exception*.
  - iii) If any other error preventing commitment of the SQL-transaction has occurred, then any changes to SQL-data or schemas that were made by the current SQL-transaction are canceled and an exception condition is raised: *transaction rollback* with an implementation-defined subclass value.
  - iv) Otherwise, any changes to SQL-data or schemas that were made by the current SQL-transaction are made accessible to all concurrent and subsequent SQL-transactions.
- e) Every savepoint established in the current SQL-transaction is destroyed.
- f) Every valid non-holdable locator value is marked invalid.
- g) The current SQL-transaction is terminated. If *CT* indicates COMMIT AND CHAIN, then a new SQL-transaction is initiated with the same access mode and isolation level as the SQL-transaction just terminated. Any branch transactions of the SQL-transaction are initiated with the same access mode and isolation level as the corresponding branch of the SQL-transaction just terminated.
- 13) If *CT* indicates SAVEPOINT NAME COMMIT or SAVEPOINT NUMBER COMMIT, then:
- a) If *HT* is not CONNECTION HANDLE, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Case:
    - i) If *CT* indicates SAVEPOINT NAME COMMIT, then let *SP* be the value of the SAVEPOINT NAME connection attribute of *C*.
    - ii) If *CT* indicates SAVEPOINT NUMBER COMMIT, then let *SP* be the value of the SAVEPOINT NUMBER connection attribute of *C*.
  - c) If *SP* does not specify a savepoint established within the current SQL-transaction, then an exception condition is raised: *savepoint exception — invalid specification*.

- d) The savepoint identified by *SP* and all savepoints established by the current SQL-transaction subsequent to the establishment of *SP* are destroyed.
- 14) If *CT* indicates ROLLBACK or ROLLBACK AND CHAIN, then:
- If an atomic execution context is active, then an exception condition is raised: *invalid transaction termination*.
  - All changes to SQL-data or schemas that were made by the current SQL-transaction are canceled.
  - Every savepoint established in the current SQL-transaction is destroyed.
  - Every valid non-holdable locator value is marked invalid.
  - The current SQL-transaction is terminated. If *CT* indicates ROLLBACK AND CHAIN, then a new SQL-transaction is initiated with the same access mode and isolation level as the SQL-transaction just terminated. Any branch transactions of the SQL-transaction are initiated with the same access mode and isolation level as the corresponding branch of the SQL-transaction just terminated.
- 15) If *CT* indicates SAVEPOINT NAME RELEASE or SAVEPOINT NUMBER RELEASE, then:
- If *HT* is not CONNECTION HANDLE, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - Case:
    - If *CT* indicates SAVEPOINT NAME RELEASE, then let *SP* be the value of the SAVEPOINT NAME connection attribute of *C*.
    - If *CT* indicates SAVEPOINT NUMBER RELEASE, then let *SP* be the value of the SAVEPOINT NUMBER connection attribute of *C*.
  - If *SP* does not specify a savepoint established within the current SQL-transaction, then an exception condition is raised: *savepoint exception — invalid specification*.
  - If an atomic execution context is active and *SP* specifies a savepoint established before the beginning of the most recent atomic execution context, then an exception condition is raised: *savepoint exception — invalid specification*.
  - Any changes to SQL-data or schemas that were made by the current SQL-transaction subsequent to the establishment of *SP* are canceled.
  - All savepoints established by the current SQL-transaction subsequent to the establishment of *SP* are destroyed.
  - Every valid locator is marked invalid.
  - For every open cursor *OC* in *L3* that was opened subsequent to the establishment of *SP*:
    - Let *S* be the allocated SQL-statement with which *OC* is associated.
    - OC* is placed in the closed state and its copy of the select source is destroyed.
    - Any fetched row associated with *OC* is removed from association with *S*.

**6.17 EndTran**

- i) The status of any open cursors in *L3* that were opened by the current SQL-transaction before the establishment of *SP* is implementation-defined.

NOTE 26 – The current SQL-transaction is not terminated, and there is no other effect on the SQL-data or schemas.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.18 Error

### Function

Return diagnostic information.

### Definition

```

Error (
    EnvironmentHandle    IN    INTEGER,
    ConnectionHandle     IN    INTEGER,
    StatementHandle      IN    INTEGER,
    Sqlstate             OUT   CHARACTER(5),
    NativeError          OUT   INTEGER,
    MessageText          OUT   CHARACTER(L),
    BufferLength          IN    SMALLINT,
    TextLength           OUT   SMALLINT )
RETURNS SMALLINT

```

where  $L$  is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

1) Case:

- a) If StatementHandle identifies an allocated SQL-statement, then let  $IH$  be the value of StatementHandle and let  $HT$  be the code value for STATEMENT HANDLE from Table 13, "Codes used for handle types".
- b) If StatementHandle is zero and ConnectionHandle identifies an allocated SQL-connection, then let  $IH$  be the value of ConnectionHandle and let  $HT$  be the code value for CONNECTION HANDLE from Table 13, "Codes used for handle types".
- c) If ConnectionHandle is zero and EnvironmentHandle identifies an allocated SQL-environment, then let  $IH$  be the value of EnvironmentHandle and let  $HT$  be the code value for ENVIRONMENT HANDLE from Table 13, "Codes used for handle types".
- d) Otherwise, an exception condition is raised: *CLI-specific condition — invalid handle*.

2) Let  $R$  be the most recently executed CLI routine, other than Error, GetDiagField, or GetDiagRec, for which  $IH$  was passed as a value of an input handle.

NOTE 27 – The GetDiagField, GetDiagRec and Error routines may cause exception or completion conditions to be raised, but they do not cause status records to be generated.

3) Let  $N$  be the number of status records generated by the execution of  $R$ . Let  $AP$  be the number of status records generated by the execution of  $R$  already processed by Error. If  $N$  is zero or  $AP$  equals  $N$  then a completion condition is raised: *no data*, Sqlstate is set to '00000', the values of NativeError, MessageText, and TextLength are set to implementation-dependent values, and no further rules of this Subclause are applied.

4) Let  $SR$  be the first status record generated by the execution of  $R$  not yet processed by Error. Let  $RN$  be the number of the status record  $SR$ . Information is retrieved by implicitly executing GetDiagRec as follows:

```

GetDiagRec (HT, IH, RN, Sqlstate,

```

**6.18 Error**

`NativeError, MessageText, BufferLength, TextLength)`

- 5) Add *SR* to the list of status records generated by the execution of *R* already processed by Error.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.19 ExecDirect

### Function

Execute a statement directly.

### Definition

```

ExecDirect (
    StatementHandle  IN      INTEGER,
    StatementText    IN      CHARACTER(L),
    TextLength       IN      INTEGER )
RETURNS SMALLINT

```

where  $L$  is determined by the value of TextLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $TL$  be the value of TextLength.
- 4) Case:
  - a) If  $TL$  is not negative, then let  $L$  be  $TL$ .
  - b) If  $TL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of StatementText that precede the implementation-defined null character that terminates a C character string.
  - c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 5) Case:
  - a) If  $L$  is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - b) Otherwise, let  $P$  be the first  $L$  octets of StatementText.
- 6) If  $P$  is a <preparable dynamic delete statement: positioned> or a <preparable dynamic update statement: positioned>, then let  $CN$  be the cursor name referenced by  $P$ . Let  $C$  be the allocated SQL-connection with which  $S$  is associated. If  $CN$  is not the name of a cursor associated with another allocated SQL-statement associated with  $C$ , then an exception condition is raised: *invalid cursor name*.

## 6.19 ExecDirect

7) If one or more of the following are true, then an exception condition is raised: *syntax error or access rule violation*.

- a) *P* does not conform to the Format, Syntax Rules or Access Rules for a <preparable statement> or *P* is a <start transaction statement>, a <commit statement>, a <rollback statement>, or a <release savepoint statement>.

NOTE 28 – See Table 26, "SQL-statement codes", in ISO/IEC 9075-2 and Table 9, "SQL-statement codes", in ISO/IEC 9075-5 for the list of <preparable statement>s. Other parts of ISO/IEC 9075 may have corresponding tables that define additional codes representing statements defined by those parts of ISO/IEC 9075.

- b) *P* contains a <simple comment>.

- c) *P* contains a <dynamic parameter specification> whose data type is undefined as determined by the rules specified in Subclause 15.6, "<prepare statement>", in ISO/IEC 9075-5.

8) The data type of any <dynamic parameter specification> contained in *P* is determined by the rules specified in Subclause 15.6, "<prepare statement>", in ISO/IEC 9075-5.

9) Let *DTGN* be the default transform group name and *TFL* be the list of user-defined type name—transform group name pairs used to identify the group of transform functions for every user-defined type that is referenced in *P*. *DTGN* and *TFL* are not affected by the execution of a <set transform group statement> after *P* is prepared.

10) The following objects associated with *S* are destroyed:

- a) Any prepared statement.  
b) Any cursor.  
c) Any select source.

If a cursor associated with *S* is destroyed, then so are any prepared statements that reference that cursor.

11) *P* is prepared.

12) Case:

- a) If *P* is a <dynamic select statement> or a <dynamic single row select statement>, then:

i) *P* becomes the *select source* associated with *S*.

ii) If there is no cursor name associated with *S*, then a unique implementation-dependent name that has the prefix 'SQLCUR' or the prefix 'SQL\_CUR' becomes the cursor name associated with *S*.

iii) The General Rules of Subclause 5.5, "Implicit DESCRIBE USING clause", are applied to *P* and *S*, as *SOURCE* and *ALLOCATED STATEMENT*, respectively.

iv) The General Rules of Subclause 5.4, "Implicit cursor", are applied to *P* and *S* as *SELECT SOURCE* and *ALLOCATED STATEMENT*, respectively.

- b) Otherwise:

i) The General Rules of Subclause 5.5, "Implicit DESCRIBE USING clause", are applied to *P* and *S*, as *SOURCE* and *ALLOCATED STATEMENT*, respectively.

- ii) The General Rules of Subclause 5.6, "Implicit EXECUTE USING and OPEN USING clauses", are applied to 'EXECUTE', *P*, and *S*, as *TYPE*, *SOURCE*, and *ALLOCATED STATEMENT*, respectively.
- iii) Case:
- 1) If *P* is a <preparable dynamic delete statement: positioned>, then:
    - A) Let *CR* be the cursor referenced by *P* and let *SCR* be the statement associated with *CR*.
    - B) All the General Rules in Subclause 15.21, "<preparable dynamic delete statement: positioned>", in ISO/IEC 9075-5 apply to *P*. For the purposes of the application of these Rules, the row in *CR* identified by *SCR*'s CURRENT OF POSITION statement attribute is the *current row* of *CR*.
    - C) If the execution of *P* deleted the current row of *CR*, then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.
  - 2) If *P* is a <preparable dynamic update statement: positioned>, then:
    - A) Let *CR* be the cursor referenced by *P* and let *SCR* be the statement associated with *CR*.
    - B) All the General Rules in Subclause 15.22, "<preparable dynamic update statement: positioned>", in ISO/IEC 9075-5 apply to *P*. For the purposes of the application of these Rules, the row in *CR* identified by *SCR*'s CURRENT OF POSITION statement attribute is the *current row* of *CR*.
    - C) If the execution of *P* updated the current row of *CR*, then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.
  - 3) Otherwise, the results of the execution are the same as if the statement were contained in an <externally-invoked procedure> and executed; these are described in Subclause 13.3, "<externally-invoked procedure>", in ISO/IEC 9075-2.
- iv) If *P* is a <call statement>, then the General Rules of Subclause 5.7, "Implicit CALL USING clause", are applied to *P* and *S*, as *SOURCE* and *ALLOCATED STATEMENT*, respectively.
- 13) Let *R* be the value of the ROW\_COUNT field from the diagnostics area associated with *S*.
  - 14) *R* becomes the row count associated with *S*.
  - 15) If *P* executed successfully, then any executed statement associated with *S* is destroyed and *P* becomes the executed statement associated with *S*.

**6.20 Execute****6.20 Execute****Function**

Execute a prepared statement.

**Definition**

```
Execute (
    StatementHandle IN INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no prepared statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*. Otherwise, let *P* be the statement that was prepared.
- 3) If an open cursor is associated with *S*, then an exception condition is raised: *invalid cursor state*.
- 4) *P* is executed.
- 5) Case:
  - a) If *P* is a <dynamic select statement> or a <dynamic single row select statement>, then the General Rules of Subclause 5.4, "Implicit cursor", are applied to *P* and *S* as *SELECT SOURCE* and *ALLOCATED STATEMENT*, respectively.
  - b) Otherwise:
    - i) The General Rules of Subclause 5.6, "Implicit EXECUTE USING and OPEN USING clauses", are applied to 'EXECUTE', *P*, and *S*, as *TYPE*, *SOURCE*, and *ALLOCATED STATEMENT*, respectively.
    - ii) Case:
      - 1) If *P* is a <preparable dynamic delete statement: positioned>, then:
        - A) Let *CR* be the cursor referenced by *P* and let *SCR* be the statement associated with *CR*.
        - B) All the General Rules in Subclause 15.21, "<preparable dynamic delete statement: positioned>", in ISO/IEC 9075-5 apply to *P*. For the purposes of the application of these Rules, the row in *CR* identified by *SCR*'s CURRENT OF POSITION statement attribute is the *current row* of *CR*.
        - C) If the execution of *P* deleted the current row of *CR*, then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.

- 2) If  $P$  is a <preparable dynamic update statement: positioned>, then:
  - A) Let  $CR$  be the cursor referenced by  $P$  and let  $SCR$  be the statement associated with  $CR$ .
  - B) All the General Rules in Subclause 15.22, "<preparable dynamic update statement: positioned>", in ISO/IEC 9075-5 apply to  $P$ . For the purposes of the application of these Rules, the row in  $CR$  identified by  $SCR$ 's CURRENT OF POSITION statement attribute is the *current row* of  $CR$ .
  - C) If the execution of  $P$  updated the current row of  $CR$ , then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.
- 3) Otherwise, the results of the execution are the same as if the statement were contained in an <externally-invoked procedure> and executed; these are described in Subclause 13.3, "<externally-invoked procedure>", in ISO/IEC 9075-2.
  - iii) If  $P$  is a <call statement>, then the General Rules of Subclause 5.7, "Implicit CALL USING clause", are applied to  $P$  and  $S$ , as *SOURCE* and *ALLOCATED STATEMENT*, respectively.
- 6) Let  $R$  be the value of the ROW\_COUNT field from the diagnostics area associated with  $S$ .
- 7)  $R$  becomes the row count associated with  $S$ .
- 8) If  $P$  executed successfully, then any executed statement associated with  $S$  is destroyed and  $P$  becomes the executed statement associated with  $S$ .

**6.21 Fetch****6.21 Fetch****Function**

Fetch the next row of a cursor.

**Definition**

```
Fetch (
    StatementHandle      IN      INTEGER )
    RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no executed statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) If there is no open cursor associated with *S*, then an exception condition is raised: *invalid cursor state*. Otherwise, let *CR* be the open cursor associated with *S* and let *T* be the table associated with the open cursor.
- 4) Let *ARD* be the current application row descriptor for *S* and let *N* be the value of the TOP\_LEVEL\_COUNT field of *ARD*.
- 5) For each item descriptor area in *ARD* whose LEVEL is 0 (zero) in the first *AD* item descriptor areas of *ARD*, and for all of their subordinate descriptor areas, refer to a <target specification> whose corresponding item descriptor area has a non-zero value of DATA\_POINTER as a *bound target* and refer to the corresponding <select list> column as a *bound column*.
- 6) Let *IDA* be the item descriptor area of *ARD* corresponding to the *i*-th bound target and let *TT* be the value of the TYPE field of *IDA*.
- 7) If *TT* indicates DEFAULT, then:
  - a) Let *IRD* be the implementation row descriptor associated with *S*.
  - b) Let *CT*, *P*, and *SC* be the values of the TYPE, PRECISION, and SCALE fields, respectively, for the item descriptor area of *IRD* corresponding to the *i*-th bound column.
  - c) The data type, precision, and scale of the <target specification> described by *IDA* are effectively set to *CT*, *P*, and *SC*, respectively, for the purposes of this Fetch invocation only.
- 8) Let *R* be the rowset on which *CR* is positioned and let *AS* be the value of the ARRAY\_SIZE field in the header of the ARD for *S*.
- 9) If *T* is empty, or if *R* contains the last row of *T*, or if *CR* is positioned after the end of the result set, then:
  - a) *CR* is positioned after the last row of *T*. An empty rowset becomes the fetched rowset associated with *CR*.
  - b) No database values are assigned to bound targets.

- c) A completion condition is raised: *no data* and no further rules of this Subclause are applied.

## 10) Case:

- a) If the position of *CR* is before the start of *T*, then:
  - i) If the number of rows in *T* is less than or equal to *AS*, then *CR* is positioned on the rowset that has all the rows in *T*.
  - ii) Otherwise, *CR* is positioned on the rowset that has the first *AS* rows of *T*.
- b) Otherwise, let  $T_t$  be the table that contains all the rows of *T* that immediately follow the last row of *R*, preserving their order in *T*.

## Case:

- i) If the number of rows in  $T_t$  is less than or equal to *AS*, then *CR* is positioned on the rowset that has all the rows in  $T_t$ .
- ii) Otherwise, *CR* is positioned on the rowset that has the first *AS* rows of  $T_t$ .

- 11) Let *NR* be the rowset on which *CR* is positioned. Let *ASP* and *RPP* be the values of the ARRAY\_STATUS\_POINTER and ROWS\_PROCESSED\_POINTER fields, respectively, in the header of the IRD of *S*.

- 12) If *RPP* is not a null pointer, then set the value of the host variable addressed by *RPP* to zero.

- 13) Let *RS* be the number of rows in *NR*. For *RN* ranging from 1 (one) to *RS*:

- a) Let *RNR* be the *RN*-th row of *NR*. Set *ROWS\_PROCESSED* to 0 (zero).

## Case:

- i) If an exception condition is raised during derivation of any <derived column> associated with *RNR* and *ASP* is not a null pointer, then set the *RN*-th element of *ASP* to 5 (indicating **Row error**). For all diagnostic records that result from the application of this rule, the ROW\_NUMBER field is set to *RN* and the COLUMN\_NUMBER field is set to the appropriate column number, if any.
- ii) Otherwise, the row *RNR* is fetched and *ROWS\_PROCESSED* is incremented by 1 (one).

## 14) Case:

- a) If *ROWS\_PROCESSED* is greater than 0 (zero), then:
  - i) Let *SS* be the select source associated with *S*.
  - ii) *NR* becomes the fetched rowset associated with *S*.
  - iii) Set *ROWS\_PROCESSED* to 0 (zero).
  - iv) The General Rules of Subclause 5.8, "Implicit FETCH USING clause", are applied with *SS*, *RS*, *ROWS\_PROCESSED*, and *S* as *SOURCE*, *ROWS*, *ROWS PROCESSED*, and *ALLOCATED STATEMENT*, respectively.

**6.21 Fetch**

Case:

- 1) If *ROWS\_PROCESSED* is greater than 0 (zero), *RN* is less than *AS*, and *ASP* is not a null pointer, then set the *RN*+1-th through *AS*-th elements of *ASP* to 3 (indicating **No row**). If *ROWS\_PROCESSED* is less than *RN*, then a completion condition is raised: *warning*.
  - 2) If *ROWS\_PROCESSED* is 0 (zero), then the values of all bound targets are implementation-dependent, and *CR* remains positioned on *NR*.
- b) Otherwise, the values of all bound targets are implementation-dependent and *CR* remains positioned on *NR*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.22 FetchScroll

### Function

Position a cursor on the specified row and retrieve values from that row.

### Definition

```
FetchScroll (
    StatementHandle      IN      INTEGER,
    FetchOrientation     IN      SMALLINT,
    FetchOffset         IN      INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) If there is no executed statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) If there is no open cursor associated with *S*, then an exception condition is raised: *invalid cursor state*; otherwise, let *CR* be the open cursor associated with *S* and let *T* be the table associated with the open cursor.
- 4) If *FetchOrientation* is not one of the code values in Table 24, “Codes used for fetch orientation”, then an exception condition is raised: *CLI-specific condition — invalid fetch orientation*.
- 5) Let *FO* be the value of *FetchOrientation*.
- 6) If the value of the CURSOR\_SCROLLABLE attribute of *S* is NONSCROLLABLE, and *FO* does not indicate NEXT, then an exception condition is raised: *CLI-specific condition — invalid fetch orientation*.
- 7) Let *ARD* be the current application row descriptor for *S* and let *N* be the value of the TOP\_LEVEL\_COUNT field of *ARD*.
- 8) For each item descriptor area in *ARD* whose LEVEL is 0 (zero) in the first *AD* item descriptor areas of *ARD*, and for all of their subordinate descriptor areas, refer to a <target specification> whose corresponding item descriptor area has a non-zero value of DATA\_POINTER as a *bound target* and refer to the corresponding <select list> column as a *bound column*.
- 9) Let *IDA* be the item descriptor area of *ARD* corresponding to the *i*-th bound target and let *TT* be the value of the TYPE field of *IDA*.
- 10) If *TT* indicates DEFAULT, then:
  - a) Let *IRD* be the implementation row descriptor associated with *S*.
  - b) Let *CT*, *P*, and *SC* be the values of the TYPE, PRECISION, and SCALE fields, respectively, for the item descriptor area of *IRD* corresponding to the *i*-th bound column.
  - c) The data type, precision, and scale of the <target specification> described by *IDA* are effectively set to *CT*, *P*, and *SC*, respectively, for the purposes of this fetch only.

- 11) Case:
- If  $FO$  indicates ABSOLUTE or RELATIVE, then let  $J$  be the value of FetchOffset.
  - If  $FO$  indicates NEXT or FIRST, then let  $J$  be +1.
  - If  $FO$  indicates PRIOR or LAST, then let  $J$  be -1.
- 12) Let  $R$  be the rowset on which  $CR$  is positioned and let  $AS$  be the value of the ARRAY SIZE field in the header of the ARD for  $S$ .
- 13) Let  $T_t$  be a table of the same degree as  $T$ .
- Case:
- If  $FO$  indicates ABSOLUTE, FIRST, or LAST, then let  $T_t$  contain all rows of  $T$ , preserving their order in  $T$ .
  - If  $FO$  indicates NEXT or indicates RELATIVE with a positive value of  $J$ , then:
    - If the table  $T$  identified by cursor  $CR$  is empty or if  $R$  contains the last row of  $T$ , then let  $T_t$  be a table of no rows.
    - If  $CR$  is positioned before the start of the result set, then let  $T_t$  contain all rows of  $T$ , preserving their order in  $T$ .
    - Otherwise, let  $T_t$  contain all rows of  $T$  after the first row of  $R$ , preserving their order in  $T$ .
  - If  $FO$  indicates PRIOR or indicates RELATIVE with a negative value of  $J$ , then:
    - If the table  $T$  identified by cursor  $CR$  is empty or if  $R$  contains the first row of  $T$ , then let  $T_t$  be a table of no rows.
    - If  $CR$  is positioned after the end of the result set, then let  $T_t$  contain all rows of  $T$ , preserving their order in  $T$ .
    - Otherwise, let  $T_t$  contain all rows of  $T$  before the first row of  $R$ , preserving their order in  $T$ .
  - If  $FO$  indicates RELATIVE with a zero value of  $J$ , then:
    - If  $R$  is not empty, then let  $T_t$  be a table comprising all the rows in  $R$ , preserving their order in  $R$ .
    - Otherwise, let  $T_t$  be an empty table.
- 14) Let  $N$  be the number of rows in  $T_t$ . If  $J$  is positive, then let  $K$  be  $J$ . If  $J$  is negative, then let  $K$  be  $N+J+1$ . If  $J$  is zero, then let  $K$  be 1 (one).
- 15) Case:
- If  $K$  is greater than 0 (zero), then  
Case:
    - If  $(K + AS - 1)$  is greater than  $N$ , then:

Case:

- 1) If  $J$  is less than 0 (zero), then

Case:

- A) If  $(K + AS - 1)$  is greater than the number of rows in  $T$ , then  $CR$  is positioned on the rowset that has all the rows in  $T$ .
- B) Otherwise,  $CR$  is positioned on the rowset whose first row is the  $K$ -th row of  $T$ ; that rowset has  $AS$  rows.

- 2) Otherwise, if  $K$  is less than  $N$ , then  $CR$  is positioned on the rowset that has all the rows in  $T_t$ .

- ii) Otherwise,  $CR$  is positioned on the rowset whose first row is the  $K$ -th row of  $T_i$ ; that rowset has  $AS$  rows.

- b) If  $K$  is less than 0 (zero), but the absolute value of  $K$  is less than or equal to  $AS$ , then

Case:

- i) If  $AS$  is greater than the number of rows in  $T$ , then  $CR$  is positioned on the rowset that has all the rows in  $T$ .

- ii) Otherwise,  $CR$  is positioned on the rowset that has the first  $AS$  rows in  $T$ .

- c) Otherwise, no SQL-data values are assigned and a completion condition is raised: *no data*.

Case:

- i) If  $FO$  indicates RELATIVE with  $J$  equal to zero, then the position of  $CR$  is unchanged.

- ii) If  $FO$  indicates NEXT, indicates ABSOLUTE or RELATIVE with  $K$  greater than  $N$ , or indicates LAST, then  $CR$  is positioned after the last row.

- iii) Otherwise,  $FO$  indicates PRIOR, FIRST, or ABSOLUTE or RELATIVE with  $K$  not greater than  $N$  and  $CR$  is positioned before the first row.

No further rules of this Subclause are applied.

- 16) Let  $NR$  be the rowset on which  $CR$  is positioned. Let  $ASP$  and  $RPP$  be the values of the ARRAY\_STATUS\_POINTER and ROWS\_PROCESSED\_POINTER fields respectively in the header of the IRD of  $S$ .

- 17) If  $RPP$  is not a null pointer, then set the value of the host variable addressed by  $RPP$  to 0 (zero).

- 18) Let  $RS$  be the number of rows in  $NR$ . For  $RN$  ranging from 1 (one) to  $RS$ :

- a) Let  $R$  be the  $RN$ -th row of  $NR$ . Set  $ROWS_PROCESSED$  to 0 (zero).

Case:

- i) If an exception condition is raised during derivation of any <derived column> associated with  $R$  and  $ASP$  is not a null pointer, then set the  $RN$ -th element of  $ASP$  to 5 (indicating **Row error**). For all diagnostic records that result from the application of this Rule, the ROW\_NUMBER field is set to  $RN$  and the COLUMN\_NUMBER field is set to the appropriate column number, if any.

ii) Otherwise the row *R* is fetched and *ROWS\_PROCESSED* is incremented by 1 (one).

19) Case:

a) If *ROWS\_PROCESSED* is greater than 0 (zero), then:

i) Let *SS* be the select source associated with *S*.

ii) *NR* becomes the fetched rowset associated with *S*.

iii) Set *ROWS\_PROCESSED* to 0 (zero).

iv) The general rules of Subclause 5.8, "Implicit FETCH USING clause", are applied with *SS*, *RS*, *ROWS\_PROCESSED*, and *S* as *SOURCE*, *ROWS*, *ROWS PROCESSED*, and *ALLOCATED STATEMENT*, respectively.

Case:

1) If *ROWS\_PROCESSED* is greater than 0 (zero), *RN* is less than *AS*, and *ASP* is not 0 (zero), then set the *RN+1*-th through *AS*-th elements of *ASP* to 3 (indicating **No row**). If *ROWS\_PROCESSED* is less than *RN*, then a completion condition is raised: *warning*.

2) If *ROWS\_PROCESSED* is 0 (zero), then the values of all bound targets are implementation-dependent and *CR* remains positioned on *NR*.

b) Otherwise, the values of all bound targets are implementation-dependent and *CR* remains positioned on *R*.

## 6.23 ForeignKeys

### Function

Return a result set that contains information about foreign keys either in or referencing a single specified table stored in the Information Schema of the connected data source. The result set contains information about either:

- The primary key of a single specified table together with the foreign keys in all other tables that reference that primary key.
- The foreign keys of a single specified table together with the primary or unique keys to which they refer.

### Definition

```
ForeignKeys (
    StatementHandle          IN          INTEGER,
    PKCatalogName          IN          CHARACTER(L1),
    NameLength1             IN          SMALLINT,
    PKSchemaName           IN          CHARACTER(L2),
    NameLength2             IN          SMALLINT,
    PKTableName            IN          CHARACTER(L3),
    NameLength3             IN          SMALLINT,
    FKCatalogName          IN          CHARACTER(L4),
    NameLength4             IN          SMALLINT,
    FKSchemaName           IN          CHARACTER(L5),
    NameLength5             IN          SMALLINT,
    FKTableName            IN          CHARACTER(L6),
    NameLength6             IN          SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ ,  $L3$ ,  $L4$ ,  $L5$ , and  $L6$  are determined by the values of NameLength1, NameLength2, NameLength3, NameLength4, NameLength5, and NameLength6 respectively and each of  $L1$ ,  $L2$ ,  $L3$ ,  $L4$ ,  $L5$ , and  $L6$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $FOREIGN\_KEYS\_QUERY$  be a table, with the definition:

```
CREATE TABLE FOREIGN_KEYS_QUERY (
    UK_TABLE_CAT           CHARACTER VARYING(128),
    UK_TABLE_SCHEM        CHARACTER VARYING(128) NOT NULL,
    UK_TABLE_NAME          CHARACTER VARYING(128) NOT NULL,
    UK_COLUMN_NAME         CHARACTER VARYING(128) NOT NULL,
```

## 6.23 ForeignKeys

|                   |                                  |
|-------------------|----------------------------------|
| FK_TABLE_CAT      | CHARACTER VARYING(128),          |
| FK_TABLE_SCHEM    | CHARACTER VARYING(128) NOT NULL, |
| FK_TABLE_NAME     | CHARACTER VARYING(128) NOT NULL, |
| FK_COLUMN_NAME    | CHARACTER VARYING(128) NOT NULL, |
| ORDINAL_POSITION  | SMALLINT NOT NULL,               |
| UPDATE_RULE       | SMALLINT,                        |
| DELETE_RULE       | SMALLINT,                        |
| FK_NAME           | CHARACTER VARYING(128),          |
| UK_NAME           | CHARACTER VARYING(128),          |
| DEFERABILITY      | SMALLINT,                        |
| UNIQUE_OR_PRIMARY | CHARACTER(7) )                   |

6) Let *PKN* and *FKN* be the value of PKTableName and FKTableName, respectively.

7) Case:

- a) If  $\text{CHAR\_LENGTH}(PKN) = 0$  (zero) and  $\text{CHAR\_LENGTH}(FKN) \neq 0$  (zero), then the result set returned describes all the foreign keys (if any) of the specified table, and describes the primary or unique keys to which they refer.
  - i) Let *FKS* represent the set of rows formed by a natural inner join on the values in the CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME columns between the rows in SSs Information Schema REFERENTIAL\_CONSTRAINTS view and the matching rows in SSs Information Schema TABLE\_CONSTRAINTS view.
  - ii) Let *UK* represent the row in SSs Information Schema TABLE\_CONSTRAINTS view that defines the primary or unique key referenced by an individual foreign key in *FKS*. This row is obtained by matching the values in the UNIQUE\_CONSTRAINT\_CATALOG, UNIQUE\_CONSTRAINT\_SCHEMA, and UNIQUE\_CONSTRAINT\_NAME columns in a row of *FKS* to the values in the CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME columns in TABLE\_CONSTRAINTS.
  - iii) Let *FK\_COLS* represent the set of rows in SSs Information Schema KEY\_COLUMN\_USAGE view that define the columns within an individual foreign key row in *FKS*.
  - iv) Let *FKS\_COLS* represent the set of rows in the combination of all *FK\_COLS* sets.
  - v) Let *UK\_COLS* represent the set of rows in SSs Information Schema KEY\_COLUMN\_USAGE view that define the columns within an individual *UK*.
  - vi) Let *UKS\_COLS* represent the set of rows in the combination of all *UK\_COLS* sets.
  - vii) Let *XKS\_COLS* represent the set of extended rows formed by a natural inner join on the values in the CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, CONSTRAINT\_NAME, and ORDINAL\_POSITION columns between the rows of *FKS\_COLS* and *UKS\_COLS*.

Let *FKS\_COLS\_NAME* be the name of each column of *FKS\_COLS* considered in turn; the names of the columns of *XKS\_COLS* originating from *FKS\_COLS* are respectively 'F\_' || *FKS\_COLS\_NAME*.

Let *UKS\_COLS\_NAME* be the name of each column of *UKS\_COLS* considered in turn; the names of the columns of *XKS\_COLS* originating from *UKS\_COLS* are respectively 'U\_' || *UKS\_COLS\_NAME*.

- viii) *FOREIGN\_KEYS\_QUERY* contains a row for each row in *XKS\_COLS* where:
- 1) Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
  - 2) Case:
    - A) If the value of *SUP* is 1 (one), then *FOREIGN\_KEYS\_QUERY* contains a row for each column of all the foreign keys within a specific table in *SS*'s Information Schema *TABLE\_CONSTRAINTS* view.
    - B) Otherwise, *FOREIGN\_KEYS\_QUERY* contains a row for each column of all the foreign keys within a specific table in *SS*'s Information Schema *TABLE\_CONSTRAINTS* view in accordance with implementation-defined authorization criteria.
- ix) For each row of *FOREIGN\_KEYS\_QUERY*:
- 1) If the implementation does not support catalog names, then *UK\_TABLE\_CAT* is set to the null value; otherwise, the value of *UK\_TABLE\_CAT* in *FOREIGN\_KEYS\_QUERY* is the value of the *U\_TABLE\_CATALOG* column in *XKS\_COLS*.
  - 2) The value of *UK\_TABLE\_SCHEM* in *FOREIGN\_KEYS\_QUERY* is the value of the *U\_TABLE\_SCHEMA* column in *XKS\_COLS*.
  - 3) The value of *UK\_TABLE\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *U\_TABLE\_NAME* column in *XKS\_COLS*.
  - 4) The value of *UK\_COLUMN\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *U\_COLUMN\_NAME* column in *XKS\_COLS*.
  - 5) If the implementation does not support catalog names, then *FK\_TABLE\_CAT* is set to the null value; otherwise, the value of *FK\_TABLE\_CAT* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_CATALOG* column in *XKS\_COLS*.
  - 6) The value of *FK\_TABLE\_SCHEM* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_SCHEMA* column in *XKS\_COLS*.
  - 7) The value of *FK\_TABLE\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_NAME* column in *XKS\_COLS*.
  - 8) The value of *FK\_COLUMN\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_COLUMN\_NAME* column in *XKS\_COLS*.
  - 9) The value of *ORDINAL\_POSITION* in *FOREIGN\_KEYS\_QUERY* is the value of the *ORDINAL\_POSITION* column in *XKS\_COLS*.
  - 10) The value of *UPDATE\_RULE* in *FOREIGN\_KEYS\_QUERY* is determined by the value of the *UPDATE\_RULE* column in *XKS\_COLS* as follows:
    - A) Let *UR* be the value in the *UPDATE\_RULE* column.
    - B) If *UR* is 'CASCADE', then the value of *UPDATE\_RULE* is the code for CASCADE in Table 26, "Miscellaneous codes used in CLI".

## 6.23 ForeignKeys

- C) If *UR* is 'RESTRICT', then the value of *UPDATE\_RULE* is the code for RESTRICT in Table 26, "Miscellaneous codes used in CLI".
- D) If *UR* is 'SET NULL', then the value of *UPDATE\_RULE* is the code for SET NULL in Table 26, "Miscellaneous codes used in CLI".
- E) If *UR* is 'NO ACTION', then the value of *UPDATE\_RULE* is the code for NO ACTION in Table 26, "Miscellaneous codes used in CLI".
- F) If *UR* is 'SET DEFAULT', then the value of *UPDATE\_RULE* is the code for SET DEFAULT in Table 26, "Miscellaneous codes used in CLI".
- 11) The value of *DELETE\_RULE* in *FOREIGN\_KEYS\_QUERY* is determined by the value of the *DELETE\_RULE* column in *XKS\_COLS* as follows:
- A) Let *DR* be the value in the *DELETE\_RULE* column.
- B) If *DR* is 'CASCADE', then the value of *DELETE\_RULE* is the code for CASCADE in Table 26, "Miscellaneous codes used in CLI".
- C) If *DR* is 'RESTRICT', then the value of *DELETE\_RULE* is the code for RESTRICT in Table 26, "Miscellaneous codes used in CLI".
- D) If *DR* is 'SET NULL', then the value of *DELETE\_RULE* is the code for SET NULL in Table 26, "Miscellaneous codes used in CLI".
- E) If *DR* is 'NO ACTION', then the value of *DELETE\_RULE* is the code for NO ACTION in Table 26, "Miscellaneous codes used in CLI".
- F) If *DR* is 'SET DEFAULT', then the value of *DELETE\_RULE* is the code for SET DEFAULT in Table 26, "Miscellaneous codes used in CLI".
- 12) The value of *FK\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *CONSTRAINT\_NAME* column in *XKS\_COLS*.
- 13) The value of *UK\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *UNIQUE\_CONSTRAINT\_NAME* column in *XKS\_COLS*.
- 14) If there are no implementation-defined mechanisms for setting the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* to the value of the code for INITIALLY DEFERRED or to the value of the code for INITIALLY IMMEDIATE in Table 26, "Miscellaneous codes used in CLI", then the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* is the code for NOT DEFERRABLE in Table 26, "Miscellaneous codes used in CLI"; otherwise, the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* can be the code for INITIALLY DEFERRED, the value of the code for INITIALLY IMMEDIATE, or the code for NOT DEFERRABLE in Table 26, "Miscellaneous codes used in CLI".
- 15) The value of *UNIQUE\_OR\_PRIMARY* in *FOREIGN\_KEYS\_QUERY* is 'UNIQUE' if the foreign key references a UNIQUE key and 'PRIMARY' if the foreign key references a primary key.
- x) Let *NL1*, *NL2*, and *NL3* be the values of *NameLength4*, *NameLength5*, and *NameLength6*, respectively.

- xi) Let *CATVAL*, *SCHVAL*, and *TBLVAL* be the values of FKCatalogName, FKSchemaName, and FKTableName, respectively.
- xii) If the METADATA ID attribute of *S* is TRUE, then:
- 1) If FKCatalogName is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", *Y*, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - 2) If FKSchemaName is a null pointer or if FKTableName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- xiii) If FKCatalogName is a null pointer, then *NL1* is set to zero. If FKSchemaName is a null pointer, then *NL2* is set to zero. If FKTableName is a null pointer, then *NL3* is set to zero.
- xiv) Case:
- 1) If *NL1* is not negative, then let *L* be *NL1*.
  - 2) If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of FKCatalogName that precede the implementation-defined null character that terminates a C character string.
  - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- Let *CATVAL* be the first *L* octets of FKCatalogName.
- xv) Case:
- 1) If *NL2* is not negative, then let *L* be *NL2*.
  - 2) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of FKSchemaName that precede the implementation-defined null character that terminates a C character string.
  - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- Let *SCHVAL* be the first *L* octets of FKSchemaName.
- xvi) Case:
- 1) If *NL3* is not negative, then let *L* be *NL3*.
  - 2) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of FKTableName that precede the implementation-defined null character that terminates a C character string.
  - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- Let *TBLVAL* be the first *L* octets of FKTableName.

xvii) Case:

1) If the METADATA ID attribute of *S* is TRUE, then:

A) Case:

I) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.

II) Otherwise,

Case:

1) If `SUBSTRING(TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(CATVAL) FROM CHAR_LENGTH(TRIM(CATVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(CATVAL) FROM 2
          FOR CHAR_LENGTH(TRIM(CATVAL)) - 2)
```

and let *CATSTR* be the character string:

```
FK_TABLE_CAT = 'TEMPSTR' AND
```

2) Otherwise, let *CATSTR* be the character string:

```
UPPER(FK_TABLE_CAT) = UPPER('CATVAL') AND
```

B) Case:

I) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

II) Otherwise,

Case:

1) If `SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(SCHVAL) FROM CHAR_LENGTH(TRIM(SCHVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(SCHVAL) FROM 2
          FOR CHAR_LENGTH(TRIM(SCHVAL)) - 2)
```

and let *SCHSTR* be the character string:

```
FK_TABLE_SCHEM = 'TEMPSTR' AND
```

2) Otherwise, let *SCHSTR* be the character string:

```
UPPER(FK_TABLE_SCHEM) = UPPER('SCHVAL') AND
```

C) Case:

I) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

II) Otherwise,

Case:

- 1) If `SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(TBLVAL) FROM CHAR_LENGTH(TRIM(TBLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(TBLVAL) FROM 2
          FOR CHAR_LENGTH(TRIM(TBLVAL)) - 2)
```

and let *TBLSTR* be the character string:

```
FK_TABLE_NAME = 'TEMPSTR' AND
```

- 2) Otherwise, let *TBLSTR* be the character string:

```
UPPER(FK_TABLE_NAME) = UPPER('TBLVAL') AND
```

- 2) Otherwise:

- A) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
FK_TABLE_CAT = 'CATVAL' AND
```

- B) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
FK_TABLE_SCHEM = 'SCHVAL' AND
```

- C) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string. Otherwise, let *TBLSTR* be the character string:

```
FK_TABLE_NAME = 'TBLVAL' AND
```

- xviii) Let *PRED* be the result of evaluating:

```
CATSTR || ',' || SCHSTR || ',' || TBLSTR || ',' || 1=1
```

- xix) Let *STMT* be the character string:

```
SELECT *
FROM FOREIGN_KEYS_QUERY
WHERE PRED
ORDER BY FK_TABLE_CAT, FK_TABLE_SCHEM, FK_TABLE_NAME, ORDINAL_POSITION
```

- xx) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

- b) If `CHAR_LENGTH(PKN) ≠ 0` (zero) and `CHAR_LENGTH(FKN) = 0` (zero), then the result set returned contains a description of the primary key (if any) of the specified table together with the descriptions of foreign keys in all other tables that reference that primary key.

- i) Let *PKS* represent the set of rows in *SS*'s Information Schema `TABLE_CONSTRAINTS` view where the value of `CONSTRAINT_TYPE` is 'PRIMARY KEY'.

## 6.23 ForeignKeys

- ii) Let  $X$  represent the set of rows formed by a natural inner join on the values in the `CONSTRAINT_CATALOG`, `CONSTRAINT_SCHEMA`, and `CONSTRAINT_NAME` columns between the rows in *SS*'s Information Schema `REFERENTIAL_CONSTRAINTS` view and the matching rows in *SS*'s Information Schema `TABLE_CONSTRAINTS` view.
- iii) Let  $FKS$  represent the rows defining the foreign keys that reference an individual primary key in  $PKS$ . These rows are obtained by matching the values of `CONSTRAINT_CATALOG`, `CONSTRAINT_SCHEMA`, and `CONSTRAINT_NAME` columns in a row of  $PKS$  to the values in the `UNIQUE_CONSTRAINT_CATALOG`, `UNIQUE_CONSTRAINT_SCHEMA`, and `UNIQUE_CONSTRAINT_NAME` columns in  $X$ .
- iv) Let  $FKSS$  represent the set of rows in the combination of all  $FKS$  sets.
- v) Let  $PK\_COLS$  represent the set of rows in *SS*'s Information Schema `KEY_COLUMN_USAGE` view that define the columns within an individual primary key row in  $PKS$ .
- vi) Let  $PKS\_COLS$  represent the set of rows in the combination of all  $PK\_COLS$  sets.
- vii) Let  $FK\_COLS$  represent the set of rows in *SS*'s Information Schema `KEY_COLUMN_USAGE` view that define the columns within an individual foreign key in  $FKSS$ .
- viii) Let  $FKS\_COLS$  represent the set of rows in the combination of all  $FK\_COLS$  sets.
- ix) Let  $XKS\_COLS$  represent the set of extended rows formed by a natural inner join on the values in the `CONSTRAINT_CATALOG`, `CONSTRAINT_SCHEMA`, `CONSTRAINT_NAME`, and `ORDINAL_POSITION` columns between the rows of  $PKS\_COLS$  and  $FKS\_COLS$ .

Let  $PKS\_COLS\_NAME$  be the name of each column of  $PKS\_COLS$  considered in turn; the names of the columns of  $XKS\_COLS$  originating from  $PKS\_COLS$  are respectively 'P\_' ||  $PKS\_COLS\_NAME$ .

Let  $FKS\_COLS\_NAME$  be the name of each column of  $FKS\_COLS$  considered in turn; the names of the columns of  $XKS\_COLS$  originating from  $FKS\_COLS$  are respectively 'F\_' ||  $FKS\_COLS\_NAME$ .

- x) `FOREIGN_KEYS_QUERY` contains a row for each row in  $XKS\_COLS$  where:
  - 1) Let  $SUP$  be the value of Supported that is returned by the execution of `GetFeatureInfo` with `FeatureType = 'FEATURE'` and `FeatureId = 'C041'` (corresponding to the feature "Information Schema metadata constrained by privileges").
  - 2) Case:
    - A) If the value of  $SUP$  is 1 (one), then `FOREIGN_KEYS_QUERY` contains one or more rows describing the foreign keys that reference the primary key of a specific table in *SS*'s information schema `TABLE_CONSTRAINTS` view.
    - B) Otherwise, `FOREIGN_KEYS_QUERY` contains a row for each column of all the foreign keys that reference the primary key of a specific table in *SS*'s information schema `TABLE_CONSTRAINTS` view in accordance with implementation-defined authorization criteria.

- xi) For each row of *FOREIGN\_KEYS\_QUERY*:
- 1) If the implementation does not support catalog names, then *UK\_TABLE\_CAT* is set to the null value; otherwise, the value of *UK\_TABLE\_CAT* in *FOREIGN\_KEYS\_QUERY* is the value of the *P\_TABLE\_CATALOG* column in *XKS*.
  - 2) The value of *UK\_TABLE\_SCHEM* in *FOREIGN\_KEYS\_QUERY* is the value of the *P\_TABLE\_SCHEMA* column in *XKS*.
  - 3) The value of *UK\_TABLE\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *P\_TABLE\_NAME* column in *XKS*.
  - 4) The value of *UK\_COLUMN\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *P\_COLUMN\_NAME* column in *XKS*.
  - 5) If the implementation does not support catalog names, then *UK\_TABLE\_CAT* is set to the null value; otherwise, the value of *UK\_TABLE\_CAT* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_CATALOG* column in *XKS*.
  - 6) The value of *FK\_TABLE\_SCHEM* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_SCHEMA* column in *XKS*.
  - 7) The value of *FK\_TABLE\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_TABLE\_NAME* column in *XKS*.
  - 8) The value of *FK\_COLUMN\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *F\_COLUMN\_NAME* column in *XKS*.
  - 9) The value of *ORDINAL\_POSITION* in *FOREIGN\_KEYS\_QUERY* is the value of the *ORDINAL\_POSITION* column in *XKS*.
  - 10) The value of *UPDATE\_RULE* in *FOREIGN\_KEYS\_QUERY* is determined by the value of the *UPDATE\_RULE* column in *XKS* as follows.
    - A) Let *UR* be the value in the *UPDATE\_RULE* column.
    - B) If *UR* is 'CASCADE', then the value of *UPDATE\_RULE* is the code for CASCADE in Table 26, "Miscellaneous codes used in CLI".
    - C) If *UR* is 'RESTRICT', then the value of *UPDATE\_RULE* is the code for RESTRICT in Table 26, "Miscellaneous codes used in CLI".
    - D) If *UR* is 'SET NULL', then the value of *UPDATE\_RULE* is the code for SET NULL in Table 26, "Miscellaneous codes used in CLI".
    - E) If *UR* is 'NO ACTION', then the value of *UPDATE\_RULE* is the code for NO ACTION in Table 26, "Miscellaneous codes used in CLI".
    - F) If *UR* is 'SET DEFAULT', then the value of *UPDATE\_RULE* is the code for SET DEFAULT in Table 26, "Miscellaneous codes used in CLI".
  - 11) The value of *DELETE\_RULE* in *FOREIGN\_KEYS\_QUERY* is determined by the value of the *DELETE\_RULE* column in *XKS*.
    - A) Let *DR* be the value in the *DELETE\_RULE* column.

## 6.23 ForeignKeys

- B) If *DR* is 'CASCADE', then the value of *DELETE\_RULE* is the code for CASCADE in Table 26, "Miscellaneous codes used in CLI".
- C) If *DR* is 'RESTRICT', then the value of *DELETE\_RULE* is the code for RESTRICT in Table 26, "Miscellaneous codes used in CLI".
- D) If *DR* is 'SET NULL', then the value of *DELETE\_RULE* is the code for SET NULL in Table 26, "Miscellaneous codes used in CLI".
- E) If *DR* is 'NO ACTION', then the value of *DELETE\_RULE* is the code for NO ACTION in Table 26, "Miscellaneous codes used in CLI".
- F) If *DR* is 'SET DEFAULT', then the value of *DELETE\_RULE* is the code for SET DEFAULT in Table 26, "Miscellaneous codes used in CLI".
- 12) The value of *FK\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *CONSTRAINT\_NAME* column in *XKS*.
- 13) The value of *UK\_NAME* in *FOREIGN\_KEYS\_QUERY* is the value of the *UNIQUE\_CONSTRAINT\_NAME* column in *XKS*.
- 14) If there are no implementation-defined mechanisms for setting the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* to the value of the code for INITIALLY DEFERRED or to the value of the code for INITIALLY IMMEDIATE in Table 26, "Miscellaneous codes used in CLI", then the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* is the code for NOT DEFERRABLE in Table 26, "Miscellaneous codes used in CLI"; otherwise, the value of *DEFERABILITY* in *FOREIGN\_KEYS\_QUERY* can be the code for INITIALLY DEFERRED, the value of the code for INITIALLY IMMEDIATE, or the code for NOT DEFERRABLE in Table 26, "Miscellaneous codes used in CLI".
- 15) The value of *UNIQUE\_OR\_PRIMARY* in *FOREIGN\_KEYS\_QUERY* is 'PRIMARY'.
- xii) Let *NL1*, *NL2*, and *NL3* be the values of *NameLength1*, *NameLength2*, and *NameLength3*, respectively.
- xiii) Let *CATVAL*, *SCHVAL*, and *TBLVAL* be the values of *PKCatalogName*, *PKSchemaName*, and *PKTableName*, respectively.
- xiv) If the METADATA ID attribute of *S* is TRUE, then:
- 1) If *PKCatalogName* is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", *Y*, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - 2) If *PKSchemaName* is a null pointer or if *PKTableName* is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- xv) If *PKCatalogName* is a null pointer, then *NL1* is set to zero. If *PKSchemaName* is a null pointer, then *NL2* is set to zero. If *PKTableName* is a null pointer, then *NL3* is set to zero.
- xvi) Case:
- 1) If *NL1* is not negative, then let *L* be *NL1*.

- 2) If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of PKCatalogName that precede the implementation-defined null character that terminates a C character string.
- 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *CATVAL* be the first *L* octets of PKCatalogName.

xvii) Case:

- 1) If *NL2* is not negative, then let *L* be *NL2*.
- 2) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of PKSchemaName that precede the implementation-defined null character that terminates a C character string.
- 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *SCHVAL* be the first *L* octets of PKSchemaName.

xviii) Case:

- 1) If *NL3* is not negative, then let *L* be *NL3*.
- 2) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of PKTableName that precede the implementation-defined null character that terminates a C character string.
- 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TBLVAL* be the first *L* octets of PKTableName.

xix) Case:

- 1) If the METADATA ID attribute of *S* is TRUE, then:

A) Case:

- I) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
- II) Otherwise,

Case:

- 1) If `SUBSTRING( TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING( TRIM(CATVAL) FROM CHAR_LENGTH( TRIM(CATVAL) ) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(CATVAL) FROM 2
            FOR CHAR_LENGTH ( TRIM(CATVAL) ) - 2 )
```

and let *CATSTR* be the character string:

```
FK_TABLE_CAT = 'TEMPSTR' AND
```

2) Otherwise, let *CATSTR* be the character string:

```
UPPER(FK_TABLE_CAT) = UPPER('CATVAL') AND
```

B) Case:

I) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

II) Otherwise,

Case:

1) If `SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(SCHVAL) FROM CHAR_LENGTH(TRIM(SCHVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(SCHVAL) FROM 2  
FOR CHAR_LENGTH ( TRIM(SCHVAL) ) - 2 )
```

and let *SCHSTR* be the character string:

```
FK_TABLE_SCHEM = 'TEMPSTR' AND
```

2) Otherwise, let *SCHSTR* be the character string:

```
UPPER(FK_TABLE_SCHEM) = UPPER('SCHVAL') AND
```

C) Case:

I) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

II) Otherwise,

Case:

1) If `SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(TBLVAL) FROM CHAR_LENGTH(TRIM(TBLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(TBLVAL) FROM 2  
FOR CHAR_LENGTH ( TRIM(TBLVAL) ) - 2 )
```

and let *TBLSTR* be the character string:

```
FK_TABLE_NAME = 'TEMPSTR' AND
```

2) Otherwise, let *TBLSTR* be the character string:

```
UPPER(FK_TABLE_NAME) = UPPER('TBLVAL') AND
```

2) Otherwise:

A) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
FK_TABLE_CAT = 'CATVAL' AND
```

- B) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
FK_TABLE_SCHEM = 'SCHVAL' AND
```

- C) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string. Otherwise, let *TBLSTR* be the character string:

```
FK_TABLE_NAME = 'TBLVAL' AND
```

- xx) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || 1=1
```

- xxi) Let *STMT* be the character string:

```
SELECT *
FROM FOREIGN_KEYS_QUERY
WHERE PRED
ORDER BY FK_TABLE_CAT, FK_TABLE_SCHEM, FK_TABLE_NAME, ORDINAL_POSITION
```

- xxii) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

- c) If  $\text{CHAR\_LENGTH}(PKN) \neq 0$  (zero) and  $\text{CHAR\_LENGTH}(FKN) \neq 0$  (zero), then the result of the routine is implementation-defined.

## 6.24 FreeConnect

### Function

Deallocate an SQL-connection.

### Definition

```
FreeConnect (
    ConnectionHandle          IN    INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *CH* be the value of ConnectionHandle.
- 2) FreeHandle is implicitly invoked with HandleType indicating CONNECTION HANDLE and with *CH* as the value of Handle.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.25 FreeEnv

### Function

Deallocate an SQL-environment.

### Definition

```
FreeEnv (
    EnvironmentHandle          IN    INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *EH* be the value of EnvironmentHandle.
- 2) FreeHandle is implicitly invoked with HandleType indicating ENVIRONMENT HANDLE and with *EH* as the value of Handle.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.26 FreeHandle

### Function

Free a resource.

### Definition

```
FreeHandle (  
    HandleType      IN    SMALLINT,  
    Handle          IN    INTEGER )  
RETURNS SMALLINT
```

### General Rules

- 1) Let *HT* be the value of HandleType and let *H* be the value of Handle.
- 2) If *HT* is not one of the code values in Table 13, “Codes used for handle types”, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If *HT* indicates ENVIRONMENT HANDLE, then:
    - i) If *H* does not identify an allocated SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Let *E* be the allocated SQL-environment identified by *H*.
    - iii) The diagnostics area associated with *E* is emptied.
    - iv) If an allocated SQL-connection is associated with *E*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
    - v) *E* is deallocated and all its resources are freed.
  - b) If *HT* indicates CONNECTION HANDLE, then:
    - i) If *H* does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Let *C* be the allocated SQL-connection identified by *H*.
    - iii) The diagnostics area associated with *C* is emptied.
    - iv) If an established SQL-connection is associated with *C*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
    - v) *C* is deallocated and all its resources are freed.
  - c) If *HT* indicates STATEMENT HANDLE, then:
    - i) If *H* does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Let *S* be the allocated SQL-statement identified by *H*.

- iii) The diagnostics area associated with *S* is emptied.
  - iv) Let *C* be the allocated SQL-connection with which *S* is associated and let *EC* be the established SQL-connection associated with *C*.
  - v) If *EC* is not the current connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant connection.
  - vi) If there is a deferred parameter number associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - vii) If there is an open cursor associated with *S*, then:
    - 1) The open cursor associated with *S* is placed in the closed state and its copy of the select source is destroyed.
    - 2) Any fetched row associated with *S* is removed from association with *S*.
  - viii) The automatically allocated CLI descriptor areas associated with *S* are deallocated and all their resources are freed.
  - ix) *S* is deallocated and all its resources are freed.
- d) If *HT* indicates DESCRIPTOR HANDLE, then:
- i) If *H* does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - ii) Let *D* be the allocated CLI descriptor area identified by *H*.
  - iii) The diagnostics area associated with *D* is emptied.
  - iv) Let *C* be the allocated SQL-connection with which *D* is associated and let *EC* be the established SQL-connection associated with *C*.
  - v) If *EC* is not the current connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant connection.
  - vi) The General Rules of Subclause 5.11, “Deferred parameter check”, are applied to *D* as the DESCRIPTOR AREA.
  - vii) Let *AT* be the value of the ALLOC\_TYPE field of *D*.
  - viii) If *AT* indicates AUTOMATIC, then an exception condition is raised: *CLI-specific condition — invalid use of automatically-allocated descriptor handle*.
  - ix) Let *L1* be a list of allocated SQL-statements associated with *C* for which *D* is the current application row descriptor. For each allocated SQL-statement *S* in *L1*, the automatically-allocated application row descriptor associated with *S* becomes the current application row descriptor for *S*.
  - x) Let *L2* be a list of allocated SQL-statements associated with *C* for which *D* is the current application parameter descriptor. For each allocated SQL-statement *S* in *L2*, the automatically-allocated application parameter descriptor associated with *S* becomes the current application parameter descriptor for *S*.

- xi) *D* is deallocated and all its resources are freed.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.27 FreeStmt

### Function

Deallocate an SQL-statement.

### Definition

```
FreeStmt (
    StatementHandle      IN    INTEGER ,
    Option               IN    SMALLINT )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *SH* be the value of StatementHandle and let *S* be the allocated SQL-statement identified by *SH*.
- 2) Let *OPT* be the value of Option.
- 3) If *OPT* is not one of the codes in Table 18, “Codes used for FreeStmt options”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) Let *ARD* be the current application row descriptor for *S* and let *RC* be the value of the COUNT field of *ARD*.
- 5) Let *APD* be the current application parameter descriptor for *S* and let *PC* be the value of the COUNT field of *APD*.
- 6) Case:
  - a) If *OPT* indicates CLOSE CURSOR and there is an open cursor associated with *S*, then:
    - i) The open cursor associated with *S* is placed in the closed state and its copy of the select source is destroyed.
    - ii) Any fetched row associated with *S* is removed from association with *S*.
  - b) If *OPT* indicates FREE HANDLE, then FreeHandle is implicitly invoked with HandleType indicating STATEMENT HANDLE and with *SH* as the value of Handle.
  - c) If *OPT* indicates UNBIND COLUMNS, then for each of the first *RC* item descriptor areas of *ARD*, the value of the DATA\_POINTER field is set to zero.
  - d) If *OPT* indicates UNBIND PARAMETERS, then for each of the first *PC* item descriptor areas of *APD*, the value of the DATA\_POINTER field is set to zero.
  - e) If *OPT* indicates REALLOCATE, then the following objects associated with *S* are destroyed:
    - i) Any prepared statement.
    - ii) Any cursor.
    - iii) Any select source.

**6.27 FreeStmt**

iv) Any executed statement.

and the original automatically allocated descriptors are associated with the allocated SQL-statement with their original default values as described in the General Rules of Subclause 6.3, "AllocHandle".

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.28 GetConnectAttr

### Function

Get the value of an SQL-connection attribute.

### Definition

```

GetConnectAttr (
    ConnectionHandle    IN        INTEGER,
    Attribute           IN        INTEGER,
    Value              OUT       ANY,
    BufferLength        IN        INTEGER,
    StringLength       OUT       INTEGER )
RETURNS SMALLINT

```

### General Rules

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Let *A* be the value of Attribute.
- 3) If *A* is not one of the code values in Table 16, “Codes used for connection attributes”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) If *A* indicates POPULATE IPD, then:
  - a) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise:
    - i) If POPULATE IPD for *C* is true, then Value is set to 1 (one).
    - ii) If POPULATE IPD for *C* is false, then Value is set to 0 (zero).
- 5) If *A* indicates SAVEPOINT NAME, then:
  - a) Let *BL* be the value of BufferLength.
  - b) Let *AV* be the value of the SAVEPOINT NAME connection attribute.
  - c) The General Rules of Subclause 5.9, “Character string retrieval”, are applied with Value, *AV*, *BL*, and StringLength as TARGET, VALUE, TARGET OCTET LENGTH, and RETURNED OCTET LENGTH, respectively.

**6.28 GetConnectAttr**

6) If *A* indicates SAVEPOINT NUMBER, then Value is set to the value of the SAVEPOINT NUMBER connection attribute.

7) If *A* specifies an implementation-defined connection attribute, then

Case:

a) If the data type for the connection attribute is specified in Table 19, "Data types of attributes", as INTEGER, then Value is set to the value of the implementation-defined connection attribute.

b) Otherwise:

i) Let *BL* be the value of BufferLength.

ii) Let *AV* be the value of the implementation-defined connection attribute.

iii) The General Rules of Subclause 5.9, "Character string retrieval", are applied with Value, *AV*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

## 6.29 GetCursorName

### Function

Get a cursor name.

### Definition

```

GetCursorName (
    StatementHandle IN    INTEGER,
    CursorName      OUT  CHARACTER(L),
    BufferLength     IN    SMALLINT,
    NameLength      OUT  SMALLINT )
RETURNS SMALLINT

```

where  $L$  is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) Case:
  - a) If there is no cursor name associated with  $S$ , then a unique implementation-dependent name that has the prefix 'SQLCUR' or the prefix 'SQL\_CUR' becomes the cursor name associated with  $S$ ; let  $CN$  be that associated cursor name.
  - b) Otherwise, let  $CN$  be the cursor name associated with  $S$ .
- 3) Let  $BL$  be the value of BufferLength.
- 4) The General Rules of Subclause 5.9, "Character string retrieval", are applied with CursorName,  $CN$ ,  $BL$ , and NameLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

**6.30 GetData****6.30 GetData****Function**

Retrieve a column value.

**Definition**

```
GetData (
    StatementHandle      IN      INTEGER,
    ColumnNumber         IN      SMALLINT,
    TargetType           IN      SMALLINT,
    TargetValue          OUT     ANY,
    BufferLength          IN      INTEGER,
    StrLen_or_Ind        OUT     INTEGER )
RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) Case:
  - a) If there is no fetched rowset associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) If the fetched rowset associated with *S* is empty, then a completion condition is raised: *no data*, *TargetValue* and *StrLen\_or\_Ind* are set to implementation-dependent values, and no further rules of this Subclause are applied.
  - c) Otherwise, let *R* be the fetched rowset associated with *S*.
- 3) Let *ARD* be the current application row descriptor for *S* and let *N* be the value of the *TOP\_LEVEL\_COUNT* field of *ARD*.
- 4) Let *AS* be the value of the *ARRAY\_SIZE* field in the header of *ARD*. Let *P* be the value of the attribute *CURRENT OF POSITION* of *S*.
- 5) If *P* is greater than *AS*, the *P*-th row in *R* has not been fetched, or the value of the *CURSOR SCROLLABLE* attribute of *S* is *NONSCROLLABLE* and *AS* is greater than 1 (one), then an exception condition is raised: *CLI-specific condition — invalid cursor position*.
- 6) Let *FR* be the *P*-th row of *R*.
- 7) Let *D* be the degree of the table defined by the select source associated with *S*.
- 8) If *N* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
- 9) Let *CN* be the value of *ColumnNumber*.
- 10) If *CN* is less than 1 (one) or greater than *D*, then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.

- 11) If DATA\_POINTER is non-zero for at least one of the first  $N$  item descriptor areas of  $ARD$  for which LEVEL is 0 (zero) and the value of TYPE is neither ROW nor ARRAY, then let  $BCN$  be the column number associated with such an item descriptor area and let  $HBCN$  be the value of  $MAX(BCN)$ . Otherwise, let  $HBCN$  be zero.
- 12) Let  $IDA$  be the item descriptor area of  $ARD$  specified by  $CN$ . If the value of TYPE in  $IDA$  is either ROW or ARRAY, or if the LEVEL of  $IDA$  is greater than 0 (zero), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 29 – GetData cannot be called to retrieve the data corresponding to a subordinate descriptor record such as, for example, from an individual field of a ROW type.
- 13) If  $CN$  is not greater than  $HBCN$ , then  
Case:  
a) If the DATA\_POINTER field of  $IDA$  is not zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
b) If the DATA\_POINTER field of  $IDA$  is zero, then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 30 – This implementation-defined feature determines whether columns before the highest bound column can be accessed by GetData.
- 14) If there is a fetched column number associated with  $FR$ , then let  $FCN$  be that column number; otherwise, let  $FCN$  be zero.  
NOTE 31 – “fetched column number” is the ColumnNumber value used with the previous invocation (if any) of the GetData routine with  $FR$ . See the General Rules later in this Subclause where this value is set.
- 15) Case:  
a) If  $FCN$  is greater than zero and  $CN$  is not greater than  $FCN$ , then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 32 – This implementation-defined feature determines whether GetData can only access columns in ascending column number order.  
b) If  $FCN$  is less than zero, then:  
i) Let  $AFCN$  be the absolute value of  $FCN$ .  
ii) Case:  
1) If  $CN$  is less than  $AFCN$ , then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 33 – This implementation-defined feature determines whether GetData can only access columns in ascending column number order.  
2) If  $CN$  is greater than  $AFCN$ , then let  $FCN$  be  $AFCN$ .
- 16) Let  $T$  be the value of TargetType.
- 17) Let  $HL$  be the standard programming language of the invoking host program. Let *operative data type correspondence table* be the data type correspondence table for  $HL$  as specified in Subclause 5.15, “Data type correspondences”. Refer to the two columns of the operative data type correspondence table as the *SQL data type column* and the *host data type column*.

**6.30 GetData**

- 18) If either of the following is true, then an exception condition is raised: *CLI-specific condition — invalid data type in application descriptor*.
- T* indicates neither DEFAULT nor ARD TYPE and is not one of the code values in Table 8, “Codes used for application data types in SQL/CLI”.
  - T* is one of the code values in Table 8, “Codes used for application data types in SQL/CLI”, but the row that contains the corresponding SQL data type in the SQL data type column of the operative data type correspondence table contains 'None' in the host data type column.
- 19) If *T* does not indicate ARD TYPE, then the data type of the <target specification> described by *IDA* is set to *T*.
- 20) Let *IRD* be the implementation row descriptor associated with *S*.
- 21) If the value of the TYPE field of *IDA* indicates DEFAULT, then:
- Let *CT*, *P*, and *SC* be the values of the TYPE, PRECISION, and SCALE fields, respectively, for the *CN*-th item descriptor area of *IRD* for which LEVEL is 0 (zero).
  - The data type, precision, and scale of the <target specification> described by *IDA* are set to *CT*, *P*, and *SC*, respectively, for the purposes of this GetData invocation only.
- 22) If *IDA* is not valid as specified in Subclause 5.13, “Description of CLI item descriptor areas”, then an exception condition is raised: *dynamic SQL error — using clause does not match target specifications*.
- 23) Let *TT* be the value of the TYPE field of *IDA*.
- 24) Case:
- If *TT* indicates CHARACTER, then:
    - Let *UT* be the code value corresponding to CHARACTER VARYING as specified in Table 7, “Codes used for implementation data types in SQL/CLI”.
    - Let *CL* be the implementation-defined maximum length for a CHARACTER VARYING data type.
  - Otherwise, let *UT* be *TT* and let *CL* be zero.
- 25) Case:
- If *FCN* is less than zero, then
 

Case:

    - If *TT* does not indicate CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, then *AFCN* becomes the fetched column number associated with the fetched row associated with *S* and an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
    - Otherwise, let *FL*, *DV*, and *DL* be the fetched length, data value and data length, respectively, associated with *FCN* and let *TV* be the result of the <string value function>:

SUBSTRING#( DV FROM#(FL+1) )

## b) Otherwise:

- i) Let *FL* be zero.
- ii) Let *SDT* be the effective data type of the *CN*-th <select list> column as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the *CN*-th item descriptor area of *IRD*. Let *SV* be the value of the <select list> column, with data type *SDT*.
- iii) If TYPE indicates USER-DEFINED TYPE, then let the most specific type of the *CN*-th <select list> column whose value is *SV* be represented by the values of the SPECIFIC\_TYPE\_CATALOG, SPECIFIC\_TYPE\_SCHEMA, and SPECIFIC\_TYPE\_NAME fields in the corresponding item descriptor area of *IRD*.
- iv) Let *TDT* be the effective data type of the *CN*-th <target specification> as represented by the type *UT*, the length value *CL*, and the values of the PRECISION, SCALE, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields of *IDA*.
- v) Let *LTDT* be the data type on the last retrieval of the *CN*-th <target specification>, if any. If any of the following is true, then it is implementation-defined whether or not exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
  - 1) If *LTDT* and *TDT* both identify a binary large object type and only one of *LTDT* and *TDT* is a binary large object locator.
  - 2) If *LTDT* and *TDT* both identify a character large object type and only one of *LTDT* and *TDT* is a character large object locator.
  - 3) If *LTDT* and *TDT* both identify an array type and only one of *LTDT* and *TDT* is an array locator.
  - 4) If *LTDT* and *TDT* both identify a user-defined type and only one of *LTDT* and *TDT* is a user-defined type locator.
- vi) Case:
  - 1) If *TDT* is a locator type, then;
    - A) If *SV* is not the null value, then a locator *L* that uniquely identifies *SV* is generated and the value *TV* of the *CN*-th <target specification> is set to an implementation-dependent four-octet value that represents *L*.
    - B) Otherwise, the value *TV* of the *CN*-th <target specification> is the null value.
  - 2) If *SDT* and *TDT* are predefined data types, then

## 6.30 GetData

Case:

- A) If the <cast specification>

CAST ( SV AS TDT )

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *TDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *TDT*, and the result is the value *TV* of the *CN*-th <target specification>.

- B) Otherwise:

- I) If the <cast specification>

CAST ( SV AS TDT )

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

- II) If the <cast specification>

CAST ( SV AS TDT )

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

- III) The <cast specification>

CAST ( SV AS TDT )

is effectively performed, and the result is the value *TV* of the *CN*-th <target specification>.

- 3) If *SDT* is a user-defined type and *TDT* is a predefined data type, then:

- A) Let *DT* be the data type identified by *SDT*.

- B) If the current SQL-session has a group name corresponding to the user-defined name of *DT*, then let *GN* be that group name; otherwise, let *GN* be the default transform group name associated with the current SQL-session.

- C) The Syntax Rules of Subclause 10.15, "Determination of a from-sql function", in ISO/IEC 9075-2, are applied with *DT* and *GN* as *TYPE* and *GROUP*, respectively.

Case:

- I) If there is an applicable from-sql function, then let *FSF* be that from-sql function and let *FSFRT* be the <returns data type> of *FSF*.

Case:

- 1) If *FSFRT* is compatible with *TDT*, then the from-sql function *TSF* is effectively invoked with *SV* as its input parameter and the <return value> is the value *TV* of the *CN*-th <target specification>.

- 2) Otherwise, an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
- II) Otherwise, an exception condition is raised: *dynamic SQL error — data type transform function violation*.
- 26) *CN* becomes the fetched column number associated with the fetched row associated with *S*.
- 27) If *TV* is the null value, then  
Case:  
a) If *StrLen\_or\_Ind* is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.  
b) Otherwise, *StrLen\_or\_Ind* is set to the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", and the value of *TargetValue* is implementation-dependent.
- 28) Let *OL* be the value of *BufferLength*.
- 29) If null termination is *true* for the current SQL-environment, then let *NB* be the length in octets of a null terminator in the character set of the *i*-th bound target; otherwise let *NB* be 0 (zero).
- 30) If *TV* is not the null value, then:  
a) *StrLen\_or\_Ind* is set to 0 (zero).  
b) Case:  
i) If *TT* does not indicate CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, then *TargetValue* is set to *TV*.  
ii) Otherwise:  
1) If *TT* is CHARACTER or CHARACTER LARGE OBJECT, then:  
A) If *TV* is a zero-length character string, then it is implementation-defined whether or not an exception condition is raised: *data exception — zero-length character string*.  
B) The General Rules of Subclause 5.9, "Character string retrieval", are applied with *TargetValue*, *TV*, *OL*, and *StrLen\_or\_Ind* as *TARGET*, *VALUE*, *OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.  
2) If *TT* is BINARY LARGE OBJECT, then the General Rules of Subclause 5.10, "Binary large object string retrieval", are applied with *TargetValue*, *TV*, *OL*, and *StrLen\_or\_Ind* as *TARGET*, *VALUE*, *OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.  
3) If *FCN* is not less than zero, then let *DV* be *TV* and let *DL* be the length of *TV* in octets.  
4) Let *FL* be  $(FL+OL-NB)$ .

**6.30 GetData**

- 5) If *FL* is less than *DL*, then  $-CN$  becomes the fetched column number associated with the fetched row associated with *S* and *FL*, *DV* and *DL* become the fetched length, data value, and data length, respectively, associated with the fetched column number.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.31 GetDescField

### Function

Get a field from a CLI descriptor area.

### Definition

```
GetDescField (
    DescriptorHandle    IN        INTEGER,
    RecordNumber       IN        SMALLINT,
    FieldIdentifier     IN        SMALLINT,
    Value              OUT       ANY,
    BufferLength        IN        INTEGER,
    StringLength       OUT       INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let  $D$  be the allocated CLI descriptor area identified by `DescriptorHandle` and let  $N$  be the value of the `COUNT` field of  $D$ .
- 2) Let  $FI$  be the value of `FieldIdentifier`.
- 3) If  $FI$  is not one of the code values in Table 20, "Codes used for descriptor fields", then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.
- 4) Let  $RN$  be the value of `RecordNumber`.
- 5) Let  $TYPE$  be the value of the `Type` column in the row of Table 20, "Codes used for descriptor fields", that contains  $FI$ .
- 6) The General Rules of Subclause 5.11, "Deferred parameter check", are applied to  $D$  as the `DESCRIPTOR AREA`.
- 7) If  $TYPE$  is 'ITEM', then:
  - a) If  $RN$  is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
  - b) If  $RN$  is greater than  $N$ , then a completion condition is raised: *no data*.
- 8) If  $D$  is an implementation row descriptor, then let  $S$  be the allocated SQL-statement associated with  $D$ .
- 9) Let  $MBR$  be the value of the `May Be Retrieved` column in the row of Table 22, "Ability to retrieve SQL/CLI descriptor fields", that contains  $FI$  and the column that contains the descriptor type  $D$ .
- 10) If  $MBR$  is 'PS' and there is no prepared or executed statement associated with  $S$ , then an exception condition is raised: *CLI-specific condition — associated statement is not prepared*.
- 11) If  $MBR$  is 'No', then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.

**6.31 GetDescField**

- 12) If *FI* indicates a descriptor field whose value is the initially undefined value created when the descriptor was created, then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.
- 13) Let *IDA* be the item descriptor area of *D* specified by *RN*.
- 14) If *TYPE* is 'HEADER', then header information from the descriptor area *D* is retrieved as follows.  
Case:
  - a) If *FI* indicates COUNT, then the value retrieved is *N*.
  - b) If *FI* indicates ALLOC\_TYPE, then the value retrieved is the allocation type for *D*.
  - c) If *FI* indicates an implementation-defined descriptor header field, then the value retrieved is the value of the implementation-defined descriptor header field identified by *FI*.
  - d) Otherwise, if *FI* indicates a descriptor header field defined in Table 20, "Codes used for descriptor fields", then the value retrieved is the value of the descriptor header field identified by *FI*.
- 15) If *TYPE* is 'ITEM', then item information from the descriptor area *D* is retrieved as follows:  
Case:
  - a) If *FI* indicates an implementation-defined descriptor item field, then the value retrieved is the value of the implementation-defined descriptor item field of *IDA* identified by *FI*.
  - b) Otherwise, if *FI* indicates a descriptor item field defined in Table 20, "Codes used for descriptor fields", then the value retrieved is the value of the descriptor item field of *IDA* identified by *FI*.
- 16) Let *V* be the value retrieved.
- 17) If *FI* indicates a descriptor field whose row in Table 6, "Fields in SQL/CLI row and parameter descriptor areas", contains a Data Type that is not CHARACTER VARYING, then Value is set to *V* and no further rules of this Subclause are applied.
- 18) Let *BL* be the value of BufferLength.
- 19) If *FI* indicates a descriptor field whose row in Table 6, "Fields in SQL/CLI row and parameter descriptor areas", contains a Data Type that is CHARACTER VARYING, then the General Rules of Subclause 5.9, "Character string retrieval", are applied with Value, *V*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

## 6.32 GetDescRec

### Function

Get commonly-used fields from a CLI descriptor area.

### Definition

```

GetDescRec (
    DescriptorHandle    IN          INTEGER ,
    RecordNumber       IN          SMALLINT ,
    Name               OUT         CHARACTER(L) ,
    BufferLength        IN          SMALLINT ,
    NameLength         OUT         SMALLINT ,
    Type               OUT         SMALLINT ,
    SubType            OUT         SMALLINT ,
    Length             OUT         INTEGER ,
    Precision          OUT         SMALLINT ,
    Scale              OUT         SMALLINT ,
    Nullable           OUT         SMALLINT )
RETURNS SMALLINT

```

where  $L$  is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $D$  be the allocated CLI descriptor area identified by DescriptorHandle and let  $N$  be the value of the COUNT field of  $D$ .
- 2) The General Rules of Subclause 5.11, "Deferred parameter check", are applied to  $D$  as the DESCRIPTOR AREA.
- 3) Let  $RN$  be the value of RecordNumber.
- 4) Case:
  - a) If  $RN$  is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
  - b) Otherwise, if  $RN$  is greater than  $N$ , then a completion condition is raised: *no data*.
- 5) If  $D$  is an implementation row descriptor associated with an allocated SQL-statement  $S$  and there is no prepared or executed statement associated with  $S$ , then an exception condition is raised: *CLI-specific condition — associated statement is not prepared*.
- 6) Let  $ITEM$  be the <dynamic parameter specification> or <select list> column (or part thereof, if the item descriptor area of  $D$  is a subordinate descriptor) described by the item descriptor area of  $D$  specified by  $RN$ .
- 7) Let  $BL$  be the value of BufferLength.
- 8) Information is retrieved from  $D$ :
  - a) If Type is not a null pointer, then Type is set to the value of the TYPE field of  $ITEM$ .

**6.32 GetDescRec**

- b) If SubType is not a null pointer, then SubType is set to the value of the DATETIME\_INTERVAL\_CODE field of *ITEM*.
- c) If Length is not a null pointer, then Length is set to value of the OCTET\_LENGTH field of *ITEM*.
- d) If Precision is not a null pointer, then Precision is set to the value of the PRECISION field of *ITEM*.
- e) If Scale is not a null pointer, then Scale is set to the value of the SCALE field of *ITEM*.
- f) If Nullable is not a null pointer, then Nullable is set to the value of the NULLABLE field of *ITEM*.
- g) If Name is not a null pointer, then
  - Case:
    - i) If null termination is *false* for the current SQL-environment and *BL* is zero, then no further rules of this Subclause are applied.
    - ii) Otherwise:
      - 1) The value retrieved is the value of the NAME field of *ITEM*.
      - 2) Let *V* be the value retrieved.
      - 3) The General Rules of Subclause 5.9, "Character string retrieval", are applied with Name, *V*, *BL*, and NameLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

## 6.33 GetDiagField

### Function

Get information from a CLI diagnostics area.

### Definition

```

GetDiagField (
    HandleType          IN          SMALLINT ,
    Handle              IN          INTEGER ,
    RecordNumber        IN          SMALLINT ,
    DiagIdentifier       IN          SMALLINT ,
    DiagInfo            OUT         ANY ,
    BufferLength         IN          SMALLINT ,
    StringLength        OUT         SMALLINT )
RETURNS SMALLINT

```

### General Rules

- 1) Let *HT* be the value of HandleType.
- 2) If *HT* is not one of the code values in Table 13, “Codes used for handle types”, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If *HT* indicates ENVIRONMENT HANDLE and Handle does not identify an allocated SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) If *HT* indicates CONNECTION HANDLE and Handle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - c) If *HT* indicates STATEMENT HANDLE and Handle does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - d) If *HT* indicates DESCRIPTOR HANDLE and Handle does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 4) Let *DI* be the value of DiagIdentifier.
- 5) If *DI* is not one of the code values in Table 12, “Codes used for diagnostic fields”, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 6) Let *TYPE* be the value of the Type column in the row that contains *DI* in Table 12, “Codes used for diagnostic fields”.
- 7) Let *RN* be the value of RecordNumber.

**6.33 GetDiagField**

- 8) Let *R* be the most recently executed CLI routine, other than GetDiagRec, GetDiagField, or Error, for which Handle was passed as the value of an input handle and let *N* be the number of status records generated by the execution of *R*.

NOTE 34 – The GetDiagRec, GetDiagField, and Error routines may cause exception or completion conditions to be raised, but they do not cause diagnostic information to be generated.

- 9) If *TYPE* is 'STATUS', then:

- a) If *RN* is less than 1 (one), then an exception condition is raised: *invalid condition number*.
- b) If *RN* is greater than *N*, then a completion condition is raised: *no data*, and no further rules of this Subclause are applied.

- 10) If *DI* indicates ROW\_COUNT and *R* is neither Execute nor ExecDirect, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.

- 11) If *TYPE* is 'HEADER', then header information from the diagnostics area associated with the resource identified by Handle is retrieved.

- a) If *DI* indicates NUMBER, then the value retrieved is *N*.
- b) If *DI* indicates DYNAMIC\_FUNCTION, then

Case:

- i) If no SQL-statement was being prepared or executed by *R*, then the value retrieved is a zero-length string.
- ii) Otherwise, the value retrieved is the character identifier of the SQL-statement being prepared or executed by *R*. The value DYNAMIC\_FUNCTION values are specified in Table 26, "SQL-statement codes", in ISO/IEC 9075-2 and in Table 9, "SQL-statement codes", in ISO/IEC 9075-5.

NOTE 35 – Additional valid DYNAMIC\_FUNCTION values may be defined in other parts of ISO/IEC 9075.

- c) If *DI* indicates DYNAMIC\_FUNCTION\_CODE, then

Case:

- i) If no SQL-statement was being prepared or executed by *R*, then the value retrieved is 0 (zero).
- ii) Otherwise, the value retrieved is the integer identifier of the SQL-statement being prepared or executed by *R*. The value DYNAMIC\_FUNCTION\_CODE values are specified in Table 26, "SQL-statement codes", in ISO/IEC 9075-2, and in Table 9, "SQL-statement codes", in ISO/IEC 9075-5.

NOTE 36 – Additional valid DYNAMIC\_FUNCTION\_CODE values may be defined in other parts of ISO/IEC 9075.

- d) If *DI* indicates RETURNCODE, then the value retrieved is the code indicating the basic result of the execution of *R*. Subclause 4.2, "Return codes", specifies the code values and their meanings.

NOTE 37 – The value retrieved will never indicate **Invalid handle** or **Data needed**, since no diagnostic information is generated if this is the basic result of the execution of *R*.

- e) If *DI* indicates ROW\_COUNT, the value retrieved is the number of rows affected as the result of executing a <delete statement: searched>, <insert statement> or <update statement: searched> as a direct result of the execution of the SQL-statement executed by *R*. Let *S* be the <delete statement: searched>, <insert statement> or <update statement: searched>. Let *T* be the table identified by the <table name> directly contained in *S*.

Case:

- i) If *S* is an <insert statement>, then the value retrieved is the number of rows inserted into *T*.
- ii) If *S* is not an <insert statement> and does not contain a <search condition>, then the value retrieved is the cardinality of *T* before the execution of *S*.
- iii) Otherwise, let *SC* be the <search condition> directly contained in *S*. The value retrieved is effectively derived by executing the statement:

```
SELECT COUNT(*)
FROM T
WHERE SC
```

before the execution of *S*.

The value retrieved following the execution by *R* of an SQL-statement that does not directly result in the execution of a <delete statement: searched>, <insert statement> or <update statement: searched> is implementation-dependent.

- f) If *DI* indicates MORE, then the value retrieved is

Case:

- i) If more conditions were raised during execution of *R* than have been stored in the diagnostics area, then 1 (one).
  - ii) If all the conditions that were raised during execution of *R* have been stored in the diagnostics area, then 0 (zero).
- g) If *DI* indicates TRANSACTIONS\_COMMITTED, then the value retrieved is the number of SQL-transactions that have been committed since the most recent time at which the diagnostics area for *HT* was emptied.
- NOTE 38 – See the General Rules of Subclause 13.3, "<externally-invoked procedure>", and Subclause 13.4, "Calls to an <externally-invoked procedure>", in ISO/IEC 9075-2. TRANSACTIONS\_COMMITTED indicates the number of SQL-transactions that were committed during the invocation of an external routine.
- h) If *DI* indicates TRANSACTIONS\_ROLLED\_BACK, then the value retrieved is the number of SQL-transactions that have been rolled back since the most recent time at which the diagnostics area for *HT* was emptied.
- NOTE 39 – See the General Rules of Subclause 13.3, "<externally-invoked procedure>", and Subclause 13.4, "Calls to an <externally-invoked procedure>", in ISO/IEC 9075-2. TRANSACTIONS\_ROLLED\_BACK indicates the number of SQL-transactions that were rolled back during the invocation of an external routine.

**6.33 GetDiagField**

- i) If *DI* indicates TRANSACTION\_ACTIVE, then the value retrieved is 1 (one) if an SQL-transaction is currently active and is 0 (zero) if an SQL-transaction is not currently active.

NOTE 40 – TRANSACTION\_ACTIVE indicates whether an SQL-transaction is active upon return from an external routine.

- j) If *DI* indicates an implementation-defined diagnostics header field, then the value retrieved is the value of the implementation-defined diagnostics header field.
- 12) If *TYPE* is 'STATUS', then information from the *RN*-th status record in the diagnostics area associated with the resource identified by Handle is retrieved.
- a) If *DI* indicates CONDITION\_NUMBER, then the value retrieved is *RN*.
  - b) If *DI* indicates SQLSTATE, then the value retrieved is the SQLSTATE value corresponding to the status condition.
  - c) If *DI* indicates NATIVE\_CODE, then the value retrieved is the implementation-defined native error code corresponding to the status condition.
  - d) If *DI* indicates MESSAGE\_TEXT, then the value retrieved is  
Case:
    - i) If the value of SQLSTATE corresponds to *external routine invocation exception, external routine exception, or warning*, then the message text item of the SQL-invoked routine that raised the exception condition.
    - ii) Otherwise, an implementation-defined character string.  
NOTE 41 – An implementation may provide <space>s or a zero-length string or a character string that describes the status condition.
  - e) If *DI* indicates MESSAGE\_LENGTH, then the value retrieved is the length in characters of the character string value of MESSAGE\_TEXT corresponding to the status condition.
  - f) If *DI* indicates MESSAGE\_OCTET\_LENGTH, then the value retrieved is the length in octets of the character string value of MESSAGE\_TEXT corresponding to the status condition.
  - g) If *DI* indicates CLASS\_ORIGIN, then the value retrieved is the identification of the naming authority that defined the class value of the SQLSTATE value corresponding to the status condition. That value shall be 'ISO 9075' if the class value is fully defined in Subclause 22.1, "SQLSTATE", in ISO/IEC 9075-2 or Subclause 5.12, "CLI-specific status codes", and shall be an implementation-defined character string other than 'ISO 9075' for any implementation-defined class value.
  - h) If *DI* indicates SUBCLASS\_ORIGIN, then the value retrieved is the identification of the naming authority that defined the subclass value of the SQLSTATE value corresponding to the status condition. That value shall be 'ISO 9075' if the subclass value is fully defined in Subclause 22.1, "SQLSTATE", in ISO/IEC 9075-2, or Subclause 5.12, "CLI-specific status codes", and shall be an implementation-defined character string other than 'ISO 9075' for any implementation-defined subclass value.

- i) If *DI* indicates *CURSOR\_NAME*, *CONSTRAINT\_CATALOG*, *CONSTRAINT\_SCHEMA*, *CONSTRAINT\_NAME*, *CATALOG\_NAME*, *SCHEMA\_NAME*, *TABLE\_NAME*, *COLUMN\_NAME*, *PARAMETER\_MODE*, *PARAMETER\_NAME*, *PARAMETER\_ORDINAL\_POSITION*, *ROUTINE\_CATALOG*, *ROUTINE\_SCHEMA*, *ROUTINE\_NAME*, *SPECIFIC\_NAME*, *TRIGGER\_CATALOG*, *TRIGGER\_SCHEMA*, or *TRIGGER\_NAME*, then the values retrieved are

Case:

- i) If the value of *SQLSTATE* corresponds to *warning — cursor operation conflict*, then the value of *CURSOR\_NAME* is the name of the cursor that caused the completion condition to be raised.
- ii) If the value of *SQLSTATE* corresponds to *integrity constraint violation*, *transaction rollback — integrity constraint violation*, or *triggered data change violation*, then:
- 1) The values of *CONSTRAINT\_CATALOG* and *CONSTRAINT\_SCHEMA* are the <catalog name> and the <unqualified schema name> of the <schema name> of the schema containing the constraint or assertion. The value of *CONSTRAINT\_NAME* is the <qualified identifier> of the constraint or assertion.
  - 2) Case:
    - A) If the violated integrity constraint is a table constraint, then the values of *CATALOG\_NAME*, *SCHEMA\_NAME*, and *TABLE\_NAME* are the <catalog name>, the <unqualified schema name> of the <schema name>, and the <qualified identifier> or <local table name>, respectively, of the table in which the table constraint is contained.
    - B) If the violated integrity constraint is an assertion and if only one table referenced by the assertion has been modified as a result of executing the SQL-statement, then the values of *CATALOG\_NAME*, *SCHEMA\_NAME*, and *TABLE\_NAME* are the <catalog name>, the <unqualified schema name> of the <schema name>, and the <qualified identifier> or <local table name>, respectively, of the modified table.
    - C) Otherwise, the values of *CATALOG\_NAME*, *SCHEMA\_NAME*, and *TABLE\_NAME* are <space>s.

If the value of *TABLE\_NAME* identifies a declared local temporary table, then the value of *CATALOG\_NAME* is <space>s and the value of *SCHEMA\_NAME* is 'MODULE'.

- iii) If the value of *SQLSTATE* corresponds to *syntax error or access rule violation*, then:
- 1) The values of *CATALOG\_NAME*, *SCHEMA\_NAME*, and *TABLE\_NAME* are the <catalog name>, the <unqualified schema name> of the <schema name> of the schema that contains the table that caused the syntax error or the access rule violation and the <qualified identifier> or <local table name>, respectively. If *TABLE\_NAME* refers to a declared local temporary table, then *CATALOG\_NAME* is <space>s and *SCHEMA\_NAME* contains 'MODULE'.
  - 2) If the syntax error or the access rule violation was for an inaccessible column, then the value of *COLUMN\_NAME* is the <column name> of that column. Otherwise, the value of *COLUMN\_NAME* is <space>s.

**6.33 GetDiagField**

- iv) If the value of SQLSTATE corresponds to *invalid cursor state*, then the value of CURSOR\_NAME is the name of the cursor that is in the invalid state.
- v) If the value of SQLSTATE corresponds to *with check option violation*, then the values of CATALOG\_NAME, SCHEMA\_NAME, and TABLE\_NAME are the <catalog name> and the <unqualified schema name> of the <schema name> of the schema that contains the view that caused the violation of the WITH CHECK OPTION, and the <qualified identifier> of that view, respectively.
- vi) If the value of SQLSTATE does not correspond to *syntax error or access rule violation*, then:
  - 1) If the values of CATALOG\_NAME, SCHEMA\_NAME, TABLE\_NAME, and COLUMN\_NAME identify a column for which no privileges are granted to the enabled authorization identifiers, then the value of COLUMN\_NAME is replaced by a zero-length string.
  - 2) If the values of CATALOG\_NAME, SCHEMA\_NAME, and TABLE\_NAME identify a table for which no privileges are granted to the enabled authorization identifiers, then the values of CATALOG\_NAME, SCHEMA\_NAME, and TABLE\_NAME are replaced by a zero-length string.
  - 3) If the values of CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME identify a <table constraint> for some table *T* and if no privileges for *T* are granted to the enabled authorization identifiers, then the values of CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME are replaced by a zero-length string.
  - 4) If the values of CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME identify an assertion contained in some schema *S* and if the owner of *S* is not included in the set of enabled authorization identifiers, then the values of CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME are replaced by a zero-length string.
- vii) If the value of SQLSTATE corresponds to *triggered action exception*, to *transaction rollback — triggered action exception*, or to *triggered data change violation* that was caused by a trigger, then:
  - 1) The values of TRIGGER\_CATALOG and TRIGGER\_SCHEMA are the <catalog name> and the <unqualified schema name>, respectively, of the <schema name> of the schema containing the trigger. The value of TRIGGER\_NAME is the <qualified identifier> of the <trigger name> of the trigger.
  - 2) The values of CATALOG\_NAME, SCHEMA\_NAME, and TABLE\_NAME are the <catalog name>, the <unqualified schema name> of the <schema name>, and the <qualified identifier> of the <table name>, respectively, of the table on which the trigger is defined.
- viii) If the value of SQLSTATE corresponds to *external routine invocation exception*, or to *external routine exception*, then:
  - 1) The values of ROUTINE\_CATALOG and ROUTINE\_SCHEMA are the <catalog name> and the <unqualified schema name>, respectively, of the <schema name> of the schema containing the SQL-invoked routine.

- 2) The values of ROUTINE\_NAME and SPECIFIC\_NAME are the <identifier> of the <routine name> and the <identifier> of the <specific name> of the SQL-invoked routine, respectively.
- 3) Case:
  - A) If the condition is related to some parameter  $P_i$  of the SQL-invoked routine, then:
    - I) The value of PARAMETER\_MODE is the <parameter mode> of  $P_i$ .
    - II) The value of PARAMETER\_ORDINAL\_POSITION is the value of  $i$ .
    - III) The value of PARAMETER\_NAME is a zero-length string.
  - B) Otherwise:
    - I) The value of PARAMETER\_MODE is a zero-length string.
    - II) The value of PARAMETER\_ORDINAL\_POSITION is 0 (zero).
    - III) The value of PARAMETER\_NAME is a zero-length string.
- ix) If the value of SQLSTATE corresponds to *data exception — numeric value out of range*, *data exception — invalid character value for cast*, *data exception — string data, right truncation*, *data exception — interval field overflow*, *integrity constraint violation*, *warning — string data, right truncation*, or *warning — implicit zero-bit padding*, and the condition was raised as the result of an assignment to an SQL parameter during an SQL-invoked routine invocation, then:
  - 1) The values of ROUTINE\_CATALOG and ROUTINE\_SCHEMA are the <catalog name> and <unqualified schema name>, respectively, of the <schema name> of the schema containing the SQL-invoked routine.
  - 2) The values of ROUTINE\_NAME and SPECIFIC\_NAME are the <identifier> of the <routine name> and the <identifier> of the <specific name>, respectively, of the SQL-invoked routine.
  - 3) If the condition is related to some parameter  $P_i$  of the SQL-invoked routine, then:
    - A) The value of PARAMETER\_MODE is the <parameter mode> of  $P_i$ .
    - B) The value of PARAMETER\_ORDINAL\_POSITION is the value of  $i$ .
    - C) If an <SQL parameter name> was specified for the SQL parameter when the SQL-invoked routine was created, then the value of PARAMETER\_NAME is the <SQL parameter name> of that SQL parameter,  $P_i$ ; otherwise, the value of PARAMETER\_NAME is a zero-length string.
- j) If  $DI$  indicates SERVER\_NAME or CONNECTION\_NAME, then the values retrieved are  
Case:
  - i) If  $R$  is Connect, then the name of the SQL-server explicitly or implicitly referenced by  $R$  and the implementation-defined connection name associated with that SQL-server reference, respectively.

**6.33 GetDiagField**

- ii) If *R* is Disconnect, then the name of the SQL-server and the associated implementation-defined connection name, respectively, associated with the allocated SQL-connection referenced by *R*.
  - iii) If the status condition was caused by the application of the General Rules of Subclause 5.3, “Implicit set connection”, then the name of the SQL-server and the implementation-defined connection name, respectively, associated with the dormant connection specified in the application of that Subclause.
  - iv) If the status condition was raised in an SQL-session, then the name of the SQL-server and the implementation-defined connection name, respectively, associated with the SQL-session in which the status condition was raised.
  - v) Otherwise, zero-length strings.
- k) If *DI* indicates CONDITION\_IDENTIFIER, then the value retrieved is
- Case:
- i) If the value of SQLSTATE corresponds to *unhandled user-defined exception*, then the <condition name> of the user-defined exception.
  - ii) Otherwise, a zero-length string.
- l) If *FI* indicates ROW\_NUMBER, then the value retrieved is the number of the row in the rowset to which this diagnostic record corresponds. If the diagnostic record does not correspond to any particular row, then the value retrieved is 0 (zero).
- m) If *FI* indicates COLUMN\_NUMBER, then the value retrieved is the number of the column to which this diagnostic record corresponds. If the diagnostic record does not correspond to any particular column, then the value retrieved is 0 (zero).
- n) If *DI* indicates an implementation-defined diagnostics status field, then the value retrieved is the value of the implementation-defined diagnostics status field.
- 13) Let *V* be the value retrieved.
- 14) If *DI* indicates a diagnostics field whose row in Table 2, “Fields in SQL/CLI diagnostics areas”, contains a Data Type that is neither CHARACTER nor CHARACTER VARYING, then DiagInfo is set to *V* and no further rules of this Subclause are applied.
- 15) Let *BL* be the value of BufferLength.
- 16) If *BL* is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 17) Let *L* be the length in octets of *V*.
- 18) If StringLength is not a null pointer, then StringLength is set to *L*.
- 19) Case:
- a) If null termination is *false* for the current SQL-environment, then:
    - i) If *L* is not greater than *BL*, then the first *L* octets of DiagInfo are set to *V* and the values of the remaining octets of DiagInfo are implementation-dependent.

- ii) Otherwise, DiagInfo is set to the first  $BL$  octets of  $V$ .
- b) Otherwise, let  $k$  be the number of octets in a null terminator in the character set of DiagInfo and let the phrase “implementation-defined null character that terminates a C character string” imply  $k$  octets, all of whose bits are zero.
  - i) If  $L$  is not greater than  $(BL-k)$ , then the first  $(L+k)$  octets of DiagInfo are set to  $V$  concatenated with a single implementation-defined null character that terminates a C character string. The values of the remaining characters of DiagInfo are implementation-dependent.
  - ii) Otherwise, DiagInfo is set to the first  $(BL-k)$  octets of  $V$  concatenated with a single implementation-defined null character that terminates a C character string.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

**6.34 GetDiagRec****6.34 GetDiagRec****Function**

Get commonly-used information from a CLI diagnostics area.

**Definition**

```
GetDiagRec (
    HandleType           IN           SMALLINT ,
    Handle               IN           INTEGER ,
    RecordNumber        IN           SMALLINT ,
    Sqlstate             OUT          CHARACTER( 5 ) ,
    NativeError         OUT          INTEGER ,
    MessageText         OUT          CHARACTER( L ) ,
    BufferLength         IN           SMALLINT ,
    TextLength          OUT          SMALLINT )
RETURNS SMALLINT
```

where  $L$  is the value of BufferLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

**General Rules**

- 1) Let  $HT$  be the value of HandleType.
- 2) If  $HT$  is not one of the code values in Table 13, “Codes used for handle types”, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If  $HT$  indicates ENVIRONMENT HANDLE and Handle does not identify an allocated SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) If  $HT$  indicates CONNECTION HANDLE and Handle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - c) If  $HT$  indicates STATEMENT HANDLE and Handle does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - d) If  $HT$  indicates DESCRIPTOR HANDLE and Handle does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 4) Let  $RN$  be the value of RecordNumber.
- 5) Let  $R$  be the most recently executed CLI routine, other than GetDiagRec, GetDiagField, or Error, for which Handle was passed as the value of an input handle and let  $N$  be the number of status records generated by the execution of  $R$ .  
NOTE 42 – The GetDiagRec, GetDiagField, and Error routines may cause exception or completion conditions to be raised, but they do not cause diagnostic information to be generated.
- 6) If  $RN$  is less than 1 (one), then an exception condition is raised: *invalid condition number*.

- 7) If  $RN$  is greater than  $N$ , then a completion condition is raised: *no data*, and no further rules of this Subclause are applied.
- 8) Let  $BL$  be the value of BufferLength.
- 9) Information from the  $RN$ -th status record in the diagnostics area associated with the resource identified by Handle is retrieved.
  - a) If Sqlstate is not a null pointer, then Sqlstate is set to the SQLSTATE value corresponding to the status condition.
  - b) If NativeError is not a null pointer, then NativeError is set to the implementation-defined native error code corresponding to the status condition.
  - c) If MessageText is not a null pointer, then

Case:

- i) If null termination is *false* for the current SQL-environment and  $BL$  is zero, then no further rules of this Subclause are applied.
- ii) Otherwise, an implementation-defined character string is retrieved. Let  $MT$  be the implementation-defined character string that is retrieved and let  $L$  be the length in octets of  $MT$ . If  $BL$  is not greater than zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*. If TextLength is not a null pointer, then TextLength is set to  $L$ .

Case:

- 1) If null termination is *false* for the current SQL-environment, then:
  - A) If  $L$  is not greater than  $BL$ , then the first  $L$  octets of MessageText are set to  $MT$  and the values of the remaining octets of MessageText are implementation-dependent.
  - B) Otherwise, MessageText is set to the first  $BL$  octets of  $MT$ .
- 2) Otherwise, let  $k$  the number of octets in a null terminator in the character set of MessageText and let the phrase “implementation-defined null character that terminates a C character string” imply  $k$  octets, all of whose bits are zero.
  - A) If  $L$  is not greater than  $(BL-k)$ , then the first  $(L+k)$  octets of MessageText are set to  $MT$  concatenated with a single implementation-defined null character that terminates a C character string. The values of the remaining characters of MessageText are implementation-dependent.
  - B) Otherwise, MessageText is set to the first  $(BL-k)$  octets of  $MT$  concatenated with a single implementation-defined null character that terminates a C character string.

NOTE 43 – An implementation may provide <space>s or a zero-length string or a character string that describes the status condition.

## 6.35 GetEnvAttr

## 6.35 GetEnvAttr

## Function

Get the value of an SQL-environment attribute.

## Definition

```
GetEnvAttr (
    EnvironmentHandle    IN          INTEGER,
    Attribute            IN          INTEGER,
    Value               OUT         ANY,
    BufferLength         IN          INTEGER,
    StringLength        OUT         INTEGER )
RETURNS SMALLINT
```

## General Rules

- 1) Case:
  - a) If EnvironmentHandle does not identify an allocated SQL-environment or if it identifies an allocated skeleton SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *E* be the allocated SQL-environment identified by EnvironmentHandle.
    - ii) The diagnostics area associated with *E* is emptied.
- 2) Let *A* be the value of Attribute.
- 3) If *A* is not one of the code values in Table 15, “Codes used for environment attributes”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) If *A* indicates NULL TERMINATION, then
 

Case:

  - a) If null termination for *E* is true , then Value is set to 1 (one).
  - b) If null termination for *E* is false , then Value is set to 0 (zero).
- 5) If *A* specifies an implementation-defined environment attribute, then
 

Case:

  - a) If the data type for the environment attribute is specified in Table 19, “Data types of attributes”, as INTEGER, then Value is set to the value of the implementation-defined environment attribute.
  - b) Otherwise:
    - i) Let *BL* be the value of BufferLength.
    - ii) Let *AV* be the value of the implementation-defined environment attribute.

- iii) The General Rules of Subclause 5.9, “Character string retrieval”, are applied with Value, *AV*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.36 GetFeatureInfo

### Function

Get information about features supported by the CLI implementation.

### Definition

```
GetFeatureInfo (
    ConnectionHandle    IN        INTEGER ,
    FeatureType         IN        CHARACTER(L1) ,
    FeatureTypeLength   IN        SMALLINT ,
    FeatureId           IN        CHARACTER(L2) ,
    FeatureIdLength     IN        SMALLINT ,
    SubFeatureId        IN        CHARACTER(L3) ,
    SubFeatureIdLength  IN        SMALLINT ,
    Supported           OUT       SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ , and  $L3$  are determined by the values of FeatureTypeLength, FeatureIdLength, and SubFeatureIdLength, respectively, and each of  $L1$ ,  $L2$ , and  $L3$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let  $C$  be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with  $C$  is emptied.
- 2) Case:
  - a) If there is no established SQL-connection associated with  $C$ , then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise, let  $EC$  be the established SQL-connection associated with  $C$ .
- 3) If  $EC$  is not the current SQL-connection, then the General Rules of Subclause 5.3, "Implicit set connection", are applied to  $EC$  as the dormant SQL-connection.
- 4) Let  $FTL$  be the value of FeatureTypeLength.
- 5) Case:
  - a) If  $FTL$  is not negative, then let  $L$  be  $FTL$ .
  - b) If  $FTL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of FeatureType that precede the implementation-defined null character that terminates a C character string.

c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

6) Case:

a) If  $L$  is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

b) Otherwise, let  $FTV$  be the first  $L$  octets of FeatureType and let  $FT$  be the value of

```
TRIM ( BOTH ' ' FROM FTV )
```

7) If  $FT$  is other than 'FEATURE', 'SUBFEATURE', or 'PACKAGE', then an exception condition is raised: *CLI-specific condition — invalid attribute value.*

8) Let  $FIL$  be the value of FeatureIdIdLength.

9) Case:

a) If  $FIL$  is not negative, then let  $L$  be  $FIL$ .

b) If  $FIL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of FeatureId that precede the implementation-defined null character that terminates a C character string.

c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

10) Case:

a) If  $L$  is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

b) Otherwise, let  $FIV$  be the first  $L$  octets of FeatureId and let  $FI$  be the value of

```
TRIM ( BOTH ' ' FROM FIV )
```

11) Case:

a) If  $FT$  is 'SUBFEATURE', then:

i) Let  $SFIL$  be the value of SubFeatureIdLength.

ii) Case:

1) If  $SFIL$  is not negative, then let  $L$  be  $SFIL$ .

2) If  $SFIL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of SubFeatureId that precede the implementation-defined null character that terminates a C character string.

3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

iii) Case:

- 1) If *L* is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 2) Otherwise, let *SFIV* be the first *L* octets of SubFeatureId and let *SFI* be the value of

```
TRIM ( BOTH ' ' FROM SFIV )
```

b) Otherwise, let *SFI* be a character string consisting of a single space.

- 12) If there is no row in the INFORMATION\_SCHEMA.SQL\_FEATURES view with FEATURE\_SUBFEATURE\_PACKAGE\_CODE equal to *FT*, FEATURE\_ID equal to *FI*, and SUB\_FEATURE\_ID equal *SFI*, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 13) Let *SH* be an allocated statement handle on *C*.
- 14) Let *STMT* be the character string:

```
SELECT IS_SUPPORTED  
FROM INFORMATION_SCHEMA.SQL_FEATURES  
WHERE FEATURE_SUBFEATURE_PACKAGE_CODE = 'FT'  
AND FEATURE_ID = 'FI'  
AND SUB_FEATURE_ID = 'SFI'
```

- 15) Let *IS* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.
- 16) If any status condition, such as connection failure, is caused by the implicit execution of ExecDirect, then:
  - a) The status records returned by ExecDirect are returned on ConnectionHandle.
  - b) This invocation of GetFeatureInfo returns the same return code that was returned by the implicit invocation of ExecDirect and no further Rules of this Subclause are applied.
- 17) If the value of *IS* is 'YES', then Supported is set to 1 (one); otherwise, Supported is set to 0 (zero).

## 6.37 GetFunctions

### Function

Determine whether a CLI routine is supported.

### Definition

```

GetFunctions (
    ConnectionHandle      IN      INTEGER,
    FunctionId            IN      SMALLINT,
    Supported             OUT     SMALLINT )
RETURNS SMALLINT

```

### General Rules

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Case:
  - a) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise, let *EC* be the established SQL-connection associated with *C*.
- 3) If *EC* is not the current SQL-connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant SQL-connection.
- 4) Let *FI* be the value of FunctionId.
- 5) If *FI* is not one of the codes in Table 27, “Codes used to identify SQL/CLI routines”, then an exception condition is raised: *CLI-specific condition — invalid FunctionId specified*.
- 6) If *FI* identifies a CLI routine that is supported by the implementation, then Supported is set to 1 (one); otherwise, Supported is set to 0 (zero). Table 27, “Codes used to identify SQL/CLI routines”, specifies the codes used to identify the CLI routines defined in this part of ISO/IEC 9075.

**6.38 GetInfo****6.38 GetInfo****Function**

Get information about the implementation.

**Definition**

```
GetInfo (
    ConnectionHandle      IN      INTEGER,
    InfoType              IN      SMALLINT,
    InfoValue             OUT     ANY,
    BufferLength           IN      SMALLINT,
    StringLength          OUT     SMALLINT )
RETURNS SMALLINT
```

**General Rules**

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Case:
  - a) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise, let *EC* be the established SQL-connection associated with *C*.
- 3) If *EC* is not the current SQL-connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant SQL-connection.
- 4) Several General Rules in this Subclause cause implicit invocation of ExecDirect. If any status condition, such as a connection failure, is caused by such implicit invocation of ExecDirect, then:
  - a) The status records returned by ExecDirect are returned on ConnectionHandle.
  - b) This invocation of GetInfo returns the same return code that was returned by the implicit invocation of ExecDirect and no further Rules of this Subclause are applied.
- 5) Let *IT* be the value of InfoType.
- 6) If *IT* is not one of the codes in Table 28, “Codes and data types for implementation information”, then an exception condition is raised: *CLI-specific condition — invalid information type*.
- 7) Let *SS* be the SQL-server associated with *EC*.

- 8) Refer to a component of the SQL-client that is responsible for communicating with one or more SQL-servers as a driver.
- 9) Let *SH* be an allocated statement handle on *C*.
- 10) Case:

a) If *IT* indicates any of the following:

- MAXIMUM COLUMN NAME LENGTH
- MAXIMUM COLUMNS IN GROUP BY
- MAXIMUM COLUMNS IN ORDER BY
- MAXIMUM COLUMNS IN SELECT
- MAXIMUM COLUMNS IN TABLE
- MAXIMUM CONCURRENT ACTIVITIES
- MAXIMUM CURSOR NAME LENGTH
- MAXIMUM DRIVER CONNECTIONS
- MAXIMUM IDENTIFIER LENGTH
- MAXIMUM SCHEMA NAME LENGTH
- MAXIMUM STATEMENT OCTETS DATA
- MAXIMUM STATEMENT OCTETS SCHEMA
- MAXIMUM STATEMENT OCTETS
- MAXIMUM TABLE NAME LENGTH
- MAXIMUM TABLES IN SELECT
- MAXIMUM USER NAME LENGTH
- MAXIMUM CATALOG NAME LENGTH

then:

i) Let *STMT* be the character string;

```
SELECT SUPPORTED_VALUE
FROM INFORMATION_SCHEMA.SQL_SIZING
WHERE SIZING_ID = IT
```

ii) Let *V* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

b) If *IT* indicates any of the following:

- CATALOG NAME

## 6.38 GetInfo

- COLLATING SEQUENCE
- CURSOR COMMIT BEHAVIOR
- DATA SOURCE NAME
- DBMS NAME
- DBMS VERSION
- NULL COLLATION
- SEARCH PATTERN ESCAPE
- SERVER NAME
- SPECIAL CHARACTERS

then:

- i) Let *STMT* be the character string;

```
SELECT CHARACTER_VALUE
FROM INFORMATION_SCHEMA.SQL_IMPLEMENTATION_INFO
WHERE IMPLEMENTATION_INFO_ID = IT
```

- ii) Let *V* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

- c) If *IT* indicates any of the following:

- DEFAULT TRANSACTION ISOLATION
- IDENTIFIER CASE
- TRANSACTION CAPABLE

then:

- i) Let *STMT* be the character string;

```
SELECT INTEGER_VALUE
FROM INFORMATION_SCHEMA.SQL_IMPLEMENTATION_INFO
WHERE IMPLEMENTATION_INFO_ID = IT
```

- ii) Let *V* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

- d) If *IT* indicates ALTER TABLE, then:

- i) Let *V* be 0 (zero).
- ii) If *SS* supports the <add column definition> clause on the <alter table statement>, then add the numeric value for ADD COLUMN from Table 30, "Values for ALTER TABLE with GetInfo" to *V*.

- iii) If *SS* supports the <drop column definition> clause on the <alter table statement>, then add the numeric value for DROP COLUMN from Table 30, "Values for ALTER TABLE with GetInfo" to *V*.
- iv) If *SS* supports the <alter column definition> clause on the <alter table statement>, then add the numeric value for ALTER COLUMN from Table 30, "Values for ALTER TABLE with GetInfo" to *V*.
- v) If *SS* supports the <add table constraint definition> clause on the <alter table statement>, then add the numeric value for ADD CONSTRAINT from Table 30, "Values for ALTER TABLE with GetInfo" to *V*.
- vi) If *SS* supports the <drop table constraint definition> clause on the <alter table statement>, then add the numeric value for DROP CONSTRAINT from Table 30, "Values for ALTER TABLE with GetInfo" to *V*.

NOTE 44 – The ability to specify ALTER TABLE in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId combinations that indicate Features F031-03, F381-01, F381-02, and F381-03, and FeatureId to indicate Feature F033.

- e) If *IT* indicates CURSOR SENSITIVITY, then let *V* be set as follows to indicate support for cursor sensitivity at *SS*:
  - i) If *SS* supports both the behavior associated with the INSENSITIVE keyword and the behavior associated with the SENSITIVE keyword in Clause 14, "Data manipulation", in ISO/IEC 9075-2, then let *V* be the value of SENSITIVE for the CURSOR SENSITIVITY attribute from Table 26, "Miscellaneous codes used in CLI".
  - ii) If *SS* supports the behavior associated with the INSENSITIVE keyword in Clause 14, "Data manipulation", in ISO/IEC 9075-2 but not the behavior associated with the SENSITIVE keyword in Clause 14, "Data manipulation", in ISO/IEC 9075-2, then let *V* be the value of INSENSITIVE for the CURSOR SENSITIVITY attribute from Table 26, "Miscellaneous codes used in CLI".
  - iii) If *SS* supports the behavior of associated with the ASENSITIVE keyword in Clause 14, "Data manipulation", in ISO/IEC 9075-2, then let *V* be the value of ASENSITIVE for the CURSOR SENSITIVITY attribute from Table 26, "Miscellaneous codes used in CLI".

NOTE 45 – The ability to specify CURSOR SENSITIVITY in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId to indicate Feature F791 or T231.

- f) If *IT* indicates DATA SOURCE READ ONLY, then:
  - i) If the data from *SS* can be read but not modified, then let *V* be 'Y'.
  - ii) Otherwise, let *V* be 'N'.

NOTE 46 – The ability to specify DATA SOURCE READ ONLY in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId to indicate Feature C081.

- g) If *IT* indicates DESCRIBE PARAMETER, then:
  - i) If *SS* is capable of describing <dynamic parameter specification>s, then let *V* be 'Y'.

**6.38 GetInfo**

ii) Otherwise, let  $V$  be 'N'.

NOTE 47 – The ability to specify DESCRIBE PARAMETER in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using the FeatureId and SubFeatureId combination to indicate Feature B032-01.

h) If  $IT$  indicates FETCH DIRECTION, then:

i) Let  $V$  be 0 (zero).

ii) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies ABSOLUTE, then add the numeric value for FETCH ABSOLUTE from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

iii) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies FIRST, then add the numeric value for FETCH FIRST from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

iv) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies LAST, then add the numeric value for FETCH LAST from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

v) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies NEXT, then add the numeric value for FETCH NEXT from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

vi) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies PRIOR, then add the numeric value for FETCH PRIOR from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

vii) If  $SS$  supports the behavior specified in Subclause 14.3, "<fetch statement>", in ISO/IEC 9075-2, associated with a <fetch orientation> that specifies RELATIVE, then add the numeric value for FETCH RELATIVE from Table 31, "Values for FETCH DIRECTION with GetInfo", to  $V$ .

NOTE 48 – The ability to specify FETCH DIRECTION in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Feature F341 with any of its subfeatures.

i) If  $IT$  indicates GETDATA EXTENSIONS, then  $V$  is set as follows to indicate whether the implementation supports certain extensions to the GetData routine:

i) Let  $V$  be 0 (zero).

ii) If GetData can be called to obtain columns that precede the last bound column, then add the numeric value for ANY COLUMN from Table 32, "Values for GETDATA EXTENSIONS with GetInfo", to  $V$ .

iii) If GetData can be called for columns in any order, then add the numeric value for ANY ORDER from Table 32, "Values for GETDATA EXTENSIONS with GetInfo", to  $V$ .

NOTE 49 – This also means that a column can be accessed by GetData even though previous GetData calls retrieved all the data for that column.

NOTE 50 – The ability to specify GETDATA EXTENSIONS in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Feature C051 with any of its subfeatures.

- j) If *IT* indicates OUTER JOIN CAPABILITIES, then:
- i) Let *V* be 0 (zero).
  - ii) If *SS* supports the behavior for an <outer join type> specified as LEFT as specified in Subclause 7.7, "<joined table>", in ISO/IEC 9075-2, then add the numeric value for LEFT from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - iii) If *SS* supports the behavior for an <outer join type> specified as RIGHT as specified in Subclause 7.7, "<joined table>", in ISO/IEC 9075-2, then add the numeric value for RIGHT from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - iv) If *SS* supports the behavior for an <outer join type> specified as FULL as specified in Subclause 7.7, "<joined table>", in ISO/IEC 9075-2, then add the numeric value for FULL from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - v) If *SS* supports nested outer joins, then add the numeric value for NESTED from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - vi) If *SS* supports join operations where the order of tables in the ON clause need not be the same as the order of the tables within the associated JOIN clause, then add the numeric value for NOT ORDERED from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - vii) If *SS* permits an inner table to be the result of a INNER JOIN, then add the numeric value for INNER from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.
  - viii) If *SS* supports any predicate within an ON clause of an OUTER JOIN, then add the numeric value for ALL COMPARISON OPS from Table 33, "Values for OUTER JOIN CAPABILITIES with GetInfo", to *V*.

NOTE 51 – The ability to specify OUTER JOIN CAPABILITIES in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Feature F041 with any of its subfeatures.

- k) If *IT* indicates ORDER BY COLUMNS IN SELECT, then:
- i) If *SS* requires that columns in the ORDER BY clause also appear in the associated <select list>, then let *V* be 'Y'.
  - ii) Otherwise, let *V* be 'N'.

NOTE 52 – The ability to specify ORDER BY COLUMNS IN SELECT in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Feature F121-02.

- l) If *IT* indicates SCROLL CONCURRENCY, then:
- i) Let *V* be 0 (zero).
  - ii) If *SS* supports read-only scrollable cursors, then add the numeric value for READ ONLY from Table 34, "Values for SCROLL CONCURRENCY with GetInfo", to *V*.

**6.38 GetInfo**

- iii) If *SS* supports scrollable cursors and allows this with the lowest level of locking that ensures that the row can be updated, then add the numeric value for LOCK from Table 34, “Values for SCROLL CONCURRENCY with GetInfo”, to *V*.
- iv) If *SS* supports scrollable cursors and allows this with optimistic concurrency using row identifiers or timestamps, add the numeric value for OPT ROWVER from Table 34, “Values for SCROLL CONCURRENCY with GetInfo”, to *V*.
- v) If *SS* supports scrollable cursors and allows this with optimistic concurrency by comparing values, add the numeric value for OPT VALUES from Table 34, “Values for SCROLL CONCURRENCY with GetInfo”, to *V*.

NOTE 53 – The ability to specify SCROLL CONCURRENCY in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Feature C071 with any of its subfeatures.

- m) If *IT* indicates TRANSACTION ISOLATION OPTION, then:
  - i) Let *V* be 0 (zero).
  - ii) If *SS* supports the READ UNCOMMITTED isolation level, then add the numeric value for READ UNCOMMITTED from Table 35, “Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran”, to *V*.
  - iii) If *SS* supports the READ COMMITTED isolation level, then add the numeric value for READ COMMITTED from Table 35, “Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran”, to *V*.
  - iv) If *SS* supports the REPEATABLE READ isolation level, then add the numeric value for REPEATABLE READ from Table 35, “Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran”, to *V*.
  - v) If *SS* supports the SERIALIZABLE isolation level, then add the numeric value for SERIALIZABLE from Table 35, “Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran”, to *V*.

NOTE 54 – The ability to specify TRANSACTION ISOLATION OPTION in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId and SubFeatureId to indicate Features E151-01, F111-01, F111-02, and F111-03.

- n) If *IT* indicates USER NAME, then let *V* be the value of CURRENT\_USER.

NOTE 55 – The ability to specify USER NAME in GetInfo is deprecated. This capability is replaced with the ability to invoke GetSessionInfo using the InfoType value that indicates CURRENT USER.

- o) If *IT* indicates INTEGRITY, then:

- i) If *SS* supports feature E141 (Basic integrity constraints), then let *V* be 'Y'.
- ii) Otherwise, let *V* be 'N'.

NOTE 56 – The ability to specify INTEGRITY in GetInfo is deprecated. This capability is replaced with the ability to invoke GetFeatureInfo using FeatureId to indicate Feature E141.

- p) If  $IT \geq 21000$  and  $IT \leq 24999$ , or if  $IT \geq 11000$  and  $IT \leq 14999$ , then:

- i) Let *STMT* be the character string;

```
SELECT COALESCE (CHARACTER_VALUE, INTEGER_VALUE)
FROM INFORMATION_SCHEMA.SQL_IMPLEMENTATION_INFO
WHERE IMPLEMENTATION_INFO_ID = IT
```

- ii) Let *V* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.
- q) If  $IT \geq 25000$  and  $IT \leq 29999$ , or if  $IT \geq 15000$  and  $IT \leq 19999$ , then:
- i) Let *STMT* be the character string;

```
SELECT SUPPORTED_VALUE
FROM INFORMATION_SCHEMA.SQL_SIZING
WHERE IMPLEMENTATION_INFO_ID = IT
```

- ii) Let *V* be the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.
- 11) Let *BL* be the value of BufferLength.
- 12) Case:
- a) If the data type of *V* is character string, then the General Rules of Subclause 5.9, “Character string retrieval”, are applied with InfoValue, *V*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET LENGTH*, and *RETURNED LENGTH*, respectively.
  - b) Otherwise, InfoValue is set to *V*.

**6.39 GetLength****6.39 GetLength****Function**

Retrieve the length of the string value represented by a Large Object locator.

**Definition**

```

GetLength(
    StatementHandle      IN          INTEGER,
    LocatorType         IN          SMALLINT,
    Locator             IN          INTEGER,
    StringLength        OUT         INTEGER,
    IndicatorValue      OUT         INTEGER )
RETURNS SMALLINT

```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) If there is a prepared statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) If the value of *LocatorType* is not that of either CHARACTER LARGE OBJECT LOCATOR or BINARY LARGE OBJECT LOCATOR from Table 8, “Codes used for application data types in SQL/CLI”, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 4) Let *LL* be the Large Object locator value in *Locator*.
- 5) If *LL* is not a valid Large Object locator, then an exception condition is raised: *locator exception — invalid specification*.
- 6) Let *TL* be the actual data type of the Large Object string on the server.
- 7) If the value of *LocatorType* is not consistent with *TL* (e.g., a CHARACTER LARGE OBJECT LOCATOR for a BINARY LARGE OBJECT value), then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
- 8) Let *SV* be the string value that is represented by *LL*.
- 9) **Case:**
  - a) If *SV* contains the null value, then:
 

Case:

    - i) If *IndicatorValue* is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
    - ii) Otherwise:
      - 1) *IndicatorValue* is set to the appropriate ‘Code’ for SQL NULL DATA in Table 26, “Miscellaneous codes used in CLI”.
      - 2) The value of *StringLength* is implementation-dependent.

b) Otherwise:

- i) IndicatorValue is set to 0 (zero).
- ii) If *TL* is CHARACTER LARGE OBJECT, then StringLength is set to the length in characters of *SV*.
- iii) If *TL* is BINARY LARGE OBJECT, then StringLength is set to the length in octets of *SV*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.40 GetParamData

## 6.40 GetParamData

## Function

Retrieve the value of a dynamic output parameter.

## Definition

```
GetParamData (
    StatementHandle      IN      INTEGER,
    ParameterNumber     IN      SMALLINT,
    TargetType          IN      SMALLINT,
    TargetValue         OUT     ANY,
    BufferLength        IN      INTEGER,
    StrLen_or_Ind       OUT     INTEGER )
RETURNS SMALLINT
```

## General Rules

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) If there is no executed SQL-statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*; otherwise, let *P* be the SQL-statement that was prepared.
- 3) If *P* is not a <call statement>, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 4) Let *APD* be the current application parameter descriptor for *S* and let *N* be the value of the *TOP\_LEVEL\_COUNT* field of *APD*.
- 5) If *N* is less than zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor count*.
- 6) Let *PN* be the value of *ParameterNumber*.
- 7) If *PN* is less than 1 (one) or greater than *N*, then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 8) If *DATA\_POINTER* is non-zero for at least one of the first *N* item descriptor areas of *APD* for which the *TYPE* value is neither *ROW* nor *ARRAY*, then let *BPN* be the parameter number associated with such an item descriptor area and let *HBPN* be the value of *MAX(BPN)*. Otherwise, let *HBPN* be 0 (zero).
- 9) Let *IDA* be the item descriptor area of *APD* specified by *PN*. if the value of *TYPE* of *IDA* is either *ROW* or *ARRAY*, or if *LEVEL* of *IDA* is greater than 0 (zero), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 57 – *GetParamData* cannot be called to retrieve the data corresponding to a subordinate descriptor record such as, for example, from an individual field of a *ROW* type.
- 10) Let *IDA1* be the item descriptor area of *IPD* specified by *PN*.
- 11) Let *PM* be the value of *PARAMETER\_MODE* in *IDA1*.

- 12) If *PM* is PARAM MODE IN then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 13) If *PN* is not greater than *HBPN*, then  
Case:
- a) If the DATA\_POINTER field of *IDA* is not zero, then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
  - b) If the DATA\_POINTER field of *IDA* is zero, then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 58 – This implementation-defined feature determines whether parameters before the highest bound parameter can be accessed by GetParamData.
- 14) If there is a fetched parameter number associated with *S*, then let *FPN* be that parameter number; otherwise, let *FPN* be zero.  
NOTE 59 – “fetched parameter number” is the ParameterNumber value used with the previous invocation (if any) of the GetParamData routine with *S*. See the General Rules later in this Subclause where this value is set.
- 15) Case:
- a) If *FPN* is greater than zero and *PN* is not greater than *FPN*, then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 60 – This implementation-defined feature determines whether GetParam Data can only access parameters in ascending parameter number order.
  - b) If *FPN* is less than zero, then:
    - i) Let *AFPN* be the absolute value of *FPN*.
    - ii) Case:
      - 1) If *PN* is less than *AFPN*, then it is implementation-defined whether an exception condition is raised: *dynamic SQL error — invalid descriptor index*.  
NOTE 61 – This implementation-defined feature determines whether GetParamData can only access parameters in ascending parameter number order.
      - 2) If *PN* is greater than *AFPN*, then let *FPN* be *AFPN*.
- 16) Let *T* be the value of TargetType.
- 17) Let *HL* be the standard programming language of the invoking host program. Let *operative data type correspondence table* be the data type correspondence table for *HL* as specified in Subclause 5.15, “Data type correspondences”. Refer to the two columns of the operative data type correspondence table as the *SQL data type column* and the *host data type column*.
- 18) If either of the following is true, then an exception condition is raised: *CLI-specific condition — invalid data type in application descriptor*.
- a) *T* indicates neither DEFAULT nor APD TYPE and is not one of the code values in Table 8, “Codes used for application data types in SQL/CLI”.

**6.40 GetParamData**

- b) *T* is one of the code values in Table 8, “Codes used for application data types in SQL/CLI”, but the row that contains the corresponding SQL data type in the SQL data type column of the operative data type correspondence table contains ‘None’ in the host data type column.
- 19) If *T* does not indicate APD TYPE, then the data type of the <target specification> described by *IDA* is set to *T*.
- 20) Let *IPD* be the implementation parameter descriptor associated with *S*.
- 21) If the value of the TYPE field of *IDA* indicates DEFAULT, then:
- Let *PT*, *P*, and *SC* be the values of the TYPE, PRECISION, and SCALE fields, respectively, for the *PN*-th item descriptor area of *IPD* for which LEVEL is 0 (zero).
  - The data type, precision, and scale of the <target specification> described by *IDA* are set to *PT*, *P*, and *SC*, respectively, for the purposes of this GetParamData invocation only.
- 22) If *IDA* is not valid as specified in Subclause 5.13, “Description of CLI item descriptor areas”, then an exception condition is raised: *dynamic SQL error — using clause does not match target specifications*.
- 23) Let *TT* be the value of the TYPE field of *IDA*.
- 24) Case:
- If *TT* indicates CHARACTER, then:
    - Let *UT* be the code value corresponding to CHARACTER VARYING as specified in Table 7, “Codes used for implementation data types in SQL/CLI”.
    - Let *CL* be the implementation-defined maximum length for a CHARACTER VARYING data type.
  - Otherwise, let *UT* be *TT* and let *CL* be zero.
- 25) Case:
- If *FPN* is less than zero, then
 

Case:

    - If *TT* does not indicate CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, then *AFPN* becomes the *fetch parameter number* associated with *S* and an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
    - Otherwise, let *FL*, *DV*, and *DL* be the fetched length, data value and data length, respectively, associated with *FPN* and let *TV* be the result of the <string value function>:

```
SUBSTRING (DV FROM (FL+1))
```
  - Otherwise:
    - Let *FL* be zero.

- ii) Let *SDT* be the effective data type of the *PCN*-th <select list> column as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME fields in the *PN*-th item descriptor area of *IPD*. Let *SV* be the value of the parameter, with data type *SDT*.
- iii) Let *TDT* be the effective data type of the *PN*-th <target specification> as represented by the type *UT*, the length value *CL*, and the values of the PRECISION, SCALE, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, and USER\_DEFINED\_TYPE\_NAME fields of *IDA*.
- iv) Case:
- 1) If *TDT* is a locator type, then;
    - A) If *SV* is not the null value, then a locator *L* that uniquely identifies *SV* is generated and the value of *TV* of the *i*-th bound target is set to an implementation-dependent four-octet value that represents *L*.
    - B) Otherwise, the value *TV* of the *PN*-th <target specification> is the null value.
  - 2) If *SDT* and *TDT* are predefined data types, then
 

Case:

    - A) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *TDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *TDT*, and the result is the value *TV* of the *PN*-th <target specification>.
    - B) Otherwise:
      - I) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
      - II) If the <cast specification>
 

```
CAST ( SV AS TDT )
```

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

III) The <cast specification>

CAST ( SV AS TDT )

is effectively performed, and is the value *TV* of the *PN*-th <target specification>.

3) If *SDT* is a user-defined type and *TDT* is a predefined data type, then:

- A) Let *DT* be the data type identified by *SDT*.
- B) If the current SQL-session has a group name corresponding to the user-defined name of *DT*, then let *GN* be that group name; otherwise, let *GN* be the default transform group name associated with the current SQL-session.
- C) The Syntax Rules of Subclause 10.15, "Determination of a from-sql function", in ISO/IEC 9075-2, are applied with *DT* and *GN* as *TYPE* and *GROUP*, respectively.

Case:

- I) If there is an applicable from-sql function, then let *FSF* be that from-sql function and let *FSFRT* be the <returns data type> of *FSF*.

Case:

- 1) If *FSFRT* is compatible with *TDT*, then the from-sql function *TSF* is effectively invoked with *SV* as its input parameter and the <return value> is the value *TV* of the *CN*-th <target specification>.
- 2) Otherwise, an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

- II) Otherwise, an exception condition is raised: *dynamic SQL error — data type transform function violation*.

26) *PN* becomes the *fetch parameter number* associated with *S*.

27) If *TV* is the null value, then

Case:

- a) If *StrLen\_or\_Ind* is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
- b) Otherwise, *StrLen\_or\_Ind* is set to the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", and the value of *TargetValue* is implementation-dependent.

28) Let *OL* be the value of *BufferLength*.

29) If null termination is *true* for the current SQL-environment, then let *NB* be the length in octets of a null terminator in the character set of the *i*-th bound target; otherwise let *NB* be 0 (zero).

30) If *TV* is not the null value, then:

- a) *StrLen\_or\_Ind* is set to 0 (zero).

## b) Case:

i) If *TT* does not indicate CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, then TargetValue is set to *TV*.

## ii) Otherwise:

1) If *TT* is CHARACTER or CHARACTER LARGE OBJECT, then:

A) If *TV* is a zero-length character string, then it is implementation-defined whether or not an exception condition is raised: *data exception — zero-length character string*.

B) The General Rules of Subclause 5.9, “Character string retrieval”, are applied with TargetValue, *TV*, *OL*, and StrLen\_or\_Ind as *TARGET*, *VALUE*, *OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

2) If *TT* is BINARY LARGE OBJECT, then the General Rules of Subclause 5.10, “Binary large object string retrieval”, are applied with TargetValue, *TV*, *OL*, and StrLen\_or\_Ind as *TARGET*, *VALUE*, *OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

3) If *FCN* is not less than zero, then let *DV* be *TV* and let *DL* be the length of *TV* in octets.

4) Let *FL* be  $(FL + OL - NB)$ .

5) If *FL* is less than *DL*, then *PN* becomes the *fetched parameter number* associated with the fetched parameter associated with *S* and *FL*, *DV* and *DL* become the fetched length, data value, and data length, respectively, associated with the fetched parameter number.

**6.41 GetPosition****6.41 GetPosition****Function**

Retrieve the starting position of a string value within another string value, where the second string value is represented by a Large Object locator.

**Definition**

```
GetPosition(
    StatementHandle      IN      INTEGER,
    LocatorType          IN      SMALLINT,
    SourceLocator        IN      INTEGER,
    SearchLocator        IN      INTEGER,
    SearchLiteral        IN      ANY,
    SearchLiteralLength IN      INTEGER,
    FromPosition        IN      INTEGER,
    LocatedAt           OUT     INTEGER,
    IndicatorValue       OUT     INTEGER )
RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is a prepared statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) If the value of LocatorType is not that of either CHARACTER LARGE OBJECT LOCATOR or BINARY LARGE OBJECT LOCATOR from Table 8, “Codes used for application data types in SQL/CLI”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) Let *SRCL* be the Large Object locator value in SourceLocator.
- 5) If *SRCL* is not a valid Large Object locator, then an exception condition is raised: *locator exception — invalid specification*.
- 6) Let *SRCT* be the actual data type of the Large Object string on the server.
- 7) If the value of LocatorType is not consistent with *SRCT* (e.g., a CHARACTER LARGE OBJECT LOCATOR for a BINARY LARGE OBJECT value), then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
- 8) Case:
  - a) If *SRCL* represents the null value, then
 

Case:

    - i) If IndicatorValue is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
    - ii) Otherwise, IndicatorValue is set to the appropriate ‘Code’ for SQL NULL DATA in Table 26, “Miscellaneous codes used in CLI”, the value of all other output arguments is implementation-dependent, and no further rules of this Subclause are applied.

- b) Otherwise:
- i) IndicatorValue is set to 0 (zero).
  - ii) Let *SRCV* be the actual value that is represented by *SRCL*.
- 9) Let *SLL* be the value of SearchLiteralLength.
- 10) Case:
- a) If *SLL* is equal to zero, then:
    - i) Let *SCHL* be the Large Object locator value in SearchLocator.
    - ii) If *SCHL* is not a valid Large Object locator, then an exception condition is raised: *locator exception — invalid specification*.
    - iii) Let *SCHT* be the actual data type of the Large Object string on the server.
    - iv) If the value of LocatorType is not consistent with *SCHT*, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
    - v) If *SCHL* represents the null value, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
    - vi) Let *SCHV* be the actual value that is represented by *SCHL*.
  - b) Otherwise,
    - Case:
      - i) If SearchLiteral is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
      - ii) Otherwise, let *SCHV* be the value of that literal.
- 11) Let *FP* be the value of FromPosition. Let *SRCVL* be the length of *SRCV* (in characters if *SRCV* is a character string and in octets if *SRCV* is a binary string).
- 12) If *FP* is less than 1 (one) or greater than *SRCVL*, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 13) If *FP* is greater than 1 (one), then let *SRCV* be the value of  
 SUBSTRING (*SRCV* FROM *FP*)
- 14) Case:
- a) If *SRCV* contains a string *MV* of contiguous characters (if *SRCV* is a character string) or contiguous octets (if *SRCV* is a binary string) that is the same as the string of characters or octets (as appropriate) in *SCHV* then LocatedAt is set to the starting position (in characters or octets, as appropriate) of the first occurrence of *MV* within *SRCV*.
  - b) Otherwise, LocatedAt is set to 0 (zero).

## 6.42 GetSessionInfo

### Function

Get information about <general value specification>s supported by the implementation.

### Definition

```
GetSessionInfo(  
    ConnectionHandle    IN        INTEGER ,  
    InfoType            IN        SMALLINT ,  
    InfoValue           OUT       ANY ,  
    BufferLength        IN        SMALLINT ,  
    StringLength       OUT       SMALLINT )  
RETURNS SMALLINT
```

### General Rules

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Case:
  - a) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.
  - b) Otherwise, let *EC* be the established SQL-connection associated with *C*.
- 3) If *EC* is not the current SQL-connection, then the General Rules of Subclause 5.3, “Implicit set connection”, are applied to *EC* as the dormant SQL-connection.
- 4) Let *IT* be the value of InfoType.
- 5) If *IT* is not one of the codes in Table 29, “Codes and data types for session implementation information”, then an exception condition is raised: *CLI-specific condition — invalid information type*.
- 6) Let *GVS* be the value of <general value specification> in the same row as *IT* in Table 29, “Codes and data types for session implementation information”.
- 7) Let *SH* be an allocated statement handle on *C*.
- 8) Let *STMT* be the character string:

```
SELECT UNIQUE GVS
FROM INFORMATION_SCHEMA.TABLES -- Any table would do
WHERE 1 = 1                      ---Any predicate that is TRUE would do
```

- 9) *V* is set to the single column value returned by the implicit invocation of ExecDirect with *SH* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.
- 10) If any status condition, such as connection failure, is caused by the implicit invocation of ExecDirect, then:
  - a) The status records returned by ExecDirect on *SH* are returned on ConnectionHandle.
  - b) This invocation of GetSessionInfo returns the same return code that was returned by the implicit invocation of ExecDirect and no further Rules of this Subclause are applied.
- 11) Let *BL* be the value of BufferLength.
- 12) The General Rules of Subclause 5.9, "Character string retrieval", are applied with InfoValue, *V*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.43 GetStmtAttr

## 6.43 GetStmtAttr

**Function**

Get the value of an SQL-statement attribute.

**Definition**

```
GetStmtAttr (
    StatementHandle      IN      INTEGER,
    Attribute            IN      INTEGER,
    Value                OUT     ANY,
    BufferLength         IN      INTEGER,
    StringLength        OUT     INTEGER )
RETURNS SMALLINT
```

**General Rules**

- 1) Let *S* be the allocated SQL-statement identified by `StatementHandle`.
- 2) Let *A* be the value of `Attribute`.
- 3) If *A* is not one of the code values in Table 17, “Codes used for statement attributes”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) Case:
  - a) If *A* indicates `APD_HANDLE`, then `Value` is set to the handle of the current application parameter descriptor for *S*.
  - b) If *A* indicates `ARD_HANDLE`, then `Value` is set to the handle of the current application row descriptor for *S*.
  - c) If *A* indicates `IPD_HANDLE`, then `Value` is set to the handle of the implementation parameter descriptor associated with *S*.
  - d) If *A* indicates `IRD_HANDLE`, then `Value` is set to the handle of the implementation row descriptor associated with *S*.
  - e) If *A* indicates `CURSOR_SCROLLABLE`, then
 

Case:

    - i) If the implementation supports scrollable cursors, then
 

Case:

      - 1) If the value of the `CURSOR_SCROLLABLE` attribute of *S* is `NONSCROLLABLE`, then `Value` is set to the code value for `NONSCROLLABLE` from Table 26, “Miscellaneous codes used in CLI”.
      - 2) If the value of the `CURSOR_SCROLLABLE` attribute of *S* is `SCROLLABLE`, then `Value` is set to the code value for `SCROLLABLE` from Table 26, “Miscellaneous codes used in CLI”.

- ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented.*
- f) If *A* indicates CURSOR SENSITIVITY, then
- Case:
- i) If the implementation supports cursor sensitivity, then
- Case:
- 1) If the value of the CURSOR SENSITIVITY attribute of *S* is ASENSITIVE, then Value is set to the code value for ASENSITIVE from Table 26, “Miscellaneous codes used in CLI”.
  - 2) If the value of the CURSOR SENSITIVITY attribute of *S* is INSENSITIVE, then Value is set to the code value for INSENSITIVE from Table 26, “Miscellaneous codes used in CLI”.
  - 3) If the value of the CURSOR SENSITIVITY attribute of *S* is SENSITIVE, then Value is set to the code value for SENSITIVE from Table 26, “Miscellaneous codes used in CLI”.
- ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented.*
- g) If *A* indicates METADATA ID, then
- Case:
- i) If the METADATA ID attribute for *S* has been set by the SetStmtAttr routine, then Value is set to the code value of that attribute from Table 19, “Data types of attributes”.
- ii) Otherwise, Value is set to the code value for FALSE from Table 26, “Miscellaneous codes used in CLI”.
- h) If *A* indicates CURSOR HOLDABLE, then
- Case:
- i) If the implementation supports cursor holdability, then
- Case:
- 1) If the value of the CURSOR HOLDABLE attribute of *S* is NONHOLDABLE, then the Value is set to the code value for NONHOLDABLE from Table 26, “Miscellaneous codes used in CLI”.
  - 2) If the value of the CURSOR HOLDABLE attribute of *S* is HOLDABLE, then the Value is set to the code value for HOLDABLE from Table 26, “Miscellaneous codes used in CLI”.
  - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value.*
- ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented.*

**6.43 GetStmtAttr**

- i) If *A* indicates CURRENT OF POSITION, then

Case:

- i) If there is no fetched rowset associated with *S*, then an exception condition is raised:  
*CLI-specific condition — invalid cursor state*.

- ii) Otherwise, Value is set to the current position within the fetched rowset associated with *S*.

- j) If *A* indicates NEST DESCRIPTOR, then

Case:

- i) If the NEST DESCRIPTOR attribute for *S* has been set by the SetStmtAttr routine, then Value is set to the code value of that attribute from Table 19, "Data types of attributes".

- ii) Otherwise, VALUE is set to the code value for FALSE from Table 26, "Miscellaneous codes used in CLI".

- 5) If *A* specifies an implementation-defined statement attribute, then

Case:

- a) If the data type for the statement attribute is specified in Table 19, "Data types of attributes", as INTEGER, then Value is set to the value of the implementation-defined statement attribute.

- b) Otherwise:

- i) Let *BL* be the value of BufferLength.

- ii) Let *AV* be the value of the implementation-defined statement attribute.

- iii) The General Rules of Subclause 5.9, "Character string retrieval", are applied with Value, *AV*, *BL*, and StringLength as *TARGET*, *VALUE*, *TARGET OCTET LENGTH*, and *RETURNED OCTET LENGTH*, respectively.

## 6.44 GetSubString

### Function

Either retrieve a portion of a string value that is represented by a Large Object locator or create a Large Object value at the server and retrieve a Large Object locator for that value.

### Definition

```

GetSubString(
    StatementHandle      IN      INTEGER,
    LocatorType         IN      SMALLINT,
    SourceLocator       IN      INTEGER,
    FromPosition       IN      INTEGER,
    ForLength          IN      INTEGER,
    TargetType         IN      SMALLINT,
    TargetValue        OUT     ANY,
    BufferLength       IN      INTEGER,
    StringLength      OUT     INTEGER,
    IndicatorValue     OUT     INTEGER )
RETURNS SMALLINT

```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is a prepared statement associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 3) If the value of LocatorType is not that of either CHARACTER LARGE OBJECT LOCATOR or BINARY LARGE OBJECT LOCATOR from Table 8, “Codes used for application data types in SQL/CLI”, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 4) Let *SRCL* be the Large Object locator value in SourceLocator.
- 5) If *SRCL* is not a valid Large Object locator, then an exception condition is raised: *locator exception — invalid specification*.
- 6) Let *SRCT* be the actual data type of the Large Object string on the server.
- 7) If the value of LocatorType is not consistent with *SRCT* (e.g., a CHARACTER LARGE OBJECT LOCATOR for a BINARY LARGE OBJECT value), then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.
- 8) Let *TT* be the value of TargetType.
- 9) If *TT* is not equal to one of the values for CHARACTER, CHARACTER LARGE OBJECT, BINARY LARGE OBJECT, CHARACTER LARGE OBJECT LOCATOR, or BINARY LARGE OBJECT LOCATOR from Table 8, “Codes used for application data types in SQL/CLI”, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 10) If *SRCL* is the null value, then

## 6.44 GetSubString

Case:

- a) If IndicatorValue is a null pointer, then an exception condition is raised: *data exception — null value, no indicator parameter*.
- b) Otherwise, IndicatorValue is set to the value of the 'Code' for SQL NULL DATA from Table 26, "Miscellaneous codes used in CLI", the values of all other output arguments are implementation-dependent, and no further rules of this Subclause are applied.

11) Let *OL* be the value of BufferLength.

12) If *SRCL* is not the null value, then:

- a) IndicatorValue is set to 0 (zero).
- b) Let *SRCV* be the large object value that is represented by *SRCL*.
- c) If *SRCV* is a character string, then let *SRCVL* be the length of *SRCV* in characters; if *SRCV* is a binary string, then let *SRCVL* be the length of *SRCV* in octets.
- d) Let *FP* be the value of FromPosition and let *FL* be the value of ForLength.
- e) If any of the following is true, then an exception condition is raised: *CLI-specific condition — invalid attribute value*.
  - i) *FP* is less than 1 (one).
  - ii) *FL* is less than 1 (one).
  - iii)  $FP+FL-1$  is greater than *SRCVL*.
- f) Let *RV* be the value of the string that starts at position *FP* and ends at position  $FP+FL-1$  in *SRCV* (where the positions are in characters or octets, as appropriate).
- g) Let *RVL* be the number of octets in *RV*.
- h) Case:
  - i) If *TT* indicates CHARACTER or CHARACTER LARGE OBJECT, then:
    - 1) If *TV* is a zero-length character string, then it is implementation-defined whether or not an exception condition is raised: *data exception — zero-length character string*.
    - 2) The General Rules of Subclause 5.9, "Character string retrieval", are applied with TargetValue, *RV*, *OL*, and *RVL* as *TARGET*, *VALUE*, *OCTET LENGTH* and *RETURNED OCTET LENGTH*, respectively.
  - ii) If *TT* indicates BINARY LARGE OBJECT, then the General Rules of Subclause 5.10, "Binary large object string retrieval", are applied with TargetValue, *RV*, *OL*, and *RVL* as *TARGET*, *VALUE*, *OCTET LENGTH* and *RETURNED OCTET LENGTH*, respectively.
  - iii) Otherwise, set TargetValue to the value of a Large Object locator that represents the value *RV* at the server.

## 6.45 GetTypeInfo

### Function

Get information about one or all of the predefined data types supported by the implementation.

### Definition

```
GetTypeInfo (
    StatementHandle      IN      INTEGER,
    DataType             IN      SMALLINT )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) If an open cursor is associated with *S*, then an exception condition is raised: *invalid cursor state*.
- 3) Let *D* be the value of *DataType*.
- 4) If *D* is not the code value corresponding to ALL TYPES in Table 26, “Miscellaneous codes used in CLI”, and is not one of the code values in Table 37, “Codes used for concise data types”, then an exception condition is raised: *CLI-specific condition — invalid data type*.
- 5) Let *C* be the allocated SQL-connection with which *S* is associated.
- 6) Let *EC* be the established SQL-connection associated with *C* and let *SS* be the SQL-server associated with *EC*.
- 7) Let *TYPE\_INFO* be a table, with a definition and description as specified below, that contains a row for each predefined data type supported by *SS*. For all supported predefined data types for which more than one name is supported, it is implementation-defined whether *TYPE\_INFO* contains a single row or a row for each supported name.

```
CREATE TABLE TYPE_INFO (
    TYPE_NAME          CHARACTER VARYING(128) NOT NULL
        PRIMARY KEY,
    DATA_TYPE         SMALLINT              NOT NULL,
    COLUMN_SIZE        INTEGER,
    LITERAL_PREFIX     CHARACTER VARYING(128),
    LITERAL_SUFFIX     CHARACTER VARYING(128),
    CREATE_PARAMS      CHARACTER VARYING(128)
        CHARACTER SET SQL_TEXT,
    NULLABLE           SMALLINT              NOT NULL
        CHECK ( NULLABLE IN (0, 1, 2) ),
    CASE_SENSITIVE     SMALLINT              NOT NULL
        CHECK ( CASE_SENSITIVE IN (0, 1) ),
    SEARCHABLE         SMALLINT              NOT NULL
        CHECK ( SEARCHABLE IN (0, 1, 2, 3) ),
    UNSIGNED_ATTRIBUTE SMALLINT
        CHECK ( UNSIGNED_ATTRIBUTE IN (0, 1)
            OR UNSIGNED_ATTRIBUTE IS NULL),
    FIXED_PREC_SCALE   SMALLINT NOT NULL
        CHECK ( FIXED_PREC_SCALE IN (0, 1)),
    AUTO_UNIQUE_VALUE  SMALLINT NOT NULL
        CHECK ( AUTO_UNIQUE_VALUE IN (0, 1)),
```

## 6.45 GetTypeInfo

```

LOCAL_TYPE_NAME      CHARACTER VARYING(128)
CHARACTER SET SQL_TEXT,
MINIMUM_SCALE        INTEGER,
MAXIMUM_SCALE        INTEGER,
SQL_DATA_TYPE        SMALLINT          NOT NULL,
SQL_DATETIME_SUB     SMALLINT
CHECK ( SQL_DATETIME_SUB IN (1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13)
OR SQL_DATETIME_SUB IS NULL),
NUM_PREC_RADIX       INTEGER,
INTERVAL_PRECISION   SMALLINT )

```

## 8) The description of the table TYPE\_INFO is:

- a) The value of TYPE\_NAME is the name of the data type. If multiple names are supported for this data type and TYPE\_INFO contains only a single row for this data type, then it is implementation-defined which of the names is in TYPE\_NAME.
- b) The value of DATA\_TYPE is the code value for the predefined data type as defined in Table 37, "Codes used for concise data types".
- c) The value of COLUMN\_SIZE is:
  - i) The null value if the data type has neither a length nor a precision.
  - ii) The maximum length in characters for a character string data type.
  - iii) The maximum length in bits for a bit string data type.
  - iv) The maximum or fixed precision, as appropriate, for a numeric data type.
  - v) The maximum or fixed length in positions, as appropriate, for a datetime or interval data type.
  - vi) An implementation-defined value for an implementation-defined data type that has a length or a precision.
- d) The value of LITERAL\_PREFIX is the character string that must precede the data type value when a <literal> of this data type is specified. The value of LITERAL\_PREFIX is the null value if no such string is required.
- e) The value of LITERAL\_SUFFIX is the character string that must follow the data type value when a <literal> of this data type is specified. The value of LITERAL\_SUFFIX is the null value if no such string is required.
- f) The value of CREATE\_PARAMS is a comma-separated list of specifiable attributes for the data type in the order in which the attributes may be specified. The attributes <length>, <precision>, <scale>, and <time fractional seconds precision> appear in the list as LENGTH, PRECISION, SCALE, and PRECISION, respectively. The appearance of attributes in implementation-defined data types is implementation-defined.
- g) The value of NULLABLE is 1 (one).
- h) The value of CASE\_SENSITIVE is 1 (one) if the data type is a character string type and the default collation for its implementation-defined implicit character repertoire would result in a case sensitive comparison when two values with this data type are compared. Otherwise, the value of CASE\_SENSITIVE is 0 (zero).

- i) Refer to the <comparison predicate>, <between predicate>, <in predicate>, <null predicate>, <quantified comparison predicate>, and <match predicate> as the *basic predicates*. If the data type can be the data type of an operand in the <like predicate>, then let  $V1$  be 1 (one); otherwise let  $V1$  be 0 (zero). If the data type can be the data type of a column of a <row value constructor> immediately contained in a basic predicate, then let  $V2$  be 2; otherwise let  $V2$  be 0 (zero). The value of SEARCHABLE is  $(V1+V2)$ .
- j) The value of UNSIGNED\_ATTRIBUTE is
- Case:
- i) If the data type is unsigned, then 1 (one).
  - ii) If the data type is signed, then 0 (zero).
  - iii) If a sign is not applicable to the data type, then the null value.
- k) The value of FIXED\_PREC\_SCALE is
- Case:
- i) If the data type is an exact numeric with a fixed precision and scale, then 1 (one).
  - ii) Otherwise, 0 (zero).
- l) The value of AUTO\_UNIQUE\_VALUE is
- Case:
- i) If a column of this data type is set to a value unique among all rows of that column when a row is inserted, then 1 (one).
  - ii) Otherwise, 0 (zero).
- m) The value of LOCAL\_TYPE\_NAME is an implementation-defined localized representation of the name of the data type, intended primarily for display purposes. The value of LOCAL\_TYPE\_NAME is the null value if a localized representation is not supported.
- n) The value of MINIMUM\_SCALE is:
- i) The null value if the data type has neither a scale nor a fractional seconds precision.
  - ii) The minimum value of the scale for a data type that has a scale.
  - iii) The minimum value of the fractional seconds precision for a data type that has a fractional seconds precision.
- o) The value of MAXIMUM\_SCALE is:
- i) The null value if the data type has neither a scale nor a fractional seconds precision.
  - ii) The maximum value of the scale for a data type that has a scale.
  - iii) The maximum value of the fractional seconds precision for a data type that has a fractional seconds precision.
- p) The value of SQL\_DATA\_TYPE is the code value for the predefined data type as defined in Table 7, "Codes used for implementation data types in SQL/CLI".

**6.45 GetTypeInfo**

q) The value of SQL\_DATETIME\_SUB is

Case:

- i) If the data type is a datetime type, then the code value for the datetime type as defined in Table 9, "Codes associated with datetime data types in SQL/CLI".
- ii) If the data type is an interval type, then the code value for the interval type as defined in Table 10, "Codes associated with <interval qualifier> in SQL/CLI".
- iii) Otherwise, the null value.

r) The value of NUM\_PREC\_RADIX is

Case:

- i) If the value of PRECISION is the value of a precision, then the radix of that precision.
- ii) Otherwise, the null value.

s) The value of SQL\_INTERVAL\_PRECISION is

Case:

- i) If the data type is an interval type, then <interval leading field precision>.
- ii) Otherwise, the null value.

9) Case:

- a) If  $D$  is the code value corresponding to ALL TYPES in Table 26, "Miscellaneous codes used in CLI", then let  $P$  be the character string

```
SELECT *
FROM TYPE_INFO
ORDER BY DATA_TYPE
```

- b) Otherwise, let  $P$  be the character string

```
SELECT *
FROM TYPE_INFO
WHERE DATA_TYPE =  $d$ 
```

- 10) ExecDirect is implicitly invoked with  $S$  as the value of StatementHandle,  $P$  as the value of StatementText, and the length of  $P$  as the value of TextLength.

## 6.46 MoreResults

### Function

Determine whether there are more result sets available on a statement handle and, if there are, initialize processing for those result sets.

### Definition

```
MoreResults (
    StatementHandle      IN      INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no executed SQL-statement associated with *S*, then a completion condition is raised: *no data — no additional dynamic result sets returned*.
- 3) Case:
  - a) If there is no cursor associated with *S* and there exists an implementation-defined capability to support that situation, then implementation-defined rules are evaluated and no further General Rules of this Subclause are evaluated.
  - b) If there is no cursor associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - c) Otherwise, let *CR* be the cursor associated with *S*.
- 4) If *CR* is currently open, then:
  - a) *CR* is placed in the closed state.
  - b) Any fetched row associated with *S* is removed from association with *S*.
- 5) Case:
  - a) If there is another result set that was returned for the executed statement associated with *S*, then:
    - i) Let *SS* be the <dynamic select statement> or <dynamic single row select statement> that was used to create the result set.
    - ii) The General Rules of Subclause 5.5, “Implicit DESCRIBE USING clause”, are applied with *SS* and *S* as *SOURCE* and *ALLOCATED STATEMENT*, respectively.
    - iii) *CR* is opened on that result set and positioned before the first row.
    - iv) A completion condition is raised: *successful completion*.
  - b) Otherwise, a completion condition is raised: *no data — no additional dynamic result sets returned*.

**6.47 NextResult****6.47 NextResult****Function**

Determine whether there are more result sets available on a statement handle and, if there are, initialize processing for the next result set on a separate statement handle.

**Definition**

```
NextResult (
    StatementHandle1    IN          INTEGER,
    StatementHandle2    IN          INTEGER )
RETURNS SMALLINT
```

**General Rules**

- 1) Let *S1* be the allocated SQL-statement identified by StatementHandle1.
- 2) If there is no executed SQL-statement associated with *S1*, then a completion condition is raised: *no data — no additional dynamic result sets returned*.
- 3) Let *S2* be the allocated SQL-statement identified by StatementHandle2.
- 4) If there is a prepared statement associated with *S2*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 5) Case:
  - a) If there is another result set that was returned for the executed statement associated with *S1*, then:
    - i) A cursor *CR* is associated with *S2*.
    - ii) Let *SS* be the <dynamic select statement> or <dynamic single row select statement> that was used to create the result set.
    - iii) The General Rules of Subclause 5.5, “Implicit DESCRIBE USING clause”, are applied with *SS* and *S2* as *SOURCE* and *ALLOCATED STATEMENT*, respectively.
    - iv) *CR* is opened on that result set and positioned before the first row.
    - v) A completion condition is raised: *successful completion*.
  - b) Otherwise, a completion condition is raised: *no data — no additional dynamic result sets returned*.

## 6.48 NumResultCols

### Function

Get the number of result columns.

### Definition

```
NumResultCols (
    StatementHandle    IN    INTEGER,
    ColumnCount        OUT   SMALLINT )
RETURNS SMALLINT
```

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) Case:
  - a) If there is no prepared or executed statement associated with  $S$ , then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) Otherwise, let  $D$  be the implementation row descriptor associated with  $S$  and let  $N$  be the value of the TOP\_LEVEL\_COUNT field of  $D$ .
- 3) ColumnCount is set to  $N$ .

## 6.49 ParamData

### Function

Process a deferred parameter value.

### Definition

```
ParamData (  
    StatementHandle    IN    INTEGER,  
    Value              OUT   ANY )  
RETURNS SMALLINT
```

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by `StatementHandle`.
- 2) Case:
  - a) If there is no deferred parameter number associated with  $S$ , then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) Otherwise, let  $DPN$  be the deferred parameter number associated with  $S$ .
- 3) Let  $APD$  be the current application parameter descriptor for  $S$  and let  $N$  be the value of the `TOP_LEVEL_COUNT` field of  $APD$ .
- 4) For each item descriptor area for which `DEFERRED` is true in the first  $N$  item descriptor areas of  $APD$  for which `LEVEL` is 0 (zero), refer to the corresponding <dynamic parameter specification> value as a *deferred parameter value*.
- 5) Let  $IDA$  be the  $DPN$ -th item descriptor area of  $APD$  and let  $PT$  and  $DP$  be the values of the `TYPE` and `DATA_POINTER` fields, respectively, of  $IDA$ .
- 6) If there is no parameter value associated with  $DPN$ , then  
Case:
  - a) If there is a `DATA_POINTER` value associated with  $DPN$ , then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) Otherwise:
    - i) Value is set to  $DP$ .
    - ii)  $DP$  becomes the `DATA_POINTER` value associated with  $DPN$ .
    - iii) An exception condition is raised: *CLI-specific condition — dynamic parameter value needed*.
- 7) Let  $IPD$  be the implementation parameter descriptor associated with  $S$ .
- 8) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 9) Let  $V$  be the parameter value associated with  $DPN$ .

## 10) Case:

a) If  $V$  is not the null value, then:

i) Case:

1) If  $PT$  indicates CHARACTER, then:A) Let  $LO$  be the parameter length associated with  $DPN$  and let  $L$  be the number of characters of  $V$  wholly contained in the first  $LO$  octets of  $V$ .B) If  $L$  exceeds the implementation-defined maximum length value for the CHARACTER data type, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*2) If  $PT$  indicates CHARACTER LARGE OBJECT, then:A) Let  $LO$  be the parameter length associated with  $DPN$  and let  $L$  be the number of characters of  $V$  wholly contained in the first  $LO$  octets of  $V$ .B) If  $L$  exceeds the implementation-defined maximum length value for the CHARACTER LARGE OBJECT data type, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*3) If  $PT$  indicates BINARY LARGE OBJECT, then:A) Let  $LO$  be the parameter length associated with  $DPN$  and let  $L$  be the number of characters of  $V$  wholly contained in the first  $LO$  octets of  $V$ .B) If  $L$  exceeds the implementation-defined maximum length value for the BINARY LARGE OBJECT data type, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*4) Otherwise, let  $L$  be zero.ii) Let  $SV$  be  $V$  with effective data type  $SDT$  as represented by the length value  $L$  and by the values of the TYPE, PRECISION, and SCALE fields of  $IDA$ .b) Otherwise, let  $SV$  be the null value.11) Let  $TDT$  be the effective data type of the  $DPN$ -th <dynamic parameter specification> as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields of the  $DPN$ -th item descriptor area of  $IPD$ .12) Let  $SDT$  be the effective data type of the  $DPN$ -th parameter as represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields in the corresponding item descriptor area of  $APD$ .

## 13) Case:

a) If  $SDT$  is a locator type, then let  $TV$  be the value  $SV$ .

## 6.49 ParamData

b) If *SDT* and *TDT* are predefined types, then

i) Case:

1) If the <cast specification>

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *TDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *TDT*, and the result is the value *TV* of the *i*-th bound target.

2) Otherwise:

A) If the <cast specification>

```
CAST ( SV AS TDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

B) If the <cast specification>

```
CAST ( SV AS TDT )
```

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

C) Let *TV* be the value obtained, with data type *TDT*, by effectively performing the <cast specification>

```
CAST ( SV AS TDT )
```

NOTE 62 — It is implementation-dependent whether the establishment of *TV* occurs at this time or during the preceding invocation of PutData.

ii) Let *UDT* be the effective data type of the actual *DPN*-th <dynamic parameter specification>, defined to be the data type represented by the values of the TYPE, LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, and SCOPE\_NAME fields that would automatically be set in the *DPN*-th item descriptor area of *IPD* if POPULATE IPD was true for *C*.

iii) Case:

1) If the <cast specification>

```
CAST ( TV AS UDT )
```

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, and there is an implementation-defined conversion from type *SDT* to type *UDT*, then that implementation-defined conversion is effectively performed, converting *SV* to type *UDT*, and the result is the value *TV* of the *i*-th bound target.

2) Otherwise:

A) If the <cast specification>

CAST ( TV AS UDT )

does not conform to the Syntax Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised: *dynamic SQL error — restricted data type attribute violation*.

B) If the <cast specification>

CAST ( TV AS UDT )

does not conform to the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2, then an exception condition is raised in accordance with the General Rules of Subclause 6.22, "<cast specification>", in ISO/IEC 9075-2.

C) The <cast specification>

CAST ( TV AS UDT )

is effectively performed and is the value of the *DPN*-th dynamic parameter.

14) Let *PN* be the parameter number associated with a deferred parameter value and let *HPN* be the value of MAX(*PN*).

15) If *DPN* is not equal to *HPN*, then:

a) Let *NPN* be the lowest value of *PN* for which  $DPN < NPN \leq HPN$ .

b) Let *DP* be the value of the DATA\_POINTER field of the *NPN*-th item descriptor area of *APD* for which LEVEL is 0 (zero).

c) *NPN* becomes the deferred parameter number associated with *S* and *DP* becomes the DATA\_POINTER value associated with the deferred parameter number.

d) An exception condition is raised: *CLI-specific condition — dynamic parameter value needed*.

16) If *DPN* is equal to *HPN*, then:

a) *DPN* is removed from association with *S*.

b) Case:

i) If there is a select source associated with *S*, then:

1) Let *SS* be the select source associated with *S*.

2) If the value of the CURSOR\_SCROLLABLE attribute of *S* is SCROLLABLE, then let *CT* be 'SCROLL'; otherwise, let *CT* be an empty string.

3) Case:

A) If the value of the CURSOR\_SENSITIVITY attribute of *S* is INSENSITIVE, then let *CS* be 'INSENSITIVE'.

B) If the value of the CURSOR\_SENSITIVITY attribute of *S* is SENSITIVE, then let *CS* be 'SENSITIVE'.

## 6.49 ParamData

- C) Otherwise, let *CS* be 'ASENSITIVE'.
- 4) If the value of the CURSOR HOLDABLE attribute of *S* is HOLDABLE, then let *CH* be 'WITH HOLD'; otherwise, let *CH* be an empty string.
- 5) Let *CN* be the name of the cursor associated with *S* and let *CR* be the following <declare cursor>:
- ```
DECLARE CN CS CT CURSOR CH FOR SS
```
- 6) A copy of *SS* is effectively created in which:
- A) Each <dynamic parameter specification> is replaced by the value of the corresponding dynamic parameter.
- B) Each <value specification> generally contained in *SS* that is CURRENT\_USER, CURRENT\_ROLE, SESSION\_USER, or SYSTEM\_USER is replaced by the value resulting from evaluation of CURRENT\_USER, CURRENT\_ROLE, SESSION\_USER, or SYSTEM\_USER, respectively, with all such evaluations effectively done at the same instant in time.
- C) Each <datetime value function> generally contained in *SS* is replaced by the value resulting from evaluation of that <datetime value function>, with all evaluations effectively done at the same instant in time.
- D) Each <value specification> generally contained in *S* that is CURRENT\_PATH is replaced by the value resulting from evaluation of CURRENT\_PATH, with all such evaluations effectively done at the same instant in time.
- 7) Let *T* be the table specified by the copy of *SS*.
- 8) A table descriptor for *T* is effectively created.
- 9) The General Rules of Subclause 14.1, "<declare cursor>", in ISO/IEC 9075-2, are applied to *CR*.
- 10) Case:
- A) If *CR* specifies INSENSITIVE, then a copy of *T* is effectively created and the cursor identified by *CN* is placed in the open state and its position is before the first row of the copy of *T*.
- B) Otherwise, the cursor identified by *CN* is placed in the open state and its position is before the first row of *T*.
- 11) If *CR* specifies SENSITIVE, and the implementation is unable to guarantee that significant changes will be invisible through *CR* during the SQL-transaction in which *CR* is opened and every subsequent SQL-transaction during which it may be held open, then an exception condition is raised: *cursor sensitivity exception — request rejected*.
- 12) If *CR* specifies SENSITIVE, and the implementation is unable to guarantee that significant changes will be visible through *CR* during the SQL-transaction in which *CR* is opened, then an exception condition is raised: *cursor sensitivity exception — request rejected*.

NOTE 63 – The visibility of significant changes through a sensitive holdable cursor during a subsequent SQL-transaction is implementation-defined.

- 13) Whether an implementation is able to disallow significant changes that would not be visible through a currently open cursor is implementation-defined.
- ii) Otherwise:
- 1) Let *SS* be the statement source associated with *S*.
  - 2) *SS* is removed from association with *S*.
  - 3) Case:
    - A) If *SS* is a <preparable dynamic delete statement: positioned>, then:
      - I) Let *CR* be the cursor referenced by *SS*.
      - II) The General Rules in Subclause 15.21, "<preparable dynamic delete statement: positioned>", in ISO/IEC 9075-5 are applied to *SS*.
      - III) If the execution of *SS* deleted the current row of *CR*, then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.
    - B) If *SS* is a <preparable dynamic update statement: positioned>, then:
      - I) Let *CR* be the cursor referenced by *SS*.
      - II) All the General Rules in Subclause 15.22, "<preparable dynamic update statement: positioned>", in ISO/IEC 9075-5 apply to *SS*.
      - III) If the execution of *SS* updated the current row of *CR*, then the effect on the fetched row, if any, associated with the allocated SQL-statement under which that current row was established, is implementation-defined.
    - C) Otherwise, the results of the execution are the same as if the statement were contained in an <externally-invoked procedure> and executed; these are described in Subclause 10.4, "<routine invocation>", in ISO/IEC 9075-2.
  - 4) If *SS* is a <call statement>, then the General Rules of Subclause 5.7, "Implicit CALL USING clause", are applied with *SS* and *S* as *SOURCE* and *ALLOCATED STATEMENT*, respectively.
- c) Let *R* be the value of the ROW\_COUNT field from the diagnostics area associated with *S*.
- d) *R* becomes the row count associated with *S*.
- e) If *P* executed successfully, then any executed statement associated with *S* is destroyed and *SS* becomes the executed statement associated with *S*.

**6.50 Prepare****6.50 Prepare****Function**

Prepare a statement.

**Definition**

```
Prepare (
    StatementHandle      IN      INTEGER,
    StatementText        IN      CHARACTER(L),
    TextLength           IN      INTEGER )
    RETURNS SMALLINT
```

where  $L$  is determined by the value of TextLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

**General Rules**

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $TL$  be the value of TextLength.
- 4) Case:
  - a) If  $TL$  is not negative, then let  $L$  be  $TL$ .
  - b) If  $TL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of StatementText that precede the implementation-defined null character that terminates a C character string.
  - c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 5) Case:
  - a) If  $L$  is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - b) Otherwise, let  $P$  be the first  $L$  octets of StatementText.
- 6) If  $P$  is a <preparable dynamic delete statement: positioned> or a <preparable dynamic update statement: positioned>, then let  $CN$  be the cursor name referenced by  $P$ . Let  $C$  be the allocated SQL-connection with which  $S$  is associated. If  $CN$  is not the name of a cursor associated with another allocated SQL-statement associated with  $C$ , then an exception condition is raised: *invalid cursor name*.

7) If one or more of the following are true, then an exception condition is raised: *syntax error* or *access rule violation*.

- a) *P* does not conform to the Format, Syntax Rules or Access Rules for a <preparable statement> or *P* is a <start transaction statement>, a <commit statement>, a <rollback statement>, or a <release savepoint statement>.

NOTE 64 – See Table 26, "SQL-statement codes", in ISO/IEC 9075-2 and Table 9, "SQL-statement codes", in ISO/IEC 9075-5 for the list of <preparable statement>s. Other parts of ISO/IEC 9075 may have corresponding tables that define additional codes representing statements defined by those parts of ISO/IEC 9075.

- b) *P* contains a <simple comment>.

- c) *P* contains a <dynamic parameter specification> whose data type is undefined as determined by the rules specified in Subclause 15.6, "<prepare statement>", in ISO/IEC 9075-5.

8) The data type of any <dynamic parameter specification> contained in *P* is determined by the rules specified in Subclause 15.6, "<prepare statement>", in ISO/IEC 9075-5.

9) Let *DTGN* be the default transform group name and *TFL* be the list of user-defined type name—transform group name pairs used to identify the group of transform functions for every user-defined type that is referenced in *P*. *DTGN* and *TFL* are not affected by the execution of a <set transform group statement> after *P* is prepared.

10) The following objects associated with *S* are destroyed:

- a) Any prepared statement.
- b) Any cursor.
- c) Any select source.
- d) Any executed statement.

If a cursor associated with *S* is destroyed, then so are any prepared statements that reference that cursor.

11) *P* is prepared and the prepared statement is associated with *S*.

12) If *P* is a <dynamic select statement> or a <dynamic single row select statement>, then:

- a) *P* becomes the select source associated with *S*.
- b) If there is no cursor name associated with *S*, then a unique implementation-dependent name that has the prefix 'SQLCUR' or the prefix 'SQL\_CUR' becomes the cursor name associated with *S*.

13) The General Rules of Subclause 5.5, "Implicit DESCRIBE USING clause", are applied with *SS* and *S* as *SOURCE* and *ALLOCATED STATEMENT*, respectively.

14) The validity of a prepared statement in an SQL-transaction different from the one in which the statement was prepared is implementation-dependent.

## 6.51 PrimaryKeys

## 6.51 PrimaryKeys

## Function

Return a result set that contains a list of the column names that comprise the primary key for a single specified table stored in the information schemas of the connected data source.

## Definition

```
PrimaryKeys (
    StatementHandle      IN INTEGER,
    CatalogName         IN CHARACTER(L1),
    NameLength1         IN SMALLINT,
    SchemaName          IN CHARACTER(L2),
    NameLength2         IN SMALLINT,
    TableName           IN CHARACTER(L3),
    NameLength3         IN SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ , and  $L3$  are determined by the values of NameLength1, NameLength2, and NameLength3 respectively and each of  $L1$ ,  $L2$ , and  $L3$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

## General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $PRIMARY\_KEYS\_QUERY$  be a table, with the definition:

```
CREATE TABLE PRIMARY_KEYS_QUERY (
    TABLE_CAT          CHARACTER VARYING(128),
    TABLE_SCHEM       CHARACTER VARYING(128) NOT NULL,
    TABLE_NAME        CHARACTER VARYING(128) NOT NULL,
    COLUMN_NAME        CHARACTER VARYING(128) NOT NULL,
    ORDINAL_POSITION   SMALLINT NOT NULL,
    PK_NAME             CHARACTER VARYING(128) )
```

- 6) Let  $PKS$  represent the set of rows in  $SS$ 's Information Schema TABLE\_CONSTRAINTS view where the value of CONSTRAINT\_TYPE is 'PRIMARY KEY'.
- 7) Let  $PK\_COLS$  represent the set of rows that define the columns within an individual primary key row in  $PKS$ . These rows are formed by a natural inner join on the values in the CONSTRAINT\_CATALOG, CONSTRAINT\_SCHEMA, and CONSTRAINT\_NAME columns between a row in  $PKS$  and the matching row or rows in  $SS$ 's Information Schema KEY\_COLUMN\_USAGE view.

- 8) Let *PKS\_COLS* represent the set of rows in the combination of all *PK\_COLS* sets.
- 9) *PRIMARY\_KEYS\_QUERY* contains a row for each row in *PKS\_COLS* where:
- a) Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
  - b) Case:
    - i) If the value of *SUP* is 1 (one), then *PRIMARY\_KEYS\_QUERY* contains a row for each column of the primary key for a specific table in *SS*'s Information Schema *TABLE\_CONSTRAINTS* view.
    - ii) Otherwise, *PRIMARY\_KEYS\_QUERY* contains a row for each column of the primary key for a specific table in *SS*'s Information Schema *TABLE\_CONSTRAINTS* view in accordance with implementation-defined authorization criteria.
- 10) For each row of *PRIMARY\_KEYS\_QUERY*:
- a) If the implementation does not support catalog names, then *TABLE\_CAT* is set to the null value; otherwise, the value of *TABLE\_CAT* in *PRIMARY\_KEYS\_QUERY* is the value of the *TABLE\_CATALOG* column in *PKS*.
  - b) The value of *TABLE\_SCHEM* in *PRIMARY\_KEYS\_QUERY* is the value of the *TABLE\_SCHEMA* column in *PKS*.
  - c) The value of *TABLE\_NAME* in *PRIMARY\_KEYS\_QUERY* is the value of the *TABLE\_NAME* column in *PKS*.
  - d) The value of *COLUMN\_NAME* in *PRIMARY\_KEYS\_QUERY* is the value of the *COLUMN\_NAME* column in *PKS\_COLS*.
  - e) The value of *ORDINAL\_POSITION* in *PRIMARY\_KEYS\_QUERY* is the value of the *ORDINAL\_POSITION* column in *PKS\_COLS*.
  - f) The value of *PK\_NAME* in *PRIMARY\_KEYS\_QUERY* is the value of the *CONSTRAINT\_NAME* column in *PKS*.
- 11) Let *NL1*, *NL2*, and *NL3* be the values of NameLength1, NameLength2, and NameLength3, respectively.
- 12) Let *CATVAL*, *SCHVAL*, and *TBLVAL* be the values of CatalogName, SchemaName, and TableName, respectively.
- 13) If the METADATA ID attribute of *S* is TRUE, then:
- a) If CatalogName is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", *Y*, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - b) If SchemaName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- 14) If TableName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.

**6.51 PrimaryKeys**

15) If CatalogName is a null pointer, then *NL1* is set to zero. If SchemaName is a null pointer, then *NL2* is set to zero. If TableName is a null pointer, then *NL3* is set to zero.

16) Case:

- a) If *NL1* is not negative, then let *L* be *NL1*.
- b) If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of CatalogName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *CATVAL* be the first *L* octets of CatalogName.

17) Case:

- a) If *NL2* is not negative, then let *L* be *NL2*.
- b) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of SchemaName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *SCHVAL* be the first *L* octets of SchemaName.

18) Case:

- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of TableName that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TBLVAL* be the first *L* octets of TableName.

19) Case:

- a) If the METADATA ID attribute of *S* is TRUE, then:

i) Case:

- 1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
- 2) Otherwise,

Case:

- A) If `SUBSTRING(TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(CATVAL) FROM CHAR_LENGTH(TRIM(CATVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

`SUBSTRING(TRIM(CATVAL) FROM 2`

FOR CHAR\_LENGTH(TRIM(CATVAL)) - 2)

and let *CATSTR* be the character string:

TABLE\_CAT = 'TEMPSTR' AND

B) Otherwise, let *CATSTR* be the character string:

UPPER(TABLE\_CAT) = UPPER('CATVAL') AND

ii) Case:

1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

2) Otherwise,

Case:

A) If SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = '' and if SUBSTRING(TRIM(SCHVAL) FROM CHAR\_LENGTH(TRIM(SCHVAL)) FOR 1) = '', then let *TEMPSTR* be the value obtained from evaluating:

SUBSTRING(TRIM(SCHVAL) FROM 2  
FOR CHAR\_LENGTH(TRIM(SCHVAL)) - 2)

and let *SCHSTR* be the character string:

TABLE\_SCHEM = 'TEMPSTR' AND

B) Otherwise, let *SCHSTR* be the character string:

UPPER(TABLE\_SCHEM) = UPPER('SCHVAL') AND

iii) Case:

1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

2) Otherwise,

Case:

A) If SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = '' and if SUBSTRING(TRIM(TBLVAL) FROM CHAR\_LENGTH(TRIM(TBLVAL)) FOR 1) = '', then let *TEMPSTR* be the value obtained from evaluating:

SUBSTRING(TRIM(TBLVAL) FROM 2  
FOR CHAR\_LENGTH(TRIM(TBLVAL)) - 2)

and let *TBLSTR* be the character string:

TABLE\_NAME = 'TEMPSTR' AND

B) Otherwise, let *TBLSTR* be the character string:

UPPER(TABLE\_NAME) = UPPER('TBLVAL') AND

b) Otherwise,

i) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

TABLE\_CAT = 'CATVAL' AND

**6.51 PrimaryKeys**

- ii) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'SCHVAL' AND
```

- iii) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string. Otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME = 'TBLVAL' AND
```

- 20) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || 1=1
```

- 21) Let *STMT* be the character string:

```
SELECT *
FROM PRIMARY_KEYS_QUERY
WHERE PRED
ORDER BY TABLE_CAT, TABLE_SCHEM, TABLE_NAME, ORDINAL_POSITION
```

- 22) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

## 6.52 PutData

### Function

Provide a deferred parameter value.

### Definition

```
PutData (
    StatementHandle      IN    INTEGER,
    Data                 IN    ANY,
    StrLen_or_Ind        IN    INTEGER )
    RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by *StatementHandle*.
- 2) Case:
  - a) If there is no deferred parameter number associated with *S*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
  - b) Otherwise, let *DPN* be the deferred parameter number associated with *S*.
- 3) If there is no *DATA\_POINTER* value associated with *DPN*, then an exception condition is raised: *CLI-specific condition — function sequence error*.
- 4) Let *APD* be the current application parameter descriptor for *S*.
- 5) Let *PT* be the value of the *TYPE* field of the *DPN*-th item descriptor area of *APD* for which *LEVEL* is 0 (zero).
- 6) Let *IV* be the value of *StrLen\_or\_Ind*.
- 7) If there is a parameter value associated with *DPN* and *PT* does not indicate *CHARACTER*, *CHARACTER LARGE OBJECT*, or *BINARY LARGE OBJECT*, then an exception is raised: *CLI-specific condition — non-string data cannot be sent in pieces*.
- 8) Case:
  - a) If *IV* is the appropriate 'Code' for SQL NULL DATA in Table 26, "Miscellaneous codes used in CLI", then let *V* be the null value.
  - b) If *PT* indicates *CHARACTER* or *CHARACTER LARGE OBJECT*, then:
    - i) Case:
      - 1) If *IV* is not negative, then let *L* be *IV*.
      - 2) If *IV* indicates *NULL TERMINATED*, then let *L* be the number of octets in the characters of *Data* that precede the implementation-defined null character that terminates a C character string.

## 6.52 PutData

- 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*
- ii) Let  $V$  be the first  $L$  octets of Data.
- c) If  $PT$  indicates BINARY LARGE OBJECT, then:
- i) Case:
- 1) If  $IV$  is not negative, then let  $L$  be  $IV$ .
- 2) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value.*
- ii) Let  $V$  be the first  $L$  octets of Data.
- d) Otherwise, let  $V$  be the value of Data.
- 9) If  $V$  is not a valid value of the data type indicated by  $PT$ , then an exception condition is raised: *dynamic SQL error — using clause does not match dynamic parameter specifications.*
- 10) If there is no parameter value associated with  $DPN$ , then:
- a)  $V$  becomes the parameter value associated with  $DPN$ .
- b) If  $V$  is not the null value and  $PT$  indicates CHARACTER, CHARACTER LARGE OBJECT, or BINARY LARGE OBJECT, then  $L$  becomes the parameter length associated with  $DPN$ .
- 11) If there is a parameter value associated with  $DPN$ , then
- Case:
- a) If  $V$  is the null value, then:
- i)  $DPN$  is removed from association with  $S$ .
- ii) Any statement source associated with  $S$  is removed from association with  $S$ .
- iii) An exception condition is raised: *CLI-specific condition — attempt to concatenate a null value.*
- b) Otherwise:
- i) Let  $PV$  be the parameter value associated with  $DPN$ .
- ii) Case:
- 1) If  $PV$  is the null value, then:
- A)  $DPN$  is removed from association with  $S$ .
- B) Any statement source associated with  $S$  is removed from association with  $S$ .
- C) An exception condition is raised: *CLI-specific condition — attempt to concatenate a null value.*
- 2) Otherwise:
- A) Let  $PL$  be the parameter length associated with  $DPN$ .

B) Let  $NV$  be the result of the <string value function>

$PV \parallel V$

C)  $NV$  becomes the parameter value associated with  $DPN$  and  $(PL+L)$  becomes the parameter length associated with  $DPN$ .

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.53 RowCount

### Function

Get the row count.

### Definition

```
RowCount (
    StatementHandle    IN          INTEGER,
    RowCount           OUT        INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If there is no executed statement associated with  $S$ , then an exception condition is raised:  
*CLI-specific condition — function sequence error.*
- 3) RowCount is set to the value of the row count associated with  $S$ .

## 6.54 SetConnectAttr

### Function

Set the value of an SQL-connection attribute.

### Definition

```

SetConnectAttr(
    ConnectionHandle    IN    INTEGER,
    Attribute           IN    INTEGER,
    Value              IN    ANY,
    StringLength       IN    INTEGER )
RETURNS SMALLINT

```

### General Rules

- 1) Case:
  - a) If ConnectionHandle does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let *C* be the allocated SQL-connection identified by ConnectionHandle.
    - ii) The diagnostics area associated with *C* is emptied.
- 2) Let *A* be the value of Attribute.
- 3) If *A* is not one of the code values in Table 16, “Codes used for connection attributes”, or if *A* is one of the code values in Table 16, “Codes used for connection attributes”, but the row that contains *A* contains 'No' in the 'May be set' column, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 4) If *A* indicates SAVEPOINT NAME, then:
  - a) Let *SL* be the value of StringLength.
  - b) Case:
    - i) If *SL* is not negative, then let *L* be *SL*.
    - ii) If *SL* indicates NULL TERMINATED, then let *L* be the number of octets of Value that precede the implementation-defined null character that terminates a C character string.
    - iii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - c) The SAVEPOINT NAME attribute of *C* is set to the first *L* octets of Value.
- 5) If *A* indicates SAVEPOINT NUMBER, then the SAVEPOINT NUMBER attribute of *C* is set to the value of Value.
- 6) If *A* specifies an implementation-defined connection attribute, then

**6.54 SetConnectAttr**

Case:

- a) If the data type for the connection attribute is specified as INTEGER in Table 19, "Data types of attributes", then the connection attribute is set to the value of Value.
- b) Otherwise:
  - i) Let  $SL$  be the value of StringLength.
  - ii) Case:
    - 1) If  $SL$  is not negative, then let  $L$  be  $SL$ .
    - 2) If  $SL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of Value that precede the implementation-defined null character that terminates a C character string.
    - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - iii) The connection attribute is set to the first  $L$  octets of Value.

## 6.55 SetCursorName

### Function

Set a cursor name.

### Definition

```

SetCursorName (
    StatementHandle      IN    INTEGER,
    CursorName           IN    CHARACTER ( L ),
    NameLength           IN    SMALLINT )
RETURNS SMALLINT

```

where  $L$  is determined by the value of NameLength and has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $NL$  be the value of NameLength.
- 4) Case:
  - a) If  $NL$  is not negative, then let  $L$  be  $NL$ .
  - b) If  $NL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of CursorName that precede the implementation-defined null character that terminates a C character string.
  - c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- 5) Case:
  - a) If  $L$  is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - b) Otherwise:
    - i) Let  $N$  be the number of whole characters in the first  $L$  octets of CursorName and let  $NO$  be the number of octets occupied by those  $N$  characters. If  $NO \neq L$ , then an exception condition is raised: *invalid cursor name*.
    - ii) Otherwise, let  $CV$  be the first  $L$  octets of CursorName and let  $TCN$  be the value of
 

```
TRIM ( BOTH ' ' FROM CV )
```
- 6) Let  $ML$  be the maximum length in characters allowed for an <identifier> as specified in the Syntax Rules of Subclause 5.4, "Names and identifiers", in ISO/IEC 9075-2, and let  $TCNL$  be the length in characters of  $TCN$ .

**6.55 SetCursorName**

7) Case:

a) If *TCNL* is greater than *ML*, then *CN* is set to the first *ML* characters of *TCN* and a completion condition is raised: *warning — string data, right truncation*.

b) Otherwise, *CN* is set to *TCN*.

8) If *CN* does not conform to the Format and Syntax Rules of an <identifier>, then an exception condition is raised: *invalid cursor name*.

9) Let *C* be the allocated SQL-connection with which *S* is associated and let *SC* be the <search condition>:

```
CN LIKE 'SQL\_CUR%' ESCAPE '\ ' OR CN LIKE 'SQLCUR%'
```

If *SC* is true or if *CN* is identical to the value of any cursor name associated with an allocated SQL-statement associated with *C*, then an exception condition is raised: *invalid cursor name*.

10) *CN* becomes the cursor name associated with *S*.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.56 SetDescField

### Function

Set a field in a CLI descriptor area.

### Definition

```
SetDescField (
    DescriptorHandle      IN          INTEGER ,
    RecordNumber         IN          SMALLINT ,
    FieldIdentifier       IN          SMALLINT ,
    Value                IN          ANY ,
    BufferLength          IN          INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let *D* be the allocated CLI descriptor area identified by DescriptorHandle and let *N* be the value of the COUNT field of *D*.
- 2) The General Rules of Subclause 5.11, “Deferred parameter check”, are applied to *D* as the DESCRIPTOR AREA.
- 3) Let *FI* be the value of FieldIdentifier.
- 4) If *FI* is not one of the code values in Table 20, “Codes used for descriptor fields”, then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.
- 5) Case:
  - a) If the ALLOC\_TYPE field of descriptor *D* is USER and *D* is not being used as the current ARD or current APD of any statement handle, then let *DT* be ARD.
  - b) Otherwise, let *DT* be the type of the descriptor *D*.
- 6) Let *MBS* be the value of the May Be Set column in the row of Table 21, “Ability to set SQL/CLI descriptor fields”, that contains *FI* and in the column that contains the descriptor type *DT*.
- 7) If *MBS* is ‘No’, then an exception condition is raised: *CLI-specific condition — invalid descriptor field identifier*.
- 8) Let *RN* be the value of RecordNumber.
- 9) Let *TYPE* be the value of the Type column in the row of Table 20, “Codes used for descriptor fields”, that contains *FI*.
- 10) If *TYPE* is ‘ITEM’ and *RN* is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 11) Let *IDA* be the item descriptor area of *D* specified by *RN*.
- 12) If an exception condition is raised in any of the following General Rules, then all fields of *IDA* for which specific values were provided in the invocation of SetDescField are set to implementation-dependent values and the value of COUNT for *D* is unchanged.

13) Information is set in *D*:

Case:

a) If *FI* indicates COUNT, then

Case:

- i) If the memory requirements to manage the CLI descriptor area cannot be satisfied, then an exception condition is raised: *CLI-specific condition — memory allocation error*.
- ii) Otherwise, the count of the number of item descriptor areas is set to the value of Value.

b) If *FI* indicates ARRAY\_SIZE, then the value of the ARRAY\_SIZE header field of descriptor *D* is set to Value.

c) If *FI* indicates ARRAY\_STATUS\_POINTER, then the value of the ARRAY\_STATUS\_POINTER header field of descriptor *D* is set to the address of Value. If Value is a null pointer, then the address is set to 0 (zero).

d) If *FI* indicates ROWS\_PROCESSED\_POINTER, then the value of the ROWS\_PROCESSED\_POINTER header field of descriptor *D* is set to the address of Value. If Value is a null pointer, then the address is set to 0 (zero).

e) If *FI* indicates OCTET\_LENGTH\_POINTER, then the value of the OCTET\_LENGTH\_POINTER field of *IDA* is set to the address of Value.

f) If *FI* indicates DATA\_POINTER, then the value of the DATA\_POINTER field of *IDA* is set to the address of Value. If Value is a null pointer, then the address is set to 0 (zero).

g) If *FI* indicates INDICATOR\_POINTER, then the value of the INDICATOR\_POINTER field of *IDA* is set to the address of Value.

h) If *FI* indicates RETURNED\_CARDINALITY\_POINTER, then the value of the RETURNED\_CARDINALITY\_POINTER field of *IDA* is set to the address of Value.

i) If *FI* indicates CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, or CHARACTER\_SET\_NAME, then:

i) Let *BL* be the value of BufferLength.

ii) Case:

1) If *BL* is not negative, then let *L* be *BL*.

2) If *BL* indicates NULL TERMINATED, then let *L* be the number of octets of Value that precedes the implementation-defined null character that terminates a C character string.

3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

iii) Case:

1) If *L* is zero, then an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

2) Otherwise, let *FV* be the first *l* octets of Value and let *TFV* be the value of

TRIM ( BOTH ' ' FROM *FV* )

iv) Let *ML* be the maximum length in characters allowed for an <identifier> as specified in the Syntax Rules of Subclause 5.4, "Names and identifiers", in ISO/IEC 9075-2, and let *TFVL* be the length in characters of *TFV*.

v) Case:

1) If *TFVL* is greater than *ML*, then *FV* is set to the first *ML* characters of *TFV* and a completion condition is raised: *warning — string data, right truncation*.

2) Otherwise, *FV* is set to *TFV*.

vi) Case:

1) If *FI* indicates CHARACTER\_SET\_CATALOG and *FV* does not conform to the Format and Syntax Rules of an <identifier>, then an exception condition is raised: *invalid catalog name*.

2) If *FI* indicates CHARACTER\_SET\_SCHEMA and *FV* does not conform to the Format and Syntax Rules of an <identifier>, then an exception condition is raised: *invalid schema name*.

3) If *FI* indicates CHARACTER\_SET\_NAME and *FV* does not conform to the Format and Syntax Rules of an <identifier>, then an exception condition is raised: *invalid character set name*.

vii) The value of the field of *IDA* identified by *FI* is set to the value of *FV*.

j) Otherwise, the value of the field of *IDA* identified by *FI* is set to the value of Value.

14) If *FI* indicates LEVEL, then:

a) If *RI* is 1 (one) and value is not 0 (zero), then an exception condition is raised: *dynamic SQL error — invalid LEVEL value*.

b) If *RI* is greater than 1 (one), then let *PIDA* be *IDA*'s immediately preceding item descriptor area and let *K* be its LEVEL value.

i) If Value is *K*+1 and TYPE in *PIDA* does not indicate ROW ARRAY, or ARRAY LOCATOR, then an exception condition is raised: *dynamic SQL error — invalid LEVEL value*.

ii) If Value is greater than *K*+1, then an exception condition is raised: *dynamic SQL error — invalid LEVEL value*.

iii) If value is less than *K*+1, then let *OIDA<sub>i</sub>* be the *i*-th item descriptor area to which *PIDA* is subordinate and whose TYPE field indicates ROW. Let *NS<sub>i</sub>* be the number of immediately subordinate descriptor areas of *OIDA<sub>i</sub>* between *OIDA<sub>i</sub>* and *IDA*, and let *D<sub>i</sub>* be the value of DEGREE of *OIDA<sub>i</sub>*.

1) For each *OIDA<sub>i</sub>* whose LEVEL value is greater than *V*, if *D<sub>i</sub>* is not equal to *NS<sub>i</sub>*, then an exception condition is raised: *dynamic SQL error — invalid LEVEL value*.

## 6.56 SetDescField

- 2) If  $K$  is not 0 (zero), then let  $OIDA_i$  be the  $OIDA_j$  whose LEVEL value is  $K$ . If there exists no such  $OIDA_j$  or  $D_j$  is not greater than  $NS_j$ , then an exception condition is raised: *dynamic SQL error — invalid LEVEL value.*
- c) The value of LEVEL in  $IDA$  is set to Value.
- 15) If  $TYPE$  is 'ITEM' and  $RN$  is greater than  $N$ , then the COUNT field of  $D$  is set to  $RN$ .
- 16) If  $FI$  indicates TYPE, LENGTH, OCTET\_LENGTH, PRECISION, SCALE, DATETIME\_INTERVAL\_CODE, DATETIME\_INTERVAL\_PRECISION, PARAMETER\_MODE, PARAMETER\_ORDINAL\_POSITION, PARAMETER\_SPECIFIC\_CATALOG, PARAMETER\_SPECIFIC\_SCHEMA, PARAMETER\_SPECIFIC\_NAME, CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, CHARACTER\_SET\_NAME, USER\_DEFINED\_TYPE\_CATALOG, USER\_DEFINED\_TYPE\_SCHEMA, USER\_DEFINED\_TYPE\_NAME, SCOPE\_CATALOG, SCOPE\_SCHEMA, or SCOPE\_NAME, then the DATA\_POINTER field of  $IDA$  is set to zero.
- 17) If  $FI$  indicates DATA\_POINTER, and Value is not a null pointer, and  $IDA$  is not consistent as specified in Subclause 5.13, "Description of CLI item descriptor areas", then an exception condition is raised: *CLI-specific condition — inconsistent descriptor information.*
- 18) Let  $V$  be the value of Value.
- 19) If  $FI$  indicates TYPE, then:
- a) All the other fields of  $IDA$  are set to implementation-dependent values.
  - b) Case:
    - i) If  $V$  indicates CHARACTER, CHARACTER VARYING or CHARACTER LARGE OBJECT then the CHARACTER\_SET\_CATALOG, CHARACTER\_SET\_SCHEMA, and CHARACTER\_SET\_NAME fields of  $IDA$  are set to the values for the default character set name for the SQL session and the LENGTH field of  $IDA$  is set to the maximum possible length in characters of the indicated data type.
    - ii) If  $V$  indicates BIT or BIT VARYING, then the LENGTH field of  $IDA$  is set to the maximum possible length in bits of the indicated data type.
    - iii) If  $V$  indicates BINARY LARGE OBJECT, then the LENGTH field of  $IDA$  is set to the maximum possible length in octets of the indicated data type.
    - iv) If  $V$  indicates a <datetime type>, then the PRECISION field of  $IDA$  is set to 0 (zero).
    - v) If  $V$  indicates INTERVAL, then the DATETIME\_INTERVAL\_PRECISION field of  $IDA$  is set to 2.
    - vi) If  $V$  indicates NUMERIC or DECIMAL, then the SCALE field of  $IDA$  is set to 0 (zero) and the PRECISION field of  $IDA$  is set to the implementation-defined default value for the precision of the NUMERIC or DECIMAL data types, respectively.
    - vii) If  $V$  indicates SMALLINT or INTEGER, then the SCALE field of  $IDA$  is set to 0 (zero) and the PRECISION field of  $IDA$  is set to the implementation-defined value for the precision of the SMALLINT or INTEGER data types, respectively.
    - viii) If  $V$  indicates FLOAT, then the PRECISION field of  $IDA$  is set to the implementation-defined default value for the precision of the FLOAT data type.

- ix) If *V* indicates REAL or DOUBLE PRECISION, then the PRECISION field of *IDA* is set to the implementation-defined value for the precision of the REAL or DOUBLE PRECISION data types, respectively.
  - x) If *V* indicates an implementation-defined data type, then an implementation-defined set of fields of *IDA* are set to implementation-defined default values.
  - xi) Otherwise, an exception condition is raised: *CLI-specific condition — invalid data type*.
- 20) If *FI* indicates DATETIME\_INTERVAL\_CODE and the TYPE field of *IDA* indicates a <datetime type>, then:
- a) All the fields of *IDA* other than DATETIME\_INTERVAL\_CODE and TYPE are set to implementation-dependent values.
  - b) Case:
    - i) If *V* indicates DATE, TIME, or TIME WITH TIME ZONE, then the PRECISION field of *IDA* is set to 0 (zero).
    - ii) If *V* indicates TIMESTAMP or TIMESTAMP WITH TIME ZONE, then the PRECISION field of *IDA* is set to 6.
- 21) If *FI* indicates DATETIME\_INTERVAL\_CODE and the TYPE field of *IDA* indicates INTERVAL, then the DATETIME\_INTERVAL\_PRECISION field of *IDA* is set to 2 and
- a) If *V* indicates DAY TO SECOND, HOUR TO SECOND, MINUTE TO SECOND, or SECOND, then the PRECISION field of *IDA* is set to 6.
  - b) Otherwise, the PRECISION field of *IDA* is set to 0 (zero).
- 22) Restrictions on the differences allowed between implementation and application parameter descriptors are implementation-defined, except as specified in the General Rules of Subclause 5.6, “Implicit EXECUTE USING and OPEN USING clauses”, in the General Rules of Subclause 5.7, “Implicit CALL USING clause”, and in the General Rules of Subclause 6.49, “ParamData”. Restrictions on the differences between the implementation and application row descriptors are implementation-defined, except as specified in the General Rules of Subclause 5.8, “Implicit FETCH USING clause”, and the General Rules of Subclause 6.30, “GetData”.

## 6.57 SetDescRec

### Function

Set commonly-used fields in a CLI descriptor area.

### Definition

```
SetDescRec (  
    DescriptorHandle    IN        INTEGER ,  
    RecordNumber       IN        SMALLINT ,  
    Type               IN        SMALLINT ,  
    SubType            IN        SMALLINT ,  
    Length             IN        INTEGER ,  
    Precision          IN        SMALLINT ,  
    Scale              IN        SMALLINT ,  
    Data               DEF       ANY ,  
    StringLength       DEF       INTEGER ,  
    Indicator          DEF       INTEGER )  
RETURNS SMALLINT
```

### General Rules

- 1) Let  $D$  be the allocated CLI descriptor area identified by `DescriptorHandle` and let  $N$  be the value of the `COUNT` field of  $D$ .
- 2) The General Rules of Subclause 5.11, "Deferred parameter check", are applied to  $D$  as the `DESCRIPTOR AREA`.
- 3) If  $D$  is an implementation row descriptor, then an exception condition is raised: *CLI-specific condition — cannot modify an implementation row descriptor*.
- 4) Let  $RN$  be the value of `RecordNumber`.
- 5) If  $RN$  is less than 1 (one), then an exception condition is raised: *dynamic SQL error — invalid descriptor index*.
- 6) If  $RN$  is greater than  $N$ , then  
Case:
  - a) If the memory requirements to manage the larger CLI descriptor area cannot be satisfied, then an exception condition is raised: *CLI-specific condition — memory allocation error*.
  - b) Otherwise, the `COUNT` field of  $D$  is set to  $RN$ .
- 7) Let  $IDA$  be the item descriptor area of  $D$  specified by  $RN$ .
- 8) Information is set in  $D$  as follows:
  - a) The data type, precision, scale, and datetime data type of the item described by  $IDA$  are set to the values of `Type`, `Precision`, `Scale`, and `SubType`, respectively.

- b) Case:
- i) If *D* is an implementation parameter descriptor, then the length (in characters, bits, or positions, as appropriate) of the item described by *IDA* is set to the value of *Length*.
  - ii) Otherwise, the length in octets of the item described by *IDA* is set to the value of *Length*.
- c) If *StringLength* is not a null pointer, then the address of the host variable that is to provide the length of the item described by *IDA*, or that is to receive the returned length in octets of the item described by *IDA*, is set to the address of *StringLength*.
  - d) The address of the host variable that is to provide a value for the item described by *IDA*, or that is to receive a value for the item described by *IDA*, is set to the address of *Data*. If *Data* is a null pointer, then the address is set to 0 (zero).
  - e) If *Indicator* is not a null pointer, then the address of the <indicator variable> associated with the item described by *IDA* is set to the address of *Indicator*.
- 9) If *Data* is not a null pointer and *IDA* is not consistent as specified in Subclause 5.13, "Description of CLI item descriptor areas", then an exception condition is raised: *CLI-specific condition — inconsistent descriptor information*.
  - 10) If an exception condition is raised, then all fields of *IDA* for which specific values were provided in the invocation of *SetDescRec* are set to implementation-dependent values and the value of the *COUNT* field of *D* is unchanged.
  - 11) Restrictions on the differences allowed between implementation and application parameter descriptors are implementation-defined, except as specified in the General Rules of Subclause 5.6, "Implicit EXECUTE USING and OPEN USING clauses", in the General Rules of Subclause 5.7, "Implicit CALL USING clause", and in the General Rules of Subclause 6.49, "ParamData". Restrictions on the differences between the implementation and application row descriptors are implementation-defined, except as specified in the General Rules of Subclause 5.8, "Implicit FETCH USING clause", and the General Rules of Subclause 6.30, "GetData".

## 6.58 SetEnvAttr

### Function

Set the value of an SQL-environment attribute.

### Definition

```
SetEnvAttr (  
    EnvironmentHandle    IN        INTEGER ,  
    Attribute            IN        INTEGER ,  
    Value                IN        ANY ,  
    StringLength         IN        INTEGER )  
RETURNS SMALLINT
```

### General Rules

- 1) Case:
  - a) If EnvironmentHandle does not identify an allocated SQL-environment or if it identifies an allocated skeleton SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - b) Otherwise:
    - i) Let  $E$  be the allocated SQL-environment identified by EnvironmentHandle.
    - ii) The diagnostics area associated with  $E$  is emptied.
- 2) If there are any allocated SQL-connections associated with  $E$ , then an exception condition is raised: *CLI-specific condition — attribute cannot be set now*.
- 3) Let  $A$  be the value of Attribute.
- 4) If  $A$  is not one of the code values in Table 15, “Codes used for environment attributes”, then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 5) If  $A$  indicates NULL TERMINATION, then  
Case:
  - a) If Value indicates TRUE, then null termination for  $E$  is set to true .
  - b) If Value indicates FALSE, then null termination for  $E$  is set to false .
  - c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 6) If  $A$  specifies an implementation-defined environment attribute, then  
Case:
  - a) If the data type for the environment attribute is specified as INTEGER in Table 19, “Data types of attributes”, then the environment attribute is set to the value of Value.

- b) Otherwise:
- i) Let  $SL$  be the value of StringLength.
  - ii) Case:
    - 1) If  $SL$  is not negative, then let  $L$  be  $SL$ .
    - 2) If  $SL$  indicates NULL TERMINATED, then let  $L$  be the number of octets of Value that precede the implementation-defined null character that terminates a C character string.
    - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - iii) The environment attribute is set to the first  $L$  octets of Value.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 6.59 SetStmtAttr

### Function

Set the value of an SQL-statement attribute.

### Definition

```
SetStmtAttr (
    StatementHandle      IN          INTEGER,
    Attribute            IN          INTEGER,
    Value               IN          ANY,
    StringLength        IN          INTEGER )
RETURNS SMALLINT
```

### General Rules

- 1) Let *S* be the allocated SQL-statement identified by `StatementHandle`.
- 2) Let *A* be the value of `Attribute`.
- 3) If *A* is not one of the code values in Table 17, “Codes used for statement attributes”, or if *A* is one of the code values in Table 17, “Codes used for statement attributes”, but the row that contains *A* contains 'No' in the 'May be set' column, then an exception condition is raised:  
*CLI-specific condition — invalid attribute identifier.*
- 4) Let *V* be the value of `Value`.
- 5) Case:
  - a) If *A* indicates `APD_HANDLE`, then:
    - i) Case:
      - 1) If *V* does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid attribute value.*
      - 2) Otherwise, let *DA* be the CLI descriptor area identified by *V* and let *AT* be the value of the `ALLOC_TYPE` field for *DA*.
        - ii) Case:
          - 1) If *AT* indicates `AUTOMATIC` but *DA* is not the application parameter descriptor associated with *S*, then an exception condition is raised: *CLI-specific condition — invalid use of automatically-allocated descriptor handle.*
          - 2) Otherwise, *DA* becomes the current application parameter descriptor for *S*.
    - b) If *A* indicates `ARD_HANDLE`, then:
      - i) Case:
        - 1) If *V* does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid attribute value.*

- 2) Otherwise, let *DA* be the CLI descriptor area identified by *V* and let *AT* be the value of the *ALLOC\_TYPE* field for *DA*.
- ii) Case:
- 1) If *AT* indicates AUTOMATIC but *DA* is not the application row descriptor associated with *S*, then an exception condition is raised: *CLI-specific condition — invalid use of automatically-allocated descriptor handle*.
  - 2) Otherwise, *DA* becomes the current application row descriptor for *S*.
- c) If *A* indicates CURSOR SCROLLABLE, then
- Case:
- i) If the implementation supports scrollable cursors, then:
    - 1) If an open cursor is associated with *S*, then an exception condition is raised: *CLI-specific condition — attribute cannot be set now*.
    - 2) Case:
      - A) If *V* indicates NONSCROLLABLE, then the CURSOR SCROLLABLE attribute of *S* is set to NONSCROLLABLE.
      - B) If *V* indicates SCROLLABLE, then the CURSOR SCROLLABLE attribute of *S* is set to SCROLLABLE.
      - C) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value*.
  - ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented*.
- d) If *A* indicates CURSOR SENSITIVITY, then
- Case:
- i) If the implementation supports cursor sensitivity, then
- Case:
- 1) If an open cursor is associated with *S*, then an exception condition is raised: *CLI-specific condition — attribute cannot be set now*.
  - 2) Case:
    - A) If *V* indicates ASENSITIVE, then the CURSOR SENSITIVITY attribute of *S* is set to ASENSITIVE.
    - B) If *V* indicates INSENSITIVE, then the CURSOR SENSITIVITY attribute of *S* is set to INSENSITIVE.
    - C) If *V* indicates SENSITIVE, then the CURSOR SENSITIVITY attribute of *S* is set to SENSITIVE.
    - D) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value*.

**6.59 SetStmtAttr**

- ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented.*
- e) If *A* indicates METADATA ID, then
  - Case:
    - i) If *V* indicates FALSE, then the METADATA ID attribute of *S* is set to FALSE.
    - ii) If *V* indicates TRUE, then the METADATA ID attribute of *S* is set to TRUE.
    - iii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value.*
  - f) If *A* indicates CURSOR HOLDABLE, then
    - Case:
      - i) If the implementation supports cursor holdability, then
        - Case:
          - 1) If an open cursor is associated with *S*, then an exception condition is raised: *CLI-specific condition — attribute cannot be set now.*
          - 2) Case:
            - A) If *V* indicates NONHOLDABLE, then the CURSOR HOLDABLE attribute of *S* is set to NONHOLDABLE.
            - B) If *V* indicates HOLDABLE, then the CURSOR HOLDABLE attribute of *S* is set to HOLDABLE.
            - C) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value.*
        - ii) Otherwise, an exception condition is raised: *CLI-specific condition — optional feature not implemented.*
      - g) If *A* indicates CURRENT OF POSITION, then
        - Case:
          - i) If there is no open cursor associated with *S*, then an exception condition is raised: *CLI-specific condition — Invalid cursor state.*
          - ii) If *V* is greater than the ARRAY\_SIZE field of the application row descriptor associated with *S*, then an exception condition is raised: *CLI-specific condition — row value out of range.*
          - iii) If the value of the CURSOR SCROLLABLE attribute of *S* is NONSCROLLABLE, then an exception condition is raised: *CLI-specific condition — invalid cursor position.*
          - iv) Otherwise, the current row within the fetched rowset associated with *S* is set to *V*.
        - h) If *A* indicates NEST DESCRIPTOR, then

Case:

- i) If there is a prepared statement associated with StatementHandle, then an exception condition is raised: *CLI-specific condition — function sequence error*.

- ii) Otherwise,

Case:

- 1) If *V* indicates FALSE, then the NEST DESCRIPTOR attribute of *S* is set to FALSE.
  - 2) If *V* indicates TRUE, then the NEST DESCRIPTOR attribute of *S* is set to TRUE.
  - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute value*.
- 6) If *A* specifies an implementation-defined statement attribute, then

Case:

- a) If the data type for the statement attribute is specified as INTEGER in Table 19, "Data types of attributes", then the statement attribute is set to the value of Value.
- b) Otherwise:
  - i) Let *SL* be the value of StringLength.
  - ii) Case:
    - 1) If *SL* is not negative, then let *L* be *SL*.
    - 2) If *SL* indicates NULL TERMINATED, then let *L* be the number of octets of Value that precede the implementation-defined null character that terminates a C character string.
    - 3) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
  - iii) The statement attribute is set to the first *L* octets of Value.

## 6.60 SpecialColumns

### Function

Return a result set that contains a list of columns the combined values of which can uniquely identify any row within a single specified table described by the Information Schemas of the connected data source.

### Definition

```
SpecialColumns (
    StatementHandle          IN INTEGER,
    IdentifierType          IN SMALLINT,
    CatalogName             IN CHARACTER(L1),
    NameLength1             IN SMALLINT,
    SchemaName              IN CHARACTER(L2),
    NameLength2             IN SMALLINT,
    TableName               IN CHARACTER(L3),
    NameLength3             IN SMALLINT,
    Scope                   IN SMALLINT,
    Nullable                 IN SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ , and  $L3$  are determined by the values of NameLength1, NameLength2, and NameLength3 respectively and each of  $L1$ ,  $L2$ , and  $L3$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let *SPECIAL\_COLUMNS\_QUERY* be a table, with the definition:

```
CREATE TABLE SPECIAL_COLUMNS_QUERY (
    SCOPE                    SMALLINT,
    COLUMN_NAME              CHARACTER VARYING(128) NOT NULL,
    DATA_TYPE               SMALLINT NOT NULL,
    TYPE_NAME                CHARACTER VARYING(128) NOT NULL,
    COLUMN_SIZE              INTEGER,
    BUFFER_LENGTH            INTEGER,
    DECIMAL_DIGITS           SMALLINT,
    PSEUDO_COLUMN            SMALLINT )
```

- 6) *SPECIAL\_COLUMNS\_QUERY* contains a row for each column that is part of a set of columns that can be used to best uniquely identify a row within the tables listed in  $SS$ 's Information Schema TABLES view. Some tables may not have such a set of columns. Some tables may have more than one such set, in which case it is implementation-dependent as to which set of

columns is chosen. It is implementation-dependent as to whether a column identified for a given table is a pseudo-column.

- a) Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
- b) Case:
  - i) If the value of *SUP* is 1 (one), then Table 28, "Codes and data types for implementation information", is 'Y', then *SPECIAL\_COLUMNS\_QUERY* contains a row for each identifying column in *SS*'s Information Schema COLUMNS view and each implementation-dependent pseudo-column.
  - ii) Otherwise, *SPECIAL\_COLUMNS\_QUERY* contains a row for each identifying column in *SS*'s Information Schema COLUMNS view and each implementation-dependent pseudo-column in accordance with implementation-defined authorization criteria.
- 7) If the value of IdentifierType is other than the code for BEST ROWID in Table 43, "Column types and scopes used with SpecialColumns", or an implementation-defined extension to that table, then an exception condition is raised: *CLI-specific condition — column type out of range*.
- 8) If the value of Scope is other than the code SCOPE CURRENT ROW, SCOPE TRANSACTION, or SCOPE SESSION in Table 43, "Column types and scopes used with SpecialColumns", or an implementation-defined extension to that table, then an exception condition is raised: *CLI-specific condition — scope out of range*.
- 9) If the value of Nullable is other than the code for NO NULLS or NULLABLE in Table 43, "Column types and scopes used with SpecialColumns", then an exception condition is raised: *CLI-specific condition — nullable type out of range*.
- 10) For each row of *SPECIAL\_COLUMNS\_QUERY*:
  - a) The value of SCOPE in *SPECIAL\_COLUMNS\_QUERY* is either the code for one of SCOPE CURRENT ROW, SCOPE TRANSACTION, or SCOPE SESSION from Table 43, "Column types and scopes used with SpecialColumns", or it is an implementation-defined value, determined as follows:
 

Case:

    - i) If the value that uniquely identifies a row is only guaranteed to be valid while positioned on that row, then the code is that for SCOPE CURRENT ROW.
    - ii) If the value that uniquely identifies a row is only guaranteed to be valid for the current transaction, then the code is that for SCOPE TRANSACTION.
    - iii) If the value that uniquely identifies a row is only guaranteed to be valid for the current session, then the code is that for SCOPE SESSION.
    - iv) Otherwise, the value is implementation-defined.
  - b) The value of COLUMN\_NAME in *SPECIAL\_COLUMNS\_QUERY* is the value of the COLUMN\_NAME column in the COLUMNS view.
  - c) The value of DATA\_TYPE in *SPECIAL\_COLUMNS\_QUERY* is derived from the values of the DATA\_TYPE and INTERVAL\_TYPE columns in the COLUMNS view as follows:

**6.60 SpecialColumns**

Case:

- i) If the value of DATA\_TYPE in the COLUMNS view is 'INTERVAL', then the value of DATA\_TYPE in (SPECIAL\_COLUMNS\_QUERY) is the appropriate Code from Table 37, "Codes used for concise data types", that matches the interval specified in the INTERVAL\_TYPE column in the COLUMNS view.
- ii) Otherwise, the value of DATA\_TYPE in SPECIAL\_COLUMNS\_QUERY is the appropriate Code from Table 37, "Codes used for concise data types", that matches the interval specified in the DATA\_TYPE column in the COLUMNS view.
- d) The value of TYPE\_NAME in SPECIAL\_COLUMNS\_QUERY is an implementation-defined value that is the character string by which the data type is known at the data source.
- e) The value of COLUMN\_SIZE in SPECIAL\_COLUMNS\_QUERY is

Case:

- i) If the value of DATA\_TYPE in the COLUMNS view is 'CHARACTER', 'CHARACTER VARYING', 'CHARACTER LARGE OBJECT', or 'BINARY LARGE OBJECT', then the value is that of the CHARACTER\_MAXIMUM\_LENGTH in the same row of the COLUMNS view.
- ii) If the value of DATA\_TYPE in the COLUMNS view is 'BIT' or 'BIT VARYING', then the value is that of the CHARACTER\_MAXIMUM\_LENGTH in the same row of the COLUMNS view.
- iii) If the value of DATA\_TYPE in the COLUMNS view is 'DECIMAL' or 'NUMERIC', then the value is that of the NUMERIC\_PRECISION column in the same row of the COLUMNS view.
- iv) If the value of DATA\_TYPE in the COLUMNS view is 'SMALLINT', 'INTEGER', 'REAL', 'DOUBLE PRECISION', or 'FLOAT', then the value is implementation-defined.
- v) If the value of DATA\_TYPE in the COLUMNS view is 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE', then the value of COLUMN\_SIZE is that derived from Syntax Rule 33), in Subclause 6.1, "<data type>", of ISO/IEC 9075-2, where the value of <time fractional seconds precision> is the value of the NUMERIC\_PRECISION column in the same row of the COLUMNS view.
- vi) If the value of DATA\_TYPE in the COLUMNS view is 'INTERVAL', then the value of COLUMN\_SIZE is that derived from the General Rules of Subclause 10.1, "<interval qualifier>", of ISO/IEC 9075-2, where:
  - 1) The value of <interval qualifier> is the value of the INTERVAL\_TYPE column in the same row of the COLUMNS view.
  - 2) The value of <interval leading field precision> is the value of the INTERVAL\_PRECISION column in the same row of the COLUMNS view.
  - 3) The value of <interval fractional seconds precision> is the value of the NUMERIC\_PRECISION column in the same row of the COLUMNS view.
- vii) If the value of DATA\_TYPE in the COLUMNS view is 'REF', then the value is the length in octets of the reference type.
- viii) Otherwise, the value is implementation-dependent.

- f) The value of `BUFFER_LENGTH` in `SPECIAL_COLUMNS_QUERY` is implementation-defined.

NOTE 65 – The purpose of `BUFFER_LENGTH` is to record the number of octets transferred for the column with a Fetch routine, a FetchScroll routine, or a GetData routine when the TYPE field in the application row descriptor indicates DEFAULT. This length excludes any null terminator.

- g) The value of `DECIMAL_DIGITS` in `SPECIAL_COLUMNS_QUERY` is:

Case:

- i) If the value of `DATA_TYPE` in the COLUMNS view is one of 'DATE', 'TIME', 'TIMESTAMP', 'TIME WITH TIME ZONE', or 'TIMESTAMP WITH TIME ZONE', then the value of `DECIMAL_DIGITS` in `SPECIAL_COLUMNS_QUERY` is the value of the `DATETIME_PRECISION` column in the COLUMNS view.
- ii) If the value of `DATA_TYPE` in the COLUMNS view is one of 'DECIMAL', 'INTEGER', 'NUMERIC', or 'SMALLINT', then the value of `DECIMAL_DIGITS` in `SPECIAL_COLUMNS_QUERY` is the value of the `NUMERIC_SCALE` column in the COLUMNS view.
- iii) Otherwise, the value of `DECIMAL_DIGITS` in `SPECIAL_COLUMNS_QUERY` is the null value.

- h) The value of `PSEUDO_COLUMN` in `SPECIAL_COLUMNS_QUERY` is the code for one of PSEUDO UNKNOWN, NOT PSEUDO, or PSEUDO from Table 43, "Column types and scopes used with SpecialColumns". The algorithm used to set this value is implementation-dependent.

- 11) Let `NL1`, `NL2`, and `NL3` be the values of `NameLength1`, `NameLength2`, and `NameLength3`, respectively.

- 12) Let `CATVAL`, `SCHVAL`, `TBLVAL`, `SCPVAL`, and `NULVAL` be the values of `CatalogName`, `SchemaName`, and `TableName`, `Scope`, and `Nullable` respectively.

- 13) If the METADATA ID attribute of `S` is TRUE, then:

- a) If `CatalogName` is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", is 'Y', then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- b) If `SchemaName` is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.

- 14) If `TableName` is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.

- 15) If `CatalogName` is a null pointer, then `NL1` is set to zero. If `SchemaName` is a null pointer, then `NL2` is set to zero. If `TableName` is a null pointer, then `NL3` is set to zero.

- 16) Case:

- a) If `NL1` is not negative, then let `L` be `NL1`.
- b) If `NL1` indicates NULL TERMINATED, then let `L` be the number of octets of `CatalogName` that precede the implementation-defined null character that terminates a C character string.

**6.60 SpecialColumns**

- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

Let *CATVAL* be the first *L* octets of *CatalogName*.

## 17) Case:

- a) If *NL2* is not negative, then let *L* be *NL2*.
- b) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of *SchemaName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

Let *SCHVAL* be the first *L* octets of *SchemaName*.

## 18) Case:

- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of *TableName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length.*

Let *TBLVAL* be the first *L* octets of *TableName*.

## 19) Case:

- a) If the METADATA ID attribute of *S* is TRUE, then:

## i) Case:

- 1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
- 2) Otherwise,

## Case:

- A) If `SUBSTRING( TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING( TRIM(CATVAL) FROM CHAR_LENGTH( TRIM(CATVAL) ) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING( TRIM(CATVAL) FROM 2
FOR CHAR_LENGTH( TRIM(CATVAL) ) - 2)
```

and let *CATSTR* be the character string:

```
TABLE_CAT = 'TEMPSTR' AND
```

- B) Otherwise, let *CATSTR* be the character string:

```
UPPER( TABLE_CAT ) = UPPER( 'CATVAL' ) AND
```

## ii) Case:

- 1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING( TRIM( SCHVAL ) FROM 1 FOR 1 ) = ''` and if `SUBSTRING( TRIM( SCHVAL ) FROM CHAR_LENGTH( TRIM( SCHVAL ) ) FOR 1 ) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING( TRIM( SCHVAL ) FROM 2
FOR CHAR_LENGTH( TRIM( SCHVAL ) ) - 2)
```

and let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'TEMPSTR' AND
```

B) Otherwise, let *SCHSTR* be the character string:

```
UPPER( TABLE_SCHEM ) = UPPER( 'SCHVAL' ) AND
```

iii) Case:

1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

2) Otherwise,

Case:

A) If `SUBSTRING( TRIM( TBLVAL ) FROM 1 FOR 1 ) = ''` and if `SUBSTRING( TRIM( TBLVAL ) FROM CHAR_LENGTH( TRIM( TBLVAL ) ) FOR 1 ) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING( TRIM( TBLVAL ) FROM 2
FOR CHAR_LENGTH( TRIM( TBLVAL ) ) - 2)
```

and let *TBLSTR* be the character string:

```
TABLE_NAME = 'TEMPSTR' AND
```

B) Otherwise, let *TBLSTR* be the character string:

```
UPPER( TABLE_NAME ) = UPPER( 'TBLVAL' ) AND
```

b) Otherwise:

i) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
TABLE_CAT = 'CATVAL' AND
```

ii) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'SCHVAL' AND
```

iii) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string; otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME = 'TBLVAL' AND
```

20) Let the value of *SCPSTR* be the character string:

```
SCOPE >= SCPVAL
```

21) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || SCPSTR
```

22) Case:

- a) If *NULVAL* is equal to the code for NO NULLS in Table 26, "Miscellaneous codes used in CLI", and any of the rows selected by the above query would describe a column for which the value of *IS\_NULLABLE* column in the *COLUMNS* view is 'YES', then let *STMT* be the character string:

```
SELECT *  
FROM SPECIAL_COLUMNS_QUERY  
WHERE 1 = 2 -- select no rows  
ORDER BY SCOPE
```

- b) Otherwise, let *STMT* be the character string:

```
SELECT *  
FROM SPECIAL_COLUMNS_QUERY  
WHERE PRED  
ORDER BY SCOPE
```

23) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

## 6.61 StartTran

### Function

Explicitly start an SQL-transaction and set its characteristics.

### Definition

```

StartTran (
    HandleType           IN SMALLINT,
    Handle               IN INTEGER,
    AccessMode           IN INTEGER,
    IsolationLevel       IN INTEGER )
RETURNS SMALLINT

```

### General Rules

- 1) Let *HT* be the value of HandleType and let *H* be the value of Handle.
- 2) If *HT* is not one of the code values in Table 13, "Codes used for handle types", then an exception condition is raised: *CLI-specific condition — invalid handle*.
- 3) Case:
  - a) If *HT* indicates STATEMENT HANDLE, then:
    - i) If *H* does not identify an allocated SQL-statement, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
  - b) If *HT* indicates DESCRIPTOR HANDLE, then:
    - i) If *H* does not identify an allocated CLI descriptor area, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise, an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
  - c) If *HT* indicates CONNECTION HANDLE, then:
    - i) If *H* does not identify an allocated SQL-connection, then an exception condition is raised: *CLI-specific condition — invalid handle*.
    - ii) Otherwise:
      - 1) Let *C* be the allocated SQL-connection identified by *H*.
      - 2) The diagnostics area associated with *C* is emptied.
      - 3) Case:
        - A) If there is no established SQL-connection associated with *C*, then an exception condition is raised: *connection exception — connection does not exist*.

**6.61 StartTran**

- B) Otherwise, let *EC* be the established SQL-connection associated with *C*.
- 4) If *C* has an associated established SQL-connection that is active, then let *L1* be a list containing *EC*; otherwise, let *L1* be an empty list.
- d) If *HT* indicates ENVIRONMENT HANDLE, then:
- i) If *H* does not identify an allocated SQL-environment or if it identifies an allocated SQL-environment that is a skeleton SQL-environment, then an exception condition is raised: *CLI-specific condition — invalid handle*.
  - ii) Otherwise:
    - 1) Let *E* be the allocated SQL-environment identified by *H*.
    - 2) The diagnostics area associated with *E* is emptied.
    - 3) Let *L* be a list of the allocated SQL-connections associated with *E*. Let *L1* be a list of the allocated SQL-connections in *L* that have an associated established SQL-connection that is active.
- 4) If an SQL-transaction is currently active on any of the SQL-connections contained in *L1*, then an exception condition is raised: *invalid transaction state — active SQL-transaction*.
- 5) Let *AM* be the value for AccessMode. If *AM* is not one of the codes in Table 36, "Values for TRANSACTION ACCESS MODE with StartTran", then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 6) Let *IL* be the value for IsolationLevel. If *IL* is not one of the codes in Table 35, "Values for TRANSACTION ISOLATION OPTION with GetInfo and StartTran", then an exception condition is raised: *CLI-specific condition — invalid attribute identifier*.
- 7) Let *TXN* be the SQL-transaction that is started by this invocation of the StartTran routine.
- 8) If READ ONLY is specified by *AM*, then the access mode of *TXN* is set to read-only. If READ WRITE is specified by *AM*, then the access mode of *TXN* is set to read-write.
- 9) The isolation level of *TXN* is set to an implementation-defined isolation level that will not exhibit any of the phenomena that the isolation level indicated by *TIL* would not exhibit, as specified in Table 10, "SQL-transaction isolation levels and the three phenomena", in ISO/IEC 9075-2.
- 10) *TXN* is started in each SQL-connection contained in *L1*.

## 6.62 TablePrivileges

### Function

Return a result set that contains a list of the privileges held on the tables whose names adhere to the requested pattern(s) within tables described by the Information Schemas of the connected data source.

### Definition

```
TablePrivileges (
    StatementHandle      IN      INTEGER,
    CatalogName          IN      CHARACTER(L1),
    NameLength1          IN      SMALLINT,
    SchemaName           IN      CHARACTER(L2),
    NameLength2          IN      SMALLINT,
    TableName            IN      CHARACTER(L3),
    NameLength3          IN      SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ , and  $L3$  are determined by the values of NameLength1, NameLength2, and NameLength3, respectively and each of  $L1$ ,  $L2$ , and  $L3$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

### General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $TABLE\_PRIVILEGES\_QUERY$  be a table, with the definition:

```
CREATE TABLE TABLE_PRIVILEGES_QUERY (
    TABLE_CAT          CHARACTER VARYING(128),
    TABLE_SCHEM       CHARACTER VARYING(128) NOT NULL,
    TABLE_NAME        CHARACTER VARYING(128) NOT NULL,
    GRANTOR             CHARACTER VARYING(128) NOT NULL,
    GRANTEE            CHARACTER VARYING(128) NOT NULL,
    PRIVILEGE          CHARACTER VARYING(128) NOT NULL,
    IS_GRANTABLE       CHARACTER VARYING(3) NOT NULL,
    WITH_HIERARCHY     CHARACTER VARYING(254) NOT NULL )
```

- 6)  $TABLE\_PRIVILEGES\_QUERY$  contains a row for each privilege in  $SS$ 's Information Schema  $TABLE\_PRIVILEGES$  view where:
  - a) Let  $SUP$  be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").

**6.62 TablePrivileges**

- b) Case:
- i) If the value of *SUP* is 1 (one), then *TABLE\_PRIVILEGES\_QUERY* contains a row for each privilege in *SS*'s Information Schema *TABLE\_PRIVILEGES* view.
  - ii) Otherwise, *TABLE\_PRIVILEGES\_QUERY* contains a row for each privilege in *SS*'s Information Schema *TABLE\_PRIVILEGES* view that meets implementation-defined authorization criteria.
- 7) For each row of *TABLE\_PRIVILEGES\_QUERY*:
- a) If the implementation does not support catalog names, then *TABLE\_CAT* is the null value; otherwise, the value of *TABLE\_CAT* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *TABLE\_CATALOG* column in the *TABLE\_PRIVILEGES* view in the information schema.
  - b) The value of *TABLE\_SCHEM* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *TABLE\_SCHEMA* column in the *TABLE\_PRIVILEGES* view.
  - c) The value of *TABLE\_NAME* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *TABLE\_NAME* column in the *TABLE\_PRIVILEGES* view.
  - d) The value of *GRANTOR* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *GRANTOR* column in the *TABLE\_PRIVILEGES* view.
  - e) The value of *GRANTEE* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *GRANTEE* column in the *TABLE\_PRIVILEGES* view.
  - f) The value of *PRIVILEGE* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *PRIVILEGE\_TYPE* column in the *TABLE\_PRIVILEGES* view.
  - g) The value of *IS\_GRANTABLE* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *IS\_GRANTABLE* column in the *TABLE\_PRIVILEGES* view.
  - h) The value of *WITH\_HIERARCHY* in *TABLE\_PRIVILEGES\_QUERY* is the value of the *WITH\_HIERARCHY* column in the *TABLE\_PRIVILEGES* view.
- 8) Let *NL1*, *NL2*, and *NL3* be the values of *NameLength1*, *NameLength2*, and *NameLength3*, respectively.
- 9) Let *CATVAL*, *SCHVAL*, and *TBLVAL* be the values of *CatalogName*, *SchemaName*, and *TableName*, respectively.
- 10) If the METADATA ID attribute of *S* is TRUE, then:
- a) If *CatalogName* is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", is 'Y', then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - b) If *SchemaName* is a null pointer or if *TableName* is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- 11) If *CatalogName* is a null pointer, then *NL1* is set to zero. If *SchemaName* is a null pointer, then *NL2* is set to zero. If *TableName* is a null pointer, then *NL3* is set to zero.
- 12) Case:
- a) If *NL1* is not negative, then let *L* be *NL1*.

- b) If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of *CatalogName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *CATVAL* be the first *L* octets of *CatalogName*.

13) Case:

- a) If *NL2* is not negative, then let *L* be *NL2*.
- b) If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of *SchemaName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *SCHVAL* be the first *L* octets of *SchemaName*.

14) Case:

- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of *TableName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TBLVAL* be the first *L* octets of *TableName*.

15) Case:

- a) If the METADATA ID attribute of *S* is TRUE, then:

- i) Case:

- 1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
    - 2) Otherwise,

- Case:

- A) If `SUBSTRING(TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(CATVAL) FROM CHAR_LENGTH(TRIM(CATVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING(TRIM(CATVAL) FROM 2
FOR CHAR_LENGTH(TRIM(CATVAL)) - 2)
```

and let *CATSTR* be the character string:

```
TABLE_CAT = 'TEMPSTR' AND
```

B) Otherwise, let *CATSTR* be the character string:

UPPER(TABLE\_CAT) = UPPER('CATVAL') AND

ii) Case:

1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.

2) Otherwise,

Case:

A) If SUBSTRING(TRIM(*SCHVAL*) FROM 1 FOR 1) = '' and if SUBSTRING(TRIM(*SCHVAL*) FROM CHAR\_LENGTH(TRIM(*SCHVAL*)) FOR 1) = '', then let *TEMPSTR* be the value obtained from evaluating:

a) SUBSTRING(TRIM(*SCHVAL*) FROM 2  
FOR CHAR\_LENGTH(TRIM(*SCHVAL*)) - 2)

and let *SCHSTR* be the character string:

TABLE\_SCHEM = 'TEMPSTR' AND

B) Otherwise, let *SCHSTR* be the character string:

UPPER(TABLE\_SCHEM) = UPPER('SCHVAL') AND

iii) Case:

1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.

2) Otherwise,

Case:

A) If SUBSTRING(TRIM(*TBLVAL*) FROM 1 FOR 1) = '' and if SUBSTRING(TRIM(*TBLVAL*) FROM CHAR\_LENGTH(TRIM(*TBLVAL*)) FOR 1) = '', then let *TEMPSTR* be the value obtained from evaluating:

SUBSTRING(TRIM(*TBLVAL*) FROM 2  
FOR CHAR\_LENGTH(TRIM(*TBLVAL*)) - 2)

and let *TBLSTR* be the character string:

TABLE\_NAME = 'TEMPSTR' AND

B) Otherwise, let *TBLSTR* be the character string:

UPPER(TABLE\_NAME) = UPPER('TBLVAL') AND

b) Otherwise,

i) Let *SPC* be the Code value from Table 28, "Codes and data types for implementation information", that corresponds to the Information Type SEARCH PATTERN ESCAPE in that same table.

ii) Let *ESC* be the value of InfoValue that is returned by the execution of GetInfo() with the value of InfoType set to *SPC*.

- iii) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
TABLE_CAT = 'CATVAL' AND
```

- iv) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM LIKE 'SCHVAL' ESCAPE 'ESC' AND
```

- v) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string. Otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME LIKE 'TBLVAL' ESCAPE 'ESC' AND
```

- 16) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || 1=1
```

- 17) Let *STMT* be the character string:

```
SELECT *
FROM TABLE_PRIVILEGES_QUERY
WHERE PRED
ORDER BY TABLE_CAT, TABLE_SCHEM, TABLE_NAME, PRIVILEGE
```

- 18) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

## 6.63 Tables

## 6.63 Tables

## Function

Based on the specified selection criteria, return a result set that contains information about tables described by the information schemas of the connected data source.

## Definition

```
Tables (
    StatementHandle      IN      INTEGER,
    CatalogName         IN      CHARACTER(L1),
    NameLength1         IN      SMALLINT,
    SchemaName          IN      CHARACTER(L2),
    NameLength2         IN      SMALLINT,
    TableName           IN      CHARACTER(L3),
    NameLength3         IN      SMALLINT,
    TableType           IN      CHARACTER(L4),
    NameLength4         IN      SMALLINT )
RETURNS SMALLINT
```

where  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  are determined by the values of NameLength1, NameLength2, and NameLength3, and NameLength4, respectively, and each of  $L1$ ,  $L2$ ,  $L3$ , and  $L4$  has a maximum value equal to the implementation-defined maximum length of a variable-length character string.

## General Rules

- 1) Let  $S$  be the allocated SQL-statement identified by StatementHandle.
- 2) If an open cursor is associated with  $S$ , then an exception condition is raised: *invalid cursor state*.
- 3) Let  $C$  be the allocated SQL-connection with which  $S$  is associated.
- 4) Let  $EC$  be the established SQL-connection associated with  $C$  and let  $SS$  be the SQL-server on that connection.
- 5) Let  $TABLES\_QUERY$  be a table with the definition:

```
CREATE TABLE TABLES_QUERY (
    TABLE_CAT          CHARACTER VARYING(128),
    TABLE_SCHEM        CHARACTER VARYING(128),
    TABLE_NAME         CHARACTER VARYING(128),
    TABLE_TYPE         CHARACTER VARYING(254),
    REMARKS              CHARACTER VARYING(254),
    SELF_REF_COLUMN     CHARACTER VARYING(128),
    REF_GENERATION      CHARACTER VARYING(254),
    UDT_CAT              CHARACTER VARYING(128),
    UDT_SCHEM           CHARACTER VARYING(128),
    UDT_NAME             CHARACTER VARYING(128),
    UNIQUE (TABLE_CAT, TABLE_SCHEM, TABLE_NAME) )
```

- 6) *TABLES\_QUERY* contains a row for each table described by *SS*'s Information Schema *TABLES* view where:
- a) Let *SUP* be the value of Supported that is returned by the execution of GetFeatureInfo with FeatureType = 'FEATURE' and FeatureId = 'C041' (corresponding to the feature "Information Schema metadata constrained by privileges").
  - b) Case:
    - i) If the value of *SUP* is 1 (one), then *TABLES\_QUERY* contains a row for each row describing a table in *SS*'s Information Schema *TABLES* view for which the connected UserName has selection privileges.
    - ii) Otherwise, *TABLES\_QUERY* contains a row for each row describing a table in *SS*'s Information Schema *TABLES* view that meets implementation-defined authorization criteria.
- 7) The description of the table *TABLES\_QUERY* is:
- a) The value of *TABLE\_CAT* in *TABLES\_QUERY* is the value of the *TABLE\_CATALOG* column in the *TABLES* view. If *SS* does not support catalog names, then *TABLE\_CAT* is set to the null value.
  - b) The value of *TABLE\_SCHEM* in *TABLES\_QUERY* is the value of the *TABLE\_SCHEMA* column in the *TABLES* view. The value of *TABLE\_NAME* in *TABLES\_QUERY* is the value of the *TABLE\_NAME* column in the *TABLES* view.
  - c) The value of *TABLE\_TYPE* in *TABLES\_QUERY* is determined by the values of the *TABLE\_TYPE* column in the *TABLES* view.
 

Case:

    - i) If the value of *TABLE\_TYPE* in the *TABLES* view is 'VIEW', then:
 

Case:

      - 1) If the defined view is within the Information Schema itself, then the value of *TABLE\_TYPE* in *TABLES\_QUERY* is set to 'SYSTEM TABLE'.
      - 2) Otherwise, the value of *TABLE\_TYPE* in *TABLES\_QUERY* is set to 'VIEW'.
    - ii) If the value of *TABLE\_TYPE* in the *TABLES* view is 'BASE TABLE', then the value of *TABLE\_TYPE* in *TABLES\_QUERY* is set to 'TABLE'.
    - iii) If the value of *TABLE\_TYPE* in the *TABLES* view is 'GLOBAL TEMPORARY' or 'LOCAL TEMPORARY', then the value of *TABLE\_TYPE* in *TABLES\_QUERY* is set to that value.
    - iv) Otherwise, the value of *TABLE\_TYPE* in *TABLES\_QUERY* is an implementation-defined value.
  - d) The value of *REMARKS* in *TABLES\_QUERY* is an implementation-defined description of the table.
  - e) The value of *SELF\_REF\_COLUMN* in *TABLES\_QUERY* is the value of the *SELF\_REFERENCING\_COLUMN\_NAME* column in the *TABLES* view.

**6.63 Tables**

- f) The value of REF\_GENERATION in *TABLES\_QUERY* is the value of the REFERENCE\_GENERATION column in the TABLES view.
- g) The value of UDT\_CAT in *TABLES\_QUERY* is the value of the USER\_DEFINED\_TYPE\_CATALOG column in the TABLES view.
- h) The value of UDT\_SCHEMA in *TABLES\_QUERY* is the value of the USER\_DEFINED\_TYPE\_SCHEMA column in the TABLES view.
- i) The value of UDT\_NAME in *TABLES\_QUERY* is the value of the USER\_DEFINED\_TYPE\_NAME column in the TABLES view.
- 8) Let *NL1*, *NL2*, *NL3*, and *NL4* be the values of NameLength1, NameLength2, NameLength3, and NameLength4, respectively.
- 9) Let *CATVAL*, *SCHVAL*, *TBLVAL*, and *TYPVAL* be the values of CatalogName, SchemaName, TableName, and TableType, respectively.
- 10) If the METADATA ID attribute of *S* is TRUE, then:
- If CatalogName is a null pointer and the value of the CATALOG NAME information type from Table 28, "Codes and data types for implementation information", is 'Y', then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
  - If SchemaName is a null pointer or if TableName is a null pointer, then an exception condition is raised: *CLI-specific condition — invalid use of null pointer*.
- 11) If CatalogName is a null pointer, then *NL1* is set to zero. If SchemaName is a null pointer, then *NL2* is set to zero. If TableName is a null pointer, then *NL3* is set to zero. If TableType is a null pointer, then *NL4* is set to zero.
- 12) Case:
- If *NL1* is not negative, then let *L* be *NL1*.
  - If *NL1* indicates NULL TERMINATED, then let *L* be the number of octets of CatalogName that precede the implementation-defined null character that terminates a C character string.
  - Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- Let *CATVAL* be the first *L* octets of CatalogName.
- 13) Case:
- If *NL2* is not negative, then let *L* be *NL2*.
  - If *NL2* indicates NULL TERMINATED, then let *L* be the number of octets of SchemaName that precede the implementation-defined null character that terminates a C character string.
  - Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.
- Let *SCHVAL* be the first *L* octets of SchemaName.

## 14) Case:

- a) If *NL3* is not negative, then let *L* be *NL3*.
- b) If *NL3* indicates NULL TERMINATED, then let *L* be the number of octets of *TableName* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TBLVAL* be the first *L* octets of *TableName*.

## 15) Case:

- a) If *NL4* is not negative, then let *L* be *NL4*.
- b) If *NL4* indicates NULL TERMINATED, then let *L* be the number of octets of *TableType* that precede the implementation-defined null character that terminates a C character string.
- c) Otherwise, an exception condition is raised: *CLI-specific condition — invalid string length or buffer length*.

Let *TYPVAL* be the first *L* octets of *ColumnName*.

## 16) Case:

- a) If the METADATA ID attribute of *S* is TRUE, then:

## i) Case:

- 1) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string.
- 2) Otherwise,

Case:

- A) If `SUBSTRING( TRIM(CATVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING( TRIM(CATVAL) FROM CHAR_LENGTH( TRIM(CATVAL) ) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(CATVAL) FROM 2
FOR CHAR_LENGTH ( TRIM(CATVAL) ) - 2 )
```

and let *CATSTR* be the character string:

```
TABLE_CAT = 'TEMPSTR' AND
```

- B) Otherwise, let *CATSTR* be the character string:

```
UPPER(TABLE_CAT) = UPPER('CATVAL') AND
```

## ii) Case:

- 1) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string.
- 2) Otherwise,

## 6.63 Tables

Case:

- A) If `SUBSTRING(TRIM(SCHVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(SCHVAL) FROM CHAR_LENGTH(TRIM(SCHVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(SCHVAL) FROM 2
           FOR CHAR_LENGTH ( TRIM(SCHVAL) ) - 2 )
```

and let *SCHSTR* be the character string:

```
TABLE_SCHEM = 'TEMPSTR' AND
```

- B) Otherwise, let *SCHSTR* be the character string:

```
UPPER(TABLE_SCHEM) = UPPER('SCHVAL') AND
```

iii) Case:

- 1) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string.
- 2) Otherwise,

Case:

- A) If `SUBSTRING(TRIM(TBLVAL) FROM 1 FOR 1) = ''` and if `SUBSTRING(TRIM(TBLVAL) FROM CHAR_LENGTH(TRIM(TBLVAL)) FOR 1) = ''`, then let *TEMPSTR* be the value obtained from evaluating:

```
SUBSTRING ( TRIM(TBLVAL) FROM 2
           FOR CHAR_LENGTH ( TRIM(TBLVAL) ) - 2 )
```

and let *TBLSTR* be the character string:

```
TABLE_NAME = 'TEMPSTR' AND
```

- B) Otherwise, let *TBLSTR* be the character string:

```
UPPER(TABLE_NAME) = UPPER('TBLVAL') AND
```

b) Otherwise:

- i) Let *SPC* be the Code value from Table 28, "Codes and data types for implementation information", that corresponds to the Information Type SEARCH PATTERN ESCAPE in that same table.
- ii) Let *ESC* be the value of InfoValue that is returned by the execution of GetInfo() with the value of InfoType set to *SPC*.
- iii) If the value of *NL1* is zero, then let *CATSTR* be a zero-length string; otherwise, let *CATSTR* be the character string:

```
TABLE_CAT = 'CATVAL' AND
```

- iv) If the value of *NL2* is zero, then let *SCHSTR* be a zero-length string; otherwise, let *SCHSTR* be the character string:

```
TABLE_SCHEM LIKE 'SCHVAL' ESCAPE 'ESC' AND
```

- v) If the value of *NL3* is zero, then let *TBLSTR* be a zero-length string; otherwise, let *TBLSTR* be the character string:

```
TABLE_NAME LIKE 'TBLVAL' ESCAPE 'ESC' AND
```

17) Case:

- a) If the value of *NL4* is zero, then let *TYPSTR* be a zero-length string.
- b) Otherwise,
- i) *TableType* is a comma-separated list of one or more types of tables that are to be returned in the result set. Each value may optionally be enclosed within <quote> characters. The types are 'TABLE', 'VIEW', 'GLOBAL TEMPORARY', 'LOCAL TEMPORARY', and 'SYSTEM TABLE'.  
NOTE 66 – These types are mutually exclusive; for instance, 'TABLE' includes only user-created base tables and 'SYSTEM TABLE' includes only views from the Information Schemas. Implementation-defined types may also be specified.
  - ii) Let *N* be the number of comma-separated values specified within *TableType*.
  - iii) Let *TT* be the set of comma-separated values *TT<sub>i</sub>*,  $1 \leq i \leq N$ , specified within *TableType*.
  - iv) *TYPSTR* is a string that is the predicate required to select the requested types of tables from *TABLES\_QUERY*:

```
TABLE_TYPE = ' ' || TRIM(TT1) || ' ' OR
TABLE_TYPE = ' ' || TRIM(TT2) || ' ' OR
.
.
TABLE_TYPE = ' ' || TRIM(TTN) || ' '
```

18) Let *PRED* be the result of evaluating:

```
CATSTR || ' ' || SCHSTR || ' ' || TBLSTR || ' ' || TYPSTR || ' ' || 1=1
```

19) Case:

- a) If the value of *CATVAL* is the value in the 'Value' column for ALL CATALOGS in Table 42, "Special parameter values", and both *SCHVAL* and *TBLVAL* are zero-length strings, then let *STMT* be the character string:

```
SELECT DISTINCT TABLE_CAT,
               CAST (NULL AS VARCHAR(128)),
               CAST (NULL AS VARCHAR(128)),
               CAST (NULL AS VARCHAR(254)),
               CAST (NULL AS VARCHAR(254))
FROM TABLES_QUERY
ORDER BY TABLE_CAT
```

NOTE 67 – All tables qualify for selection and no privileges are required for access to the underlying TABLES view.

## 6.63 Tables

- b) If the value of *SCHVAL* is the value in the 'Value' column for ALL SCHEMAS in Table 42, "Special parameter values", and both *CATVAL* and *TBLVAL* are zero-length strings, then let *STMT* be the character string:

```
SELECT DISTINCT CAST (NULL AS VARCHAR(128)),
                TABLE_SCHEM,
                CAST (NULL AS VARCHAR(128)),
                CAST (NULL AS VARCHAR(254)),
                CAST (NULL AS VARCHAR(254))
FROM TABLES_QUERY
ORDER BY TABLE_SCHEM
```

NOTE 68 – All tables qualify for selection and no privileges are required for access to the underlying TABLES view.

- c) If the value of *TYPVAL* is the value in the 'Value' column for ALL TYPES in Table 42, "Special parameter values", and *CATVAL*, *SCHVAL*, and *TBLVAL* are zero-length strings, then let *STMT* be the character string:

```
SELECT DISTINCT CAST (NULL AS VARCHAR(128)),
                CAST (NULL AS VARCHAR(128)),
                CAST (NULL AS VARCHAR(128)),
                TABLE_TYPE,
                CAST (NULL AS VARCHAR(254))
FROM TABLES_QUERY
ORDER BY TABLE_TYPE
```

NOTE 69 – All tables qualify for selection and no privileges are required for access to the underlying TABLES view.

- d) Otherwise, let *STMT* be the character string:

```
SELECT *
FROM TABLES_QUERY
WHERE PRED
ORDER BY TABLE_TYPE, TABLE_CAT, TABLE_SCHEM, TABLE_NAME
```

- 20) ExecDirect is implicitly invoked with *S* as the value of StatementHandle, *STMT* as the value of StatementText, and the length of *STMT* as the value of TextLength.

## 7 Definition Schema

### 7.1 SQL\_IMPLEMENTATION\_INFO base table

#### Function

The SQL\_IMPLEMENTATION\_INFO base table has one row for each implementation information item defined by ISO/IEC 9075.

#### Definition

*No additional Definition items*

#### Description

- 1)  Some IMPLEMENTATION\_INFO\_ID values assigned by ISO/IEC 9075 have been assigned for backwards compatibility with ISO/IEC 9075-3:1995. All other values assigned by ISO/IEC 9075 are in the range 21000 through 24999, inclusive.
- 2)  Implementation-defined items that are represented in this table shall have an IMPLEMENTATION\_INFO\_ID value that is in the range 11000 through 14999, inclusive.

#### Table population

The implementation shall effectively populate the SQL\_IMPLEMENTATION\_INFO base table with an <insert statement> that is equivalent to the <insert statement> shown below; the <insert statement> shown below provides values only for certain columns and implicitly assigns the null value to other columns of the table.

The implementation effectively populates the table so that, for each row containing information about some facility that the implementation supports, either the INTEGER\_VALUE column or the CHARACTER\_VALUE column is set to a value that specifies the requisite information about that supported facility. For all information items that the implementation does not support, both the INTEGER\_VALUE and the CHARACTER\_VALUE column have the null value. The COMMENTS column may be set to any value deemed appropriate by the implementation, or it may be set to the null value.

## 7.1 SQL\_IMPLEMENTATION\_INFO base table

```

INSERT INTO sql_implementation_info ( implementation_info_id,
                                     implementation_info_name,
                                     comments )
VALUES ( ( 10003, 'CATALOG NAME',
            'CHAR: 'Y' if supported, otherwise 'N' ),
        ( 10004, 'COLLATING SEQUENCE',
            'CHAR: default collation name' ),
        ( 23, 'CURSOR COMMIT BEHAVIOR',
            'INT: 0: close cursors & delete prepared stmts
                  1: close cursors & retain prepared stmts
                  2: leave cursors open & retain stmts' ),
        ( 2, 'DATA SOURCE NAME',
            'CHAR: <connection name> on CONNECT statement' ),
        ( 17, 'DBMS NAME',
            'CHAR: Name of the implementation software' ),
        ( 18, 'DBMS VERSION',
            'CHAR: Version of the implementation software
            The format is:
              <part1>.<part2>.<part3>[<part4>]
            where:
              <part1 ::= <digit><digit>
              <part2 ::= <digit><digit>
              <part3 ::= <digit><digit><digit><digit>
              <part4 ::= <character representation>' ),
        ( 26, 'DEFAULT TRANSACTION ISOLATION',
            'INT: 1: READ UNCOMMITTED
                  2: READ COMMITTED
                  3: REPEATABLE READ
                  4: SERIALIZABLE' ),
        ( 28, 'IDENTIFIER CASE',
            'The case in which identifiers are stored in the Definition Schema
            INT: 1: stored in upper case
                  2: stored in lower case
                  3: stored in mixed case - case sensitive
                  4: stored in mixed case - case insensitive' ),
        ( 85, 'NULL COLLATION',
            'INT: 0: nulls higher than non-nulls
                  1: nulls lower than non-nulls' ),
        ( 13, 'SERVER NAME',
            'CHAR: <SQL server name> on CONNECT statement' ),
        ( 94, 'SPECIAL CHARACTERS',
            'CHAR: All special chars OK in non-delimited ids' ),
        ( 46, 'TRANSACTION CAPABLE',
            'INT: 0: not supported
                  1: DML only - error if DDL
                  2: both DML and DDL
                  3: DML only - commit before DDL
                  4: DML only - ignore DDL' )
);

```

## 7.2 SQL\_SIZING base table

### Function

The SQL\_SIZING base table has one row for each sizing item defined by ISO/IEC 9075.

### Definition

*No additional Definition items*

### Description

- 1)  Some SIZING\_ID values assigned by ISO/IEC 9075 have been assigned for backwards compatibility with ISO/IEC 9075-3:1995. All other values assigned by ISO/IEC 9075 are in the range 25000 through 29999, inclusive.
- 2)  Implementation-defined items that are represented in this table shall have a SIZING\_ID value that is in the range 15000 through 19999, inclusive.

### Table population

The implementation shall effectively populate the SQL\_SIZING base table with an <insert statement> that is equivalent to the <insert statement> shown below; the <insert statement> shown below provides values only for certain columns and implicitly assigns the null value to other columns of the table.

The implementation effectively populates the table so that, for each row containing information about some facility that the implementation supports, the SUPPORTED\_VALUE column is set to a value that specifies the requisite information about that supported facility. For all information items that the implementation does not support, the SUPPORTED\_VALUE column has the null value. The COMMENTS column may be set to any value deemed appropriate by the implementation, or it may be set to the null value.

```
INSERT INTO sql_sizing ( sizing_id, sizing_name, comments )
VALUES ( ( 34, 'MAXIMUM CATALOG NAME LENGTH',
           'Length in characters' ),
        ( 30, 'MAXIMUM COLUMN NAME LENGTH',
           'Length in characters' ),
        ( 97, 'MAXIMUM COLUMNS IN GROUP BY', NULL ),
        ( 99, 'MAXIMUM COLUMNS IN ORDER BY', NULL ),
        ( 100, 'MAXIMUM COLUMNS IN SELECT',
           'Max number of expressions in <select list>' ),
        ( 101, 'MAXIMUM COLUMNS IN TABLE', NULL ),
        ( 1, 'MAXIMUM CONCURRENT ACTIVITIES',
           'Max number of SQL-statements currently active' ),
        ( 31, 'MAXIMUM CURSOR NAME LENGTH',
           'Length in characters' ),
        ( 0, 'MAXIMUM DRIVER CONNECTIONS',
           'Max number of SQL-connections currently established' ),
        ( 10005, 'MAXIMUM IDENTIFIER LENGTH',
           'Length in characters;
           If different for some objects, set to smallest max' ),
        ( 32, 'MAXIMUM SCHEMA NAME LENGTH',
           'Length in characters' ),
        ( 20000, 'MAXIMUM STATEMENT OCTETS',
           'Max length in octets of <SQL statement variable>' ),
        ( 20001, 'MAXIMUM STATEMENT OCTETS DATA',
           'Max length in octets of <SQL data statement>' ),
        ( 20002, 'MAXIMUM STATEMENT OCTETS SCHEMA',
           'Max length in octets of SQL <schema definition>' ),
        ( 35, 'MAXIMUM TABLE NAME LENGTH',
           'Max length in chars of low order table name part' ),
        ( 106, 'MAXIMUM TABLES IN SELECT',
           'Max number of table names in FROM clause' ),
        ( 107, 'MAXIMUM USER NAME LENGTH',
           'Length in characters for a <user identifier> of an SQL-session' ),
        ( 25000, 'MAXIMUM CURRENT DEFAULT TRANSFORM GROUP LENGTH',
           'Length in characters' ),
        ( 25001, 'MAXIMUM CURRENT TRANSFORM GROUP LENGTH',
           'Length in characters' ),
        ( 25002, 'MAXIMUM CURRENT PATH LENGTH',
           'Length in characters' ),
        ( 25003, 'MAXIMUM CURRENT ROLE LENGTH',
           'Length in characters' ),
        ( 25004, 'MAXIMUM SESSION USER LENGTH',
           'Length in characters' ),
        ( 25005, 'MAXIMUM SYSTEM USER LENGTH',
           'Length in characters' )
);
```

### 7.3 SQL\_LANGUAGES base table

#### Function

The SQL\_LANGUAGES table has one row for each ISO and implementation-defined SQL language binding and programming language for which conformance is claimed.

NOTE 70 – The SQL\_LANGUAGES base table provides, among other information, the same information provided by the SQL object identifier specified in Subclause 6.3, "Object identifier for Database Language SQL", in ISO/IEC 9075-1.

#### Definition

Augment the column constraint SQL\_LANGUAGE\_BINDING\_STYLE\_ISO\_1992 in Part 5 Add 'CLI' to the <in value list> of valid SQL\_LANGUAGE\_BINDING\_STYLES.

Augment the column constraint SQL\_LANGUAGE\_BINDING\_STYLE\_ISO\_1999 in Part 5 Add 'CLI' to the <in value list> of valid SQL\_LANGUAGE\_BINDING\_STYLES.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999

## 8 Conformance

### 8.1 Conformance to SQL/CLI

This part of ISO/IEC 9075 specifies conforming SQL/CLI routines and conforming SQL/CLI implementations.

A conforming SQL/CLI application is one that invokes SQL/CLI routines specified in this part of ISO/IEC 9075. Such routine invocations shall be constructed according to the BNF Format and associated Syntax Rules, Access Rules, and Definitions specified for <CLI routine>s in Clause 5, “Call-Level Interface specifications”, and Clause 6, “SQL/CLI routines”, in this part of ISO/IEC 9075.

A conforming SQL/CLI implementation shall process conforming SQL/CLI routine invocations according to the associated Definitions and General Rules in Clause 5, “Call-Level Interface specifications”, and Clause 6, “SQL/CLI routines”, in this part of ISO/IEC 9075. A conforming SQL/CLI implementation shall process SQL-statements in the manner specified in Core SQL and in the set of any additional features to which conformance is claimed by the SQL-implementation.

NOTE 71 – Certain facilities specified in this part of ISO/IEC 9075 are closely related to specific facilities specified in ISO/IEC 9075-2 and ISO/IEC 9075-5; such facilities specified in this part of ISO/IEC 9075 are not supported unless the corresponding facilities in ISO/IEC 9075-2 and ISO/IEC 9075-5 are supported. The relationships between the facilities specified in this part of ISO/IEC 9075 and the corresponding facilities in ISO/IEC 9075-2 and ISO/IEC 9075-5 are not specified, but are inferable.

For example, provision of the GetPosition, GetSubstring, and GetLength routines specified in this part of ISO/IEC 9075 is dependent on support of the LARGE OBJECT data types specified in ISO/IEC 9075-2.

### 8.2 Claims of conformance

Insert this paragraph Claims of conformance to this part of ISO/IEC 9075 shall state:

- 1)  Insert after (list element 2) in ISO/IEC 9075-1 Which of the following standard programming languages are supported for SQL/CLI routine invocation (see Subclause 5.2, “<CLI routine> invocation”):
  - a) Ada
  - b) C
  - c) COBOL
  - d) Fortran
  - e) MUMPS
  - f) Pascal
  - g) PL/I

## 8.2 Claims of conformance

- 2) Insert after list element 2) in ISO/IEC 9075-1 The definitions for all elements and actions that are specified in this part of ISO/IEC 9075 as implementation-defined.

## 8.3 Extensions and options

New paragraph A conforming implementation may provide support for additional implementation-defined routines or for implementation-defined argument values for <CLI routine>s.

New paragraph An implementation remains conforming even if it provides user options to process conforming <CLI routine> invocations in a nonconforming manner.

STANDARDSISO.COM : Click to view the full PDF of ISO/IEC 9075-3:1999