

Transformed.

ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

**ISO RECOMMENDATION
R 1020**

CINEMATOGRAPHY

**DIMENSIONS OF DAYLIGHT LOADING SPOOLS
FOR DOUBLE-8 mm MOTION-PICTURE FILM**

1st EDITION

March 1969

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1020:1969

BRIEF HISTORY

The ISO Recommendation R 1020, *Cinematography – Dimensions of daylight loading spools for double-8 mm motion-picture film*, was drawn up by Technical Committee ISO/TC 36, *Cinematography*, the Secretariat of which is held by the American National Standards Institute (ANSI).

Work on this question led to the adoption of a Draft ISO Recommendation.

In November 1966, this Draft ISO Recommendation (No. 1050) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Belgium	Germany	Netherlands
Brazil	Greece	Romania
Bulgaria	Hungary	Sweden
Canada	Israel	Switzerland
Chile	Italy	U.A.R.
Czechoslovakia	Japan	United Kingdom
France	Korea, Rep. of	U.S.A.

No Member Body opposed the approval of the Draft.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council which decided, in March 1969, to accept it as an ISO RECOMMENDATION.

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1020:1969

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1020:1969

CINEMATOGRAPHY

**DIMENSIONS OF DAYLIGHT LOADING SPOOLS
FOR DOUBLE-8 mm MOTION-PICTURE FILM**

1. SCOPE

This ISO Recommendation specifies the dimensions of daylight loading spools for double-8 mm motion-picture film.

STANDARDSISO.COM : Click to view the full PDF of ISO/R 1020:1969




FIG. 1 - Dimensions of daylight loading spools for double-8 mm motion-picture

* Flange I is provided on the side which engages the take-up spindle.

** See clause 2.8. This symbol signifies the runout of the cylindrical surface of the core with respect of the Z axis in the manner prescribed in ISO Recommendation R 1101, Tolerances of form and of position - Part 1: Generalities, symbols, indications on drawings.

*** See clause 2.6 for an explanation of P.

STANDARDSISO.COM: Click to view the full PDF of ISO/R 1020:1969




FIG. 2 - Enlarged views of 3 and 4-spined spindle holes

STANDARDSISO.COM · Click to view the full PDF of ISO/R 1020:1969

TABLE - Dimensions of double-8 mm nominal spool sizes

Dimension	Nominal spool size	millimetres	inches
<i>C</i>	7.5 m, 15 m, 30 m	7.30 $\begin{smallmatrix} +0.20 \\ 0 \end{smallmatrix}$	0.287 $\begin{smallmatrix} +0.008 \\ 0 \end{smallmatrix}$
<i>D</i>	7.5 m, 15 m, 30 m	9.8 $\begin{smallmatrix} +0.2 \\ 0 \end{smallmatrix}$	0.38 $\begin{smallmatrix} +0.01 \\ 0 \end{smallmatrix}$
<i>E</i>	7.5 m 15 m, 30 m	19.0 ± 0.3 32.0 ± 0.5	0.75 ± 0.01 1.26 ± 0.02
<i>F</i>	7.5 m, 15 m, 30 m	see clause 2.3	
<i>H</i> ₁	7.5 m, 15 m, 30 m	16.05 $\begin{smallmatrix} +0.35 \\ 0 \end{smallmatrix}$	0.632 $\begin{smallmatrix} +0.014 \\ 0 \end{smallmatrix}$
<i>H</i> ₂	7.5 m, 15 m, 30 m	16.00 min.	0.630 min.
<i>J</i> and <i>J</i> ₁	7.5 m, 15 m, 30 m	18.5 $\begin{smallmatrix} 0 \\ -0.4 \end{smallmatrix}$	0.73 $\begin{smallmatrix} 0 \\ -0.02 \end{smallmatrix}$
<i>K</i>	7.5 m 15 m, 30 m	15.6 min. 25.5 min.	0.61 min. 1.00 min.
<i>M</i> and <i>M</i> ₁	7.5 m 15 m 30 m	52.0 $\begin{smallmatrix} 0 \\ -0.8 \end{smallmatrix}$ 71.5 $\begin{smallmatrix} 0 \\ -1.0 \end{smallmatrix}$ 92.0 $\begin{smallmatrix} 0 \\ -1.0 \end{smallmatrix}$	2.05 $\begin{smallmatrix} 0 \\ -0.03 \end{smallmatrix}$ 2.81 $\begin{smallmatrix} 0 \\ -0.04 \end{smallmatrix}$ 3.62 $\begin{smallmatrix} 0 \\ -0.04 \end{smallmatrix}$
<i>P</i> (See clause 2.6)	7.5 m 15 m, 30 m	0.40 max. 0.50 max.	0.016 max. 0.020 max.
<i>S</i>	7.5 m 15 m, 30 m	0.5 0.8	0.02 0.03

2. DIMENSIONS AND CHARACTERISTICS

- 2.1 The dimensions given above are for general purpose double-8 mm motion-picture film spools with nominal capacities of 7.5 metres (25 feet), 15 metres (50 feet), and 30 metres (100 feet). Spools for high-speed cameras generally should be more carefully balanced and are not necessarily covered by this ISO Recommendation.
- 2.2 If rivet heads, or other fastening devices, extend beyond the outer surfaces of the flanges, they should lie at a diameter larger than the minimum *K* diameter and should be within the boundaries defined by other portions of the volume of rotation diagram.

- 2.3 Dimension F represents a slot in the spool core for attaching the film. Its design and dimensions are critical if a spool is to operate satisfactorily, both in self-threading cameras and cassette-loaded cameras. In self-threading cameras the film should, without fail, seek out and easily slide into the slot, but for cassette-loaded cameras the slot should resist extraction of the film by action of the clock-spring at the end of the first camera exposure run.

Starting at a point adjacent to the four-splined flange and running at least one-half the core width, the slot should be designed to meet manual-threading, self-threading, and cassette-loading requirements. Slot sides may diverge over the remaining one-half of the core width. One way of accomplishing this is to design the slot in the form of a weaving channel with an effective separation of 0.15 to 0.25 mm (0.006 to 0.010 in) between the teeth on one side of the slot and the teeth on the other side of the slot as measured with a wide, stiff blade-gauge which should slip easily into this zone.

- 2.4 Dimension H_2 is the space between the flanges inside the core, but outside the D diameter zone.
- 2.5 Dimensions J and J_1 represent the thickness or effective thickness, respectively, of the spool within the K diameter area which is centered on the spindle hole axis of each flange.
- 2.6 A reference plane of rotation for each flange is defined by a plane perpendicular to the axis of the spindle and coincident with the surface of a flat 15.0 mm (0.59 in) diameter support which is in contact with the flange and centered on the spindle hole axis of the flange.

The dimension P is the distance measured outwardly from this reference plane* of rotation to the farthest plane of rotation described by any point on the flange outside the K diameter area when the spool is rotated on an accurate, tight-fitting spindle. This includes rivets or other fastening devices, variations in flange thickness, flatness, and lateral runout of the flanges.

Selection of a dimension P value is dependent upon the thickness of the material used for the flanges. According to the flange material thickness :

- (a) the K diameter area may be depressed (with P greater than zero), or
 - (b) the outside surfaces of the flanges may be flat from spindle hole area to periphery (with P equal to zero), or
 - (c) in the case of flanges made of very thin material, the K diameter area may be raised rather than recessed (effectively, P less than zero).
- 2.7 The maximum effective thickness of spools (including all the characteristics mentioned in clause 2.6) outside the K diameter area has not been stated because it is a function of a spool's specific J_1 value between the 15.0 mm diameter reference zones on each flange. The largest over-all effective thickness, however, will be $J_1 \text{ max.} + 2 \times P \text{ max.} = 19.5 \text{ mm (0.77 in)}$.

* The reference plane from which P is measured is not necessarily coincident with all points within the K diameter area but should only be coincident with those which are in contact with the reference support which has a diameter smaller than K .