

# ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

## ISO RECOMMENDATION

**R 1944** *withdrawn 1979*

PIPE COUPLINGS FOR HYDRAULIC PIPING  
(PIPE THREADS)

1st EDITION

October 1970

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

## BRIEF HISTORY

The ISO Recommendation R 1944, *Pipe couplings for hydraulic piping (Pipe threads)*, was drawn up by Technical Committee ISO/TC 39, *Machine tools*, the Secretariat of which is held by the Association Française de Normalisation (AFNOR).

Work on this question led to the adoption of Draft ISO Recommendation No. 1944, which was circulated to all the ISO Member Bodies for enquiry in September 1969. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Australia	Japan	Sweden
Belgium	Korea, Rep. of	Switzerland
Chile	New Zealand	Thailand
Czechoslovakia	Portugal	Turkey
France	Romania	U.A.R.
Germany	South Africa, Rep. of	United Kingdom
Greece	Spain	

The following Member Bodies opposed the approval of the Draft :

Hungary  
U.S.A.  
U.S.S.R.

This Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided to accept it as an ISO RECOMMENDATION.

**PIPE COUPLINGS FOR HYDRAULIC PIPING  
(PIPE THREADS)**


**1. SCOPE**

This ISO Recommendation gives the dimensions of pipe couplings for hydraulic piping on machines and equipment, in relation to the nominal dimensions of the threads retained for these applications.

**2. THREADS**

The threads should conform to ISO Recommendation R 228, *Pipe threads where pressure-tight joints are not made on the threads (1/8 inch to 6 inches)*, tolerance class A.

**3. DIMENSIONS**



The joint surface should be perpendicular to the axis of the thread.

For detail A of the joint surface for use with flat seal, see ISO Recommendation R 1941, *Flat seal for hydraulic couplings*. For use with an O-ring connection, a further ISO Recommendation is being prepared.

Dimensions in millimetres

Nominal dimension of thread	Internal thread			External thread		
	$l_1$ min.	$D_1$ min.	$h_1$ max.	$l_2$ max.	$D_2$ h14	$h_2$ min.
$\frac{1}{8}$	7.4	15	1	7.4	14	1
$\frac{1}{4}$	11.0	19	1.5	11.0	18	1.5
$\frac{3}{8}$	11.4	23	2	11.4	22	2
$\frac{1}{2}$	15.0	27	2.5	15.0	26	2.5
$\frac{3}{4}$	16.3	33	2.5	16.3	32	2.5
1	19.1	40	2.5	19.1	39	2.5
$1 \frac{1}{4}$	21.4	50	2.5	21.4	49	2.5
$1 \frac{1}{2}$	21.4	56	2.5	21.4	55	2.5
2	25.7	69	3	25.7	68	3

NOTE. - The widths across flats should be taken from those in ISO Recommendation R 272\* , *Hexagon bolts and nuts - Widths across flats, heights of heads, thicknesses of nuts - Metric series*.

\* 2nd Edition, 1968.