

Transformed

**ISO**

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

**ISO RECOMMENDATION  
R 263**

**ISO INCH SCREW THREADS**

GENERAL PLAN AND SELECTION FOR SCREWS, BOLTS AND NUTS  
(diameter range 0.06 to 6 in)

1st EDITION  
July 1962

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

## BRIEF HISTORY

The ISO Recommendation R 263, *ISO Inch Screw Threads. General Plan and Selection for Screws, Bolts and Nuts. (diameter range 0.06 to 6 in)*, was drawn up by Technical Committee ISO/TC 1, *Screw Threads*, the Secretariat of which is held by the Sveriges Standardiseringskommission (SIS).

Work on this question by the Technical Committee began in 1957 and led, in 1959, to the adoption of a Draft ISO Recommendation.

In May 1960, this Draft ISO Recommendation (No. 362) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies:

Argentina	France	New Zealand
Australia	Germany	Norway
Austria	Greece	Poland
Canada	Hungary	Spain
Chile	India	Switzerland
Colombia	Israel	United Kingdom
Czechoslovakia	Italy	U.S.A.
Denmark	Japan	
Finland	Netherlands	

Three Member Bodies opposed the approval of the Draft:

Bulgaria	Sweden	U.S.S.R.
----------	--------	----------

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in July 1962, to accept it as an ISO RECOMMENDATION.

## FOREWORD

This ISO Recommendation is one of a number of ISO Recommendations determining internationally interchangeable triangular screw threads.

It is intended that the complete set of these ISO Recommendations will cover the following specifications:

Basic Profile for ISO Triangular Screw Threads (except for pipe threads) and design profiles for nut and bolt	(ISO Recommendation R 68, section 2)
ISO Metric Screw Threads. General Plan (diameter range 0.25 to 300 mm)	(ISO Recommendation R 261)
ISO Metric Screw Threads for screws, bolts and nuts (a) diameter range 0.25 to 5 mm	(ISO Recommendation R 68, section 3)
(b) diameter range 6 to 39 mm	(ISO Recommendation R 262)
ISO Inch Screw Threads. General Plan (diameter range 0.06 to 6 in) and selection for screws, bolts and nuts	(ISO Recommendation R 263)
ISO Selected Screw Threads for screws, bolts and nuts	(Under study)

All these ISO Recommendations on screw threads will utilize the Basic Profile for ISO Triangular Screw Threads set out in ISO Recommendation R 68, *Screw Threads*.

---

## CONTENTS

	Page
1. Introduction .....	4
2. Thread series .....	4
3. Designations .....	4
4. Screw Threads (Table 1) .....	5-6
Appendix .....	7
A1. Usage of thread series .....	7
A2. Corresponding inch-millimetre values .....	8
(a) Basic major diameters (Table 2) .....	8
(b) Pitches (Table 3) .....	8

---

## ISO INCH SCREW THREADS

### GENERAL PLAN AND SELECTION FOR SCREWS, BOLTS AND NUTS

(diameter range 0.06 to 6 in)

#### 1. INTRODUCTION

This ISO Recommendation tabulates ISO Inch Screw Threads (except for pipe threads) having the Basic Profile for ISO Triangular Screw Threads.

It comprises both a General Plan of the ISO Inch Screw Threads and the ISO Inch Screw Threads for screws, bolts and nuts, the latter being a selection from the former.

The ISO Recommendation contains sizes in the diameter range 0.06 to 6 in, comprising a number of series of diameter-pitch combinations, together with a system of thread designations.

It remains for each industry to choose for itself, by means of selection among the screw threads of this ISO Recommendation, the diameter-pitch combinations appropriate to its own needs.

#### 2. THREAD SERIES

The General Plan is characterized by a number of thread series, i. e. groups of diameter-pitch combinations distinguished from each other by the number of threads per inch associated with specific diameters of threads. These thread series are shown in Table 1.

##### 2.1 Diameters

Columns 1 and 2 of Table 1 give primary and secondary sizes which should suffice to meet the common needs of design. Column 3 gives the decimal equivalents of these sizes

##### 2.2 Number of threads per inch

Columns 4 to 14 (inclusive) of Table 1 give the number of threads per inch which are recommended for association with the sizes in columns 1 and 2. These columns of threads per inch are divided into two groups:

Series with graded pitches : columns 4, 5 and 6,  
Series with constant (uniform) pitches: columns 7 to 14.

##### 2.2.1. Series with graded pitches

There are three series with graded pitches. They are headed "coarse", "fine" and "extra-fine", in compliance with present practice.

These terms denote the relative magnitudes of the pitches of the three series for any given diameter of thread and do not imply any difference in the quality of the threads in the series.

**The coarse and fine thread series should be the first choice for general engineering applications, and they form the selected series for the commercial production of screws, bolts and nuts.**

##### 2.2.2. Series with constant (uniform) pitches

In addition to the three series of graded pitches, Table 1 includes columns of constant pitches which have been selected from the range 4 to 32 threads per inch. Each of these series is limited to an appropriate range of diameters.

#### 3. DESIGNATIONS

The screw threads in this General Plan are designated as shown in the column headings of Table 1, i. e. as follows:

##### 3.1 Series with graded pitches

Coarse thread series	Designation UNC; e. g. $\frac{1}{4}$ -20 UNC;	No. 4-40 UNC;
Fine thread series	Designation UNF; e. g. $\frac{1}{4}$ -28 UNF;	No. 4-48 UNF;
Extra-fine thread series	Designation UNEF; e. g. $\frac{1}{4}$ -32 UNEF.	

##### 3.2 Series with constant (uniform) pitches

All of the diameter-pitch combinations of the threads in these constant-pitch series are designated UN; e. g. 1-16 UN.

4. SCREW THREADS  
TABLE 1.

Sizes		Basic Major diameter in	Number of threads per inch											
			Series with graded pitches			Series with constant (uniform) pitches								
			Coarse thread series *	Fine thread series *	Extra-fine thread series	4-thread series	6-thread series	8-thread series	12-thread series	16-thread series	20-thread series	28-thread series	32-thread series	
Primary	Secondary		UNC	UNF	UNEF	UN	UN	UN	UN	UN	UN	UN	UN	
1	2	3	4	5	6	7	8	9	10	11	12	13	14	
No.0		0.060 0		80										
	No.1	0.073 0	64	72										
No.2		0.086 0	56	64										
	No.3	0.099 0	48	56										
No.4		0.112 0	40	48										
No.5		0.125 0	40	44										
No.6		0.138 0	32	40										UNC
No.8		0.164 0	32	36										UNC
No.10		0.190 0	24	32										UNF
	No.12	0.216 0	24	28	32							UNF		UNEF
1/4		0.250 0	20	28	32							UNC	UNF	UNEF
5/16		0.312 5	18	24	32							20	28	UNEF
3/8		0.375 0	16	24	32					UNC		20	28	UNEF
7/16		0.437 5	14	20	28						16	UNF	UNEF	32
1/2		0.500 0	13	20	28						16	UNF	UNEF	32
9/16		0.562 5	12	18	24				UNC	16	20	28	32	
5/8		0.625 0	11	18	24					12	16	20	28	32
	11/16	0.687 5			24					12	16	20	28	32
3/4		0.750 0	10	16	20					12	UNF	UNEF	28	32
	13/16	0.812 5			20					12	16	UNEF	28	32
7/8		0.875 0	9	14	20					12	16	UNEF	28	32
	15/16	0.937 5	8		20					12	16	UNEF	28	32
1		1.000 0	8	12	20			UNC	UNF	16	UNEF	28	32	
	1 1/16	1.062 5			18			8	12	16	20	28		
1 1/8		1.125 0	7	12	18			8	UNF	16	20	28		
	1 3/16	1.187 5			18			8	12	16	20	28		
1 1/4		1.250 0	7	12	18			8	UNF	16	20	28		
	1 5/16	1.312 5			18			8	12	16	20	28		
1 3/8		1.375 0	6	12	18		UNC	8	UNF	16	20	28		
	1 7/16	1.437 5			18		6	8	12	16	20	28		
1 1/2		1.500 0	6	12	18		UNC	8	UNF	16	20	28		
	1 9/16	1.562 5			18			6	8	12	16	20		
1 5/8		1.625 0			18			6	8	12	16	20		
	1 11/16	1.687 5			18			6	8	12	16	20		
1 3/4		1.750 0	5					6	8	12	16	20		
	1 13/16	1.812 5						6	8	12	16	20		
1 7/8		1.875 0						6	8	12	16	20		

\* Selected series for screws, bolts and nuts, and first choice for general engineering applications.

(continued)

TABLE 1. - (concluded)

Sizes		Basic major diameter in	Number of threads per inch										
			Series with graded pitches			Series with constant (uniform) pitches							
			Coarse thread series *	Fine thread series *	Extra-fine thread series	4-thread series	6-thread series	8-thread series	12-thread series	16-thread series	20-thread series	28-thread series	32-thread series
Primary	Secondary		UNC	UNF	UNEF	UN	UN	UN	UN	UN	UN	UN	UN
1	2	3	4	5	6	7	8	9	10	11	12	13	14
2	1 15/16	1.937 5					6	8	12	16	20		
		2.000 0	4 1/2				6	8	12	16	20		
	2 1/8	2.125 0					6	8	12	16	20		
2 1/4		2.250 0	4 1/2				6	8	12	16	20		
	2 3/8	2.375 0					6	8	12	16	20		
2 1/2		2.500 0	4			UNC	6	8	12	16	20		
2 3/4	2 5/8	2.625 0				4	6	8	12	16	20		
		2.750 0	4			UNC	6	8	12	16	20		
	2 7/8	2.875 0				4	6	8	12	16	20		
3		3.000 0	4			UNC	6	8	12	16	20		
	3 1/8	3.125 0				4	6	8	12	16	20		
	3 1/4	3.250 0	4			UNC	6	8	12	16	20		
3 1/2	3 3/8	3.375 0				4	6	8	12	16			
		3.500 0	4			UNC	6	8	12	16			
	3 5/8	3.625 0				4	6	8	12	16			
3 3/4		3.750 0	4			UNC	6	8	12	16			
	3 7/8	3.875 0				4	6	8	12	16			
	4	4.000 0	4			UNC	6	8	12	16			
4 1/4	4 1/8	4.125 0				4	6	8	12	16			
		4.250 0	4			4	6	8	12	16			
	4 3/8	4.375 0				4	6	8	12	16			
4 1/2		4.500 0				4	6	8	12	16			
	4 5/8	4.625 0				4	6	8	12	16			
	4 3/4	4.750 0				4	6	8	12	16			
5	4 7/8	4.875 0				4	6	8	12	16			
		5.000 0				4	6	8	12	16			
	5 1/8	5.125 0				4	6	8	12	16			
5 1/4		5.250 0				4	6	8	12	16			
	5 3/8	5.375 0				4	6	8	12	16			
	5 1/2	5.500 0				4	6	8	12	16			
5 3/4	5 5/8	5.625 0				4	6	8	12	16			
		5.750 0				4	6	8	12	16			
	5 7/8	5.875 0				4	6	8	12	16			
6		6.000 0				4	6	8	12	16			

\* Selected series for screws, bolts and nuts, and first choice for general engineering applications.