

# ISO

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION

## ISO RECOMMENDATION

### R 998

*withdrawn 1981*

POTASSIUM HYDROXIDE FOR INDUSTRIAL USE

DETERMINATION OF WATER-INSOLUBLE MATTER

1st EDITION

February 1969

COPYRIGHT RESERVED

The copyright of ISO Recommendations and ISO Standards belongs to ISO Member Bodies. Reproduction of these documents, in any country, may be authorized therefore only by the national standards organization of that country, being a member of ISO.

For each individual country the only valid standard is the national standard of that country.

Printed in Switzerland

Also issued in French and Russian. Copies to be obtained through the national standards organizations.

## BRIEF HISTORY

The ISO Recommendation R 998, *Potassium hydroxide for industrial use – Determination of water-insoluble matter*, was drawn up by Technical Committee ISO/TC 47, *Chemistry*, the Secretariat of which is held by the Ente Nazionale Italiano di Unificazione (UNI).

Work on this question led, in 1966, to the adoption of a Draft ISO Recommendation.

In December 1966, this Draft ISO Recommendation (No. 1107) was circulated to all the ISO Member Bodies for enquiry. It was approved, subject to a few modifications of an editorial nature, by the following Member Bodies :

Austria	Israel	Spain
Belgium	Italy	Switzerland
Brazil	Japan	Thailand
Chile	Korea, Dem. P. Rep. of	Turkey
Cuba	Netherlands	U.A.R.
Czechoslovakia	New Zealand	United Kingdom
Germany	Poland	U.S.S.R.
Hungary	Portugal	Yugoslavia
India	Romania	
Ireland	South Africa, Rep. of	

Two Member Bodies opposed the approval of the Draft :

France  
U.S.A.

The Draft ISO Recommendation was then submitted by correspondence to the ISO Council, which decided, in February 1969, to accept it as an ISO RECOMMENDATION.

POTASSIUM HYDROXIDE FOR INDUSTRIAL USE

DETERMINATION OF WATER-INSOLUBLE MATTER

1. SCOPE

This ISO Recommendation describes a method for the determination of water-insoluble matter in potassium hydroxide for industrial use.

2. FIELD OF APPLICATION

The method is applicable to the determination of water-insoluble matter content equal to or greater than 0.05 % (m/m) calculated on KOH.

3. PRINCIPLE

Dissolution of a test portion. Filtration of the solution through a tared filter crucible. Washing of the insoluble matter with water until the washings are no longer alkaline. Drying of the residue and weighing.

4. REAGENTS

Distilled water or water of equivalent purity should be used in the test.

- 4.1 *Phenolphthalein*, 10 g/l ethanolic solution.  
Dissolve 1 g of phenolphthalein in 95 % (v/v) ethanol and dilute to 100 ml with the same ethanol.

5. APPARATUS

- 5.1 *Ordinary laboratory apparatus.*
- 5.2 *Glass filter crucible*, with sintered disk of porosity between 5 and 15  $\mu\text{m}$ .

6. PROCEDURE

6.1 **Test portion**

In a weighing bottle of approximately 100 ml, fitted with a ground glass stopper, weigh, to the nearest 0.1 g, a mass of the test sample (solid or liquid)\* containing  $20 \pm 0.1$  g of KOH.

\* See ISO Recommendation R 988, *Potassium hydroxide for industrial use – Preparation and storage of test sample*, clause 2.2.