
**Calculation of load capacity of spur
and helical gears —**

**Part 31:
Calculation examples of micropitting
load capacity**

*Calcul de la capacité de charge des engrenages cylindriques à
dentures droite et hélicoïdale —*

*Partie 31: Exemples de calcul de la capacité de charge aux
micropiqûres*

STANDARDSISO.COM : Click to view the PDF of ISO/TR 6336-31:2018



STANDARDSISO.COM : Click to view the full PDF of ISO/TR 6336-31:2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

| | Page |
|--|-----------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and units | 1 |
| 5 Example calculation | 4 |
| 5.1 General..... | 4 |
| 5.2 Example 1 Spur gear..... | 5 |
| 5.2.1 General..... | 5 |
| 5.2.2 Input data..... | 5 |
| 5.2.3 Calculation according to method B..... | 6 |
| 5.2.4 Calculation according to method A..... | 13 |
| 5.2.5 Calculation of the permissible lubricant film thickness..... | 14 |
| 5.3 Example 2 Spur gear..... | 19 |
| 5.3.1 General..... | 19 |
| 5.3.2 Input data..... | 20 |
| 5.3.3 Calculation according to method B..... | 21 |
| 5.4 Example 3 Helical gear..... | 28 |
| 5.4.1 General..... | 28 |
| 5.4.2 Input data..... | 29 |
| 5.4.3 Calculation according to method B..... | 30 |
| 5.4.4 Calculation according to method A..... | 37 |
| 5.5 Example 4 Speed increaser..... | 38 |
| 5.5.1 General..... | 38 |
| 5.5.2 Input data..... | 39 |
| 5.5.3 Calculation according to method B..... | 41 |
| 5.5.4 Calculation according to method A..... | 47 |
| Bibliography | 49 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This document cancels and replaces ISO/TR 15144-2:2014.

Introduction

The ISO 6336 series consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see [Table 1](#)).

- International Standards contain calculation methods that are based on widely accepted practices and have been validated.
- TS contain calculation methods that are still subject to further development.
- TR contain data that is informative, such as example calculations.

The procedures specified in ISO 6336-1 to ISO 6336-19 cover fatigue analyses for gear rating. The procedures described in ISO 6336-20 to ISO 6336-29 are predominantly related to the tribological behaviour of the lubricated flank surface contact. ISO 6336-30 to ISO 6336-39 include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to ISO 6336 without referring to specific parts requires the use of only those parts that are currently designated as International Standards (see [Table 1](#) for listing). When requesting further calculations, the relevant part or parts of ISO 6336 need to be specified. Use of a Technical Specification as acceptance criteria for a specific design needs to be agreed in advance between manufacturer and purchaser.

Table 1 — Overview of ISO 6336

| Calculation of load capacity of spur and helical gears | International Standard | Technical Specification | Technical Report |
|---|------------------------|-------------------------|------------------|
| <i>Part 1: Basic principles, introduction and general influence factors</i> | X | | |
| <i>Part 2: Calculation of surface durability (pitting)</i> | X | | |
| <i>Part 3: Calculation of tooth bending strength</i> | X | | |
| <i>Part 4: Calculation of tooth flank fracture load capacity</i> | | X | |
| <i>Part 5: Strength and quality of materials</i> | X | | |
| <i>Part 6: Calculation of service life under variable load</i> | X | | |
| <i>Part 20: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Flash temperature method (Replaces ISO/TR 13989-1)</i> | | X | |
| <i>Part 21: Calculation of scuffing load capacity (also applicable to bevel and hypoid gears) — Integral temperature method (Replaces ISO/TR 13989-2)</i> | | X | |
| <i>Part 22: Calculation of micropitting load capacity (Replaces ISO/TR 15144-1)</i> | | X | |
| <i>Part 30: Calculation examples for the application of ISO 6336-1, 2, 3, 5</i> | | | X |
| <i>Part 31: Calculation examples of micropitting load capacity (Replaces: ISO/TR 15144-2)</i> | | | X |

At the time of publication of this document, some of the parts listed here were under development. Consult the ISO website.

This document provides worked examples for the application of the calculation procedures defined in ISO/TS 6336-22. The example calculations cover the application to spur and helical cylindrical involute gears for both high-speed and low-speed operating conditions, determining the micropitting safety factor for each gear pair. The calculation procedures used are consistent with those presented in ISO/TS 6336-22. No additional calculations are presented in this document that are outside of ISO/TS 6336-22.

Four worked examples are presented with the necessary input data for each gear set provided at the beginning of the calculation. The worked examples are based on real gear pairs where either laboratory or operational field performance data has been established, with the examples covering several

applications. When available, pictures and measurements are provided of the micropitting wear, experienced on the gear sets when run under the conditions used in the worked examples. Calculation details are presented in full for several of the initial calculations after which only summarized results data are included. For better applicability, the numbering of the formulae follows ISO/TS 6336-22. Several of the worked examples are presented with the calculation procedures performed in accordance with the application of both methods A and B.

STANDARDSISO.COM : Click to view the full PDF of ISO/TR 6336-31:2018

Calculation of load capacity of spur and helical gears —

Part 31:

Calculation examples of micropitting load capacity

1 Scope

The example calculations presented here are provided for guidance on the application of the technical specification ISO/TS 6336-22 only. Any of the values or the data presented should not be used as material or lubricant allowables or as recommendations for micro-geometry in real applications when applying this procedure. The necessary parameters and allowable film thickness values, λ_{GFP} , should be determined for a given application in accordance with the procedures defined in ISO/TS 6336-22.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1122-1, *Vocabulary of gear terms — Part 1: Definitions related to geometry*

ISO 6336-1, *Calculation of load capacity of spur and helical gears — Part 1: Basic principles, introduction and general influence factors*

ISO 6336-2, *Calculation of load capacity of spur and helical gears — Part 2: Calculation of surface durability (pitting)*

ISO 21771, *Gears — Cylindrical involute gears and gear pairs — Concepts and geometry*

ISO/TS 6336-22:2018, *Calculation of load capacity of spur and helical gears — Part 22: Calculation of micropitting load capacity*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1122-1, ISO 6336-1 and ISO 6336-2 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

4 Symbols and units

The symbols used in this document are given in [Table 2](#). The units of length metre, millimetre, and micrometre are chosen in accordance with common practice. The conversions of the units are already included in the given formulae.

Table 2 — Symbols and units

| Symbol | Description | Unit |
|--------------------|--|-------------------------------|
| a | centre distance | mm |
| A | ISO tolerance class according ISO 1328-1:2013 | — |
| B_{M1} | thermal contact coefficient of pinion | $N/(m \cdot s^{0,5} \cdot K)$ |
| B_{M2} | thermal contact coefficient of wheel | $N/(m \cdot s^{0,5} \cdot K)$ |
| b | face width | mm |
| C_{a1} | tip relief of pinion | μm |
| C_{a2} | tip relief of wheel | μm |
| c_{M1} | specific heat capacity of pinion | $J/(kg \cdot K)$ |
| c_{M2} | specific heat capacity of wheel | $J/(kg \cdot K)$ |
| c' | maximum tooth stiffness per unit face width (single stiffness) of a tooth pair | $N/(mm \cdot \mu m)$ |
| $c_{\gamma\alpha}$ | mean value of mesh stiffness per unit face width | $N/(mm \cdot \mu m)$ |
| d_{a1} | tip diameter of pinion | mm |
| d_{a2} | tip diameter of wheel | mm |
| d_{b1} | base diameter of pinion | mm |
| d_{b2} | base diameter of wheel | mm |
| d_{w1} | pitch diameter of pinion | mm |
| d_{w2} | pitch diameter of wheel | mm |
| d_{Y1} | Y-circle diameter of pinion | mm |
| d_{Y2} | Y-circle diameter of wheel | mm |
| E_r | reduced modulus of elasticity | N/mm^2 |
| E_1 | modulus of elasticity of pinion | N/mm^2 |
| E_2 | modulus of elasticity of wheel | N/mm^2 |
| F_{bt} | nominal transverse load in plane of action (base tangent plane) | N |
| F_t | (nominal) transverse tangential load at reference cylinder per mesh | N |
| G_M | material parameter | — |
| g_Y | parameter on the path of contact (distance of point Y from point A) | mm |
| g_α | length of path of contact | mm |
| H_v | load losses factor | — |
| h_Y | local lubricant film thickness | μm |
| K_A | application factor | — |
| K_{BY} | helical load factor | — |
| $K_{H\alpha}$ | transverse load factor | — |
| $K_{H\beta}$ | face load factor | — |
| K_v | dynamic factor | — |
| K_γ | mesh load factor | — |
| n_1 | rotation speed of pinion | min^{-1} |
| P | transmitted power | kW |
| p_{et} | transverse base pitch on the path of contact | mm |
| $p_{dyn,Y}$ | local Hertzian contact stress including the load factors K | N/mm^2 |
| $p_{H,Y}$ | local nominal Hertzian contact stress | N/mm^2 |
| R_a | effective arithmetic mean roughness value | μm |
| R_{a1} | arithmetic mean roughness value of pinion | μm |
| R_{a2} | arithmetic mean roughness value of wheel | μm |
| $S_{GF,Y}$ | local sliding parameter | — |

Table 2 (continued)

| Symbol | Description | Unit |
|----------------------------|---|-------------------------------------|
| S_λ | safety factor against micropitting | — |
| $S_{\lambda,\min}$ | minimum required safety factor against micropitting | — |
| T_1 | nominal torque at the pinion | Nm |
| U_Y | local velocity parameter | — |
| u | gear ratio | — |
| $v_{g,Y}$ | local sliding velocity | m/s |
| $v_{r1,Y}$ | local tangential velocity on pinion | m/s |
| $v_{r2,Y}$ | local tangential velocity on wheel | m/s |
| $v_{\Sigma,C}$ | sum of tangential velocities at pitch point | m/s |
| $v_{\Sigma,Y}$ | sum of tangential velocities at point Y | m/s |
| W_W | material factor | — |
| W_Y | local load parameter | — |
| $X_{\text{but},Y}$ | local buttressing factor | — |
| X_{Ca} | tip relief factor | — |
| X_L | lubricant factor | — |
| X_R | roughness factor | — |
| X_S | lubrication factor | — |
| X_Y | local load sharing factor | — |
| Z_E | elasticity factor | (N/mm ²) ^{0,5} |
| z_1 | number of teeth of pinion | — |
| z_2 | number of teeth of wheel | — |
| α_t | transverse pressure angle | ° |
| α_{wt} | pressure angle at the pitch cylinder | ° |
| $\alpha_{\theta B,Y}$ | pressure-viscosity coefficient at local contact temperature | m ² /N |
| $\alpha_{\theta M}$ | pressure-viscosity coefficient at bulk temperature | m ² /N |
| α_{38} | pressure-viscosity coefficient at 38 °C | m ² /N |
| β_b | base helix angle | ° |
| ϵ_{\max} | maximum addendum contact ratio | — |
| ϵ_α | transverse contact ratio | — |
| $\epsilon_{\alpha n}$ | virtual transverse contact ratio | — |
| ϵ_β | overlap ratio | — |
| ϵ_γ | total contact ratio | — |
| ϵ_1 | addendum contact ratio of the pinion | — |
| ϵ_2 | addendum contact ratio of the wheel | — |
| $\eta_{\theta B,Y}$ | dynamic viscosity at local contact temperature | N·s/m ² |
| $\eta_{\theta M}$ | dynamic viscosity at bulk temperature | N·s/m ² |
| $\eta_{\theta \text{oil}}$ | dynamic viscosity at oil inlet/sump temperature | N·s/m ² |
| η_{38} | dynamic viscosity at 38 °C | N·s/m ² |
| $\theta_{B,Y}$ | local contact temperature | °C |
| $\theta_{f1,Y}$ | local flash temperature | °C |
| θ_M | bulk temperature | °C |
| θ_{oil} | oil inlet/sump temperature | °C |
| $\lambda_{\text{GF},\min}$ | minimum specific lubricant film thickness in the contact area | — |
| $\lambda_{\text{GF},Y}$ | local specific lubricant film thickness | — |

Table 2 (continued)

| Symbol | Description | Unit |
|----------------------|---|--------------------|
| λ_{GFP} | permissible specific lubricant film thickness | — |
| λ_{GFT} | limiting specific lubricant film thickness of the test gears | — |
| λ_{M1} | specific heat conductivity of pinion | W/(m·K) |
| λ_{M2} | specific heat conductivity of wheel | W/(m·K) |
| μ_m | mean coefficient of friction | — |
| $\nu_{\theta B,Y}$ | kinematic viscosity at local contact temperature | mm ² /s |
| $\nu_{\theta M}$ | kinematic viscosity at bulk temperature | mm ² /s |
| ν_1 | Poisson's ratio of pinion | — |
| ν_2 | Poisson's ratio of wheel | — |
| ν_{100} | kinematic viscosity at 100 °C | mm ² /s |
| ν_{40} | kinematic viscosity at 40 °C | mm ² /s |
| ρ_{M1} | density of pinion | kg/m ³ |
| ρ_{M2} | density of wheel | kg/m ³ |
| $\rho_{n,C}$ | normal radius of relative curvature at pitch diameter | mm |
| $\rho_{n,Y}$ | normal radius of relative curvature at point Y | mm |
| $\rho_{t,Y}$ | transverse radius of relative curvature at point Y | mm |
| $\rho_{t1,Y}$ | transverse radius of curvature of pinion at point Y | mm |
| $\rho_{t2,Y}$ | transverse radius of curvature of wheel at point Y | mm |
| $\rho_{\theta B,Y}$ | density of lubricant at local contact temperature | kg/m ³ |
| $\rho_{\theta M}$ | density of lubricant at bulk temperature | kg/m ³ |
| ρ_{15} | density of lubricant at 15 °C | kg/m ³ |
| Subscript to symbols | | |
| Y | Parameter for any contact point Y in the contact area for method A and on the path of contact for method B (all parameters subscript Y has to be calculated with local values). | |

5 Example calculation

5.1 General

This clause presents examples for the calculation of the safety factor against micropitting, S_λ . Each example is first calculated according to method B and examples 1, 3, and 4 subsequently calculated according to method A. The calculation sequence for method B has been provided to follow a logical approach in relation to the input data. Beside the formulae itself, the formula numbers related to ISO/TS 6336-22 are given.


The examples calculate the safety factor, S_λ of a specific gear set when compared to an allowable λ_{GFP} value. For the examples 1, 2, and 4, the permissible specific oil film thickness, λ_{GFP} , was determined from the test result of the lubricant in the FZG-FVA micropitting test^[1]. For these calculations, medium values for the standard FZG back-to-back test rig and standard test conditions for $K_{H\beta}$ and K_V were used ($K_{H\beta} = 1,10$ and $K_V = 1,05$). The calculation of the λ_{GFP} value from the test result of the FZG-FVA micropitting test^[1] (method B) is shown exemplary on the basis of the first example. For Example 3, the permissible specific oil film thickness, λ_{GFP} , was determined from a bench test.

NOTE The calculations were performed computer-based. If the calculations are performed manually, small differences between the results can appear.

5.2 Example 1 Spur gear

5.2.1 General

The result of this example is confirmed by experimental investigations. The gears were obviously micropitted and had profile deviations of approximately $8\ \mu\text{m}$ to $10\ \mu\text{m}$. Figure 1 shows a diagram of the observed location and severity of micropitting for pinion and wheel of Example 1.



Key

- 1 tip
- 2 root

Figure 1 — Diagram of schematic profile deviations of pinion and wheel for Example 1

5.2.2 Input data

Table 3 — Input data for Example 1

| | Symbol | Description | Unit | Example 1 | |
|----------|------------|------------------------------|------|-----------|-------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| Geometry | z | number of teeth | — | 18 | 18 |
| | — | driving gear | — | x | |
| | m_n | normal module | mm | 10,93 | |
| | α_n | normal pressure angle | ° | 20 | |
| | β | helix angle | ° | 0 | |
| | b | face width | mm | 21,4 | |
| | a | centre distance | mm | 200 | |
| | x | addendum modification factor | — | 0,158 | 0,158 |

Table 3 (continued)

| | Symbol | Description | Unit | Example 1 | |
|-------------|------------------------|---|-------------------------------------|------------------|---------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| | d_a | tip diameter | mm | 221,4 | 221,4 |
| | — | tooth flank modifications | — | no modifications | |
| | A | ISO tolerance class | — | 5 | 5 |
| | R_a | arithmetic mean roughness value | μm | 0,90 | 0,90 |
| Material | — | material | — | Eh | Eh |
| | E | modulus of elasticity | N/mm^2 | 206 000 | 206 000 |
| | ν | Poisson's ratio | — | 0,3 | 0,3 |
| | λ_M | specific heat conductivity | $\text{W}/(\text{m}\cdot\text{K})$ | 45 | 45 |
| | c_M | specific heat capacity | $\text{J}/(\text{kg}\cdot\text{K})$ | 440 | 440 |
| | ρ_M | density | kg/m^3 | 7 800 | 7 800 |
| | W_w | material factor according to ISO/TS 6336-22:2018, Table A.1 (for matching case carburized/ case carburized) | — | 1,0 | |
| Application | K_A | application factor | — | 1,0 | |
| | K_V | dynamic factor | — | 1,15 | |
| | K_Y | mesh load factor | — | 1,0 | |
| | $K_{H\alpha}$ | transverse load factor | — | 1,0 | |
| | $K_{H\beta}$ | face load factor | — | 1,10 | |
| Load | T_1 | nominal torque at the pinion | Nm | 1 878 | |
| | n_1 | rotation speed of the pinion | min^{-1} | 3 000 | — |
| Lubricant | θ_{oil} | oil inlet temperature (injection lubrication) | $^{\circ}\text{C}$ | 90 | |
| | ν_{40} | kinematic viscosity at 40 $^{\circ}\text{C}$ | mm^2/s | 210 | |
| | ν_{100} | kinematic viscosity at 100 $^{\circ}\text{C}$ | mm^2/s | 18,5 | |
| | ρ_{15} | density of the lubricant at 15 $^{\circ}\text{C}$ | kg/m^3 | 895 | |
| | — | oil type | — | mineral oil | |
| | — | failure load stage at test temperature (90 $^{\circ}\text{C}$) according to FVA 54/7 | — | SKS 8 | |
| | λ_{GEP} | permissible lubricant film thickness (see 5.2.5 for calculation) | — | 0,211 | |

5.2.3 Calculation according to method B

5.2.3.1 Calculation of gear geometry (according to ISO 21771)

Basic values:

$$m_t = \frac{m_n}{\cos \beta}$$

$$m_t = 10,93 \text{ mm}$$

$$d_1 = z_1 \cdot m_t$$

$$d_1 = 196,74 \text{ mm}$$

$$d_2 = z_2 \cdot m_t$$

$$d_2 = 196,74 \text{ mm}$$

$$u = \frac{z_2}{z_1}$$

$$u = 1,00$$

$$\alpha_t = \arctan\left(\frac{\tan \alpha_n}{\cos \beta}\right)$$

$$\alpha_t = 20,000^\circ$$

$$d_{b1} = d_1 \cos \alpha_t$$

$$d_{b1} = 184,875 \text{ mm}$$

$$d_{b2} = d_2 \cos \alpha_t$$

$$d_{b2} = 184,875 \text{ mm}$$

$$d_{w1} = \frac{2 \cdot a}{u+1}$$

$$d_{w1} = 200 \text{ mm}$$

$$d_{w2} = 2 \cdot a - d_{w1}$$

$$d_{w2} = 200 \text{ mm}$$

$$\alpha_{wt} = \arccos\left[\frac{(z_1 + z_2) \cdot m_t \cdot \cos \alpha_t}{2 \cdot a}\right]$$

$$\alpha_{wt} = 22,426^\circ$$

$$\beta_b = \arcsin(\sin \beta \cdot \cos \alpha_n)$$

$$\beta_b = 0^\circ$$

$$p_{et} = m_t \cdot \pi \cdot \cos \alpha_t$$

$$p_{et} = 32,267 \text{ mm}$$

$$\varepsilon_1 = \frac{z_1}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a1}}{d_{b1}}\right)^2 - 1} - \tan \alpha_{wt} \right]$$

$$\varepsilon_1 = 0,705$$

$$\varepsilon_2 = \frac{z_2}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a2}}{d_{b2}}\right)^2 - 1} - \tan \alpha_{wt} \right]$$

$$\varepsilon_2 = 0,705$$

$$\varepsilon_\alpha = \frac{1}{p_{et}} \cdot \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + \sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - a \cdot \sin \alpha_{wt} \right)$$

$$\varepsilon_\alpha = 1,411$$

$$\varepsilon_\beta = \frac{b \cdot \sin \beta}{m_n \cdot \pi}$$

$$\varepsilon_\beta = 0$$

$$\varepsilon_\gamma = \varepsilon_\alpha + \varepsilon_\beta$$

$$\varepsilon_\gamma = 1,411$$

$$g_\alpha = 0,5 \cdot \left(\sqrt{d_{a1}^2 - d_{b1}^2} + \sqrt{d_{a2}^2 - d_{b2}^2} \right) - a \cdot \sin \alpha_{wt}$$

$$g_\alpha = 45,519 \text{ mm}$$

Coordinates of the basic points (A, AB, B, C, D, DE, E) on the line of action:

$$g_A = 0 \text{ mm} \quad (32)$$

$$g_A = 0 \text{ mm}$$

$$g_{AB} = \frac{g_\alpha - p_{et}}{2} \quad (33)$$

$$g_{AB} = 6,626 \text{ mm}$$

$$g_B = g_\alpha - p_{et} \quad (34)$$

$$g_B = 13,253 \text{ mm}$$

$$g_C = \frac{d_{b1}}{2} \cdot \tan \alpha_{wt} - \sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + g_\alpha \quad (35) \quad g_C = 22,760 \text{ mm}$$

$$g_D = p_{et} \quad (36) \quad g_D = 32,267 \text{ mm}$$

$$g_{DE} = \frac{g_\alpha - p_{et}}{2} + p_{et} \quad (37) \quad g_{DE} = 28,893 \text{ mm}$$

$$g_E = g_\alpha \quad (38) \quad g_E = 45,519 \text{ mm}$$

$$d_{A1} = 2 \cdot \sqrt{\frac{d_{b1}^2}{4} + \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} - g_\alpha + g_A \right)^2} \quad (39) \quad d_{A1} = 187,419 \text{ mm}$$

$$d_{AB1} = 190,046 \text{ mm}$$

$$d_{B1} = 193,546 \text{ mm}$$

$$d_{C1} = 200,000 \text{ mm}$$

$$d_{D1} = 207,998 \text{ mm}$$

$$d_{DE1} = 214,394 \text{ mm}$$

$$d_{E1} = 221,400 \text{ mm}$$

$$d_{A2} = 2 \cdot \sqrt{\frac{d_{b2}^2}{4} + \left(\sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - g_A \right)^2} \quad (40) \quad d_{A2} = 221,400 \text{ mm}$$

$$d_{AB2} = 214,394 \text{ mm}$$

$$d_{B2} = 207,998 \text{ mm}$$

$$d_{C2} = 200,000 \text{ mm}$$

$$d_{D2} = 193,546 \text{ mm}$$

$$d_{DE2} = 190,046 \text{ mm}$$

$$d_{E2} = 187,419 \text{ mm}$$

Normal radius of relative curvature:

$$\rho_{n,A} = \frac{\rho_{t,A}}{\cos \beta_b} \quad (43) \quad \rho_{n,A} = 12,285 \text{ mm}$$

$$\rho_{n,AB} = 15,663 \text{ mm}$$

$$\rho_{n,B} = 17,890 \text{ mm}$$

$$\rho_{n,C} = 19,074 \text{ mm}$$

$$\rho_{n,D} = 17,890 \text{ mm}$$

$$\rho_{n,DE} = 15,663 \text{ mm}$$

$$\rho_{n,E} = 12,285 \text{ mm}$$

5.2.3.2 Calculation of material data

$$E_r = 2 \cdot \left(\frac{1-\nu_1^2}{E_1} + \frac{1-\nu_2^2}{E_2} \right)^{-1} \quad (6) \quad E_r = 226\,374 \text{ N/mm}^2$$

$$B_{M1} = \sqrt{\lambda_{M1} \cdot \rho_{M1} \cdot c_{M1}} \quad (81) \quad B_{M1} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

$$B_{M2} = \sqrt{\lambda_{M2} \cdot \rho_{M2} \cdot c_{M2}} \quad (82) \quad B_{M2} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

5.2.3.3 Calculation of operating conditions

Loading:

$$P = 2 \cdot \pi \cdot \frac{n_1}{60} \cdot \frac{T_1}{1\,000} \quad (84) \quad P = 590 \text{ kW}$$

$$F_t = 2\,000 \cdot \frac{T_1}{d_1} \quad F_t = 19\,091 \text{ N}$$

$$F_{bt} = 2\,000 \cdot \frac{T_1}{d_{b1}} \quad F_{bt} = 20\,316 \text{ N}$$

Local sharing factor:

NOTE No tooth flank modifications, spur gears, ISO tolerance class ≤ 7 (see ISO/TS 6336-22:2018, Figure 2).

$$X_A = \frac{A-2}{15} + \frac{1}{3} \cdot \frac{g_A}{g_B} \quad (44) \quad X_A = 0,333$$

$$X_{AB} = 0,500 \quad X_B = 1,000 \quad X_C = 1,000$$

$$X_D = 1,000 \quad X_{DE} = 0,500 \quad X_E = 0,333$$

Elasticity factor:

$$Z_E = \sqrt{\frac{E_r}{2 \cdot \pi}} \quad (26) \quad Z_E = 189,812 \left(\text{N/mm}^2 \right)^{0,5}$$

Local Hertzian contact stress:

$$p_{H,A,B} = Z_E \cdot \sqrt{\frac{F_t \cdot X_A}{b \cdot \rho_{n,A} \cdot \cos \alpha_t}} \quad (25) \quad p_{H,A,B} = 963 \text{ N/mm}^2$$

$$p_{H,AB,B} = 1\,045 \text{ N/mm}^2 \quad p_{H,B,B} = 1\,383 \text{ N/mm}^2 \quad p_{H,C,B} = 1\,339 \text{ N/mm}^2$$

$$p_{H,D,B} = 1\,383 \text{ N/mm}^2 \quad p_{H,DE,B} = 1\,045 \text{ N/mm}^2 \quad p_{H,E,B} = 963 \text{ N/mm}^2$$

$$p_{\text{dyn},A,B} = p_{H,A,B} \cdot \sqrt{K_A \cdot K_\gamma \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta}} \quad (24) \quad p_{\text{dyn},A,B} = 1\,084 \text{ N/mm}^2$$

$$p_{\text{dyn},AB,B} = 1\,175 \text{ N/mm}^2 \quad p_{\text{dyn},B,B} = 1\,555 \text{ N/mm}^2 \quad p_{\text{dyn},C,B} = 1\,506 \text{ N/mm}^2$$

$$p_{\text{dyn},D,B} = 1\,555 \text{ N/mm}^2 \quad p_{\text{dyn},DE,B} = 1\,175 \text{ N/mm}^2 \quad p_{\text{dyn},E,B} = 1\,084 \text{ N/mm}^2$$

Velocity:

$$\begin{aligned}
 v_{g,A} &= v_{r1,A} - v_{r2,A} & (80) & & v_{g,A} &= -14,300 \text{ m/s} \\
 v_{g,AB} &= -10,137 \text{ m/s} & & & v_{g,B} &= -5,974 \text{ m/s} \\
 v_{g,D} &= 5,974 \text{ m/s} & & & v_{g,C} &= 0 \text{ m/s} \\
 v_{\Sigma,A} &= v_{r1,A} + v_{r2,A} & (13) & & v_{g,E} &= 14,300 \text{ m/s} \\
 v_{\Sigma,AB} &= 23,969 \text{ m/s} & & & v_{\Sigma,A} &= 23,969 \text{ m/s} \\
 v_{\Sigma,D} &= 23,969 \text{ m/s} & & & v_{\Sigma,B} &= 23,969 \text{ m/s} \\
 & & & & v_{\Sigma,C} &= 23,969 \text{ m/s} \\
 & & & & v_{\Sigma,DE} &= 23,969 \text{ m/s} \\
 & & & & v_{\Sigma,E} &= 23,969 \text{ m/s}
 \end{aligned}$$

Effective arithmetic mean roughness value:

$$Ra = 0,5 \cdot (Ra_1 + Ra_2) \quad (3) \quad Ra = 0,90 \text{ } \mu\text{m}$$

5.2.3.4 Calculation of lubricant data

$X_L = 1,0$ for mineral oil (see ISO/TS 6336-22:2018, Table 4)

$$\alpha_{38} = 2,657 \cdot 10^{-8} \cdot \eta_{38}^{0,134} \quad (9) \quad \alpha_{38} = 2,15 \cdot 10^{-8} \text{ m}^2/\text{N}$$

$X_S = 1,2$ for injection lubrication

$$A = \frac{\log \left[\frac{\log(v_{40} + 0,7)}{\log(v_{100} + 0,7)} \right]}{\log \left(\frac{313}{373} \right)} \quad (18) \quad A = -3,385$$

$$B = \log \left[\log(v_{40} + 0,7) \right] - A \cdot \log(313) \quad (19) \quad B = 8,815$$

5.2.3.5 Calculation of the material parameter

Mean coefficient of friction:

$$X_R = 2,2 \cdot \left(\frac{Ra}{\rho_{n,C}} \right)^{0,25} \quad (86) \quad X_R = 1,025$$

$K_{B\gamma} = 1,0$ for $\varepsilon_\gamma < 2$

$$\mu_m = 0,045 \cdot \left(\frac{K_A \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta} \cdot F_{bt} \cdot K_{B\gamma}}{b \cdot v_{\Sigma,C} \cdot \rho_{n,C}} \right)^{0,2} \cdot (10^3 \cdot \eta_{\theta\text{oil}})^{-0,05} \cdot X_R \cdot X_L \quad (85) \quad \mu_m = 0,048$$

Bulk temperature:

$$H_v = (\varepsilon_1^2 + \varepsilon_2^2 + 1 - \varepsilon_\alpha) \cdot \left(\frac{1}{z_1} + \frac{1}{z_2} \right) \cdot \frac{\pi}{\cos \beta_b} \text{ for } \varepsilon_\alpha < 2 \quad (90) \quad H_v = 0,204$$

$$\varepsilon_{\max} = \varepsilon_1 = \varepsilon_2$$

$$X_{CA} = 1,0 \text{ for no profile modification (method B)} \quad (99)$$

$$\theta_M = \theta_{\text{oil}} + 7 \cdot 400 \cdot \left(\frac{P \cdot \mu_m \cdot H_v}{a \cdot b} \right)^{0,72} \cdot \frac{X_S}{1,2 \cdot X_{Ca}} \quad (83) \quad \theta_M = 153,6 \text{ }^\circ\text{C}$$

Material parameter:

$$G_M = 10^6 \cdot \alpha_{\theta M} \cdot E_r \quad (5) \quad G_M = 2 \, 678,3$$

5.2.3.6 Calculation of dynamic viscosity at bulk temperature

$$\log[\log(v_{\theta M} + 0,7)] = A \cdot \log(\theta_M + 273) + B \quad (17) \quad v_{\theta M} = 5,824 \text{ mm}^2/\text{s}$$

$$\rho_{\theta M} = \rho_{15} \cdot \left[1 - 0,7 \cdot \frac{(\theta_M + 273) - 288}{\rho_{15}} \right] \quad (20) \quad \rho_{\theta M} = 798,0 \text{ kg/m}^3$$

$$\eta_{\theta M} = 10^{-6} \cdot v_{\theta M} \cdot \rho_{\theta M} \quad (16) \quad \eta_{\theta M} = 4,647 \cdot 10^{-3} \text{ Ns/m}^2$$

5.2.3.7 Calculation of the velocity parameter

$$U_A = \eta_{\theta M} \cdot \frac{v_{\Sigma,A}}{2 \, 000 \cdot E_r \cdot \rho_{n,A}} \quad (12) \quad U_A = 2,003 \cdot 10^{-11}$$

$$U_{AB} = 1,571 \cdot 10^{-11} \quad U_B = 1,375 \cdot 10^{-11} \quad U_C = 1,290 \cdot 10^{-11}$$

$$U_D = 1,375 \cdot 10^{-11} \quad U_{DE} = 1,571 \cdot 10^{-11} \quad U_E = 2,003 \cdot 10^{-11}$$

5.2.3.8 Calculation of the load parameter

$$W_A = \frac{2 \cdot \pi \cdot p_{\text{dyn},A}^2}{E_r^2} \quad (22) \quad W_A = 1,440 \cdot 10^{-4}$$

$$W_{AB} = 1,694 \cdot 10^{-4} \quad W_B = 2,966 \cdot 10^{-4} \quad W_C = 2,781 \cdot 10^{-4}$$

$$W_D = 2,966 \cdot 10^{-4} \quad W_{DE} = 1,694 \cdot 10^{-4} \quad W_E = 1,440 \cdot 10^{-4}$$

5.2.3.9 Calculation of the sliding parameter

Load flash temperature:

$$\theta_{fl,A} = \frac{\sqrt{\pi}}{2} \cdot \frac{10^6 \cdot \mu_m \cdot p_{dyn,A} \cdot |v_{g,A}|}{B_{M1} \sqrt{v_{r1,A}} + B_{M2} \sqrt{v_{r2,A}}} \cdot \sqrt{8 \cdot \rho_{n,A} \cdot \frac{p_{dyn,A}}{1\,000 \cdot E_r}} \quad (79) \quad \theta_{fl,A} = 175,3 \text{ } ^\circ\text{C}$$

| | | |
|--|--|---|
| $\theta_{fl,AB} = 154,1 \text{ } ^\circ\text{C}$ | $\theta_{fl,B} = 145,4 \text{ } ^\circ\text{C}$ | $\theta_{fl,C} = 0 \text{ } ^\circ\text{C}$ |
| $\theta_{fl,D} = 145,4 \text{ } ^\circ\text{C}$ | $\theta_{fl,DE} = 154,1 \text{ } ^\circ\text{C}$ | $\theta_{fl,E} = 175,3 \text{ } ^\circ\text{C}$ |

Local contact temperature as sum of bulk and local flash temperature:

$$\theta_{B,A} = \theta_M + \theta_{fl,A} \quad (78) \quad \theta_{B,A} = 328,9 \text{ } ^\circ\text{C}$$

| | | |
|---|---|--|
| $\theta_{B,AB} = 307,7 \text{ } ^\circ\text{C}$ | $\theta_{B,B} = 299,0 \text{ } ^\circ\text{C}$ | $\theta_{B,C} = 153,6 \text{ } ^\circ\text{C}$ |
| $\theta_{B,D} = 299,0 \text{ } ^\circ\text{C}$ | $\theta_{B,DE} = 307,7 \text{ } ^\circ\text{C}$ | $\theta_{B,E} = 328,9 \text{ } ^\circ\text{C}$ |

Local sliding parameter:

$$S_{GF,A} = \frac{\alpha_{\theta,B,A} \cdot \eta_{\theta B,A}}{\alpha_{\theta M} \cdot \eta_{\theta M}} \quad (27) \quad S_{GF,A} = 0,057$$

| | | |
|---------------------|---------------------|--------------------|
| $S_{GF,AB} = 0,076$ | $S_{GF,B} = 0,086$ | $S_{GF,C} = 1,000$ |
| $S_{GF,D} = 0,086$ | $S_{GF,DE} = 0,076$ | $S_{GF,E} = 0,057$ |

5.2.3.10 Calculation of the lubricant film thickness

$$h_A = 1\,600 \cdot \rho_{n,A} \cdot G_M^{0,6} \cdot U_A^{0,7} \cdot W_A^{-0,13} \cdot S_{GF,A}^{0,22} \quad (4) \quad h_A = 0,122 \text{ } \mu\text{m}$$

| | | |
|---------------------------------------|---------------------------------------|------------------------------------|
| $h_{AB} = 0,137 \text{ } \mu\text{m}$ | $h_B = 0,136 \text{ } \mu\text{m}$ | $h_C = 0,241 \text{ } \mu\text{m}$ |
| $h_D = 0,136 \text{ } \mu\text{m}$ | $h_{DE} = 0,137 \text{ } \mu\text{m}$ | $h_E = 0,122 \text{ } \mu\text{m}$ |

5.2.3.11 Calculation of the specific lubricant film thickness

$$\lambda_{GF,A} = \frac{h_A}{Ra} \quad (2) \quad \lambda_{GF,A} = 0,136$$

| | | |
|---|---------------------------|--------------------------|
| $\lambda_{GF,AB} = 0,153$ | $\lambda_{GF,B} = 0,152$ | $\lambda_{GF,C} = 0,267$ |
| $\lambda_{GF,D} = 0,152$ | $\lambda_{GF,DE} = 0,153$ | $\lambda_{GF,E} = 0,136$ |
| $\lambda_{GF,min} = \lambda_{GF,A} = \lambda_{GF,E} \quad \lambda_{GF,min} = 0,136$ | | |

5.2.3.12 Calculation of the micropitting safety factor

$$S_{\lambda} = \frac{\lambda_{GF,min}}{\lambda_{GFP}} \quad (1) \quad S_{\lambda} = 0,644$$

The calculation of the permissible specific lubricant film thickness, λ_{GFP} , for Example 1 is shown as an example in 5.2.5.

The final results for the calculation of the safety factor against micropitting, S_{λ} , for Example 1 are shown in Table 4.

Table 4 — Results of calculation according to method B — Example 1

| Point | A | AB | B | C | D | DE | E |
|--------------------|--------------|-------|-------|-------|-------|-------|--------------|
| $\lambda_{GF,Y}$ | 0,136 | 0,153 | 0,152 | 0,267 | 0,152 | 0,153 | 0,136 |
| $\lambda_{GF,min}$ | 0,136 | | | | | | |
| λ_{GFP} | 0,211 | | | | | | |
| S_{λ} | 0,644 | | | | | | |

5.2.4 Calculation according to method A

The calculation of Example 1 according to method A was carried out by a 3D-calculation programme. Calculated results during method A vary depending on the method of determining load distribution. The load distribution, on which the following calculation according to method A is based, is shown in Table 5. The maximum values are printed in bold.

Table 5 — Matrix of pressure distribution $p_{H,Y,A}$ in N/mm²

| | Width in mm | | | |
|-----------|--------------|-------|-------|-------|
| | 0,0 | 7,6 | 13,8 | 21,4 |
| A | 1 115 | 1 110 | 1 110 | 1 114 |
| AB | 1 048 | 1 044 | 1 044 | 1 047 |
| B | 1 375 | 1 373 | 1 373 | 1 375 |
| C | 1 342 | 1 339 | 1 339 | 1 342 |
| D | 1 048 | 1 045 | 1 045 | 1 048 |
| DE | 1 050 | 1 046 | 1 046 | 1 050 |
| E | 1 099 | 1 094 | 1 094 | 1 099 |

The resulting matrix of specific lubricant film thickness according to method A is shown in Table 6. The minimum value is printed in bold.

Table 6 — Matrix of resulting specific lubricant film thickness $\lambda_{GF,Y}$

| | Width in mm | | | |
|-----------|--------------|--------------|--------------|--------------|
| | 0,0 | 7,6 | 13,8 | 21,4 |
| A | 0,122 | 0,122 | 0,122 | 0,122 |
| AB | 0,159 | 0,160 | 0,159 | 0,159 |
| B | 0,159 | 0,159 | 0,159 | 0,159 |
| C | 0,270 | 0,270 | 0,270 | 0,270 |
| D | 0,197 | 0,198 | 0,198 | 0,197 |
| DE | 0,159 | 0,159 | 0,159 | 0,159 |
| E | 0,124 | 0,125 | 0,124 | 0,124 |

For the calculation of the micropitting safety factor according to method A, the minimum value of the matrix of resulting specific lubricant film thickness, shown in Table 6, was used.

$$S_\lambda = \frac{\lambda_{GF,min}}{\lambda_{GFP}} \tag{1} \quad S_\lambda = 0,577$$

NOTE The difference in safety factor calculated between methods A and B in Example 1 results from the simplified calculation of load distribution according to method B.

5.2.5 Calculation of the permissible lubricant film thickness

5.2.5.1 General

Calculation of the permissible specific lubricant film thickness from the test result of the FZG-FVA micropitting test^[1] (Method B) with the reference test gears type C-GF.

The calculation of the reference value, λ_{GFT} , is done for point A because the minimum specific lubricant film thickness for gear type C is always at point A. All data of the reference test gears type C-GF have the subscript “Ref”.

Table 7 — Input data for calculation of the permissible lubricant film thickness

| | Symbol | Description | Unit | C-GF | |
|-------------|-------------------|---|-------------------|------------------|---------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| Geometry | z_{Ref} | number of teeth | — | 16 | 24 |
| | m_{tRef} | transverse module ($m_{nRef} = m_{tRef}$) | mm | 4,5 | |
| | α_{nRef} | transverse pressure angle ($\alpha_{nRef} = \alpha_{tRef}$) | ° | 20 | |
| | β_{bRef} | base helix angle ($\beta_{bRef} = \beta_{Ref}$) | ° | 0 | |
| | b_{Ref} | face width | mm | 14 | |
| | a_{Ref} | centre distance | mm | 91,5 | |
| | x_{Ref} | addendum modification factor | — | 0,181 7 | 0,171 6 |
| | d_{aRef} | tip diameter | mm | 82,45 | 118,35 |
| | — | tooth flank modifications | — | no modifications | |
| | Ra_{Ref} | arithmetic mean roughness value | µm | 0,50 | 0,50 |
| | E_{Ref} | modulus of elasticity | N/mm ² | 206 000 | 206 000 |
| | ν_{Ref} | Poisson's ratio | — | 0,3 | 0,3 |
| | λ_{MRef} | specific heat conductivity | W/(m·K) | 45 | 45 |
| | c_{MRef} | specific heat per unit mass | J/(kg·K) | 440 | 440 |
| | ρ_{MRef} | density | kg/m ³ | 7 800 | 7 800 |
| | W_w | material factor according to ISO/TS 6336-22:2018, Table A.1 (for matching case carburized/ case carburized) | — | 1,0 | |
| Application | K_{ARef} | application factor | — | 1,0 | |
| | K_{VRef} | dynamic factor | — | 1,05 | |
| | $K_{H\alpha Ref}$ | transverse load factor | — | 1,0 | |
| | $K_{H\beta Ref}$ | face load factor | — | 1,10 | |

Table 7 (continued)

| | Symbol | Description | Unit | C-GF | |
|------|-------------|--|-------------------|-----------------------|-------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| Load | T_{1Ref} | nominal torque at the pinion for SKS 8 | Nm | 171,6 | |
| | n_{1Ref} | rotation speed of the pinion | min ⁻¹ | 2 250 | — |
| | $p_{H,A,A}$ | nominal Hertzian contact stress at point A according to method A for SKS 8 (see Table 8) | N/mm ² | 1 191 | |
| | — | lubrication | — | injection lubrication | |

NOTE The used values for K_{VRef} and $K_{H\beta Ref}$ are valid for the standard FZG back-to-back test rig and standard conditions.

Table 8 gives the nominal Hertzian contact stress at point A for the reference test gears type C-GF as a function of the reached failure load stage (SKS) in the FZG-FVA micropitting test^[1].

Table 8 — Relation between failure load stage according to FZG-FVA micropitting test^[1] and nominal Hertzian contact stress at point A

| SKS | Nominal torque at the pinion in Nm | Hertzian contact stress at point C in N/mm ² | Nominal Hertzian contact stress at point A according to method A in N/mm ² |
|-----|------------------------------------|---|---|
| 5 | 70,0 | 795,1 | 764 |
| 6 | 98,9 | 945,1 | 906 |
| 7 | 132,5 | 1 093,9 | 1 048 |
| 8 | 171,6 | 1 244,9 | 1 191 |
| 9 | 215,6 | 1 395,4 | 1 333 |
| 10 | 265,1 | 1 547,3 | 1 476 |

5.2.5.2 Calculation of gear geometry

$$d_{1Ref} = z_{1Ref} \cdot m_{tRef} \quad d_{1Ref} = 72,00 \text{ mm}$$

$$d_{2Ref} = z_{2Ref} \cdot m_{tRef} \quad d_{2Ref} = 108,00 \text{ mm}$$

$$u_{Ref} = \frac{z_{2Ref}}{z_{1Ref}} \quad u_{Ref} = 1,5$$

$$d_{b1Ref} = d_{1Ref} \cdot \cos \alpha_{tRef} \quad d_{b1Ref} = 67,658 \text{ mm}$$

$$d_{b2Ref} = d_{2Ref} \cdot \cos \alpha_{tRef} \quad d_{b2Ref} = 101,7487 \text{ mm}$$

$$d_{w1Ref} = \frac{2 \cdot a_{Ref}}{u_{Ref} + 1} \quad d_{w1Ref} = 73,20 \text{ mm}$$

$$d_{w2Ref} = 2 \cdot a_{Ref} - d_{w1Ref} \quad d_{w2Ref} = 109,80 \text{ mm}$$

$$\alpha_{wtRef} = \arccos \left[\frac{(z_{1Ref} + z_{2Ref}) \cdot m_{tRef} \cdot \cos \alpha_{tRef}}{2 \cdot a_{Ref}} \right] \quad \alpha_{wtRef} = 22,439^\circ$$

$$p_{\text{etRef}} = m_{\text{tRef}} \cdot \pi \cdot \cos \alpha_{\text{tRef}}$$

$$p_{\text{etRef}} = 13,285 \text{ mm}$$

$$\varepsilon_{1\text{Ref}} = \frac{z_{1\text{Ref}}}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{\text{a1Ref}}}{d_{\text{b1Ref}}} \right)^2 - 1} - \tan \alpha_{\text{wtRef}} \right]$$

$$\varepsilon_{1\text{Ref}} = 0,722$$

$$\varepsilon_{2\text{Ref}} = \frac{z_{2\text{Ref}}}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{\text{a2Ref}}}{d_{\text{b2Ref}}} \right)^2 - 1} - \tan \alpha_{\text{wtRef}} \right]$$

$$\varepsilon_{2\text{Ref}} = 0,714$$

$$\varepsilon_{\alpha\text{Ref}} = \frac{1}{p_{\text{etRef}}} \cdot \left(\sqrt{\frac{d_{\text{a1Ref}}^2}{4} - \frac{d_{\text{b1Ref}}^2}{4}} + \sqrt{\frac{d_{\text{a2Ref}}^2}{4} - \frac{d_{\text{b2Ref}}^2}{4}} - a_{\text{Ref}} \cdot \sin \alpha_{\text{wtRef}} \right)$$

$$\varepsilon_{\alpha\text{Ref}} = 1,436$$

$$\varepsilon_{\beta\text{Ref}} = \frac{b_{\text{Ref}} \cdot \sin \beta_{\text{Ref}}}{m_{\text{nRef}} \cdot \pi}$$

$$\varepsilon_{\beta\text{Ref}} = 0$$

$$\varepsilon_{\gamma\text{Ref}} = \varepsilon_{\alpha\text{Ref}} + \varepsilon_{\beta\text{Ref}}$$

$$\varepsilon_{\gamma\text{Ref}} = 1,436$$

$$g_{\alpha\text{Ref}} = 0,5 \cdot \left(\sqrt{d_{\text{a1Ref}}^2 - d_{\text{b1Ref}}^2} + \sqrt{d_{\text{a2Ref}}^2 - d_{\text{b2Ref}}^2} \right) - a_{\text{Ref}} \cdot \sin \alpha_{\text{wtRef}}$$

$$g_{\alpha\text{Ref}} = 19,079 \text{ mm}$$

$$g_{\text{ARef}} = 0 \text{ mm}$$

$$(32) \quad g_{\text{ARef}} = 0 \text{ mm}$$

$$d_{\text{A1Ref}} = 2 \cdot \sqrt{\frac{d_{\text{b1Ref}}^2}{4} + \left(\sqrt{\frac{d_{\text{a1Ref}}^2}{4} - \frac{d_{\text{b1Ref}}^2}{4}} - g_{\alpha\text{Ref}} + g_{\text{ARef}} \right)^2}$$

$$(39) \quad d_{\text{A1Ref}} = 68,249 \text{ mm}$$

$$d_{\text{A2Ref}} = 2 \cdot \sqrt{\frac{d_{\text{b2Ref}}^2}{4} + \left(\sqrt{\frac{d_{\text{a2Ref}}^2}{4} - \frac{d_{\text{b2Ref}}^2}{4}} - g_{\text{ARef}} \right)^2}$$

$$(40) \quad d_{\text{A2Ref}} = 118,350 \text{ mm}$$

$$\rho_{\text{t1,ARef}} = \sqrt{\frac{d_{\text{A1Ref}}^2 - d_{\text{b1Ref}}^2}{4}}$$

$$(42) \quad \rho_{\text{t1,ARef}} = 4,482 \text{ mm}$$

$$\rho_{\text{t1,CRef}} = \sqrt{\frac{d_{\text{w1Ref}}^2 - d_{\text{b1Ref}}^2}{4}}$$

$$(42) \quad \rho_{\text{t1,CRef}} = 13,970 \text{ mm}$$

$$\rho_{\text{t2,ARef}} = \sqrt{\frac{d_{\text{A2Ref}}^2 - d_{\text{b2Ref}}^2}{4}}$$

$$(42) \quad \rho_{\text{t2,ARef}} = 30,443 \text{ mm}$$

$$\rho_{t2,CRef} = \sqrt{\frac{d_{w2Ref}^2 - d_{b2Ref}^2}{4}} \quad (42) \quad \rho_{t2,CRef} = 20,955 \text{ mm}$$

$$\rho_{t,ARef} = \frac{\rho_{t1,ARef} \cdot \rho_{t2,ARef}}{\rho_{t1,ARef} + \rho_{t2,ARef}} \quad (41) \quad \rho_{t,ARef} = \rho_{n,ARef} = 3,907 \text{ mm}$$

$$\rho_{t,CRef} = \frac{\rho_{t1,CRef} \cdot \rho_{t2,CRef}}{\rho_{t1,CRef} + \rho_{t2,CRef}} \quad (41) \quad \rho_{t,CRef} = \rho_{n,CRef} = 8,382 \text{ mm}$$

5.2.5.3 Calculation of material data type C-GF

$$E_{rRef} = 2 \cdot \left(\frac{1 - \nu_{1Ref}^2}{E_{1Ref}} + \frac{1 - \nu_{2Ref}^2}{E_{2Ref}} \right)^{-1} \quad (6) \quad E_{rRef} = 226\,374 \text{ N/mm}^2$$

$$B_{M1Ref} = \sqrt{\lambda_{M1Ref} \cdot \rho_{M1Ref} \cdot c_{M1Ref}} \quad (81) \quad B_{M1Ref} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

$$B_{M2Ref} = \sqrt{\lambda_{M2Ref} \cdot \rho_{M2Ref} \cdot c_{M2Ref}} \quad (82) \quad B_{M2Ref} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

5.2.5.4 Calculation of operating conditions of FVA-FZG micropitting test

$$P_{Ref} = 2 \cdot \pi \cdot \frac{n_{1Ref}}{60} \cdot \frac{T_{1Ref}}{1\,000} \quad (84) \quad P_{Ref} = 40,43 \text{ kW}$$

$$F_{btRef} = 2\,000 \cdot \frac{T_{1Ref}}{d_{b1Ref}} \quad F_{btRef} = 5\,072,6 \text{ N}$$

$$p_{dyn,A,ARef} = p_{H,A,ARef} \cdot \sqrt{K_{ARef} \cdot K_{vRef}} \quad (23) \quad p_{dyn,A,ARef} = 1\,229 \text{ N/mm}^2$$

$$p_{H,A,ARef} = p_{H,A,A} \quad p_{H,A,ARef} = 1\,191 \text{ N/mm}^2$$

$$v_{r1,ARef} = 2 \cdot \pi \cdot \frac{n_{1Ref}}{60} \cdot \frac{d_{w1Ref}}{2\,000} \cdot \sin \alpha_{wtRef} \cdot \sqrt{\frac{d_{A1Ref}^2 - d_{b1Ref}^2}{d_{w1Ref}^2 - d_{b1Ref}^2}} \quad (14) \quad v_{r1,ARef} = 1,056 \text{ m/s}$$

$$v_{r1,CRef} = 2 \cdot \pi \cdot \frac{n_{1Ref}}{60} \cdot \frac{d_{w1Ref}}{2\,000} \cdot \sin \alpha_{wtRef} \quad (14) \quad v_{r1,CRef} = 3,292 \text{ m/s}$$

$$v_{r2,ARef} = 2 \cdot \pi \cdot \frac{n_{1Ref}}{60 \cdot u_{Ref}} \cdot \frac{d_{w2Ref}}{2\,000} \cdot \sin \alpha_{wtRef} \cdot \sqrt{\frac{d_{A2Ref}^2 - d_{b2Ref}^2}{d_{w2Ref}^2 - d_{b2Ref}^2}} \quad (15) \quad v_{r2,ARef} = 4,782 \text{ m/s}$$

$$v_{r2,CRef} = 2 \cdot \pi \cdot \frac{n_{1Ref}}{60 \cdot u_{Ref}} \cdot \frac{d_{w2Ref}}{2\,000} \cdot \sin \alpha_{wtRef} \quad (15) \quad v_{r2,CRef} = 3,292 \text{ m/s}$$

$$v_{g,ARef} = v_{r1,ARef} - v_{r2,ARef} \quad (80) \quad v_{g,ARef} = -3,726 \text{ m/s}$$

$$v_{\Sigma, ARef} = v_{r1, ARef} + v_{r2, ARef}$$

$$(13) \quad v_{\Sigma, ARef} = 5,838 \text{ m/s}$$

$$v_{\Sigma, CRef} = v_{r1, CRef} + v_{r2, CRef}$$

$$(13) \quad v_{\Sigma, CRef} = 6,583 \text{ m/s}$$

$$Ra_{Ref} = 0,5 \cdot (Ra_{1Ref} + Ra_{2Ref})$$

$$(3) \quad Ra_{Ref} = 0,50 \text{ } \mu\text{m}$$

5.2.5.5 Calculation of lubricant data

$$\theta_{oilRef} = \theta_{oil} = 90 \text{ } ^\circ\text{C}$$

$$\eta_{\theta_{oilRef}} = \eta_{\theta_{oil}} = 0,021 \text{ N} \cdot \text{s} / \text{m}^2$$

$$X_{SRef} = 1,2 \text{ for injection lubrication}$$

5.2.5.6 Calculation of the permissible specific lubricant film thickness

$$X_{RRef} = 2,2 \cdot \left(\frac{Ra_{Ref}}{\rho_{n, CRef}} \right)^{0,25}$$

$$(86) \quad X_{RRef} = 1,087$$

$$K_{B\gamma Ref} = 1,0 \text{ for } \varepsilon_\gamma < 2$$

$$(87)$$

$$\Pi K_{Ref} = K_{ARef} \cdot K_{vRef} \cdot K_{H\alpha Ref} \cdot K_{H\beta Ref} \cdot K_{B\gamma Ref}$$

$$\Pi K_{Ref} = 1,155$$

$$\mu_{mRef} = 0,045 \cdot \left(\frac{\Pi K_{Ref} \cdot F_{btRef}}{b_{Ref} \cdot v_{\Sigma, CRef} \cdot \rho_{n, CRef}} \right)^{0,2} \cdot \left(10^3 \cdot \eta_{\theta_{oilRef}} \right)^{-0,05} \cdot X_{RRef} \cdot X_L$$

$$(85) \quad \mu_{mRef} = 0,063$$

$$H_{vRef} = \left(\varepsilon_{1Ref}^2 + \varepsilon_{2Ref}^2 + 1 - \varepsilon_{\alpha Ref} \right) \cdot \left(\frac{1}{z_{1Ref}} + \frac{1}{z_{2Ref}} \right) \cdot \frac{\pi}{\cos \beta_{bRef}}$$

$$(90) \quad H_{vRef} = 0,195$$

for $\varepsilon_\alpha < 2$

$$X_{CaRef} = 1,0 \text{ for no profile modification (method B)}$$

$$(99)$$

$$\theta_{MRef} = \theta_{oilRef} + 7400 \cdot \left(\frac{P_{Ref} \cdot \mu_{mRef} \cdot H_{vRef}}{a_{Ref} \cdot b_{Ref}} \right)^{0,72} \cdot \frac{X_{SRef}}{1,2 \cdot X_{CaRef}}$$

$$(83) \quad \theta_{MRef} = 115,9 \text{ } ^\circ\text{C}$$

$$\log \left[\log (v_{\theta_{MRef}} + 0,7) \right] = A \cdot \log (\theta_{MRef} + 273) + B$$

$$(17) \quad v_{\theta_{MRef}} = 12,317 \text{ mm}^2 / \text{s}$$

$$\rho_{\theta_{MRef}} = \rho_{15} \cdot \left[1 - 0,7 \cdot \frac{(\theta_{MRef} + 273) - 288}{\rho_{15}} \right]$$

$$(20) \quad \rho_{\theta_{MRef}} = 824,4 \text{ kg} / \text{m}^3$$

$$\eta_{\theta_{MRef}} = 10^{-6} \cdot v_{\theta_{MRef}} \cdot \rho_{\theta_{MRef}}$$

$$(16) \quad \eta_{\theta_{MRef}} = 0,010 \text{ N} \cdot \text{s} / \text{m}^2$$

$$\alpha_{\theta_{MRef}} = \alpha_{38} \cdot \left[1 + 516 \cdot \left(\frac{1}{\theta_{MRef} + 273} - \frac{1}{311} \right) \right]$$

$$(8) \quad \alpha_{\theta_{MRef}} = 1,435 \cdot 10^{-8} \text{ m}^2 / \text{N}$$

$$G_{MRef} = 10^6 \cdot \alpha_{\theta MRef} \cdot E_{rRef} \quad (5) \quad G_{MRef} = 3\,249,5$$

$$U_{ARef} = \eta_{\theta MRef} \cdot \frac{v_{\Sigma, ARef}}{2\,000 \cdot E_{rRef} \cdot \rho_{n, ARef}} \quad (12) \quad U_{ARef} = 3,351 \cdot 10^{-11}$$

$$W_{ARef} = \frac{2 \cdot \pi \cdot p_{dyn, ARef}^2}{E_{rRef}^2} \quad (22) \quad W_{ARef} = 1,825 \cdot 10^{-4}$$

$$\theta_{fl, ARef} = \frac{\sqrt{\pi}}{2} \cdot \frac{10^6 \cdot \mu_{mRef} \cdot p_{dyn, ARef} \cdot |v_{g, ARef}|}{B_{M1Ref} \sqrt{v_{r1, ARef}} + B_{M2Ref} \sqrt{v_{r2, ARef}}} \cdot \sqrt{8 \cdot \rho_{n, ARef} \cdot \frac{p_{dyn, ARef}}{1\,000 \cdot E_{rRef}}} \quad (79) \quad \theta_{fl, ARef} = 82,5 \text{ } ^\circ\text{C}$$

$$\theta_{B, ARef} = \theta_{MRef} + \theta_{fl, ARef} \quad (78) \quad \theta_{B, ARef} = 198,3 \text{ } ^\circ\text{C}$$

$$\log \left[\log(v_{\theta B, ARef} + 0,7) \right] = A \cdot \log(\theta_{B, ARef} + 273) + B \quad (30) \quad v_{\theta B, ARef} = 3,112 \text{ mm}^2 / \text{s}$$

$$\rho_{\theta B, ARef} = \rho_{15} \cdot \left[1 - 0,7 \cdot \frac{(\theta_{B, ARef} + 273) - 288}{\rho_{15}} \right] \quad (31) \quad \rho_{\theta B, ARef} = 766,7 \text{ kg} / \text{m}^3$$

$$\eta_{\theta B, ARef} = 10^{-6} \cdot v_{\theta B, ARef} \cdot \rho_{\theta B, ARef} \quad (29) \quad \eta_{\theta B, ARef} = 0,002 \text{ N} \cdot \text{s} / \text{m}^2$$

$$\alpha_{\theta B, ARef} = \alpha_{38} \cdot \left[1 + 516 \cdot \left(\frac{1}{\theta_{B, ARef} + 273} - \frac{1}{311} \right) \right] \quad (28) \quad \alpha_{\theta B, ARef} = 9,363 \cdot 10^{-9} \text{ m}^2 / \text{N}$$

$$S_{GF, ARef} = \frac{\alpha_{\theta B, ARef} \cdot \eta_{\theta B, ARef}}{\alpha_{\theta MRef} \cdot \eta_{\theta MRef}} \quad (27) \quad S_{GF, ARef} = 0,153$$

$$h_{ARef} = 1\,600 \cdot \rho_{n, ARef} \cdot G_{MRef}^{0,6} \cdot U_{ARef}^{0,7} \cdot W_{ARef}^{-0,13} \cdot S_{GF, ARef}^{0,22} \quad (4) \quad h_{ARef} = 0,075 \text{ } \mu\text{m}$$


$$\lambda_{GFT} = \lambda_{GF, ARef} = \frac{h_{ARef}}{Ra_{Ref}} \quad (2) \quad \lambda_{GFT} = 0,151$$

$$\lambda_{GFP} = 1,4 \cdot W_W \cdot \lambda_{GFT} \quad (A.1) \quad \lambda_{GFP} = 0,211$$

5.3 Example 2 Spur gear

5.3.1 General

The result of this example is confirmed by experimental investigations. The gears were obviously micropitted and had profile deviations of approximately 15 μm . [Figure 2](#) shows a diagram of the observed location and severity of micropitting for the pinion of Example 2.



Key

- 1 tip
- 2 root

Figure 2 — Diagram of schematic profile deviations of the pinion for Example 2

NOTE Example 2 is only calculated according to method B. Furthermore, no modifications for the calculation according to method B were considered.

5.3.2 Input data

Table 9 — Input data for Example 2

| | Symbol | Description | Unit | Example 2 | |
|----------|---------------------------------|------------------------------|-------------------|------------------------|---------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| Geometry | z | number of teeth | — | 20 | 20 |
| | — | driving gear | — | x | |
| | m_n | normal module | mm | 10,0 | |
| | α_n | normal pressure angle | ° | 20 | |
| | β | helix angle | ° | 0 | |
| | b | face width | mm | 15 | |
| | a | centre distance | mm | 200 | |
| | x | addendum modification factor | — | 0,0 | 0,0 |
| | d_a | tip diameter | mm | 220,0 | 220,0 |
| | — | tooth flank modifications | — | no adequate tip relief | |
| | A | ISO tolerance class | — | 6 | 6 |
| Ra | arithmetic mean roughness value | μm | 0,80 | 0,80 | |
| Material | — | material | — | Eh | Eh |
| | E | modulus of elasticity | N/mm ² | 206 000 | 206 000 |
| | ν | Poisson's ratio | — | 0,3 | 0,3 |
| | λ_M | specific heat conductivity | W/(m·K) | 45 | 45 |

Table 9 (continued)

| | Symbol | Description | Unit | Example 2 | |
|-------------|-----------------|---|--------------------|-------------|-------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| | c_M | specific heat capacity | J/(kg·K) | 440 | 440 |
| | ρ_M | density | kg/m ³ | 7 800 | 7 800 |
| | W_w | material factor according to ISO/TS 6336-22:2018, Table A.1 (for matching case carburized/ case carburized) | — | 1,0 | |
| Application | K_A | application factor | — | 1,0 | |
| | K_V | dynamic factor | — | 1,038 | |
| | K_Y | mesh load factor | — | 1,0 | |
| | $K_{H\alpha}$ | transverse load factor | — | 1,0 | |
| | $K_{H\beta}$ | face load factor | — | 1,05 | |
| Load | T_1 | nominal torque at the pinion | Nm | 2 400 | |
| | n_1 | rotation speed of the pinion | min ⁻¹ | 1 000 | |
| Lubricant | θ_{oil} | oil inlet temperature (injection lubrication) | °C | 70 | |
| | ν_{40} | kinematic viscosity at 40 °C | mm ² /s | 150 | |
| | ν_{100} | kinematic viscosity at 100 °C | mm ² /s | 14,7 | |
| | ρ_{15} | density of the lubricant at 15 °C | kg/m ³ | 890 | |
| | — | oil type | — | mineral oil | |
| | — | failure load stage at test temperature (90 °C) according to FVA 5417 | — | SKS 10 | |
| | λ_{GFP} | permissible lubricant film thickness | — | 0,120 | |

5.3.3 Calculation according to method B

5.3.3.1 Calculation of gear geometry (according to ISO 21771)

Basic values:

$$m_t = \frac{m_n}{\cos \beta}$$

$$m_t = 10,00 \text{ mm}$$

$$d_1 = z_1 \cdot m_t$$

$$d_1 = 200,00 \text{ mm}$$

$$d_2 = z_2 \cdot m_t$$

$$d_2 = 200,00 \text{ mm}$$

$$u = \frac{z_2}{z_1}$$

$$u = 1,00$$

$$\alpha_t = \arctan \left(\frac{\tan \alpha_n}{\cos \beta} \right)$$

$$\alpha_t = 20,000^\circ$$

$$d_{b1} = d_1 \cos \alpha_t$$

$$d_{b1} = 187,939 \text{ mm}$$

$$d_{b2} = d_2 \cos \alpha_t$$

$$d_{b2} = 187,939 \text{ mm}$$

$$d_{w1} = \frac{2 \cdot a}{u+1} \quad d_{w1} = 200 \text{ mm}$$

$$d_{w2} = 2 \cdot a - d_{w1} \quad d_{w2} = 200 \text{ mm}$$

$$\alpha_{wt} = \arccos \left[\frac{(z_1 + z_2) \cdot m_t \cdot \cos \alpha_t}{2 \cdot a} \right] \quad \alpha_{wt} = 20,000^\circ$$

$$\beta_b = \arcsin(\sin \beta \cdot \cos \alpha_n) \quad \beta_b = 0^\circ$$

$$p_{et} = m_t \cdot \pi \cdot \cos \alpha_t \quad p_{et} = 29,521 \text{ mm}$$

$$\varepsilon_1 = \frac{z_1}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a1}}{d_{b1}} \right)^2} - 1 - \tan \alpha_{wt} \right] \quad \varepsilon_1 = 0,778$$

$$\varepsilon_2 = \frac{z_2}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a2}}{d_{b2}} \right)^2} - 1 - \tan \alpha_{wt} \right] \quad \varepsilon_2 = 0,778$$

$$\varepsilon_\alpha = \frac{1}{p_{et}} \cdot \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + \sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - a \cdot \sin \alpha_{wt} \right) \quad \varepsilon_\alpha = 1,557$$

$$\varepsilon_\beta = \frac{b \cdot \sin \beta}{m_n \cdot \pi} \quad \varepsilon_\beta = 0$$

$$\varepsilon_\gamma = \varepsilon_\alpha + \varepsilon_\beta \quad \varepsilon_\gamma = 1,557$$

$$g_\alpha = 0,5 \cdot \left(\sqrt{d_{a1}^2 - d_{b1}^2} + \sqrt{d_{a2}^2 - d_{b2}^2} \right) \cdot a \cdot \sin \alpha_{wt} \quad g_\alpha = 45,960 \text{ mm}$$

Coordinates of the basic points (A, AB, B, C, D, DE, E) on the line of action:

$$g_A = 0 \text{ mm} \quad (32) \quad g_A = 0 \text{ mm}$$

$$g_{AB} = \frac{g_\alpha - p_{et}}{2} \quad (33) \quad g_{AB} = 8,219 \text{ mm}$$

$$g_B = g_\alpha - p_{et} \quad (34) \quad g_B = 16,439 \text{ mm}$$

$$g_C = \frac{d_{b1}}{2} \cdot \tan \alpha_{wt} - \sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + g_\alpha \quad (35) \quad g_C = 22,980 \text{ mm}$$

$$g_D = p_{et} \quad (36) \quad g_D = 29,521 \text{ mm}$$

$$g_{DE} = \frac{g_\alpha - p_{et}}{2} + p_{et} \quad (37) \quad g_{DE} = 37,741 \text{ mm}$$

$$g_E = g_\alpha \quad (38) \quad g_E = 45,960 \text{ mm}$$

$$d_{A1} = 2 \cdot \sqrt{\frac{d_{b1}^2}{4} + \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} - g_{\alpha} + g_A \right)^2} \quad (39) \quad d_{A1} = 189,274 \text{ mm}$$

$$d_{AB1} = 191,919 \text{ mm}$$

$$d_{B1} = 195,912 \text{ mm}$$

$$d_{C1} = 200,000 \text{ mm}$$

$$d_{D1} = 204,844 \text{ mm}$$

$$d_{DE1} = 211,920 \text{ mm}$$

$$d_{E1} = 220,000 \text{ mm}$$

$$d_{A2} = 2 \cdot \sqrt{\frac{d_{b2}^2}{4} + \left(\sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - g_A \right)^2} \quad (40) \quad d_{A2} = 220,000 \text{ mm}$$

$$d_{AB2} = 211,920 \text{ mm}$$

$$d_{B2} = 204,844 \text{ mm}$$

$$d_{C2} = 200,000 \text{ mm}$$

$$d_{D2} = 195,912 \text{ mm}$$

$$d_{DE2} = 191,919 \text{ mm}$$

$$d_{E2} = 189,274 \text{ mm}$$

Normal radius of relative curvature:

$$\rho_{n,A} = \frac{\rho_{t,A}}{\cos \beta_b} \quad (43) \quad \rho_{n,A} = 9,281 \text{ mm}$$

$$\rho_{n,AB} = 13,916 \text{ mm}$$

$$\rho_{n,B} = 16,475 \text{ mm}$$

$$\rho_{n,C} = 17,101 \text{ mm}$$

$$\rho_{n,D} = 16,475 \text{ mm}$$

$$\rho_{n,DE} = 13,916 \text{ mm}$$

$$\rho_{n,E} = 9,381 \text{ mm}$$

5.3.3.2 Calculation of material data

$$E_r = 2 \cdot \left(\frac{1 - \nu_1^2}{E_1} + \frac{1 - \nu_2^2}{E_2} \right)^{-1} \quad (6) \quad E_r = 226\,374 \text{ N/mm}^2$$

$$B_{M1} = \sqrt{\lambda_{M1} \cdot \rho_{M1} \cdot c_{M1}} \quad (81) \quad B_{M1} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

$$B_{M2} = \sqrt{\lambda_{M2} \cdot \rho_{M2} \cdot c_{M2}} \quad (82) \quad B_{M2} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

5.3.3.3 Calculation of operating conditions

Loading:

$$P = 2 \cdot \pi \cdot \frac{n_1}{60} \cdot \frac{T_1}{1\,000} \quad (84) \quad P = 251 \text{ kW}$$

$$F_t = 2\,000 \cdot \frac{T_1}{d_1} \quad F_t = 24\,000 \text{ N}$$

$$F_{bt} = 2\,000 \cdot \frac{T_1}{d_{b1}} \quad F_{bt} = 25\,540 \text{ N}$$

Local sharing factor:

NOTE No tooth flank modifications, spur gears, ISO tolerance class ≤7 (see ISO/TS 6336-22:2018, Figure 2).

$$X_A = \frac{A-2}{15} + \frac{1}{3} \cdot \frac{g_A}{g_B} \quad (44) \quad X_A = 0,333$$

$$X_{AB} = 0,500 \quad X_B = 1,000 \quad X_C = 1,000$$

$$X_D = 1,000 \quad X_{DE} = 0,500 \quad X_E = 0,333$$

Elasticity factor:

$$Z_E = \sqrt{\frac{E_r}{2 \cdot \pi}} \quad (26) \quad Z_E = 189,812 \left(\text{N/mm}^2 \right)^{0,5}$$

Local Hertzian contact stress:

$$p_{H,A,B} = Z_E \cdot \sqrt{\frac{F_t \cdot X_A}{b \cdot \rho_{n,A} \cdot \cos \alpha_t}} \quad (25) \quad p_{H,A,B} = 1\,476 \text{ N/mm}^2$$

$$p_{H,AB,B} = 1\,485 \text{ N/mm}^2 \quad p_{H,B,B} = 1\,930 \text{ N/mm}^2 \quad p_{H,C,B} = 1\,894 \text{ N/mm}^2$$

$$p_{H,D,B} = 1\,930 \text{ N/mm}^2 \quad p_{H,DE,B} = 1\,485 \text{ N/mm}^2 \quad p_{H,E,B} = 1\,476 \text{ N/mm}^2$$

$$p_{dyn,A,B} = p_{H,A,B} \cdot \sqrt{K_A \cdot K_\gamma \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta}} \quad (24) \quad p_{dyn,A,B} = 1\,541 \text{ N/mm}^2$$

$$p_{dyn,AB,B} = 1\,550 \text{ N/mm}^2 \quad p_{dyn,B,B} = 2\,014 \text{ N/mm}^2 \quad p_{dyn,C,B} = 1\,977 \text{ N/mm}^2$$

$$p_{dyn,D,B} = 2\,014 \text{ N/mm}^2 \quad p_{dyn,DE,B} = 1\,550 \text{ N/mm}^2 \quad p_{dyn,E,B} = 1\,541 \text{ N/mm}^2$$

Velocity:

$$v_{g,A} = v_{r1,A} - v_{r2,A} \quad (80) \quad v_{g,A} = -4,813 \text{ m/s}$$

$$v_{g,AB} = -3,091 \text{ m/s} \quad v_{g,B} = -1,370 \text{ m/s} \quad v_{g,C} = 0 \text{ m/s}$$

$$v_{g,D} = 1,370 \text{ m/s} \quad v_{g,DE} = 3,091 \text{ m/s} \quad v_{g,E} = 4,813 \text{ m/s}$$

$$v_{\Sigma,A} = v_{r1,A} + v_{r2,A} \quad (13) \quad v_{\Sigma,A} = 7,163 \text{ m/s}$$

$$v_{\Sigma,AB} = 7,163 \text{ m/s} \quad v_{\Sigma,B} = 7,163 \text{ m/s} \quad v_{\Sigma,C} = 7,163 \text{ m/s}$$

$$v_{\Sigma,D} = 7,163 \text{ m/s} \quad v_{\Sigma,DE} = 7,163 \text{ m/s} \quad v_{\Sigma,E} = 7,163 \text{ m/s}$$

Effective arithmetic mean roughness value:

$$Ra = 0,5 \cdot (Ra_1 + Ra_2) \quad (3) \quad Ra = 0,80 \text{ } \mu\text{m}$$

5.3.3.4 Calculation of lubricant data

$X_L = 1,0$ for mineral oil (see ISO/TS 6336-22:2018, Table 4)

$$\alpha_{38} = 2,657 \cdot 10^{-8} \cdot \eta_{38}^{0,1348} \quad (9) \quad \alpha_{38} = 2,05 \cdot 10^{-8} \text{ m}^2 / \text{N}$$

$X_S = 1,2$ for injection lubrication

$$A = \frac{\log \left[\frac{\log(v_{40} + 0,7)}{\log(v_{100} + 0,7)} \right]}{\log \left(\frac{313}{373} \right)} \quad (18) \quad A = -3,459$$

$$B = \log \left[\log(v_{40} + 0,7) \right] - A \cdot \log(313) \quad (19) \quad B = 8,97$$

5.3.3.5 Calculation of the material parameter

Mean coefficient of friction:

$$X_R = 2,2 \cdot \left(\frac{Ra}{\rho_{n,C}} \right)^{0,25} \quad (86) \quad X_R = 1,023$$

$K_{B\gamma} = 1,0$ for $\varepsilon_\gamma < 2$

$$\mu_m = 0,045 \cdot \left(\frac{K_A \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta} \cdot F_{bt} \cdot K_{B\gamma}}{b \cdot v_{\Sigma,C} \cdot \rho_{n,C}} \right)^{0,2} \cdot (10^3 \cdot \eta_{\theta\text{oil}})^{-0,05} \cdot X_R \cdot X_L \quad (85) \quad \mu_m = 0,067$$

Bulk temperature:

$$H_v = (\varepsilon_1^2 + \varepsilon_2^2 + 1 - \varepsilon_\alpha) \cdot \left(\frac{1}{z_1} + \frac{1}{z_2} \right) \cdot \frac{\pi}{\cos \beta_b} \text{ for } \varepsilon_\alpha < 2 \quad (90) \quad H_v = 0,206$$

$$\varepsilon_{\max} = \varepsilon_1 = \varepsilon_2$$

$$X_{CA} = 1,0 \text{ for no adequate profile modification (method B)} \quad (99)$$

$$\theta_M = \theta_{\text{oil}} + 7 \cdot 400 \cdot \left(\frac{P \cdot \mu_m \cdot H_v}{a \cdot b} \right)^{0,72} \cdot \frac{X_S}{1,2 \cdot X_{Ca}} \quad (83) \quad \theta_M = 126,6 \text{ }^\circ\text{C}$$

Material parameter:

$$G_M = 10^6 \cdot \alpha_{\theta M} \cdot E_r \quad (5) \quad G_M = 2 \, 935,8$$

5.3.3.6 Calculation of the dynamic viscosity at bulk temperature

$$\log[\log(v_{\theta M} + 0,7)] = A \cdot \log(\theta_M + 273) + B \quad (17) \quad v_{\theta M} = 7,929 \text{ mm}^2 / \text{s}$$

$$\rho_{\theta M} = \rho_{15} \cdot \left[1 - 0,7 \cdot \frac{(\theta_M + 273) - 288}{\rho_{15}} \right] \quad (20) \quad \rho_{\theta M} = 811,9 \text{ kg/m}^3$$

$$\eta_{\theta M} = 10^{-6} \cdot v_{\theta M} \cdot \rho_{\theta M} \quad (16) \quad \eta_{\theta M} = 6,437 \cdot 10^{-3} \text{ Ns/m}^2$$

5.3.3.7 Calculation of the velocity parameter

$$U_A = \eta_{\theta M} \cdot \frac{v_{\Sigma,A}}{2 \, 000 \cdot E_r \cdot \rho_{n,A}} \quad (12) \quad U_A = 1,086 \cdot 10^{-11}$$

$$U_{AB} = 7,319 \cdot 10^{-12} \quad U_B = 6,182 \cdot 10^{-12} \quad U_C = 5,956 \cdot 10^{-12}$$

$$U_D = 6,182 \cdot 10^{-12} \quad U_{DE} = 7,319 \cdot 10^{-12} \quad U_E = 1,086 \cdot 10^{-11}$$

5.3.3.8 Calculation of the load parameter

$$W_A = \frac{2 \cdot \pi \cdot p_{\text{dyn},A}^2}{E_r^2} \quad (22) \quad W_A = 2,913 \cdot 10^{-4}$$

$$W_{AB} = 2,946 \cdot 10^{-4} \quad W_B = 4,976 \cdot 10^{-4} \quad W_C = 4,794 \cdot 10^{-4}$$

$$W_D = 4,976 \cdot 10^{-4} \quad W_{DE} = 2,946 \cdot 10^{-4} \quad W_E = 2,913 \cdot 10^{-4}$$

5.3.3.9 Calculation of the sliding parameter

Load flash temperature:

$$\theta_{fl,A} = \frac{\sqrt{\pi}}{2} \cdot \frac{10^6 \cdot \mu_m \cdot p_{dyn,A} \cdot |v_{g,A}|}{B_{M1} \sqrt{v_{r1,A}} + B_{M2} \sqrt{v_{r2,A}}} \cdot \sqrt{8 \cdot \rho_{n,A} \cdot \frac{p_{dyn,A}}{1000 \cdot E_r}} \quad (79) \quad \theta_{fl,A} = 225,7 \text{ } ^\circ\text{C}$$

$$\theta_{fl,AB} = 170,3 \text{ } ^\circ\text{C}$$

$$\theta_{fl,B} = 119,2 \text{ } ^\circ\text{C}$$

$$\theta_{fl,C} = 0 \text{ } ^\circ\text{C}$$

$$\theta_{fl,D} = 119,2 \text{ } ^\circ\text{C}$$

$$\theta_{fl,DE} = 170,3 \text{ } ^\circ\text{C}$$

$$\theta_{fl,E} = 225,7 \text{ } ^\circ\text{C}$$

Local contact temperature as sum of bulk and local flash temperature:

$$\theta_{B,A} = \theta_M + \theta_{fl,A} \quad (78) \quad \theta_{B,A} = 352,3 \text{ } ^\circ\text{C}$$

$$\theta_{B,AB} = 296,9 \text{ } ^\circ\text{C}$$

$$\theta_{B,B} = 245,8 \text{ } ^\circ\text{C}$$

$$\theta_{B,C} = 126,6 \text{ } ^\circ\text{C}$$

$$\theta_{B,D} = 245,8 \text{ } ^\circ\text{C}$$

$$\theta_{B,DE} = 296,9 \text{ } ^\circ\text{C}$$

$$\theta_{B,E} = 352,3 \text{ } ^\circ\text{C}$$

Local sliding parameter:

$$S_{GF,A} = \frac{\alpha_{\theta,B,A} \cdot \eta_{\theta,B,A}}{\alpha_{\theta M} \cdot \eta_{\theta M}} \quad (27) \quad S_{GF,A} = 0,024$$

$$S_{GF,AB} = 0,049$$

$$S_{GF,B} = 0,102$$

$$S_{GF,C} = 1,000$$

$$S_{GF,D} = 0,102$$

$$S_{GF,DE} = 0,049$$

$$S_{GF,E} = 0,024$$

5.3.3.10 Calculation of the lubricant film thickness

$$h_A = 1\,600 \cdot \rho_{n,A} \cdot G_M^{0,6} \cdot U_A^{0,7} \cdot W_A^{-0,13} \cdot S_{GF,A}^{0,22} \quad (4) \quad h_A = 0,048 \text{ } \mu\text{m}$$

$$h_{AB} = 0,064 \text{ } \mu\text{m}$$

$$h_B = 0,074 \text{ } \mu\text{m}$$

$$h_C = 0,124 \text{ } \mu\text{m}$$

$$h_D = 0,074 \text{ } \mu\text{m}$$

$$h_{DE} = 0,064 \text{ } \mu\text{m}$$

$$h_E = 0,048 \text{ } \mu\text{m}$$

5.3.3.11 Calculation of the specific lubricant film thickness

$$\lambda_{GF,A} = \frac{h_A}{Ra} \quad (2) \quad \lambda_{GF,A} = 0,060$$

$$\lambda_{GF,AB} = 0,080$$

$$\lambda_{GF,B} = 0,092$$

$$\lambda_{GF,C} = 0,154$$

$$\lambda_{GF,D} = 0,092$$

$$\lambda_{GF,DE} = 0,080$$

$$\lambda_{GF,E} = 0,006$$

$$\lambda_{GF,min} = \lambda_{GF,A} = \lambda_{GF,E}$$

$$\lambda_{GF,min} = 0,006$$

5.3.3.12 Calculation of the micropitting safety factor

$$S_{\lambda} = \frac{\lambda_{GF,min}}{\lambda_{GFP}} \quad (1) \quad S_{\lambda} = 0,504$$

The final results for the calculation of the safety factor against micropitting, S_{λ} , for Example 2 are shown in [Table 10](#).

Table 10 — Results of calculation according to method B — Example 2

| Point | A | AB | B | C | D | DE | E |
|---------------------------------|--------------|-------|-------|-------|-------|-------|--------------|
| $\lambda_{GF,Y}$ | 0,060 | 0,080 | 0,092 | 0,154 | 0,092 | 0,080 | 0,060 |
| $\lambda_{GF,min}$ | 0,060 | | | | | | |
| λ_{GFP} | 0,120 | | | | | | |
| S_{λ} | 0,504 | | | | | | |


NOTE With reference to ISO/TS 6336-22:2018, 5.4, for θ_{oilRef} the oil temperature, at which the test was performed, is used in the calculation. Micropitting load capacity is significantly influenced by additives, often more than by the viscosity. As the effectiveness of additives depends significantly on temperature, ISO/TS 6336-22 recommends that the oil is tested at the temperature used in the application.

Normally, the FZG-FVA micropitting test^[1] is executed at 90 °C oil temperature. The data from oil providers should contain together with the failure load stage SKS also the test temperature.

5.4 Example 3 Helical gear

5.4.1 General

The result of this example is confirmed by experimental investigations. The gears were obviously micropitted and had profile deviations of approximately 10 µm (pinion) and 5 µm (wheel). [Figure 3](#) shows a diagram of the observed location and severity of micropitting for pinion and wheel of Example 3.

**Key**

- 1 tip
2 root

Figure 3 — Diagram of schematic profile deviations of pinion and wheel for Example 3

NOTE For the calculation according to method B, no modifications were considered.

5.4.2 Input data

Table 11 — Input data for Example 3

| | Symbol | Description | Unit | Example 3 | |
|----------|--------------|------------------------------------|--------|-----------|-------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| Geometry | z | number of teeth | — | 33 | 34 |
| | — | driving gear | — | x | |
| | m_n | normal module | mm | 4,5 | |
| | α_n | normal pressure angle | ° | 20 | |
| | β | helix angle (right-hand on pinion) | ° | 19,578 | |
| | b | face width | mm | 44 | |
| | a | centre distance | mm | 160 | |
| | x | addendum modification factor | — | 0,0 | 0,0 |
| d_a | tip diameter | mm | 166,61 | 171,39 | |

^a Calculation according to method B: modifications assumed as not adequate; calculation according to method A: modifications recognized during calculation of pressure distribution.

Table 11 (continued)

| | Symbol | Description | Unit | Example 3 | |
|-------------|------------------------|---|-------------------------------------|---|---------|
| | | | | Pinion | Wheel |
| | | | | Comb. | |
| | — | tooth flank modifications ^a | — | linear tip relief $C_{a1} = 50 \mu\text{m}$, $d_{\text{End}1} = 162,72 \text{ mm}$ $C_{a2} = 50 \mu\text{m}$, $d_{\text{End}2} = 162,52 \text{ mm}$ | |
| | A | ISO tolerance class | — | 4 | 4 |
| | R_a | arithmetic mean roughness value | μm | 0,45 | 0,45 |
| Material | — | material | — | E_h | E_h |
| | E | modulus of elasticity | N/mm^2 | 206 000 | 206 000 |
| | ν | Poisson's ratio | — | 0,3 | 0,3 |
| | λ_M | specific heat conductivity | $\text{W}/(\text{m}\cdot\text{K})$ | 45 | 45 |
| | c_M | specific heat capacity | $\text{J}/(\text{kg}\cdot\text{K})$ | 440 | 440 |
| | ρ_M | density | kg/m^3 | 7 800 | 7 800 |
| | W_w | material factor according to ISO/TS 6336-22:2018, Table A.1 (for matching case carburized/ case carburized) | — | 1,0 | |
| Application | K_A | application factor | — | 1,0 | |
| | K_V | dynamic factor | — | 1,05 | |
| | K_γ | mesh load factor | — | 1,0 | |
| | $K_{H\alpha}$ | transverse load factor | — | 1,0 | |
| | $K_{H\beta}$ | face load factor | — | 1,10 | |
| Load | T_1 | nominal torque at the pinion | Nm | 4 000 | |
| | n_1 | rotation speed of the pinion | min^{-1} | 3 000 | |
| Lubricant | θ_{oil} | oil inlet temperature (injection lubrication) | $^\circ\text{C}$ | 90 | |
| | ν_{40} | kinematic viscosity at 40 $^\circ\text{C}$ | mm^2/s | 76,5 | |
| | ν_{100} | kinematic viscosity at 100 $^\circ\text{C}$ | mm^2/s | 8,0 | |
| | ρ_{15} | density of the lubricant at 15 $^\circ\text{C}$ | kg/m^3 | 895 | |
| | | oil type | — | mineral oil | |
| | λ_{GFP} | permissible lubricant film thickness determined from a representative bench test | — | 0,112 | |

^a Calculation according to method B: modifications assumed as not adequate; calculation according to method A: modifications recognized during calculation of pressure distribution.

5.4.3 Calculation according to method B

5.4.3.1 Calculation of gear geometry (according to ISO 21771)

Basic values:

$$m_t = \frac{m_n}{\cos \beta} \quad m_t = 4,776 \text{ mm}$$

$$d_1 = z_1 \cdot m_t \quad d_1 = 157,612 \text{ mm}$$

$$d_2 = z_2 \cdot m_t \quad d_2 = 162,388 \text{ mm}$$

$$u = \frac{z_2}{z_1} \quad u = 1,03$$

$$\alpha_t = \arctan\left(\frac{\tan \alpha_n}{\cos \beta}\right) \quad \alpha_t = 21,122^\circ$$

$$d_{b1} = d_1 \cos \alpha_t \quad d_{b1} = 147,023 \text{ mm}$$

$$d_{b2} = d_2 \cos \alpha_t \quad d_{b2} = 151,479 \text{ mm}$$

$$d_{w1} = \frac{2 \cdot a}{u+1} \quad d_{w1} = 157,612 \text{ mm}$$

$$d_{w2} = 2 \cdot a - d_{w1} \quad d_{w2} = 162,388 \text{ mm}$$

$$\alpha_{wt} = \arccos\left[\frac{(z_1 + z_2) \cdot m_t \cdot \cos \alpha_t}{2 \cdot a}\right] \quad \alpha_{wt} = 21,122^\circ$$

$$\beta_b = \arcsin(\sin \beta \cdot \cos \alpha_n) \quad \beta_b = 18,354^\circ$$

$$p_{et} = m_t \cdot \pi \cdot \cos \alpha_t \quad p_{et} = 13,997 \text{ mm}$$

$$\varepsilon_1 = \frac{z_1}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a1}}{d_{b1}}\right)^2 - 1} - \tan \alpha_{wt} \right] \quad \varepsilon_1 = 0,771$$

$$\varepsilon_2 = \frac{z_2}{2 \cdot \pi} \cdot \left[\sqrt{\left(\frac{d_{a2}}{d_{b2}}\right)^2 - 1} - \tan \alpha_{wt} \right] \quad \varepsilon_2 = 0,774$$

$$\varepsilon_\alpha = \frac{1}{p_{et}} \cdot \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + \sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - a \cdot \sin \alpha_{wt} \right) \quad \varepsilon_\alpha = 1,545$$

$$\varepsilon_{\beta} = \frac{b \cdot \sin \beta}{m_n \cdot \pi} \quad \varepsilon_{\beta} = 1,043$$

$$\varepsilon_{\gamma} = \varepsilon_{\alpha} + \varepsilon_{\beta} \quad \varepsilon_{\gamma} = 2,588$$

$$g_{\alpha} = 0,5 \cdot \left(\sqrt{d_{a1}^2 - d_{b1}^2} + \sqrt{d_{a2}^2 - d_{b2}^2} \right) - a \cdot \sin \alpha_{wt} \quad g_{\alpha} = 21,623 \text{ mm}$$

Coordinates of the basic points (A, AB, B, C, D, DE, E) on the line of action:

$$g_A = 0 \text{ mm} \quad (32) \quad g_A = 0 \text{ mm}$$

$$g_{AB} = \frac{g_{\alpha} - p_{et}}{2} \quad (33) \quad g_{AB} = 3,813 \text{ mm}$$

$$g_B = g_{\alpha} - p_{et} \quad (34) \quad g_B = 7,626 \text{ mm}$$

$$g_C = \frac{d_{b1}}{2} \cdot \tan \alpha_{wt} - \sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} + g_{\alpha} \quad (35) \quad g_C = 10,832 \text{ mm}$$

$$g_D = p_{et} \quad (36) \quad g_D = 13,997 \text{ mm}$$

$$g_{DE} = \frac{g_{\alpha} - p_{et}}{2} + p_{et} \quad (37) \quad g_{DE} = 17,810 \text{ mm}$$

$$g_E = g_{\alpha} \quad (38) \quad g_E = 21,623 \text{ mm}$$

$$d_{A1} = 2 \cdot \sqrt{\frac{d_{b1}^2}{4} + \left(\sqrt{\frac{d_{a1}^2}{4} - \frac{d_{b1}^2}{4}} - g_{\alpha} + g_A \right)^2} \quad (39) \quad d_{A1} = 151,162 \text{ mm}$$

$$d_{AB1} = 153,115 \text{ mm} \quad d_{B1} = 155,417 \text{ mm} \quad d_{C1} = 157,612 \text{ mm}$$

$$d_{D1} = 160,002 \text{ mm} \quad d_{DE1} = 163,161 \text{ mm} \quad d_{E1} = 166,610 \text{ mm}$$

$$d_{A2} = 2 \cdot \sqrt{\frac{d_{b2}^2}{4} + \left(\sqrt{\frac{d_{a2}^2}{4} - \frac{d_{b2}^2}{4}} - g_{\alpha} \right)^2} \quad (40) \quad d_{A2} = 171,390 \text{ mm}$$

$$d_{AB2} = 167,957 \text{ mm} \quad d_{B2} = 164,807 \text{ mm} \quad d_{C2} = 162,388 \text{ mm}$$

$$d_{D2} = 160,216 \text{ mm} \quad d_{DE2} = 157,897 \text{ mm} \quad d_{E2} = 155,916 \text{ mm}$$

Normal radius of relative curvature:

$$\rho_{n,A} = \frac{\rho_{t,A}}{\cos \beta_b} \quad (43) \quad \rho_{n,A} = 12,869 \text{ mm}$$

$$\rho_{n,AB} = 14,173 \text{ mm} \quad \rho_{n,B} = 14,945 \text{ mm} \quad \rho_{n,C} = 15,183 \text{ mm}$$

$$\rho_{n,D} = 15,050 \text{ mm} \quad \rho_{n,DE} = 14,403 \text{ mm} \quad \rho_{n,E} = 13,225 \text{ mm}$$

5.4.3.2 Calculation of material data

$$E_r = 2 \cdot \left(\frac{1 - \nu_1^2}{E_1} + \frac{1 - \nu_2^2}{E_2} \right)^{-1} \quad (6) \quad E_r = 226\,374 \text{ N/mm}^2$$

$$B_{M1} = \sqrt{\lambda_{M1} \cdot \rho_{M1} \cdot c_{M1}} \quad (81) \quad B_{M1} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

$$B_{M2} = \sqrt{\lambda_{M2} \cdot \rho_{M2} \cdot c_{M2}} \quad (82) \quad B_{M2} = 12\,427,4 \text{ N/(ms}^{0,5}\text{K)}$$

5.4.3.3 Calculation of operating conditions

Loading:

$$P = 2 \cdot \pi \cdot \frac{n_1}{60} \cdot \frac{T_1}{1\,000} \quad (84) \quad P = 1\,257 \text{ kW}$$

$$F_t = 2\,000 \cdot \frac{T_1}{d_1} \quad F_t = 50\,758 \text{ N}$$

$$F_{bt} = 2\,000 \cdot \frac{T_1}{d_{b1}} \quad F_{bt} = 54\,413 \text{ N}$$

Local sharing factor:

NOTE Helical gears, $0,8 < \varepsilon_\beta < 1,2$, unmodified profile (see ISO/TS 6336-22:2018, 11.9).

$$X_A(\varepsilon_\beta = 0,8) = \left(\frac{1}{3} \right) \cdot X_{\text{but},A} \quad (44) \quad X_A(\varepsilon_\beta = 0,8) = 0,413$$

$$[X_{\text{but},A}(\varepsilon_\beta = 0,8) = 1,24]$$

$$X_{AB}(\varepsilon_\beta = 0,8) = 0,5$$

$$X_B(\varepsilon_\beta = 0,8) = 1$$

$$X_C(\varepsilon_\beta = 0,8) = 1$$

$$[X_{\text{but},AB}(\varepsilon_\beta = 0,8) = 1,0]$$

$$[X_{\text{but},B}(\varepsilon_\beta = 0,8) = 1,0]$$

$$[X_{\text{but},C}(\varepsilon_\beta = 0,8) = 1,0]$$

$$X_D(\varepsilon_\beta = 0,8) = 1$$

$$X_{DE}(\varepsilon_\beta = 0,8) = 0,5$$

$$X_E(\varepsilon_\beta = 0,8) = 0,413$$

$$[X_{\text{but},D}(\varepsilon_\beta = 0,8) = 1,0]$$

$$[X_{\text{but},DE}(\varepsilon_\beta = 0,8) = 1,0]$$

$$[X_{\text{but},E}(\varepsilon_\beta = 0,8) = 1,24]$$

$$X_A(\varepsilon_\beta = 1,2) = \frac{1}{\varepsilon_\alpha} \cdot X_{\text{but},A} \quad (67)$$

$$X_A(\varepsilon_\beta = 1,2) = 0,841$$

$$[X_{\text{but},A}(\varepsilon_\beta = 1,2) = 1,3]$$

$$X_{AB}(\varepsilon_\beta = 1,2) = 1,0$$

$$X_B(\varepsilon_\beta = 1,2) = 0,647$$

$$X_C(\varepsilon_\beta = 1,2) = 0,647$$

$$[X_{\text{but},AB}(\varepsilon_\beta = 1,2) = 1,0]$$

$$[X_{\text{but},B}(\varepsilon_\beta = 1,2) = 1,0]$$

$$[X_{\text{but},C}(\varepsilon_\beta = 1,2) = 1,0]$$

$$X_D(\varepsilon_\beta = 1,2) = 0,647$$

$$X_{DE}(\varepsilon_\beta = 1,2) = 0,647$$

$$X_E(\varepsilon_\beta = 1,2) = 0,841$$

$$[X_{\text{but},D}(\varepsilon_\beta = 1,2) = 1,0]$$

$$[X_{\text{but},DE}(\varepsilon_\beta = 1,2) = 1,0]$$

$$[X_{\text{but},E}(\varepsilon_\beta = 1,2) = 1,3]$$

$$X_A = X_A(\varepsilon_\beta = 0,8) \cdot \frac{1,2 - \varepsilon_\beta}{0,4} + X_A(\varepsilon_\beta = 1,2) \cdot \frac{\varepsilon_\beta - 0,8}{0,4} \quad (77) \quad X_A = 0,673$$

$$X_{AB} = 0,589 \quad X_B = 0,786 \quad X_C = 0,786$$

$$X_D = 0,786 \quad X_{DE} = 0,589 \quad X_E = 0,673$$

Elasticity factor:

$$Z_E = \sqrt{\frac{E_r}{2 \cdot \pi}} \quad (26) \quad Z_E = 189,812 \left(\text{N/mm}^2 \right)^{0,5}$$

Local Hertzian contact stress:

$$p_{H,A,B} = Z_E \cdot \sqrt{\frac{F_t \cdot X_A}{b \cdot \rho_{n,A} \cdot \cos \alpha_t}} \quad (25) \quad p_{H,A,B} = 1\,527 \text{ N/mm}^2$$

$$p_{H,AB,B} = 1\,361 \text{ N/mm}^2 \quad p_{H,B,B} = 1\,531 \text{ N/mm}^2 \quad p_{H,C,B} = 1\,519 \text{ N/mm}^2$$

$$p_{H,D,B} = 1\,525 \text{ N/mm}^2 \quad p_{H,DE,B} = 1\,350 \text{ N/mm}^2 \quad p_{H,E,B} = 1\,506 \text{ N/mm}^2$$

$$p_{\text{dyn},A,B} = p_{H,A,B} \cdot \sqrt{K_A \cdot K_\gamma \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta}} \quad (24) \quad p_{\text{dyn},A,B} = 1\,641 \text{ N/mm}^2$$

$$p_{\text{dyn},AB,B} = 1\,463 \text{ N/mm}^2 \quad p_{\text{dyn},B,B} = 1\,645 \text{ N/mm}^2 \quad p_{\text{dyn},C,B} = 1\,632 \text{ N/mm}^2$$

$$p_{\text{dyn},D,B} = 1\,639 \text{ N/mm}^2 \quad p_{\text{dyn},DE,B} = 1\,451 \text{ N/mm}^2 \quad p_{\text{dyn},E,B} = 1\,619 \text{ N/mm}^2$$

Velocity:

$$v_{g,A} = v_{r1,A} - v_{r2,A} \quad (80) \quad v_{g,A} = -6,706 \text{ m/s}$$

$$v_{g,AB} = -4,345 \text{ m/s} \quad v_{g,B} = -1,984 \text{ m/s} \quad v_{g,C} = 0 \text{ m/s}$$

$$v_{g,D} = 1,959 \text{ m/s} \quad v_{g,DE} = 4,320 \text{ m/s} \quad v_{g,E} = 6,681 \text{ m/s}$$

$$v_{\Sigma,A} = v_{r1,A} + v_{r2,A} \quad (13) \quad v_{\Sigma,A} = 17,743 \text{ m/s}$$

$$v_{\Sigma,AB} = 17,778 \text{ m/s} \quad v_{\Sigma,B} = 17,813 \text{ m/s} \quad v_{\Sigma,C} = 17,843 \text{ m/s}$$

$$v_{\Sigma,D} = 17,872 \text{ m/s} \quad v_{\Sigma,DE} = 17,907 \text{ m/s} \quad v_{\Sigma,E} = 17,942 \text{ m/s}$$

Effective arithmetic mean roughness value:

$$Ra = 0,5 \cdot (Ra_1 + Ra_2) \quad (3) \quad Ra = 0,45 \mu\text{m}$$

5.4.3.4 Calculation of lubricant data

$X_L = 1,0$ for mineral oil (see ISO/TS 6336-22:2018, Table 4)

$$\alpha_{38} = 2,657 \cdot 10^{-8} \cdot \eta_{38}^{0,134} \quad (9) \quad \alpha_{38} = 1,88 \cdot 10^{-8} \text{ m}^2 / \text{N}$$

$X_S = 1,2$ for injection lubrication

$$A = \frac{\log \left[\frac{\log(v_{40} + 0,7)}{\log(v_{100} + 0,7)} \right]}{\log \left(\frac{313}{373} \right)} \quad (18) \quad A = -3,978$$

$$B = \log \left[\log(v_{40} + 0,7) \right] - A \cdot \log(313) \quad (19) \quad B = 10,204$$

5.4.3.5 Calculation of the material parameter

Mean coefficient of friction:

$$X_R = 2,2 \cdot \left(\frac{Ra}{\rho_{n,C}} \right)^{0,25} \quad (86) \quad X_R = 0,913$$

$K_{B\gamma} = 1,238$ for $2 < \varepsilon_\gamma < 3,5$

$$\mu_m = 0,045 \cdot \left(\frac{K_A \cdot K_v \cdot K_{H\alpha} \cdot K_{H\beta} \cdot F_{bt} \cdot K_{B\gamma}}{b \cdot v_{\Sigma,C} \cdot \rho_{n,C}} \right)^{0,2} \cdot (10^3 \cdot \eta_{\theta_{oil}})^{-0,05} \cdot X_R \cdot X_L \quad (85) \quad \mu_m = 0,054$$

Bulk temperature:

$$H_v = (\varepsilon_1^2 + \varepsilon_2^2 + 1 - \varepsilon_\alpha) \cdot \left(\frac{1}{z_1} + \frac{1}{z_2} \right) \cdot \frac{\pi}{\cos \beta_b} \quad \text{for } \varepsilon_\alpha < 2 \quad (90) \quad H_v = 0,128$$

$$\varepsilon_{\max} = \varepsilon_2$$

$$X_{Ca} = 1,0 \quad \text{for no adequate profile modification (method B)} \quad (99)$$

$$\theta_M = \theta_{oil} + 7\,400 \cdot \left(\frac{P \cdot \mu_m \cdot H_v}{a \cdot b} \right)^{0,72} \cdot \frac{X_S}{1,2 \cdot X_{Ca}} \quad (83) \quad \theta_M = 149,3 \text{ } ^\circ\text{C}$$

Material parameter:

$$G_M = 10^6 \cdot \alpha_{\theta_M} \cdot E_r \quad (5) \quad G_M = 2\,388,2$$

5.4.3.6 Calculation of the dynamic viscosity at bulk temperature

$$\log[\log(v_{\theta M} + 0,7)] = A \cdot \log(\theta_M + 273) + B \quad (17) \quad v_{\theta M} = 3,044 \text{ mm}^2 / \text{s}$$

$$\rho_{\theta M} = \rho_{15} \cdot \left[1 - 0,7 \cdot \frac{(\theta_M + 273) - 288}{\rho_{15}} \right] \quad (20) \quad \rho_{\theta M} = 801,0 \text{ kg} / \text{m}^3$$

$$\eta_{\theta M} = 10^{-6} \cdot v_{\theta M} \cdot \rho_{\theta M} \quad (16) \quad \eta_{\theta M} = 2,438 \cdot 10^{-3} \text{ Ns} / \text{m}^2$$

5.4.3.7 Calculation of the velocity parameter

$$U_A = \eta_{\theta M} \cdot \frac{v_{\Sigma,A}}{2\,000 \cdot E_r \cdot \rho_{n,A}} \quad (12) \quad U_A = 7,424 \cdot 10^{-12}$$

$$U_{AB} = 6,754 \cdot 10^{-12} \quad U_B = 6,418 \cdot 10^{-12} \quad U_C = 6,328 \cdot 10^{-12}$$

$$U_D = 6,394 \cdot 10^{-12} \quad U_{DE} = 6,695 \cdot 10^{-12} \quad U_E = 7,305 \cdot 10^{-12}$$

5.4.3.8 Calculation of the load parameter

$$W_A = \frac{2 \cdot \pi \cdot p_{dyn,A}^2}{E_r^2} \quad (22) \quad W_A = 3,302 \cdot 10^{-4}$$

$$W_{AB} = 2,624 \cdot 10^{-4} \quad W_B = 3,318 \cdot 10^{-4} \quad W_C = 3,266 \cdot 10^{-4}$$

$$W_D = 3,295 \cdot 10^{-4} \quad W_{DE} = 2,582 \cdot 10^{-4} \quad W_E = 3,213 \cdot 10^{-4}$$

5.4.3.9 Calculation of the sliding parameter

Load flash temperature:

$$\theta_{fl,A} = \frac{\sqrt{\pi}}{2} \cdot \frac{10^6 \cdot \mu_m \cdot p_{dyn,A} \cdot |v_{g,A}|}{B_{M1} \sqrt{v_{r1,A}} + B_{M2} \sqrt{v_{r2,A}}} \cdot \sqrt{8 \cdot \rho_{n,A} \cdot \frac{p_{dyn,A}}{1\,000 \cdot E_r}} \quad (79) \quad \theta_{fl,A} = 196,6 \text{ }^\circ\text{C}$$

$$\theta_{fl,AB} = 111,2 \text{ }^\circ\text{C} \quad \theta_{fl,B} = 61,7 \text{ }^\circ\text{C} \quad \theta_{fl,C} = 0 \text{ }^\circ\text{C}$$

$$\theta_{fl,D} = 60,7 \text{ }^\circ\text{C} \quad \theta_{fl,DE} = 109,7 \text{ }^\circ\text{C} \quad \theta_{fl,E} = 193,4 \text{ }^\circ\text{C}$$

Local contact temperature as sum of bulk and local flash temperature:

$$\theta_{B,A} = \theta_M + \theta_{fl,A} \quad (78) \quad \theta_{B,A} = 346,0 \text{ }^\circ\text{C}$$

$$\theta_{B,AB} = 260,5 \text{ }^\circ\text{C} \quad \theta_{B,B} = 211,0 \text{ }^\circ\text{C} \quad \theta_{B,C} = 149,3 \text{ }^\circ\text{C}$$

$$\theta_{B,D} = 210,1 \text{ }^\circ\text{C} \quad \theta_{B,DE} = 259,0 \text{ }^\circ\text{C} \quad \theta_{B,E} = 342,7 \text{ }^\circ\text{C}$$

Local sliding parameter:

$$S_{GF,A} = \frac{\alpha_{\theta,B,A} \cdot \eta_{\theta B,A}}{\alpha_{\theta M} \cdot \eta_{\theta M}} \quad (27) \quad S_{GF,A} = 0,054$$

$$S_{GF,AB} = 0,160 \quad S_{GF,B} = 0,327 \quad S_{GF,C} = 1,000$$

$$S_{GF,D} = 0,332 \quad S_{GF,DE} = 0,163 \quad S_{GF,E} = 0,056$$

5.4.3.10 Calculation of the lubricant film thickness

$$h_A = 1\,600 \cdot \rho_{n,A} \cdot G_M^{0,6} \cdot U_A^{0,7} \cdot W_A^{-0,13} \cdot S_{GF,A}^{0,22} \quad (4) \quad h_A = 0,053 \, \mu\text{m}$$

$$h_{AB} = 0,071 \, \mu\text{m} \quad h_B = 0,082 \, \mu\text{m} \quad h_C = 0,106 \, \mu\text{m}$$

$$h_D = 0,083 \, \mu\text{m} \quad h_{DE} = 0,073 \, \mu\text{m} \quad h_E = 0,054 \, \mu\text{m}$$

5.4.3.11 Calculation of the specific lubricant film thickness

$$\lambda_{GF,A} = \frac{h_A}{Ra} \quad (2) \quad \lambda_{GF,A} = 0,117$$

$$\lambda_{GF,AB} = 0,159 \quad \lambda_{GF,B} = 0,183 \quad \lambda_{GF,C} = 0,236$$

$$\lambda_{GF,D} = 0,185 \quad \lambda_{GF,DE} = 0,161 \quad \lambda_{GF,E} = 0,121$$

$$\lambda_{GF,\min} = \lambda_{GF,A} = \lambda_{GF,E} \quad \lambda_{GF,\min} = 0,117$$

5.4.3.12 Calculation of the micropitting safety factor

$$S_\lambda = \frac{\lambda_{GF,\min}}{\lambda_{GFP}} \quad (1) \quad S_\lambda = 1,044$$

The final results for the calculation of the safety factor against micropitting, S_λ , for Example 3 are shown in [Table 12](#).

Table 12 — Results of the calculation according to method B — Example 3

| Point | A | AB | B | C | D | DE | E |
|---------------------|--------------|-------|-------|-------|-------|-------|-------|
| $\lambda_{GF,Y}$ | 0,117 | 0,159 | 0,183 | 0,236 | 0,185 | 0,161 | 0,121 |
| $\lambda_{GF,\min}$ | 0,117 | | | | | | |
| λ_{GFP} | 0,112 | | | | | | |
| S_λ | 1,044 | | | | | | |

5.4.4 Calculation according to method A

The calculation of Example 3 according to method A was carried out by a 3D-calculation programme. Calculated results during method A vary depending on the method of determining load distribution. The load distribution, on which the following calculation according to method A is based, is shown in [Table 13](#). The maximum values are printed in bold.

Table 13 — Matrix of pressure distribution $p_{H,Y,A}$ in N/mm²

| | Width in mm | | | |
|-----------|--------------|-------|-------|--------------|
| | 0,0 | 15,5 | 28,5 | 44,0 |
| A | 1 205 | 768 | 742 | 384 |
| AB | 1 572 | 1 456 | 1 457 | 1 273 |
| B | 1 568 | 1 560 | 1 550 | 1 589 |
| C | 1 518 | 1 510 | 1 530 | 1 582 |
| D | 1 516 | 1 529 | 1 574 | 1 621 |
| DE | 1 192 | 1 423 | 1 454 | 1 623 |
| E | 250 | 655 | 765 | 1 513 |

The resulting matrix of specific lubricant film thickness according to method A is shown in [Table 14](#). The minimum value is printed in bold.

Table 14 — Matrix of resulting specific lubricant film thickness, $\lambda_{GF,Y}$

| | Width in mm | | | |
|-----------|-------------|--------------|--------------|--------------|
| | 0,0 | 15,5 | 28,5 | 44,0 |
| A | 0,198 | 0,274 | 0,280 | 0,391 |
| AB | 0,191 | 0,203 | 0,203 | 0,225 |
| B | 0,244 | 0,245 | 0,246 | 0,242 |
| C | 0,323 | 0,324 | 0,323 | 0,320 |
| D | 0,251 | 0,250 | 0,245 | 0,241 |
| DE | 0,238 | 0,209 | 0,205 | 0,188 |
| E | 0,467 | 0,306 | 0,279 | 0,163 |

For the calculation of the micropitting safety factor according to method A, the minimum value of the matrix of resulting specific lubricant film thickness, shown in [Table 14](#), was used.

$$S_{\lambda} = \frac{\lambda_{GF,min}}{\lambda_{GFP}} \qquad S_{\lambda} = 1,124$$

NOTE The difference in safety factor calculated between methods A and B in the above Example 3 results from the simplified analysis of method B, in relation to the account for profile modification. In Example 3, the amount of tip relief is not calculated as being optimum for the specified load; therefore, the calculations for method B are based on contact conditions with no consideration for tip relief.

5.5 Example 4 Speed increaser

5.5.1 General

The result of this example is confirmed by experimental investigations. The gears were obviously micropitted and had profile deviations of approximately 12 μm (pinion) and 3 μm (wheel). [Figure 3](#) shows a diagram of the observed location and severity of micropitting for pinion and wheel of Example 4.

NOTE In Example 4, the wheel is the driving gear, so that the beginning of tooth contact in this example is at the root of the wheel, point E.