
**Textile floor coverings — State of the
art on maintenance and cleaning**

*Revêtements de sol textiles — Etat de l'art relatives à l'entretien et au
nettoyage*

STANDARDSISO.COM : Click to view the full PDF of ISO/TS 21868:2023



STANDARDSISO.COM : Click to view the full PDF of ISO/TS 21868:2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword.....	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Maintenance.....	2
4.1 General.....	2
4.2 Maintenance plan.....	2
5 Cleaning.....	3
5.1 General.....	3
5.2 The principle of cleaning.....	3
5.3 Personnel training.....	3
5.4 Cleaning Steps.....	3
5.4.1 Identification.....	3
5.4.2 Formulating a cleaning programme.....	6
5.4.3 Inspection of equipment.....	6
5.4.4 Protection of surroundings, the environment and human beings.....	6
5.5 Inspection of cleaning results and relevant standards.....	7
5.5.1 Evaluation of external quality of cleaning.....	7
5.5.2 Evaluation of internal quality of cleaning.....	7
Annex A (informative) Method of maintenance and cleaning.....	8
Bibliography.....	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 219, *Floor coverings*.

This second edition cancels and replaces the first edition (ISO/TS 21868:2021), which has been technically revised.

The main changes are as follows:

- clarifications to the terms and definitions were added;
- clarifications to the requirements were added;
- [Table 1](#) “Fibre identification burn test” was deleted.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document is designed for legislators, related enterprise associations, textile floor coverings manufacturers, and textile floor covering maintenance and cleaning enterprises to develop their own specific textile floor covering maintenance or/and cleaning standards or procedures in accordance with the local conditions. Due to diversity of different regions in climates, customs and developing levels in the world, it is extremely difficult to create a specific textile floor covering maintenance and cleaning standard as a template which is globally workable. In addition, the factors which impact the result of cleaning are so abundant and the combinations of these factors are so tremendous that particular programmes are necessary to acquire the best result of textile floor covering cleaning.

This guidance standard manages to list all the factors which affect the final results of cleaning, against which legislators, relative enterprises associations and textile floor covering maintenance and cleaning enterprises are able to establish the above-mentioned particular programmes (procedures or criteria) in their standards accordingly. Therefore, this standard is not intended to be used by end-users to perform any specific maintenance and cleaning jobs.

This comprehensive guidance standard is intended to pave the way for legislators and related enterprise associations to establish specific standards for:

- regulating the development of the textile floor covering cleaning industry,
- promoting the development of the textile floor covering cleaning detergent and equipment industry,
- improving textile floor covering cleaning techniques, and
- improving sales of textile floor coverings,

since specific textile floor covering maintenance and cleaning standards are still absent in most nations.

NOTE The term "textile floor coverings" applies to wall-to-wall carpets, broadloom carpets, rugs, mat and tile carpets.

STANDARDSISO.COM : Click to view the full PDF of ISO/TS 21868:2023

Textile floor coverings — State of the art on maintenance and cleaning

1 Scope

This document gives guidelines for the development of specific textile floor covering maintenance and cleaning standards, procedures and criteria to reflect local specific conditions. This document specifies the factors which will impact the final results of textile floor covering cleaning, defining maintenance and cleaning terms to highlight differences. It establishes textile floor covering maintenance and cleaning as achieving a low-cost, non-residue and environmentally friendly cleaning under the premise of maximizing the use value of textile floor covering.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

soil

any matter that is foreign to the construction of the textile floor covering

Note 1 to entry: Soil includes spill, spot, stain, and residue.

3.2

spill

wet, dry, oily or combination states of matter that are accidentally deposited on the textile floor covering

Note 1 to entry: Depending on the composition of the spill, quick response time and cleaning procedures can assist in minimizing the probability of a spill becoming a spot or a stain.

3.3

spot

foreign material on the surface of a fibre, usually changing the texture of the fibre

EXAMPLE Sticky, oily, greasy, stiff.

Note 1 to entry: Spots can usually be removed. However, some spots, if left untreated for too long, can become stains.

3.4

stain

indication of the addition of colour, frequently in liquid or pigment form that has been strongly attracted to the textile floor covering fibre

Note 1 to entry: This added dye or pigment can bind to a dye site and actually alter the structure of the fibre. Not all stains respond positively to removal efforts.

**3.5
residue**

the foreign materials left in the cleaned textile floor coverings, which is originated from the detergents

**3.6
interim cleaning**

removal of topical appearance soil from textile flooring and return of the textile floor covering to a dry and usable state within a short period of time

**3.7
restorative cleaning**

thorough removal of soil both on the textile floor covering surface and embedded within the textile floor covering construction

4 Maintenance

4.1 General

Maintenance is the protection of textile floor coverings, vacuuming and timely removal of spills and dust which can be operated by non-professionals. Textile floor covering maintenance requires a user to develop a maintenance programme, which can be provided with the help of the textile floor covering manufacturer or provided or assisted by a contracted textile floor covering cleaner.

The significance of textile floor covering maintenance is that it is the first key step in extending the service life of the textile floor covering, and the simplest and most economical and effective means of preventing the textile floor covering from being soiled.

4.2 Maintenance plan

The maintenance plan shall include:

- Laying of door mats, which are for scraping soil and absorbing moisture. Pay attention to the length of door mats to prevent people from stepping over them. If necessary, a reminder for scraping shoes is recommended in case the door mat is too small.
- Timely removal of spills.
- Division of the textile floor coverings regions based on varying traffic frequency and varying functions to formulate a vacuum cycle accordingly.
- Protection of the textile floor coverings during the laying and maintenance of other flooring materials and furniture nearby.
- Provision of temporary or permanent convenient bins and ashtrays in special function areas.
- Controlling the dehumidification equipment to maintain the necessary dryness to prevent the room from developing mildew.

The maintenance plan is a program for end-users to follow in order to keep the textile floor coverings in good conditions and pave the way for necessary cleaning. For residential use textile floor coverings, it shall be provided by manufacturers. For commercial use textile floor coverings, it shall be discussed and, when customizing the textile floor coverings with the assistance of the textile floor coverings manufacturer or professional textile floor coverings cleaner, made to match the overall interior space designing.

5 Cleaning

5.1 General

Cleaning is the process of locating, identifying, containing, removing and properly disposing of soil, performed by professionals with professional equipment and under standard programmes.

Cleaning requires professional personnel and equipment to be implemented in accordance with professional programmes. Either interim cleaning or restorative cleaning, professional personnel, professional equipment and conformant procedures are necessary. Cleaning is mostly likely to be conducted by an independent service provider, either a professional cleaning service company or a manufacturer, other than the user, unless the user keeps a professional team with professional equipment, cleaning agents and professional programmes.

5.2 The principle of cleaning

The principles of cleaning are:

- Restoring the use value of textile floor coverings.
- Green environmental protection before and after cleaning.
- Having practices which are harmless to practitioners and users.
- Maintaining or restoring special properties attached to textile floor coverings: including but not limited to fire proof post-treatment and anti-static post-treatment.

At the same time, it shall be clear that cleaning a textile floor covering is not to transform the textile floor covering into a new one, but to remove the soil on the textile floor covering as completely as possible, and if necessary, repairs may be performed. Even after professional cleaning, it is possible that it will not be possible to reverse all damage due to permanent changes to colour or fibre.

5.3 Personnel training

Qualified and professional personnel are prerequisites for ensuring cleaning quality, cleaning personnel safety and environmental protection. Cleaning personnel shall be professionally trained by a professional company or organization before going on duty. The training shall cover not only cleaning, but also textile floor covering quality, laying and repairing.

5.4 Cleaning Steps

5.4.1 Identification

5.4.1.1 General

Identification is the most important step in a textile floor covering cleaning process and a complete identification of the factors which affect the cleaning result is required for the development of cleaning standards or individual cleaning programmes.

5.4.1.2 Identification of textile floor covering appearance and defects

Observe the overall state of the textile floor covering appearance and search for defects. Locate the spills, spots and stains. Ask the textile floor covering user about the textile floor covering laying time, the time and manner of the previous cleanings, and ask the textile floor covering user for a textile floor coverings maintenance programme and its relative execution record if the user has this, in order to determine roughly how to clean it.

5.4.1.3 Identification of textile floor covering laying quality

The laying quality defects mentioned below will directly lead to defects in cleaning results:

- a) If the textile floor covering is not stretched tightly and results in surface wrinkles, during the cleaning process, the textile floor covering surface can show watermark and shadow after cleaning and even damage to part of the textile floor covering pile.
- b) If the edge of the textile floor covering is unevenly trimmed, leading to burrs, during the cleaning process, the pile can be pulled out, seriously damaging the textile floor covering.
- c) If the textile floor covering is not fixed firmly, during the cleaning process, the textile floor covering can shrink and cause crevices.
- d) If the textile floor covering is not spliced strongly, the textile floor covering seam(s) will crack after drying.

5.4.1.4 Identification of the textile floor covering surroundings

Identify adjacent furniture, equipment, floor coverings and the building itself to avoid any damage, harm or electric shock when on-site cleaning is conducted.

5.4.1.5 Identification of climate and season

Identifying local climate and seasons is necessary to restore the qualified water content of the textile floor covering after cleaning in time.

5.4.1.6 Identification of special textile floor covering function

Determine whether the textile floor covering has special functions in a functional area. Post-treatment of fire-proof and anti-static functions shall be maintained or restored after cleaning. Special attention shall be drawn to these special locations, such as laboratories, hospitals, workshops for electronic devices and elevators, as well as certain special functional areas of a hotel. For example, static electricity can damage elevators; being fire-proof can be a requirement for an area in a hotel where smoking is permitted permanently or temporarily.

5.4.1.7 Identification of product quality

- a) Ask textile floor covering users for product label(s) and cleaning instruction(s) from textile floor covering(s) manufacturer(s).
- b) Determine the material(s) of the textile floor covering pile, the type(s) of pile, the length of pile, the pile weight.
- c) Determine the structure of the textile floor covering formation: hand-knotted, hand-tufted, semi-handmade, machine made, etc.
- d) Determine whether the formation of textile floor coverings and the adhesive (if any) adapts to washing, and the times of washing.
- e) Determine the physical and chemical properties of the base materials.
- f) Determine if there are post-treatments, such as fireproof post-treatment and/or anti-static post-treatment, to ensure that cleaning does not compromise the special properties, or completely restore these properties by reprocessing the post treatments.

5.4.1.8 Identification of the cleaning objectives

- a) Appearance identification method: identify the material by observing the appearance of the soil, for example: various food juices, paint stains, etc.

- b) Colour identification method: Identify the material by unique colour of the soil, such as ink, dye, paint, blood stains, etc.
- c) Sensory identification method: Identify the material by hand feeling and observation, such as sugar stains and glue. This can rely on the accumulation of long-term experience and knowledge.
- d) Location identification method: Identify soil based on its location.
- e) Odour identification method: Identify soil based on the unique smell of soil, such as perfume, wine, chewing gum, etc.
- f) Chemical testing: For particularly expensive textile floor coverings, laboratory chemical methods may be used for identification if necessary.
- g) Ask for the customs of using textile floor covering; in case of close touch with human being, especially with bare skin, inactivation is necessary.
- h) Ask the user about the history of cleaning and identify whether it is necessary to remove the residue from previous cleanings.

It is necessary to identify the states of soil according to the classification of the three types defined above, i.e., spill, spot and stain. Spill, spot and stain removal chemicals shall be of a type that do not harm textile floor coverings when used in accordance with the chemical manufacturer’s recommendations.

See [Table 1](#) for the types of soil and the applicable detergent categories of disposal.

Table 1 — Soil guide

	Acid Detergent	Neutral Detergent	Alkaline Detergent	Citrus Detergent	Oxidizer	Enzyme Detergent	Rust Remover	Dry Vacuum
Blood		①			②		③	
Browning (cellulosic)	①				②			
Chewing gum				①				
Coffee	②	①		⑤	④	③		
Cola	①					②		
Copler toner					④			①②③
Grease and oil				①				
Ice melt build up	②							①
Ink (waterbased)			①	②	③			
Marker				①	②			
Milk						①		
Mustard	②	①			④	③		
Nail polish	②			①	③			
Paint (oil-based)				①	②			
Paint (latex)		②		①				
Rust			②				①	
Urine	①				③	②		
Vomit			①		③	②		

① Step One ② Step Two (if necessary) ③ Step Three (if necessary) ④ Step Four (if necessary) ⑤ Step Five (if necessary)

CAUTION: Textile floor covering cleaning and maintenance enterprises shall fix specific formula and concentration after identifying product quality and cleaning objectives to ensure no harm to the textile floor covering, cleaning practitioners and environment. If detergents are purchased from detergent suppliers, textile floor covering cleaning and maintenance enterprises shall follow the instructions for that detergent. If necessary, a test on a small part of the textile floor covering shall be performed prior to the cleaning operation to ensure the safety and applicability of the detergent.

5.4.1.9 Identification of allergy patient and weak human beings

For allergy patients or vulnerable human beings in hospital, kindergarten, baby nursing homes and senior nursing centres, less chemical detergent usage for least residue, no residue, and inactivation shall have to be considered. For allergy patients, the relative allergens shall be clarified before cleaning to avoid exposure to any allergenic chemical detergent and/or thorough inactivation of the allergenic living organism shall be carried out, to protect users' health and safety. No residue can be carried out by no use of detergents but water.

5.4.1.10 Note and confirmation

The above identifications should be recorded. In particular, the results of laying quality defects and other textile floor covering defect identifications as well as the results of soil identification shall be confirmed by the textile floor covering user.

5.4.2 Formulating a cleaning programme

The programme for cleaning equipment, detergent, techniques and processes will be made based on the aforementioned identification of textile floor covering appearance, laying quality, laying environments, climates and seasons, textile floor coverings special functions, textile floor coverings qualities, type of soil and allergy patients and vulnerable human beings. This document introduces existing cleaning methods in the market for reference in [Annex A](#).

Attention shall be drawn that not all cleaning methods mentioned in [Annex A](#) are suitable for all textile floor coverings. Concerning the application of a specific cleaning process, follow the steps stipulated in [5.4.1.6](#) to avoid damage to the textile floor coverings.

However, this document does not constitute any endorsement of these methods. The maximum recovery of textile floor coverings using good-value, low-cost, non-residue, green environmental cleaning methods and processes is the future development direction identified by this document.

Textile floor covering fibres are chemically sensitive and are easily damaged by chemicals or excessive agitation. Regardless of the cleaning of spots and stains, attention should be paid to the cleaning method and chemical selection. Before starting the operation, select inconspicuous areas and conduct small-scale trial tests on all materials and colours of textile floor covering pile to determine whether the selected method and chemical substance is applicable.

Before cleaning operation, cleaning enterprises practitioners shall review the above-mentioned notes to form a cleaning programme including a checklist of key points to make sure no issue is forgotten, especially the post-treatment(s) if it exists or they exist.

5.4.3 Inspection of equipment

Qualified and well-functioning equipment is necessary to ensure the safety of the cleaning process, environmental protection and personnel safety as well as the cleaning results. Equipment testing procedures shall follow the testing and usage procedures provided by the equipment manufacturer.

5.4.4 Protection of surroundings, the environment and human beings

Cleaning shall be in accordance with the following requirements:

- It shall not damage the quality of furniture, equipment, buildings or air quality in the textile floor coverings furnishings space.
- Recycling and treatment of sewage shall not harm the environment.
- The detergent, waste water and waste gases produced in the cleaning process shall not be harmful to the operators, nearby personnel and the following users.

5.5 Inspection of cleaning results and relevant standards

5.5.1 Evaluation of external quality of cleaning

- a) Appearance recovery: including colour recovery, pile direction recovery and original elastic recovery, disappearance or significant reduction of soil.
- b) Textile floor coverings integrity: no deformation, no shrinkage, no wrinkle, no cracks, no watermark, no discoloration, no decolourization, no degumming, no odour, no pile shedding, no hardening, no sticky feeling, no greasy feeling, no mildew and no pile direction mess.

5.5.2 Evaluation of internal quality of cleaning

- a) The humidity shall be restored to 25 % at the latest 12 h after textile floor coverings cleaning to prevent odour and mildew in indoor environments with humidity control.
- b) The humidity of the environment shall also be restored to the level before the textile floor coverings are cleaned for places where strict environmental humidity is required.
- c) When detergents are applied in cleaning only a low amount of residue shall remain after cleaning, meaning that the residue cannot be seen, felt, smelt, and is not obviously released when stepped on.
- d) pH value varies from 4,0 to 7,5.
- e) The post-treatment(s) of fireproof and/or antistatic shall be restored by new treatment(s) after water cleaning. The practitioner of cleaning shall review the checklist to assure this job has been done after cleaning.
- f) Inactivation: The practitioner of cleaning shall review the checklist to assure this job will be done before cleaning. Do not recommend a lab test in case the programme of inactivation in the process of cleaning is strictly followed and noted.

Annex A (informative)

Method of maintenance and cleaning

A.1 Dry vacuuming

Effective, routine vacuuming is required for good commercial textile floor covering performance, so a proper vacuuming programme is essential in a well-designed maintenance programme. The most important aspect of a vacuuming maintenance programme is identifying high, medium and low traffic areas by continually monitoring textile floor covering performance and making any necessary adjustments to the schedule.

To protect the indoor air quality, keep all indoor surfaces as clean as possible by vacuum cleaning without putting dust back into the air. In selecting a vacuum cleaner for maximum effectiveness, use a vacuum cleaner that has adjustable and rotating brushes that are able to loosen ground-in soil, and strong enough airflow to penetrate to the backing, extracting all particles. The vacuum cleaner shall have an enclosed, high filtration bag that limits particles from re-circulating back into the air.

For the best results, no matter which type of vacuum cleaner is used, inspect it periodically to be sure it is functioning properly.

Follow the vacuum cleaner manufacturer's instructions and change the vacuum bag when it becomes more than half full. As the bag becomes full, efficiency is reduced.

Once the vacuum equipment has been selected, set a schedule for the frequency of vacuuming. Using the facility diagram, classify textile floor covering areas into high traffic, moderate traffic, and light traffic areas. High traffic areas should be vacuumed daily or more frequently as the need arises. Moderate traffic areas should be vacuumed on average two to three times a week. Light traffic areas should be vacuumed as needed or usually once a week.

Usually high traffic areas include: entrances, hallways, break rooms, cafeterias, corridors, elevator/lift lobbies, stairways, main aisles, waiting areas.

Moderate traffic areas include: Secondary aisles, research areas, classrooms, conference rooms, and atriums.

Light traffic areas include: Offices, cubicles, storage rooms, and executive areas.

Remember: Routine vacuuming is the most important part of any maintenance programme.

A.2 Interim cleaning methods

A.2.1 General

Interim cleaning usually utilises a low moisture cleaning process to remove minor soiling mostly on the surface of the textile floor covering fibre.

CAUTION — In case the property of fireproof or/and antistatic is(are) obtained by post-treatment(s). The re-treatment(s) should be done during the cleaning or after the cleaning.

A.2.2 Dry compound cleaning method

The textile floor covering should be thoroughly vacuumed prior to cleaning to remove dry soil.

In applying the dry compound, the following points are required:

- The appropriate equipment shall be on hand to suit the particular product or system.
- An adequate supply of the dry compound.
- A means of uniformly distributing the dry compound across the use-surface of the textile floor covering. Mechanical spreading devices are available commercially.
- A means of agitating the dry compound into the surface. A groomer with plastic tines is commonly used on small areas. For larger areas, special nylon bristled brushes are available which have a special fibre configuration for distributing the compound evenly within the surface and for promoting the cleansing action.
- Apply the dry compound as directed by the manufacturer and agitate it into the surface with the recommended equipment. Only a small area is required be treated at one time, commencing at the furthest point in a room and working towards the door.
- Allow the compound to dry for the period recommended by the manufacturer.
- Remove the dried compound from and within the surface with an efficient vacuum cleaner. Use of an upright vacuum cleaner fitted with an efficient power-driven brush is strongly recommended.
- Vacuum the area in one direction and then re-vacuum at right angles. Several passes of the vacuum cleaner will be needed to remove all dry compound from deep within the surface of the textile floor covering.
- Inspect the surface to ensure that the majority of the dry compound has been removed. Dry compound left within the surface can possibly subsequently absorb unwanted materials, including odorous materials, causing background odours in the cleaned area and impacted product.

In areas where soiling rapidly builds up, such as entrances, a regiment of hot water extraction and speed drying is recommended.

A.2.3 Bonnet (absorbent) pad cleaning method

The textile floor covering should be thoroughly vacuumed prior to cleaning to remove dry soil.

Although not completely dry, bonnet cleaning is considered a low moisture textile floor coverings cleaning system. The purpose of this system is to apply a cleaning agent to the textile floor covering with a soft pad or bonnet. Once the textile floor covering dries, dry vacuuming removes soils and residues.

Bonnet cleaning is accomplished by spraying a detergent solution over the face of the textile floor covering. This can be done with hand pump type sprayers, power sprayers, CO₂ (carbon dioxide) pressure tanks or specialized spray systems attached to the floor machine.

Even distribution of the cleaning agent is accomplished by using a low-speed rotary machine (175 RPM to 300 RPM), which rotates a bonnet made of cotton or other similar absorbent materials. The cleaning agent provides proper lubrication during agitation and should be used as recommended by the product manufacturer.

The soil is absorbed into the cotton pads. The cotton pads are turned over and changed or rinsed when they stop absorbing soil. They shall be thoroughly laundered prior to the next job.

Pile setting or grooming is highly recommended following bonnet cleaning to decrease drying time, remove distortion and optimize appearance. In all cases, pile setting shall be accomplished for uniform distribution if post-cleaning treatments are used.

A.2.4 Dry foam cleaning method

The textile floor covering should be thoroughly vacuumed prior to cleaning to remove dry soil.

This method is a minimum moisture method. A dense foam is produced through mechanical aeration and distributed via a mechanical brush in a specialized dry foam machine. The excess foam and suspended soil are extracted using a wet vacuum typically incorporated into the same machine.

It is advisable to pre-treat heavily soiled areas with a pre-conditioner:

- a) Following the manufacturer's label directions, a properly diluted dry foam-cleaning agent is used. The solution is aerated with mechanical agitation into a dense foam by the machine.
- b) Both pre-conditioners and the concentrated dry foam-cleaning product can be mixed with hot water increasing solution temperature and speeding soil suspension.
- c) Agitation is achieved during or immediately after the application of the dry foam. To provide proper lubrication during agitation, the product manufacturer's recommended dilutions shall be observed.
- d) A wet vacuum attached to or separate from the application machine can be used to extract excess foam with suspended soil. Additional dry vacuuming procedures can also be used after the textile floor covering has dried to extract crystallized detergent residue along with attached soil.
- e) Pile setting or grooming is highly recommended following dry foam cleaning to decrease drying times, remove distortion and optimize appearance. Usage of drying equipment is highly recommended to shorten the time of drying, if necessary, use ventilation or air conditioner to adjust air humidity.
- f) Water based shampoo that dries to a non-tacky residue is strongly recommended.

Pile setting is required if using post-cleaning treatments.

CAUTION — This cleaning process will leave high amounts of residue in the textile floor covering. Frequent usage will cause the textile floor covering to harden, change colour and smell, and will badly damage the durability of the textile floor covering.

A.2.5 Shampoo cleaning method

The textile floor covering should be thoroughly vacuumed prior to cleaning to remove dry soil.

With this method a shampoo is distributed to the floor covering either as a pre-treatment or via a solution feed during the cleaning process. The shampoo and suspended soil can be extracted by following with a wet vacuum process or by waiting for the textile floor covering to dry and using a dry vacuuming process.

The recommended equipment for agitation of a shampoo is a low-speed rotary machine (175 RPM to 300 RPM) with a "broken-in" brush designed for agitation of commercial textile floor covering.

The procedure for using this method is as follows:

- Apply a recommended dilution of shampoo and water to the textile floor covering. The rotating brush agitates the solution into the surface of the textile floor covering. A dense, wet foam shall be generated to accomplish cleaning and lubrication.

CAUTION — The textile floor covering shall be lubricated with the shampoo when using this method. Running a rotary brush on a dry textile floor covering can cause a permanent distortion of the textile floor covering face.

Immediately wet vacuum the suspended soil solution using wet vacuum equipment designed for this purpose.

Pile setting or grooming is highly recommended following shampooing to decrease drying time, remove distortion and optimize appearance. In all cases, pile setting shall be accomplished for uniform distribution if post-cleaning treatments are used. Drying equipment is highly recommended to shorten the time needed, if necessary, use ventilation and air conditioner to adjust air humidity.

CAUTION — This cleaning process will leave high amounts of residue in the textile floor covering. Frequent usage will cause the textile floor covering to harden, change colour and smell, and will badly damage the durability of the textile floor covering.

A.2.6 Encapsulation cleaning method

This method applies to textile floor covering for which the surface is comparatively clean. The textile floor covering should be thoroughly vacuumed prior to cleaning to remove dry soil.

A specialized cleaning agent is applied to the textile floor covering by spraying the detergent solution over the face of the textile floor covering. This can be accomplished with hand pump type sprayers, power sprayers, CO₂ (carbon dioxide) pressure tanks or specialized spray systems.

The encapsulating formula can also be agitated into the textile floor covering fibre with a bonnet, specialized encapsulating equipment or with a broken-in rotating brush from a low-speed rotary machine (175 RPM to 300 RPM).

Soil is dislodged and captured in the drying process and dry vacuuming removes soils and residues.

Thoroughly dry vacuum when the textile floor covering dries.

CAUTION — The textile floor covering shall be lubricated with the encapsulate formula when using this method. Running a rotary brush on a dry textile floor covering can possibly cause a permanent distortion of the textile floor covering face.

A.3 Restorative cleaning methods

A.3.1 General

Restorative cleaning is a scheduled frequent deep-cleaning process to remove deeper residues and trapped soils.

CAUTION — In case the property of fireproof or/and antistatic is(are) obtained by post-treatment(s). The re-treatment(s) should be done during the cleaning or after the cleaning.

A.3.2 Hot water extraction cleaning method

The area to be cleaned shall be thoroughly vacuumed before any type of cleaning method is used.

A pre-conditioner should be applied to the heavy traffic areas by using a pressure sprayer with a pre-mixed pre-conditioner solution prior to the application of the hot water extraction method. To avoid over wetting, follow the formulator's directions as to coverage.

Following the pre-conditioner application, agitation should be accomplished by hand brushing or mechanical brush action. Additional agitation is achieved during the injection phase using solution water pressure.

The pre-conditioner should remain on the area for approximately 10 min to 15 min (dwell time) for uniform soil suspension.

Following pre-conditioning and agitation, the soil is dislodged or flushed out of the textile floor covering with controlled jets of detergent solution (or hot water) sprayed under pressure and immediately recovered by a wet vacuum into a separate receptacle.

Multiple wet passes can be required to rinse suspended soil from the base of the yarns; however, avoid over wetting. Additional dry extraction passes reduce moisture levels and minimize drying time.

Moisture recovery rate is dependent upon fibre type, textile floor covering construction, function of equipment design, hose diameter and proximity of the vacuum motor to the textile floor covering. Performance depends on the total system used, along with the skill of the operator.