



400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE INFORMATION REPORT

SAE AIR1375

REV.
B

Issued 1978-05
Revised 1998-09

Submitted for recognition as an American National Standard

MINIMUM SAFETY REQUIREMENTS FOR SPECIAL PURPOSE AIRLINE GROUND SUPPORT EQUIPMENT

FOREWORD

This revision contains format/editorial changes only.

TABLE OF CONTENTS

1. SCOPE	2
2. REFERENCES	2
3. ELEVATED WORKING SURFACES, ACCESS AND GENERAL CONDITIONS, GUARDRAILS, HANDRAILS AND GUARDS	4
4. FUNCTIONAL/OPERATIONAL CONTROLS.....	5
5. OPERATOR FOOT CONTROLS	6
6. BRAKES	6
7. HOISTING/LIFTING EQUIPMENT.....	7
8. STABILITY DEVICES	7
9. DOORS, SERVICE AND ACCESS PANELS.....	8
10. EXHAUST SYSTEMS.....	8
11. FUEL SYSTEM	9
12. ILLUMINATION	9
13. TRAINING.....	9

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in U.S.A.

QUESTIONS REGARDING THIS DOCUMENT:
TO PLACE A DOCUMENT ORDER:
SAE WEB ADDRESS:

(724) 772-8510
(724) 776-4970
<http://www.sae.org>

FAX: (724) 776-0243
FAX: (724) 776-0790

SAE AIR1375 Revision B

TABLE OF CONTENTS (Continued)

14. OPERATIONS.....9
 15. MAINTENANCE.....10
 16. GENERAL AND MISCELLANEOUS.....10

1. SCOPE:

This document applies to special purpose equipment, excluding fixed facilities, which is used in the ground handling, servicing, and maintenance of aircraft. Equipment covered under other sections of the Federal Register Part 1910 is excluded from this document. This document is to establish minimum safety requirements and should not be used for vehicle design criteria. Equipment existing prior to publication date is excluded from the requirements of this document.

2. REFERENCES:

2.1 SAE Publications:

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

AIR1328 Aircraft GSE Vehicle Stability Analysis

2.2 Definitions:

BOOTED FOOT is the foot of an operator sheathed appropriately for protection of the operator from normal job hazards and environmental weather conditions.

DEADMAN is a control design such that continuous, deliberate pressure on the control is necessary for activation and continuous operation, and such that relief of that pressure will cause control deactivation.

ELEVATED WORKING SURFACES is any platform or area, four feet or more above the next lowest working surface, on or in which an employee may be located in the performance of his working duties.

EQUIPMENT is any and all units, not an aircraft element, but mobile or semi-mobile, motorized or portable; intended or used as a means of providing access to aircraft; intended or used as an aid to an aircraft ground support activity, at or in the vicinity of an aircraft.

FMVSS refers to the Federal Motor Vehicle Safety Standard.

FUNCTIONAL means capable of servicing the purpose for which it was designed.

GLOVED HAND is the hand of an operator sheathed appropriately for dexterity and protection of the hand from normal job hazards and environmental weather conditions.

SAE AIR1375 Revision B

2.2 (Continued):

GUARDRAIL is a barrier erected along exposed edges of elevated work surfaces to prevent falls of persons.

HANDRAIL is a member supported on a stairway or ramp, to furnish persons with a handhold.

HIGHWAY USAGE is the operation of equipment on a public street or road such that state motor vehicles licensing of the vehicle is required.

HYDROSTATIC DRIVE means a vehicle has a hydrostatic transmission as opposed to a drive shaft and differential and where the oil is pumped from the hydraulic pump on the engine or electric motor directly to the hydraulic motor on the driven axle or wheels. The oil returns directly to the pump instead of going through a reservoir.

OPERATIONAL means the ability to perform intended function.

RISE is the vertical distance from the top of one tread to the top of the next higher tread.

RUNG is a ladder cross-member for use as a horizontal foot/hand hold.

SHALL is a term used to stress maximum advisability, and to qualify a provision as the minimum acceptable.

SHOULD is a term qualifying a provision as advisable but not critical.

STABILITY means the ability of remaining in the designed position and attitude.

STEP is a horizontal flat surface member of a stair, ladder, or a single foothold between two levels, capable of accepting a working load.

STEP WIDTH is the distance between the handrails of a stair, inside to inside.

TOE BOARD is a vertical barrier erected along exposed edges of elevated work surfaces to prevent falls of materials.

TREAD is the upper horizontal flat surface of a step.

TREAD DEPTH is the horizontal distance from front tread facing edge to the riser or rear edge of the tread.

UNIT is any piece of equipment; or a coupled equipment set.

VEHICLE is any piece of mobile equipment which is self-propelled and capable of carrying the operator.

SAE AIR1375 Revision B**3. ELEVATED WORKING SURFACES, ACCESS AND GENERAL CONDITIONS, GUARDRAILS, HANDRAILS AND GUARDS:**

- 3.1 Stair angles of incline shall not be less than 20 degrees nor more than 75 degrees.
- 3.2 Handrails shall be provided on all stairs. The handrail height in relation to the stair tread shall be constant with a minimum of 30 in (76.2 cm) and a maximum of 42 in (106.68 cm).
- 3.3 Stair treads shall be provided with a rise of not more than 12 in (30.48 cm). Tread rise shall be constant throughout the entire length of the stair above the first step from ground level or a platform.
- 3.4 Stair treads shall provide a usable depth of not less than 7 in (17.78 cm). These tread depths must remain constant throughout the entire length of the stair except when broken by a landing.
- 3.5 Where ladders are used for access, the incline angle shall not be less than 75 degrees with a maximum of 90 degrees.
- 3.6 Equal spacing between ladder rungs above the first rung shall be maintained with a maximum spacing of 12 in (30.48 cm).
- 3.7 Where steps are used on ladders, they shall be provided with a minimum depth of 1-1/2 in (3.81 cm). Where rungs are used, the minimum diameter shall be 3/4 in (1.9 cm).
- 3.8 A 7-in (17.78-cm) clearance shall be maintained to any obstruction. This clearance shall be measured from the front face of a step or the centerline of a rung. When a 7-in (17.78-cm) clearance cannot be maintained due to unavoidable obstructions, the minimum clearance shall be 1-1/2 in (3.81 cm).
- 3.9 A minimum 16-in (40.64-cm) clear width shall be provided between the side rails of a ladder.
- 3.10 Where vertical grab bars are provided, a minimum of a 2-1/2 in (6.35 cm) clearance shall be maintained.
- 3.11 Where off-set ladders are used, the side rails and rungs must be carried to a minimum of 3-1/2 ft (1.07 m) above the next section unless it creates an unavoidable obstruction.
- 3.12 Off-set ladders shall have a maximum step over distance of 18 in (45.72 cm).
- 3.13 All working surfaces shall be self-draining and provided with a non-slip surface.
- 3.14 Ladder side rails shall extend a minimum of 3-1/2 ft (1.07 m) above a landing or working surface unless it creates an unavoidable obstruction.
- 3.15 Ladder and stair treads shall be designed to support a minimum working load of 200 lb (90.8 kg).

SAE AIR1375 Revision B

- 3.16 Access ramps to cargo compartments of wide-body aircraft or other working areas of equivalent height shall have a minimum of one handrail provided.
- 3.17 Stairs, ramps, ladder rungs, or treads shall be of non-slip material.
- 3.18 Working platforms elevated 4 ft (1.22 m) or more above adjacent surface or ground level shall be provided with guardrails. (Note: 30 in (76 cm) in California).
- 3.19 Sprockets, gears, chains, belts, fans and pulleys or other nip or pinch point hazards that are not protected by vehicle structures or covers shall be guarded.
4. FUNCTIONAL/OPERATIONAL CONTROLS:
- 4.1 Functional and operational controls, for the purpose of this document, are those controls specifically designed for aircraft support usage, and exclude those designed into the basic unit such as steering, brakes, etc.
- 4.2 Units equipped with an automatic transmission shall have the transmission shift sequence conforming to FMVSS #102. If the transmission shift lever is steering column mounted or operates in a transverse vertical plane, the shift positions should be P, R, N, D, L, in a clockwise direction while seated in the operator's seat. If the shift lever operates in a longitudinal vertical plane, the shift pattern should be P, R, N, D, L, going from the front of the vehicle to the rear while seated in the operator's seat.
- 4.3 Transmission shift selector shall be located on either the right side of the steering column or to the right side of the operator.
- 4.4 It is permissible to block out the park position on automatic transmission vehicles or low gear or both.
- 4.5 While it is recommended for safety purposes that the directional control (forward and reverse) lever on hydrostatically or electric motor driven ramp equipment move in the direction of travel which is in accordance with FMVSS No. 102, this equipment should be designed to facilitate easy change of directional control by the end user if a different forward/reverse control movement is desired.
- 4.6 Transmission shift selector shall be sized and located to be handled with a gloved hand with a minimum of 3 in (7.62 cm) unobstructed clearances.
- 4.7 All other operational controls shall move in the direction of travel, for the function which they control, and shall be of the deadman type, unless the control is set to achieve a function to permit the user to accomplish another task. In these cases, such set controls must be detented or similarly locked into the operating positions to prevent inadvertent deactivation or reversing. Such controls shall be readily accessible to the operator(s). Emergency only operating controls need not meet this requirement.
- 4.8 On-off switches shall be on in the UP position or away from the operator if mounted in a horizontal plane.

SAE AIR1375 Revision B

- 4.9 Controls shall be logically grouped in a location convenient to the operator.
- 4.10 Controls shall be sized and spaced to provide easy operation with a gloved hand.
- 4.11 No more than 33 lb of force (147 Newtons) shall be required to actuate any hand control. No more than 100 lb of force (445 Newtons) shall be required to actuate any foot pedal control.
- 4.12 Controls shall be identified with permanently affixed and non-fading placards. Contrast shall be sharp and in large enough letters or symbols to be easily read from the operator's position, indicating the function and direction of motion of the control.
- 4.13 Controls and controlling circuits shall be designed in a manner that failure within a control or its circuitry will not introduce an unsafe operating condition.
- 4.14 Instruments and controls exposed to the weather shall be of a weatherproof type and shall be protected from snow and ice accumulations.
- 4.15 A vehicle, while stationary and operating a functional device that requires the engine to operate above idle speed, shall be equipped with an interlock to insure that power cannot be transmitted to the drive wheels.
- 4.16 Power steering shall be provided on all vehicles with a steering axle of 9000 lb (4086 kg).
- 5. OPERATOR FOOT CONTROLS:**
- 5.1 Foot operated driver controls should be in the following sequence from left to right from the operator's position as applicable: parking brake, light dimmer switch, clutch, foot brake, and accelerator.
- 5.2 Clutch, foot brake, accelerator, and functional foot controls shall be a minimum size of 2 in (5.1 cm) by 3 in (7.62 cm) and provided with a non-slip material.
- 5.3 Controls shall be spaced to provide easy operation with a booted foot.
- 6. BRAKES:**
- 6.1 As a minimum number of vehicles used in the airline support equipment are equipped with air brakes, this section will not address itself to the minimum standard for same. If a vehicle is so equipped, it must conform to FMVSS #121.
- 6.2 Units equipped with a 4-wheel brake system shall incorporate a dual master cylinder to split the hydraulic brakes into two separate systems.

SAE AIR1375 Revision B

6.3 Based upon braking system design, two systems shall be provided for applying brakes. The primary system (service brakes) shall be pedal operated to apply brakes simultaneously on all braked wheels. The secondary system shall be hand or foot operated to apply a braking action sufficient to hold the vehicle on the maximum grade on which the vehicle is operated with rated capacity load, with the transmission in neutral and engine idling on a dry surface free of loose materials. The brake shall be effective for restraining vehicle movement in either a forward or reverse direction.

6.4 The secondary brake shall remain applied after initial actuation without further energy input.

6.5 The maximum permissible stopping distance excluding reaction distance, from a minimum initial speed of 20 mph on level dry pavement using a maximum service brake pedal force of 100 lbf (445 Newtons) shall be:

Single vehicles

*GVW 5000 lb (2270 kg) or less	25 ft (7.63 m)
*GVW 5000 lb (2270 kg) to 10 000 lb (4450 kg)	30 ft (9.15 m)
*GVW over 10 000 lb (4450 kg)	40 ft (12.2 m)

*(GVW) - Gross Vehicle Weight

6.6 Manually moved units shall have either parking brakes or other means capable of holding a maximum capacity load on a 15% grade or an empty or capacity load when subject to wind or blast load up to 80 mph (128.7 km/h). Wheel chocks or similar braking devices which accomplish this are acceptable.

6.7 Power brakes shall be provided on any vehicle with a GVW of 30 000 lb (13 620 kg) or over.

7. HOISTING/LIFTING EQUIPMENT:

7.1 The maximum capacity of all hoisting equipment shall be displayed in a location readily visible.

7.2 Fail-safe devices, to prevent the unit free falling, shall be provided.

7.3 Maintenance safety locks shall be provided.

7.4 A safe means of lowering or disconnecting shall be provided in the event of a malfunction.

8. STABILITY DEVICES:

8.1 Self-propelled type equipment with power actuated stabilizers shall have an operator warning device to indicate when the stabilizers are not in the stowed position or an interlock to prevent driving the unit with the stabilizers or outriggers extended.

SAE AIR1375 Revision B

- 8.2 Lift type units exposed to blast, wind, or irregular surfaces shall be equipped with stabilizing devices, if necessary, to preclude overturning when exposed to wind or blast up to 90 mph (144.8 km/h). Refer to AIR1328, "Aircraft GSE Vehicle Stability Analysis" for further information.
- 8.3 The stability as outlined in 8.2 shall determine at which point during elevation the stabilizing devices shall be necessary. A safety device shall be provided to insure this elevation is not exceeded unless stabilizing devices are deployed or engaged or both. Retraction of the stabilizing device shall not be possible under normal conditions until the unit has been lowered to within the stability requirements of 8.2.
- 8.4 Stabilizer activating devices shall be located so as not to expose the operator to a personal injury.
- 8.5 When emergency controls for raising the stabilizers are provided, they shall be located so the operator is not exposed to injury.
- 8.6 Stabilizer ground contact pads shall have the outside edges radiused a minimum of 1/4 in (0.64 cm) and shall be smooth.
- 8.7 Stability devices that extend beyond the vehicle profile shall be painted yellow or illuminated.
9. DOORS, SERVICE AND ACCESS PANELS:
- 9.1 All doors and panels shall be provided with securing devices to retain them in the open or closed position or both. These devices shall be capable of withstanding blast or ambient winds and shall be installed so that the doors, when open, do not create a personal injury hazard.
- 9.2 Equipment components and system requiring routine and frequent inspection and servicing shall be readily accessible. Suitable access doors or removable enclosures shall be provided for this purpose. Access doors, covers and protective guards shall be designed for quick removal or opening. Access holes in protective guards for lubrication are acceptable, but shall be held to a minimum number and size.
10. EXHAUST SYSTEMS:
- 10.1 Internal combustion engines, excluding gas turbine engines, shall be fitted with either a baffle-type muffler or spark arrestor.
- 10.2 The exhaust system, beyond the manifold, shall be supported at least 3 in (7.6 cm) clear of combustibile materials, excluding flexible mountings, and at least 2 in (5.1 cm) clear of fuel and electrical system parts and shall not be subject to drippage of fuel, oil, or grease.
- 10.3 The surfaces and the discharge of exhaust systems shall be located so that they will not expose employees to injury.

SAE AIR1375 Revision B**11. FUEL SYSTEM:**

- 11.1 Fuel lines shall be constructed of steel tubing or seamless annealed copper. Flexible fuel lines may be used in locations to absorb vibration and prevent fatigue.
- 11.2 Fuel lines shall be secured with a minimum of 2-in (5.1-cm) clearance to exhaust systems.
- 11.3 The fuel tank and lines shall be located and installed so that any overflow, during filling, or any leakage shall not impinge on the engine, exhaust, electrical system, or other ignition sources or enter the operator's compartment.
- 11.4 A visible permanent marking shall be installed adjacent to the filler indicating the type of fuel to be used.

12. ILLUMINATION:

- 12.1 Motorized self-propelled vehicle shall be equipped with a minimum of two headlights and one combination stop/tail light.
- 12.2 Operational instruments and control panels exclusive of driving control panels shall be illuminated to a minimum of 5 foot-candles and not produce a glare to the operator.
- 12.3 Units designed for interior use need not have illumination as outlined in 12.1 and 12.2.

13. TRAINING:

- 13.1 Only trained and authorized persons shall be permitted to operate ground support equipment. A qualification record shall be maintained by the operator's employer.

14. OPERATIONS:

- 14.1 Foothold, stairs, tractor and truck running boards, ladders, and work platforms shall be kept clear.
- 14.2 Vehicle lights and windshields should be kept clear.
- 14.3 Windshield wipers, defrosters, and frost shields should be properly maintained and used.
- 14.4 Tarpaulins, cargo restraining nets, side gates on carts, and other items of this nature provided to prevent cargo from falling, should be used.
- 14.5 Equipment capacities regarding cargo loads and personnel accommodations shall be enforced.
- 14.6 All units shall be operated in accordance with procedures established by the employer or manufacturer or both.
- 14.7 All motorized vehicles shall display lights from 1/2 h after sunset to 1/2 h before sunrise.