

Torque, Threaded Application, Electrical Connector and Accessory Installation

RATIONALE

This document is to provide information regarding torque as applied to general use connectors and associated hardware, typically used in military defense electronics, weapon systems and military and commercial aerospace applications.

1. SCOPE

This SAE Aerospace Information Report (AIR) is intended to provide guidelines to tightening methods and torque values as applied to electrical connectors and related hardware. The connectors and associated hardware discussed herein, are typically manufactured from aluminum alloy, high grade engineering thermoplastics or corrosion resistant steel and typically plated with a protective/conductive coating. These guidelines may be used where no rules have been mandated either contractually or otherwise.

1.1 Purpose

To aid in the proper assembly of electrical connectors and related hardware in order to avoid damage by over torque or the loosening of parts while in service.

2. REFERENCES

There are no referenced publications specified herein.

2.1 Applicable Documents

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

AS1310	Fastener Torque for Threaded Applications, Definitions of
AS50151	Connectors, Electrical, Circular Threaded, AN Type
AS85049	Connector Accessories, Electrical, General Requirements for
AS84049/1	Connector Accessories Electrical, Environmental, Cable Sealing, Straight, Grounding, Without Strain Relief

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: <http://www.sae.org>

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AIR6151>

AS85049/2	Connector Accessories, Electrical, Environmental, Cable Sealing, Straight, Strain Relief
AS85049/41	Connector Accessories, Electrical, Non-Environmental Strain Relief, Straight
AS85049/42	Connector Accessories, Electrical, Non-Environmental Strain Relief, Straight
AS81703	Connectors, Electric, Circular, Miniature, Rack and Panel or Push-Pull Coupling, Environment Resistant

2.1.2 U.S. Government Publications

Available from the Document Automation and Production Service (DAPS), Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, Tel: 215-697-9495, <https://assist.daps.dla.mil/quicksearch/>.

Military

MIL-DTL-22992	Connectors, Plugs and Receptacles, Electrical, Waterproof, Quick Disconnect, Heavy Duty Type, General Specification For
MIL-DTL-26482	Connectors, Electrical (Circular, Miniature, Quick Disconnect, Environment Resisting) Receptacles and Plugs
MIL-DTL-26500	Connectors, General Purpose, Electrical, Miniature, Circular, Environment Resisting, General Specification for
MIL-DTL-27599	Connector, Electrical, Miniature, Quick Disconnect (for Weapons Systems), Established Reliability
MIL-DTL-28840	Connectors, Electrical, Circular, Threaded, High Density, High Shock, Shipboard, Class D, General specification for
MIL-DTL-38999	Connectors, Electrical, Circular, Miniature, High Density, Quick Disconnect (Bayonet, Threaded, and Breech Coupling), Environment resistant, Removable Crimp and Hermetic Solder Contacts
MIL-C-81511	Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting and Accessories, General Specification For
MIL-DTL-83723	Connectors, Electrical, Circular (Environment resisting) Receptacles and Plugs

3. DEFINITIONS

- 3.1 Torque: Torque is the result of force times radius. Typically measured in units of Inch-Ounces, Inch-Pounds, Foot-Pounds, Newton-Meters Kilogram-Centimeters etc. (See 4.1 and Table 6)
- 3.2 Applied Torque: The torque transmitted to the thread by the installation tool.
- 3.3 Assembly Sequence: A method indicating sequence of assembling fasteners in a prescribed pattern. Also; Installation Sequence, Tightening Sequence, Torquing Sequence.
- 3.4 Assembly Torque: This shall be the design torque applied at final assembly. It shall include the net effect of the following;
 - a. The torque required to overcome kinetic friction between mating bearing faces and between mating threads.
 - b. The torque required to overcome the self-locking feature (if any).
 - c. The torque required to apply the desired axial load to a fastener assembly.

- 3.5 Breakaway Torque: This is the torque required to initiate relative motion between male and female threads. Breakaway torque can be prefixed with the words Maximum or Minimum and shall only be measured in the loosening direction.
- 3.6 Over Torque: This shall be the torque required to initially move the wrenched thread from the installed condition. Over torque is always measured in the tightening direction and exceeds the maximum limit of the desired installation torque. Also; Over Tightening Torque.
- 3.7 Prevailing Torque: This shall be the torque required to overcome kinetic friction of mating threads plus the torque required to overcome the locking feature when 100% of the locking feature is engaged and the threads are unseated. The word "prevailing" shall be understood as the average torque when it is not prefixed by the words Maximum or Minimum. The prevailing torque can be measured in either a loosening or tightening direction. Also; Run Down Torque/ Running Torque.
- 3.8 Single Torque: This shall be the installation torque applied once per assembly, usually applied to freely fitting parts, where no interference fits to hinder the seating of mating parts.
- 3.9 Torque out: This term refers to a general type of torsional failure where any fastener component reacting to the applied torque, disengages or fails. This term is also used when referring to other types of torquing elements such as interference fits.
- 3.10 Unseating Torque: This shall be the torque required to initially move the fastener from the installation torque condition. The unseating torque shall always be measured in a loosening direction. Also: Breakaway torque.

4. REQUIREMENTS

4.1 General

Torque is the force or turning moment tending to produce rotation. It is expressed in terms of applied load and the length of the moment arm applying it in inch pounds (in-lbs). The torques specified herein are those commonly used in the aerospace industry and do not represent thread strength values for qualification testing. It is the responsibility of the user/installer to determine the best torque for the application and to select the appropriate tools and holding devices for the work and the user conditions.

It should be noted that the included torque definitions apply equally to both internal and external threaded parts that may or may not have a locking feature. For all the following torque definitions, the threaded components shall be considered;

- a. Seated when its bearing surface contacts the material being joined, and any additional applied torque will produce a residual axial stress in either the male or female component.
- b. Unseated when the application of removal torque disengages the bearing surface of the threaded component from the material being joined, reducing the axial stress to zero.

4.2 Material

Torque requirements specified herein shall apply to threaded component such as couplings, nuts, screws, bolts, studs and inserts. These items may be separate hardware or integral parts of such components as connectors, backshells or clamps. They will usually be made of corrosion-resistant steel, high grade engineering thermoplastic or aluminum alloy coated with a protective coating. Threads may be locked by lockwashers, self-locking inserts, anti decoupling devices or liquid locking compounds. Threads that are locked by deformed metal threads in inserts or contain a material compound that provides a locking feature may be coated with a thread lubricant.

4.3 Temperature Effects

For ambient temperatures outside the range of -1 °C to 93 °C (30 °F to 200 °F) allowance must be made for mechanical property differences from tabulated room temperature values. These properties include tensile strength, yield strength, modulus of elasticity, etc. Where bolts and flange materials are generically dissimilar, such as aluminum and corrosion resistant steel or steel and brass, differences in thermal expansion may cause preload increase or decrease with temperature. Allowance must be made for these changes.

5. TORQUE REQUIREMENTS

5.1 Screw Torque

Recommended torque for corrosion resistant or plated steel screws is listed in Table 1. Column 1 is for standard installation into aluminum or corrosion resistant steel. Column 2 is for installation into composite material regardless of thread length or aluminum material with less than 3 full threads of engagement. Column 3 is for installation in high vibration (engine) areas, clinch nuts and ground straps.

TABLE 1 - CORROSION RESISTANT/PLATED STEEL SCREW TORQUE/IN-LBS

Screw Size	Column 1	Column 2	Column 3
	Min/Max	Min/Max	Min/Max
2-56	1.5/2.5	1.2/2.0	2.0/2.5
4-40	3.5/4.5	2.8/3.6	3.5/4.5
6-32	5.0/7.0	4.0/5.6	5.5/6.5
8-32	7.0/9.0	5.6/7.2	7.5/8.5
10-32	9.0/11.0	7.2/8.8	8.5/10.5
.250-20	11.0/13.0	8.8/10.4	10.5/15.5

5.2 Connector Receptacle Jam Nut Torque

Recommended torque for aluminum, composite and corrosion resistant steel connector jam nuts are listed in Table 2.

TABLE 2 - CONNECTOR RECEPTACLE JAM NUT TORQUE/IN-LBS

Thread Size	Torque Min/Max	Connector Shell Size Reference			
		AS50151	MIL-DTL-26482	MIL-DTL-26500	MIL-DTL-83723 Ser.1
.500-28UNEF-2B	24/30	8s			
.562-24UNEF-2B	26/32		8		8
.625-24UNEF-2B	28/34	10S - 10SL			
.625-20UN-2B	28/34			8	
.687-24UNEF-2B	30/36		10		10
.750-20UNEF-2B	34/40	12 - 12S		10	
.875-20UNEF-2B	46/50	14 - 14S	12		12
.937-20UNEF-2B	50/55			12	
1.000-20UNEF-2B	55/60	16 - 16S	14	14	14
1.125-20UN-2B	70/75			16	
1.125-18UNEF-2B	70/75	18	16		16
1.250-20UN-2B	80/85			18	18
1.250-18UNEF-2B	80/85	20	18		
1.375-18UNEF-2B	90/95	22	20	20	20
1.500-20UN-2B	105/115			22	
1.500-18UNEF-2B	105/115	24	22		22
1.625-18UNEF-2B	110/120		24	24	24
1.750-18UNS-2B	120/130	28			
2.000-18UNS-2B	150/160	32			
2.250-16UN-2B	170/180	36			
2.500-16UN-2B	200/210	40			
2.750-16UN-2B	220/230	44			
3.000-16UN-2B	240/250	48			

TABLE 2 - CONNECTOR RECEPTACLE JAM NUT TORQUE/IN-LBS (CONTINUED)

Thread Size	Torque Min/Max	Connector Shell Size Reference		
		MIL-DTL-83723 Ser. 3	MIL-DTL-38999 Ser. I	MIL-DTL-38999 Ser. II
.625-20UN-2B	28/34		9	
.687-24UNEF-2B	30/36	10		
.750-20UNEF-2B	34/40		11	
.812-20UNEF-2B	40/46			8
.875-20UNEF-2B	46/50	12		
.937-20UNEF-2B	50/55	14	13	10
1.000-20UNEF-2B	55/60	16 Bayonet		
1.125-20UN-2B	70/75	16 Threaded	15	12
1.187-18UNEF-2B	75/80	18		
1.250-20UN-2B	80/85	20	17	14
1.250-18UNEF-2B	80/85		19	16
1.437-18UNEF-2B	100/110	22		
1.500-20UN-2B	105/115	24	21	18
1.500-18UNEF-2B	105/115		23	20
1.625-18UNEF-2B	110/120		25	22
1.750-18UNS-2B	120/130			24

TABLE 2 - CONNECTOR RECEPTACLE JAM NUT TORQUE/IN-LBS (CONTINUED)

Thread Size	Torque Min/Max	Connector Shell Size Reference			
		MIL-DTL-28840 MIL-PRF-28876	MIL-DTL-27599	MIL-DTL-38999 Series III	MIL-DTL-38999 Series IV
.687-24UNEF-2B	30/36		9		
.750-20UNEF-2B	34/40				
.812-20UNEF-2B	40/46		11		
.875-20UNEF-2B	46/50	11	8		
.937-20UNEF-2B	50/55				
1.000-20UNEF-2B	55/60	13	10 & 13		
1.125-20UN-2B	70/75				
1.125-18UNEF-2B	70/75		12 & 15		
1.187-18UNEF-2B	75/80	15			
1.250-20UN-2B	80/85		14 & 17		
1.250-18UNEF-2B	80/85	17			
1.375-18UNEF-2B	90/95		16 & 19		
1.437-18UNEF-2B	100/110	19			
1.500-20UN-2B	105/115				
1.500-18UNEF-2B	105/115		18 & 21		
1.625-18UNEF-2B	110/120	23	20 & 23		
1.750-18UNS-2B	120/130	25	22 & 25		
1.875-16UN-2B	140/150		24		
1.937-16UN-2B	145/155	29			
2.000-18UNS-2B	150/160				
2.125-16UN-2B	170/180	33			

TABLE 2 - CONNECTOR RECEPTACLE JAM NUT TORQUE/IN-LBS (CONTINUED)

Thread Size	Torque Min/Max	Connector Shell Size Reference			
		MIL-DTL-28840 MIL-PRF-28876	MIL-DTL-27599	MIL-DTL-38999 Series III	MIL-DTL-38999 Series IV
M17 x 1-6H	30/36			09	
M20 x 1-6H	40/46			11	
M25 x 1-6H	55/60			13	11
M28 x 1-6H	70/75			15	13
M31 x 1-6h	70/75				15
M32 x 1-6H	80/85			17	
M34 x 1-6H	80/85				17
M35 x 1-6H	90/95			19	
M38 x 1-6H	100/110			21	19
M41 x 1-6H	110/120			23	21
M44 x 1-6H	120/130			25	23
M47 x 1-6H	120/130				25

5.3 Secondary Adapter and AS Cable Clamp Torque

Recommended torque for aluminum and corrosion resistant steel secondary adapters and AS85049/41 and /42 type cable clamps are listed in Table 3. Cable clamps that utilize elastomeric sealing grommets such as AS85049/1 and /2 need adequate torque applied to assure proper cable sealing but not over torqued to the extent that the sealing grommet extrudes. For all assemblies where metal braided RF/EMI shielding is terminated using conical metal ferrule(s), the minimum recommended torque is 35 in-lbs.

TABLE 3 – SECONDARY AND AS CABLE CLAMP TORQUE/IN-LBS

AS Clamp Size	Torque Min/Max
3	30/40
4	30/40
6	35/55
8	35/55
10	35/55
12	40/60
16	40/60
20	40/60
24	80/100
28	80/100
32	80/100
40	80/100

5.4 Connector Accessory Recommended Torque.

Recommended torque for accessories such as those defined in SAE AS85049 to connector rear threads are listed in Table 4.

Column 1 is for aluminum medium and light duty accessories including connector series;

AS50151 (AS31001 Series)
 MIL-DTL-26482 Series 1
 MIL-DTL-26500
 MIL-DTL-27599
 MIL-DTL-38999 Series I and II
 MIL-C-81511 Series 1,2,3,4
 AS81703 Series 1

Column 2 is for aluminum heavy duty accessories including connector series;

AS50151 (AS34001 Series)
 MIL-DTL-22992
 MIL-DTL-26482 Series 2
 MIL-DTL-28840
 MIL-DTL-38999 Series III and IV
 AS81703 Series 3
 MIL-DTL-83723 series 1,2,3

Column 3 is for accessories with composite (high grade engineering thermoplastic) material coupling threads.

Column 4 is for accessories with aluminum coupling threads used in high vibration (engine) applications.

Column 5 is for accessories with corrosion resistant steel coupling threads used in high vibration (engine) applications.

TABLE 4 – CONNECTOR ACCESSORY TORQUE/IN-LBS

Connector Shell Sizes	Column 1	Column 2	Column 3	Column 4	Column 5
	MIN/MAX	MIN/MAX	MIN/MAX	MIN/MAX	MIN/MAX
8,9,A	30/40	51/61	20/25	66-77	91-101
3,10,10SL, 11, B	30/40	71/81	20/30	103-113	115-125
7,12,12S,13,C	35/45	103/113	25/35	115-125	115-125
14,14S,15,D	35/45	111/121	25/35	139-149	139-149
16,16S,17,E	35/45	111/121	30/40	139-149	139-149
18,19,27,F	35/45	111/121	30/40	139-149	175-185
20,21,37,G	75/85	131/141	35/45	175-185	199-209
22,23,H	75/85	131/141	35/45	175-185	223-233
24,25,61,J	75/85	131/141	35/45	175-185	259-269
28,29	115/125	143/153	115/125	187-197	307-317
32,33	115/125	143/153			
36	115/125	142/153			
40	155/165	159/169			
44	155/165	159/169			
48	155/165	159/169			

5.5 Connector to Connector (Plug to Receptacle) Coupling Torque

Recommended torques for coupling threaded plug and receptacle connectors are shown in Table 5.

TABLE 5 – CONNECTOR TO CONNECTOR TORQUE/IN-LBS

Connector Series Shell Size					
Connector Torque Max/Inlbs	MIL-DTL-28840 MIL-PRF-28876	MIL-DTL-38999 Series III	MIL-DTL-83723 Series II	MIL-DTL-83723 Series III	AS50151
8		A (9)			
11				8	
12	A (11)	B (11)	8S		8S
13				10	
14			10S & 10SL	12	10S & 10SL
16	B (13)	C (13)	12 & 12S		12 & 12S
18				14	
20	C (15)	D (15)	14 & 14S		14 & 14S
21				16	
24	D (17)	E (17)	16 & 16S		16 & 16S
27				18	
28	E (19)	F (19)			
30			18		18
31				20	
32		G (21)		22	
36	F (23)	H (23)			
40	G (25)	J (25)	20		20
46			22	24	22
47	H (29)				
53	J (33)				
55			24		24
66			28		28
78			32		32
93			36		36
106			40		40

6. APPLICATION INFORMATION

- 6.1 Do not use tightening or gripping tools with metal jaws or grippers such as pliers and wrenches on electrical connectors, jam nuts, accessories or backshells. Non marring tools such as strap wrenches, soft jaw pliers, lined ring grippers, and similar tools shall be used to avoid damage to plating and the integrity of the connector/accessory surfaces.
- 6.2 When mating connectors, dummy connectors, and special tools configured to engage the connector keys for holding while applying torque are used, multiple keys shall be engaged (with exception of connectors conforming to AS50151). Care must also be taken not to damage spring (grounding) fingers, sealing components, plating or other features of connectors (plugs or receptacles) when these holding devices are being used.
- 6.3 When tightening Multi-Stage Backshells or connector accessories, the holding point must be moved one stage from the components being tightened to assure even tightening of each stage.
- 6.4 When tightening thin coupling rings and similar threaded components on electrical connectors, avoid gripping tools that apply force to two points (such as soft jaw pliers). Devices which apply a uniform load around the circumference of the coupling ring (such as strap wrenches and lined circular ring pliers) are preferred.