



# AEROSPACE MATERIAL SPECIFICATION

Society of Automotive Engineers, Inc.  
400 COMMONWEALTH DRIVE, WARRENDALE, PA. 15096

## AMS 2813D

Superseding AMS 2813C

Issued 1-15-63

Revised 4-15-80

### PACKAGING OF WELDING WIRE Standard Method

1. **SCOPE:** This specification covers spooling and packaging of bare welding wire to ensure cleanliness but with minimum environmental protection, spool sizes and weights of spooled wire, and package weights of cut lengths.
2. **APPLICABLE DOCUMENTS:** The following publications form a part of this specification to the extent specified herein. The latest issue of Aerospace Material Specifications (AMS) shall apply. The applicable issue of other documents shall be as specified in AMS 2350.
  - 2.1 **SAE Publications:** Available from Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.
    - 2.1.1 **Aerospace Material Specifications:**
      - AMS 2350 - Standards and Test Methods
      - AMS 2815 - Identification, Welding Wire, Line Code System
      - AMS 2816 - Identification, Welding Wire, Color Code System
    - 2.2 **U.S. Government Publications:** Available from Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.
      - 2.2.1 **Military Specifications:**
        - MIL-W-10430 - Welding Rods and Electrodes, Preparation for Delivery of
  3. **TECHNICAL REQUIREMENTS:**
    - 3.1 **Preparation:** Prior to winding on spools or cutting to length, wire shall be uncoiled for cleaning and shall be rendered free of dirt, grease, oil, corrosion, and other surface contamination which would interfere with welding.
    - 3.2 **Packaging:**
      - 3.2.1 **Spoiled Wire:**
        - 3.2.1.1 Spools shall be of such materials and construction as to provide sufficient strength and rigidity to prevent damage to, or distortion of, the wire during normal handling and use. The materials shall not induce corrosion of the wire and shall electrically insulate the wire from the spindle of the welding machine.
        - 3.2.1.2 Configuration and dimensions of spools shall conform to Fig. 1 and Table I. The size of spool shall be selected on the basis of the alloy and quantity ordered. Each spool shall provide access to approximately 8 in. (200 mm) of wire at the inside end of the coil for sampling purposes; a groove in the outer face of one flange, adjacent to the barrel, is acceptable.

# REAFFIRMED

10/91

SAE Technical Board rules provide that: "All technical reports, including standards approved and recommended, are advisory only. Their use by anyone engaged in industry or trade or their use by governmental agencies is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."

- 3.2.1.3 Wire on each spool shall be one continuous length from the same heat of alloy, except in the case of aluminum and magnesium which are not restricted, unless otherwise permitted by purchaser. Welding to form a continuous length is permissible if performed prior to the final drawing operation.
- 3.2.1.4 Wire shall be furnished on spools containing approximately the ordered spool net weight except that up to 20% of the net weight of any one combination of alloy, wire diameter, and spool size in a shipment may be on spools containing not less than 50% of the ordered spool net weight.
- 3.2.1.5 Wire shall be closely wound in layers but adjacent turns within a layer need not necessarily be touching; shall be wound so as to avoid producing kinks, waves, and sharp bends; and shall be free to unwind without restriction caused by overlapping or wedging. The outside end of the spooled wire shall be so treated that it may be readily located.
- 3.2.1.6 Net weight of wire on spools shall be as specified in Table II for the alloy type ordered.

TABLE II

Alloy Type	Spool Net Weight, lb
Aluminum	1, 10, 12-1/2, 15
Magnesium	3/4, 1, 9, 10
Titanium	1, 10, 20
Copper	25, 50
Steel, Corrosion Resistant Alloys, and Refractory Alloys	1 1/2, 2-1/2, 25, 35, 50, 60

TABLE II (SI)

Alloy Type	Spool Net Weight, kg
Aluminum	0.5, 5, 6, 7
Magnesium	0.4, 0.5, 4, 5
Titanium	0.5, 5, 9
Copper	11, 23
Steel, Corrosion Resistant Alloys, and Refractory Alloys	0.7, 1.1, 11, 16, 23, 27

**3.2.2 Cut Lengths:**

- 3.2.2.1 Containers shall be of such materials and construction as to provide sufficient strength and rigidity to prevent damage to, or distortion of, the wire during normal handling. The materials shall not induce corrosion of the wire.
- 3.2.2.2 No package shall contain wire from more than one heat of alloy, except in the case of aluminum and magnesium alloys which are not restricted.
- 3.2.2.3 Wire shall be furnished in standard packages of approximately 5, 10, 25, 50, or 100 lb (2.5, 5, 11, 23, or 45 kg), as ordered.

**3.3 Packing:**

3.3.1 Containers of wire shall be packed so as to ensure that the wire, during shipment and storage, will be protected against mechanical injury, corrosion, dirt, grease, oil, and other contamination detrimental to welding.

3.3.2 Exterior containers of spooled wire shall contain the ordered multiple of standard spool net weights up to a maximum net weight of 120 lb (55 kg).

3.3.3 Exterior shipping containers of cut lengths shall contain approximately 5, 10, 50, or 100 lb (2.5, 5, 23, or 45 kg), as ordered.

3.3.4 Containers shall be prepared for shipment in accordance with commercial practice and in compliance with applicable rules and regulations pertaining to the handling, packaging, and transportation of the wire to ensure carrier acceptance and safe delivery. Packaging shall conform to carrier rules and regulations applicable to the mode of transportation.

3.3.5 For direct U.S. Military procurement, packaging shall be in accordance with MIL-W-10430, Level A or Level C, as specified in the request for procurement. Commercial packaging as in 3.3.1 through 3.3.4 will be acceptable if it meets the requirements of Level C.

3.4 Identification: Interior containers of spools and cut lengths and all exterior shipping containers shall be marked as follows:

3.4.1 Interior Containers: Shall be permanently and legibly marked to show not less than the following information; for containers of cut lengths, the information may appear on an attached label:

WIRE, WELDING

WIRE SPECIFICATION NUMBER (and revision letter if any) \_\_\_\_\_

SIZE \_\_\_\_\_

QUANTITY \_\_\_\_\_

HEAT NUMBER (If applicable) \_\_\_\_\_

MANUFACTURER'S IDENTIFICATION \_\_\_\_\_

WIRE IDENTIFICATION SPECIFICATION (AMS 2815 or AMS 2816) \_\_\_\_\_

CODE NUMBER (from AMS 2815 or AMS 2816) \_\_\_\_\_

3.4.2 Exterior Containers: Shall be permanently and legibly marked to show not less than the following information:

WIRE, WELDING

WIRE SPECIFICATION NUMBER (and revision letter if any) \_\_\_\_\_

SIZE \_\_\_\_\_

QUANTITY \_\_\_\_\_

HEAT NUMBER (If Applicable) \_\_\_\_\_

PURCHASE ORDER NUMBER \_\_\_\_\_

MANUFACTURER'S IDENTIFICATION \_\_\_\_\_

WIRE IDENTIFICATION SPECIFICATION (AMS 2815 or AMS 2816) \_\_\_\_\_

PACKAGED PER AMS 2813

- ∅ 4. QUALITY ASSURANCE PROVISIONS: Not applicable.
- ∅ 5. PREPARATION FOR DELIVERY: See Section 3.
- 6. ACKNOWLEDGMENT: A vendor shall mention this specification number and its revision letter in all quotations and when acknowledging purchase orders.
- 7. REJECTIONS: Wire not packaged in accordance with this specification or with modifications authorized by purchaser will be subject to rejection.
- 8. NOTES:
  - 8.1 Marginal Indicia: The phi (∅) symbol is used to indicate technical changes from the previous issue of this specification.

SAENORM.COM : Click to view the full PDF of ams2813D