



<b>AEROSPACE MATERIAL SPECIFICATION</b>	<b>AMS2813™</b>	<b>REV. G</b>
	Issued 1963-01 Revised 2011-03 Reaffirmed 2022-10	
Superseding AMS2813F		
Packaging and Marking of Packages of Welding Wire Standard Method		

### RATIONALE

AMS2813G has been reaffirmed to comply with the SAE Five-Year Review policy.

#### 1. SCOPE

This specification covers spooling and packaging of bare welding wire to ensure cleanliness but with minimum environmental protection, spool sizes and weights of spooled wire, and package weights of cut lengths.

#### 2. APPLICABLE DOCUMENTS

The issue of the following documents in effect on the date of the purchase order forms a part of this specification to the extent specified herein. The supplier may work to a subsequent revision of a document unless a specific document issue is specified. When the referenced document has been cancelled and no superseding document has been specified, the last published issue of that document shall apply.

##### 2.1 U.S. Government Publications

Available from the Document Automation and Production Service (DAPS), Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, Tel: 215-697-6257, <http://assist.daps.dla.mil/quicksearch/>.

MIL-W-10430 Welding Rods and Electrodes, Preparation for Delivery of

##### 2.2 American Welding Society

Available from American Welding Society, 550 N.W. LeJeune Rd., Miami, FL 33126, U.S.A. and [www.aws.com](http://www.aws.com).

AWS A5.02/A5.02M Specification for Filler Metal Standard Sizes, Packaging, and Physical Attributes

##### 2.3 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

AMS2816 Identification, Welding Wire, Tab Marking System

AMS2819 Identification Welding Wire, Direct Color Code System

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2022 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: [CustomerService@sae.org](mailto:CustomerService@sae.org)  
<http://www.sae.org>

SAE WEB ADDRESS:

**For more information on this standard, visit**  
<https://www.sae.org/standards/content/AMS2813G/>

### 3. TECHNICAL REQUIREMENTS

#### 3.1 Preparation

Prior to winding on spools or cutting to length, wire shall be uncoiled for cleaning and shall be rendered free of dirt, grease, oil, corrosion, and other surface contamination which would interfere with welding. Chlorinated solvents shall not be used on titanium alloys.

3.2 Packaging shall be in accordance with AWS A5.02/A5.02M and the following:

#### 3.2.1 Spooled Wire

Each spool shall provide access to approximately 8 inches (203 mm) of wire at the inside end of the coil for sampling purposes; a groove in the outer face of one flange, adjacent to the barrel, is acceptable.

3.2.1.1 Unless otherwise specified in the material specification, wire on each spool shall be one continuous length from the same heat of alloy, except in the case of aluminum and magnesium alloys which are not restricted.

3.2.1.2 Wire shall be furnished on spools containing approximately the ordered spool net weight except that up to 20% of the net weight of any one combination of alloy, wire diameter, and spool size in a shipment may be on spools containing not less than 50% of the ordered spool net weight.

3.2.1.3 Wire shall be closely wound in layers but adjacent turns within a layer need not necessarily be touching; shall be wound so as to avoid producing kinks, waves, and sharp bends; and shall be free to unwind without restriction caused by overlapping or wedging. The outside end of the spooled wire shall be so treated that it may be readily located.

3.2.1.4 Net weight of wire on spools shall be as specified in Table 1 for the alloy type ordered.

#### 3.2.2 Cut Lengths

3.2.2.1 Containers shall be of such materials and construction as to provide sufficient strength and rigidity to prevent damage to, or distortion of, the wire during normal handling. The materials shall not induce corrosion of the wire.

3.2.2.2 Unless otherwise specified in the material specification, no package shall contain wire from more than one heat of alloy, except in the case of packages of aluminum and magnesium alloys which are not restricted.

3.2.2.3 Wire shall be furnished in standard packages of approximately 5, 10, 25, 50, or 100 pounds (2.3, 4.5, 11.3, 22.7, or 45.3 kg), as ordered.

#### 3.3 Packaging

3.3.1 Containers of wire shall be packed to ensure that the wire, during shipment and storage, will be protected against mechanical damage, corrosion, dirt, grease, oil, and other contamination detrimental to welding.

3.3.2 Exterior containers of spooled wire shall contain the ordered multiple of standard spool net weights up to a maximum net weight of 120 pounds (54.4 kg).

TABLE 1A - SPOOLED WIRE WEIGHT, INCH/POUND UNITS

Alloy Base	Net Weight, Pounds
Aluminum	1, 5, 10, 12-1/2, 15
Magnesium	3/4, 1, 3, 10
Titanium	1, 5, 10, 15, 20
Copper	1, 10, 25, 50
Steel, Corrosion and Heat Resistant Alloys	1-1/2, 2-1/2, 10, 12, 15, 25, 30
and Refractory Alloys	35, 44, 50, 60

TABLE 1B - SPOOLED WIRE WEIGHT, SI UNITS

Alloy Base	Net Weight, Kilograms
Aluminum	0.45, 2.3, 4.5, 5.7, 6.8
Magnesium	0.3, 0.5, 4.5
Titanium	0.5, 2.2, 4.5, 6.8, 9.1
Copper	0.45, 4.5, 11.3, 22.7
Steel, Corrosion and Heat Resistant Alloys	0.7, 1.1, 4.5, 5.5, 6.8, 11.3, 13.6,
and Refractory Alloys	15.9, 20, 22.7, 27.2

- 3.3.3 Exterior shipping containers of cut lengths shall contain approximately 5, 10, 50, 60, or 100 pounds (2.3, 4.5, 22.7, 27.2, or 45.3), as ordered.
- 3.3.4 Containers of wire shall be prepared for shipment in accordance with commercial practice and in compliance with applicable rules and regulations pertaining to the handling, packaging, and transportation of the wire to ensure carrier acceptance and safe delivery.
- 3.3.5 For direct U.S. Military procurement, packaging shall be in accordance with MIL-W-10430, Commercial Level, unless Level A is specified in the request for procurement.
- 3.4 Marking Each length of wire shall be marked in accordance with AMS2816, AMS2819 or other method acceptable to the purchaser. Interior containers of spools and cut lengths and all exterior shipping containers shall be marked as follows:
  - 3.4.1 Interior containers shall be permanently and legibly marked with not less than the following information; for containers of cut lengths, the information may appear on an attached label:

\_\_\_\_\_ WIRE, WELDING  
 WIRE SPECIFICATION NUMBER (and revision letter if any) \_\_\_\_\_  
 SIZE \_\_\_\_\_  
 QUANTITY \_\_\_\_\_  
 HEAT NUMBER (If applicable) \_\_\_\_\_  
 MANUFACTURER'S IDENTIFICATION \_\_\_\_\_

- 3.4.2 Exterior containers shall be permanently and legibly marked with not less than the following information:

\_\_\_\_\_ WIRE, WELDING  
 WIRE SPECIFICATION NUMBER (and revision letter if any) \_\_\_\_\_  
 SIZE \_\_\_\_\_  
 QUANTITY \_\_\_\_\_  
 HEAT NUMBER (If applicable) \_\_\_\_\_  
 PURCHASE ORDER NUMBER \_\_\_\_\_  
 MANUFACTURER'S IDENTIFICATION \_\_\_\_\_  
 PACKAGED PER AMS2813 \_\_\_\_\_