

**AEROSPACE
MATERIAL
SPECIFICATION**

SAE AMS3100/2B

Issued 1986-07
Reaffirmed 2004-02
Cancelled 2008-12

Superseding AMS3100/2A

Adhesion Promoter
For Polysulfide Sealing Compounds
Nonrestricted Solvent

RATIONALE

This slash sheet was incorporated into the basic specification AMS3100B.

This specification has been declared "CANCELLED" by the Aerospace Materials Division, SAE, as of December 2008 and has been superseded by AMS3100B. The requirements of the latest issue of AMS3100B shall be fulfilled whenever reference is made to the cancelled AMS3100/2A. By this action, this document will remain listed in the Numerical Section of the Index of Aerospace Material Specifications, noting that it has been superseded by AMS3100B.

SAENORM.COM : Click to view the full PDF of AMS3100_2b

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2008 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AMS3100/2B>**

AMS 3100/2A**SAE****AMS 3100/2A****3.3 Properties:**

Adhesion promoter shall have the following properties, determined in accordance with test methods listed in AMS 3100:

3.3.1 Color: Adhesion promoter shall be tinted red and shall impart a red stain on the substrate when tested for color.

3.3.2 Peel Strength: Shall be as specified in Table 1.

3.3.2.1 Acceptance peel strength tests shall consist of either of the following, using as-received adhesion promoter only:

Test 1 - substrate 4.5.2.1.5 and Test 2 - substrates 4.5.2.1.4 and 4.5.2.1.5; or
Test 1 - substrate 4.5.2.1.3 and Test 2 - substrate 4.5.2.1.4

3.3.3 Storage Stability:

3.3.3.1 Long-Term Stability: Shall be as specified in Table 1, Tests 1 and 2, using substrates 4.5.2.1.3 and 4.5.2.1.5.

3.3.3.2 Short-Term Stability: Shall be as specified in Table 1, Tests 1 and 2, using substrates 4.5.2.1.3 and 4.5.2.1.5 after standing for 168 hours.

3.3.4 Aging After Application: Shall be as specified in Table 1, Tests 1 and 2, using substrates 4.5.2.1.3 and 4.5.2.1.5.

3.3.5 Composition Control: Infrared spectrogram shall agree with that obtained on the preproduction (qualification) sample. Any variance of composition greater than $\pm 5\%$ from the originally approved sample is not acceptable.

3.3.6 Solvent Identification: Solvent may contain halogenated compounds.

4. QUALITY ASSURANCE PROVISIONS:

See AMS 3100.

5. PREPARATION FOR DELIVERY:

See AMS 3100.

6. ACKNOWLEDGMENT:

See AMS 3100.