

WEBBING, WOVEN NYLON
For Decelerators
1-3/4 (44) Wide, 10,000 (44,500) Breaking Strength

1. SCOPE:

1.1 Form: This specification covers one width and one strength of nylon webbing.

1.2 Application: Primarily for use in construction of decelerators.

1.3 Classification: 1-3/4 in. (44 mm) wide nylon webbing having 10,000 lb (44,500 N) breaking strength.

2. APPLICABLE DOCUMENTS: See AMS 3718.

3. TECHNICAL REQUIREMENTS:

3.1 Basic Specification: The complete requirements for procuring the webbing described herein shall consist of this document and the latest issue of the basic specification, AMS 3718.

3.2 Construction and Properties: Shall be as specified in Table I and the following:

3.2.1 Weave: Shall be as shown in Fig. 1, a 5 up, 1 down, 1 up, 5 down herringbone twill with one reversal at the center of the webbing.

4. QUALITY ASSURANCE PROVISIONS: See AMS 3718.

5. PREPARATION FOR DELIVERY: See AMS 3718.

6. ACKNOWLEDGMENT: See AMS 3718.

7. REJECTIONS: See AMS 3718.

8. NOTES: See AMS 3718.

REAFFIRMED

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.