

Submitted for recognition as an American National Standard

TAPE AND WEBBING, TEXTILE, PARA-ARAMID
Intermediate Modulus

3/4 in. (19 mm), 0.11 to 0.60 oz per yd (3.4 to 18.6 g/m)

1. SCOPE:

1.1 Form: This specification covers three classes of para-aramid tape and webbing of a single width and with varying weights.

1.2 Application: Primarily for use in cargo type parachutes.

1.3 Classification: Width of 3/4 in. \pm 1/16 (19 mm \pm 1.5) and three weight classes as follows:

Class	Weight, max	
	oz per yd	g/m
1	0.11	3.4
2	0.50	15.5
3	0.60	18.6

2. APPLICABLE DOCUMENTS: See AMS 3793.

3. TECHNICAL REQUIREMENTS:

3.1 Basic Specification: The complete requirements for procuring the tape and webbing described herein shall consist of this document and the latest issue of the basic specification, AMS 3793.

3.2 Properties: Tape and webbing shall conform to the requirements of Table I and the following:

3.2.1 Width: Shall be 3/4 in. \pm 1/16 (19 mm \pm 1.5).

3.2.2 Weight: Shall be as specified in 1.3 for the class ordered.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.