

SAE-AMS3814/10

ADOPTION NOTICE

SAE-AMS3814/10, "Cord, Coreless, Para-Aramid Intermediate Modulus 3500 lb (15 570 N), 67 ft per lb (45 m/kg)", was adopted on 31-AUG-95 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, Defense Industrial Supply Center, 700 Robbins Avenue, Philadelphia, PA 19111-5096. DoD activities may obtain copies of this standard from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other Government agencies may purchase copies from the Society of Automotive Engineers Inc., 400 Commonwealth Drive, Warrendale, PA 15096-0001.

Custodians:

Army - GL
 Navy - SH
 Air Force - 99
 DLA - IS

Adopting Activities:

DLA - IS
 (Project 4020-0353)

SAENORM.COM : Click to view the full PDF of SAE-AMS3814-10

FSC 4020

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.



400 Commonwealth Dr., Warrendale, PA 15096

AEROSPACE MATERIAL SPECIFICATION

SAE AMS 3814/10

Issued 7-1-86

Submitted for recognition as an American National Standard

CORD, CORELESS, PARA-ARAMID
Intermediate Modulus
3500 lb (15 570 N), 67 ft per lb (45 m/kg)

1. SCOPE:

- 1.1 Form: This specification covers one strength and weight of braided para-aramid cord.
- 1.2 Application: Primarily for use in cargo type parachutes.
- 1.3 Classification: The minimum breaking strength is 3500 lb (15 570 N) and the minimum weight is 67 ft per lb (45 m/kg).

2. APPLICABLE DOCUMENTS: See AMS 3814.

3. TECHNICAL REQUIREMENTS:

- 3.1 Basic Specification: The complete requirements for procuring the cord described herein shall consist of this document and the latest issue of the basic specification, AMS 3814.
- 3.2 Properties: Cord shall conform to the following requirements:
- | | |
|--|------------------------|
| 3.2.1 Breaking Strength, min | 3500 lb (15 570 N) |
| 3.2.2 Weight, min | 67 ft per lb (45 m/kg) |
| 3.2.3 Number of Carriers | 16 |
| 3.2.4 Distance Between Carrier Run-Offs, min | 5 ft (1.5 m) |
| 3.2.5 Ends per Carrier | 1 |

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.