

CLOTH, UPHOLSTERY, FLAME RESISTANT
Novoloid/Aramid, Waffle Type Weave

1. SCOPE:

- 1.1 Form: This specification covers one weight and one weave of novoloid/aramid cloth.
- 1.2 Application: Primarily for use in upholstering aircraft seats.
- 1.3 Classification: Novoloid/aramid cloth with a honeycomb or waffle type weave.

2. APPLICABLE DOCUMENTS: See AMS 3856.

3. TECHNICAL REQUIREMENTS:

- 3.1 Basic Specification: The complete requirements for procuring the cloth described herein shall consist of this document and the latest issue of the basic specification, AMS 3856.

3.2 Construction: Shall be as follows:

- 3.2.1 Yarn: Warp yarns used in weaving the cloth shall be singles and two ply, 50/50 staple fiber blend of aramid and novoloid, and two ply, 100% aramid. Filling yarn shall be singles and two ply, 50/50 staple fiber blend of aramid and novoloid.

3.2.2 Cloth:

- 3.2.2.1 Weave: Shall be honeycomb or waffle type.
- 3.2.2.2 Color: Shall be natural. (The novoloid fiber is a tan color.)
- 3.2.2.3 Width: Shall be 54 in. (1,350 mm) exclusive of selvages.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

AMS documents are protected under United States and international copyright laws. Reproduction of these documents by any means is strictly prohibited without the written consent of the publisher.