

# AERONAUTICAL MATERIAL SPECIFICATIONS

## AMS 7205A

SOCIETY OF AUTOMOTIVE ENGINEERS, Inc. 485 Lexington Ave., New York 17, N.Y.

Issued 11-1-52  
Revised 7-1-57

### SPRING PINS, TUBULAR, STEEL

1. **ACKNOWLEDGMENT:** A vendor shall mention this specification number and its revision letter in all quotations and when acknowledging purchase orders.
2. **TYPE:** Tubular shaped pins having a full-length longitudinal slot to permit flexure when inserted in a hole.
3. **APPLICATION:** Primarily to provide a pin with sufficient flexure to remain tight against the inner surface of a hole into which it has been inserted, after adjusting itself to the hole tolerances.
4. **MATERIAL:** Unless otherwise specified, steel strip in accordance with the latest issue of AMS 5120 or AMS 5121.
5. **TECHNICAL REQUIREMENTS:**
  - 5.1 **Shear Strength:** Shall be not lower than the value specified below when tested in double shear, in holes of the respective size shown.

Nominal Pin Diameter Inch	Hole Diameter Inch	Double Shear Strength lb, min
0.062	0.064 - 0.065	425
0.078	0.080 - 0.081	650
0.094	0.096 - 0.097	1,000
0.125	0.128 - 0.129	2,100
0.156	0.160 - 0.161	3,000
0.188	0.191 - 0.192	4,400
0.219	0.223 - 0.224	5,700
0.250	0.255 - 0.256	7,700
0.312	0.317 - 0.318	11,500
0.375	0.381 - 0.382	17,600
0.438	0.445 - 0.446	20,000
0.500	0.509 - 0.510	25,800

- 5.1.1 For intermediate sizes, the minimum hole diameter and minimum double shear strength may be determined by interpolation in the above table; the maximum hole diameter shall be 0.001 in. greater than the minimum.
- 5.1.2 **Procedure:** The shear plane shall be at least one pin diameter away from each end of the pin. The pin slot shall be located approximately 90 deg to the line of application of force. Pins too short to test in double shear shall be tested by placing two pins in single shear simultaneously. The clearance between loading member and supporting member shall be not greater than 0.005 inch. The pin supports and bushing for applying load shall each have hardness not lower than Rockwell C 58 or equivalent.

Section 7C of the SAE Technical Board rules provides that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report, in formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."