

Issued 1983-04-04
Revised 1991-04-05
Reaffirmed 2007-12

**SELF-SEALING BREAKAWAY VALVES FOR
CRASH-RESISTANT AIRCRAFT FUEL AND OIL SYSTEMS**

TABLE OF CONTENTS

1. SCOPE	2
2. REFERENCES	2
3. REQUIREMENTS	3
4. QUALITY ASSURANCE PROVISIONS	9
5. PREPARATION FOR DELIVERY	16
6. NOTES	18

SAENORM.COM : Click to view the full PDF of arp1616a

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

SAE ARP1616 Revision A

1. SCOPE:

1.1 This document defines design, performance, and test criteria for self-sealing breakaway valves for use in crash-resistant aircraft fuel systems.

2. REFERENCES:

2.1 Applicable Documents:

The following documents of issue in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein. In the event of conflict between these documents and the text of this document, the latter shall govern.

2.1.1 SAE Publications: Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

ARP868 Pressure Drop Test for Fuel System Components
AS1055 Fire Testing of Flexible Hose Tube Assemblies, Coils, Fittings & Similar System Components

2.1.2 Military Publications: Available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-276	Impregnation of Porous, Nonferrous Metal Castings
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-889	Dissimilar Metals
MIL-STD-970	Standards and Specification, Order of Preference for the Selection of
MIL-STD-1290	Light Fixed - and Rotary-Wing Aircraft Crashworthiness
MIL-STD-2073-1	DOD Material, Procedures for Development and Application of Packaging Requirements
MIL-STD-2175	Castings, Classification and Inspection of
MIL-STD-45662	Calibration System Requirements
MS20995	Wire, Safety or Lock
MS33540	Safety Wiring and Cotter Pinning, General Practices for
MS33588	Nuts, Self-Locking, Aircraft, Reliability and Maintainability Usage Requirements for
MIL-A-8625	Anodic Coatings, for Aluminum and Aluminum Alloys
MIL-B-5087	Bonding, Electrical, and Lightning Protection, for Aerospace Systems
MIL-C-7024	Calibrating Fluid for Aircraft Fuel System Components
MIL-F-8615	Fuel System Components, General Specification for
MIL-I-8500	Interchangeability and Replaceability, Physical, of Component Parts for Aerospace Vehicles
MIL-N-25027	Nut, Self Locking, 250 Degree F, 450 Degree F, and 800 Degree F, 125 Ksi Ft _u , 60 Ksi Ft _u , and 30 Ksi Ft _u

SAE ARP1616 Revision A

2.1.2 (Continued)

MIL-S-7742	Screw Threads, Standard, Optimum Selected Series, General Specification for
MIL-S-8879	Screw Threads, Controlled Radius Root with Increased Minor Diameter; General Specification for
MIL-T-5624	Turbine Fuel, Aviation, Grades JP-4 and JP-5
MIL-T-31000	Technical Data Packages, General Specification for
MIL-T-83133	Turbine Fuel, Aviation, Kerosene Type, Grade JP-8

2.1.3 U.S. Government Publications: Available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

P-D-680	Dry Cleaning and Degreasing Solvent
QQ-A-367	Aluminum Alloy Forgings
QQ-S-763	Steel Bars, Wire, Shapes, and Forgings, Corrosion Resisting
TT-S-735	Standard Test Fluids, Hydrocarbon

FED-STD-No. 595 Colors

2.1.4 ASTM Publications: Available from ASTM, 1916 Race Street, Philadelphia, PA 19103.

ASTM D 910	Standard Specification for Aviation Gasoline
ASTM D 1655	Standard Specification for Aviation Turbine Fuels

3. REQUIREMENTS:

3.1 Quality Assurance:

This document makes provisions for recommended qualification and quality conformance testing.

3.2 Description:

The requirement of this section applies to the design of breakaway self-sealing valves including the performance and design of the self-sealing mechanism and the frangible section of the valve.

SAE ARP1616 Revision A

3.3 Materials:

Materials and processes used by the manufacturer of fuel system components shall conform to applicable Government and Industry Documents. Materials conforming to contractor's documents may be used, provided prior approval is obtained from the procuring activity. The use of contractor's documents shall not constitute waiver of Government inspection. All materials used in the component shall be sufficiently resistant to liquids shown in 3.8.3.

3.3.1 Selection of Materials: Specifications and standards for all materials, parts, and processes which are not specifically designated herein and which are necessary for the execution of this specification shall be selected in accordance with MIL-STD-970.

3.3.2 Metals: All metals used in the construction of fuel-system components that are not of a corrosion-resistant type shall be suitably protected to resist corrosion during the normal service life of the component. Unless suitably protected against electrolytic corrosion, dissimilar metals as defined in MIL-STD-889 shall not be used in intimate contact with each other. Magnesium shall not be used in fuel system components. Cadmium plate and copper shall not be used where in contact with fuel.

3.3.3 Castings: Classification and inspection of ferrous and non-ferrous metal castings shall be in accordance with MIL-STD-2175. If necessary to prevent leakage due to porosity, parts shall be treated in accordance with MIL-STD-276.

3.3.4 Forgings: Forgings shall be in accordance with QQ-A-367 or QQ-S-763.

3.3.5 Fungus-Proof Materials: Materials that are nutrients for fungi shall not be used.

3.4 Finish:

Anodizing, plating, protective treatment, and painting of fuel system components shall be as specified in the model specification and applicable detail drawings.

3.5 Identification of Product:

Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.6 Color Identification:

Each fuel system component shall be identified by a red color, in approximate conformance with Federal Standard No. 595, color number 11136. The color shall be permanent and, when applied to parts that may come in contact with fuel, shall not soften, chip, crack, or cause the fuel to be affected in any way. The entire component may be red anodized but not less than 20% of the external surface area of the component shall be red.

SAE ARP1616 Revision A

3.7 Parts:

- 3.7.1 Standard Parts: Standard parts (MS, AN or NAS) shall be used wherever they are suitable for the purpose and shall be identified on the drawing by their part number. Commercial utility parts; i.e., screws, bolts, nuts, and cotter pins, may be used, provided; (1) they possess suitable properties and are replaceable by the standard parts without alteration, and (2) the corresponding standard number is referenced in the parts list and, if practicable, on the vendor's drawing. In event there are not suitable corresponding standard parts in effect on date of invitation for bids, commercial parts may be used if they conform to all requirements of this specification.
- 3.7.2 Threaded Parts: Threads shall be in accordance with MIL-S-8879 or MIL-S-7742. The use of pipe threads is prohibited.
- 3.7.3 Locking of Parts: All threaded parts shall be locked by safety wiring, self-locking nuts, cotter pins, or other methods approved by the procuring activity. Safety wiring shall be installed in accordance with MS33540 and shall conform to MS20995. Self-locking nuts shall be in accordance with MIL-N-25027 and MS33588. Lockwashers or staking are not permitted. Components installed within a fuel cell shall not have safety wire.

3.8 Design and Construction:

The valve frangible mechanisms shall be designed to meet all operational and service forces of the aircraft while being designed to separate at a predetermined point and load. Upon separation, internal self-sealing mechanisms in each valve section shall automatically close and seal, preventing leakage of system fluids. The design shall consider visual indication of valve position and a means to prevent external leakage after separation due to foreign object contact with the sealing mechanisms. Provisions shall be designed into the valve to prevent fuel leakage in the event of a partial fracture of the frangible section before the valve closes. Spillage during separation and valve closure shall not exceed the values listed in Table 1. The design of the valve shall be such that no external power source or control is required for valve closure.

SAE ARP1616 Revision A

TABLE 1 - Flow, Pressure Loss and Spillage

Valve Size Dia, Inches	Flow Rate GPM	Press. Loss @ 75°F psi Max	Spillage CC
1/2	10	4.0	3
3/4	20	4.0	8
1	50	4.0	19
1 1/4	80	4.0	38
1 1/2	120	4.0	65
2	200	4.0	150
2 1/2	250	3.0	300
3	300	3.0	520

- 3.8.1 Valve Configuration: The outside configuration of the valve, such as the method of mounting, the types of fluid connections, and the permissible envelope, shall be prescribed by the procuring activity to meet the specific needs of each fuel system.
- 3.8.2 Construction: The valves shall be constructed to withstand the strains, jars, vibrations, and other conditions as specified in MIL-STD-1290 for crashworthy fuel system. The valves shall not require, except for initial preservation, special treatment or controlled environment during storage.
- 3.8.3 Fluid Media: The valves shall be suitable for use with liquids conforming to specifications ASTM D 910; ASTM D 1655; MIL-T-5624; MIL-T-83133; MIL-C-7024 Type II; and P-D-680 Type II.
- 3.8.4 Bonding: Electrical continuity of 1.0 ohm maximum electrical resistance is required through the valve assemblies from one end to the other per MIL-B-5087 Type S.
- 3.9 Performance Characteristics:
- 3.9.1 Rated Pressure Range: The valve shall operate in the pressure range from -5 to 60 psig or the maximum anticipated fuel system operating pressure, whichever is greater.
- 3.9.2 Rated Temperature Range: The valve shall function in the fuel temperature range of -65 to +160°F or the maximum anticipated fuel temperature, whichever is greater, and in an ambient temperature range required by MIL-F-8615.

SAE ARP1616 Revision A

3.9.3 Performance: The breakaway valves shall satisfy the following performance requirements when subjected to the applicable tests specified in Section 4 and in the procuring activity's specification.

3.9.3.1 Functional - Prior to Valve Separation:

3.9.3.1.1 Proof and Leakage: There shall be no external leakage when subjected to the proof and leakage tests of 4.6.2.2.

3.9.3.1.2 Negative Pressure Leakage: There shall be no measurable inward leakage when an internal pressure of -5 psi is applied for a period of 5 min as per 4.6.2.3.

3.9.3.1.3 Pressure Loss: The pressure loss shall meet the maximum shown in Table 1 unless otherwise specified by the procuring activity. The pressure drop shall be determined in accordance with ARP868 and shall not exceed the specified pressure loss when subjected to the test of 4.6.2.4, using JP5 or corrected to the specific gravity of JP5.

3.9.3.2 Functional - After Valve Separation (Complete or Partial):

3.9.3.2.1 Proof and Leakage: External leakage shall not exceed the specified amount when each separated valve section is subjected to the leakage test of 4.6.3.

3.9.3.3 Surge Flow: The valve shall not close nor shall there be any evidence of failure or loosening of parts following the surge flow test of 4.6.4.

3.9.3.4 Fungus: The valve shall function properly and there shall be no evidence of deterioration following the fungus test of 4.6.5.

3.9.3.5 Corrosion Resistance: The valve shall function properly following the accelerated corrosion test of 4.6.6.

3.9.3.6 Contaminated Fuel Endurance: Following the contamination fuel endurance test of 4.6.7, the valve shall satisfactorily pass the proof and external leakage test of 4.6.2.2.

3.9.3.7 Fuel Resistance and Extreme Temperature: There shall be no external evidence of failure, corrosion, degradation in performance, or self-sealing capability when the valve is subjected to the applicable test of 4.6.8.

3.9.3.8 Vibration: The valve shall not close nor shall there be any evidence of structural failure, loosening of parts, leakage, or performance degradation either during or as a result of the vibration test of 4.6.9.

3.9.3.9 Shock: The valves shall not close nor shall there be any evidence of structural failure during or following the shock test of 4.6.10.

3.9.3.10 Sand and Dust: The valve shall function as specified after being subjected to the sand and dust test of 4.6.11.

SAE ARP1616 Revision A

3.9.3.11 Disassembly and Inspection: After completion of the qualification tests, disassembly and inspection shall reveal no indication of damage or excessive wear. (See 4.6.15.)

3.9.3.12 Burst Pressure: There shall be no external leakage or valve actuation when the valve is subjected to the burst pressure test of 4.6.12.

3.9.3.13 Fire Test: The fire test, if required, shall be performed in accordance with current standard practices and equipment as specified in ASI055 and by the procuring activity.

3.9.4 Separation Criteria:

3.9.4.1 Separation Modes: The valve frangible mechanism shall separate and seal upon application of a force of 25 to 50% of the load required to fail the weakest component of the fuel system adjacent to the valve assembly, or at a level specified by the procuring activity. Separation modes may be in the form of tension, bending, shear or a combination thereof. Separation may be caused by static loads, 4.6.13 or dynamic loads, 4.6.14. During separation, spillage shall be within the limits defined in 3.8. After separation each valve section shall meet the leakage requirements of 4.6.3.

3.10 Maintainability:

3.10.1 Interchangeability: All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to installation and performance in accordance with Specification MIL-I-8500. Changes in manufacturer's part numbers shall be governed by the drawing number requirements of Specification MIL-T-31000.

3.10.2 Repairability: The valve assembly shall be designed so that no adjustments, cleaning, or repairs are required during normal service life.

3.10.3 Replaceability: The valve assembly replacement shall not require special tools, facilities, or highly skilled personnel.

3.10.4 Serviceability: The valve assembly shall be so designed that, except for preservation procedures, scheduled maintenance will not be required in order to maintain physical or functional capability.

3.10.5 Service Life: Service life shall be 10 000 flight hours or 10 calendar years, whichever comes first. Service life will be computed from date of manufacture to completion of calendar/flight-hour schedule.

SAE ARP1616 Revision A

3.11 Safety:

These valves are identified as a safety critical item and the design shall preclude all human-error/material-failure modes which could result in these hazards:

- a. Inadvertent closure of the valves
- b. Inadvertent valve re-opening
- c. Leakage
- d. Failure to close when subjected to crash impact loads defined by the procuring activity

3.12 Drawings:

Manufacturer's drawings shall conform to MIL-T-31000

3.13 Failure and Corrective Action Reporting:

Each failure detected during or following qualification or acceptance tests shall be reported to the procuring activity in the format specified by them.

4. QUALITY ASSURANCE PROVISIONS:

4.1 Responsibility for Inspection:

Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. The supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, subject to approval by the procuring activity or otherwise specified in the contract or order. The procuring activity reserves the right to perform any of the inspections set forth in the specification.

4.2 Classification of Inspections:

The inspection and testing of the valves shall be classified as follows:

- a. Qualification tests 4.3
- b. Quality conformance tests 4.4

SAE ARP1616 Revision A

4.3 Qualification Tests:

- 4.3.1 Test Samples: The qualification test samples shall be subjected to the following tests or as designated by the procuring activity. Two samples of each size shall be used as a minimum. Additional test samples may be required depending on the type of frangible section used and damage sustained during separation testing. Test samples may be repaired by replacing the frangible sections for the added separation tests. Depending on design and test methods, additional test samples may be required as agreed upon by supplier and procuring agency. Supplier assumes responsibility for reuse of a test unit after separation test and only the frangible element shall be replaced.
- 4.3.2 Test Sequence for the Test Samples: The qualification test sequence shall be as listed in Table 2.
- 4.3.3 Rejection and Retest of Qualification Test Samples: In the event of a failure during qualification testing, the procuring agency shall be notified within 24 h, testing suspended and a failure report including recommended correction be submitted as soon as possible.

Concurrence of the procuring agency shall be obtained prior to resumption of testing, indicating corrections and modifications and point of test resumption.

4.4 Quality Conformance Tests:

Quality conformance tests shall consist of the acceptance tests and sampling tests.

4.4.1 Acceptance Tests - Production Lots:

Each valve assembly shall be subjected to the following:

- | | |
|--------------------------------------|-------|
| a. Examination of Product | 4.6.1 |
| b. Functional (except pressure drop) | 4.6.2 |

SAE ARP1616 Revision A

TABLE 2 - Qualification Tests

	Requirement Paragraph	Qual. Test Paragraph	Test Unit #1	Test Sequence Test Unit #2	Test Unit #Note
Examination of Product		4.6.1	1	1	*
Fuel Resistance & Extreme Temp.	3.9.3.7	4.6.8	2	2	*
Functional, Prior to Separation	3.9.3.1	4.6.2			
Bonding	3.8.4	4.6.2.1			
Proof & External Leakage Test	3.9.3.1.1	4.6.2.2	3	3	*
Negative Pressure Leakage	3.9.3.1.2	4.6.2.3	4	4	*
Pressure Loss	3.9.3.1.3	4.6.2.4	5	5	*
Vibration	3.9.3.8	4.6.9	6		
Shock	3.9.3.9	4.6.10	7		
Corrosion Resistance	3.9.3.5	4.6.6		6	
Surge Flow	3.9.3.3	4.6.4		7	
Contaminated Fuel Endurance	3.9.3.6	4.6.7		8	
Sand & Dust	3.9.3.10	4.6.11		9	
Fungus	3.9.3.4	4.6.5		10	
Static Load Separation	3.9.4.1	4.6.13	8		*
Dynamic Load Separation	3.9.4.1	4.6.14		11	*
Functional, After Separation	3.9.3.2	4.6.3	9	12	*
Disassembly and Inspection	3.9.3.11	4.6.15	10	13	*
Burst Pressure	3.9.3.12	4.6.12	11		

NOTE: If additional test units are required, they shall be tested as marked.*

SAE ARP1616 Revision A

4.4.2 Sampling Tests - Production Lots: Two valve samples shall be selected from each lot of 100 or fraction thereof manufactured and submitted for acceptance at the same time or as specified by the procuring activity and shall be subjected to the following:

- | | |
|--|--------|
| a. Examination of Product | 4.6.1 |
| b. Functional, Prior to Valve Separation | 4.6.2 |
| c. Static Load | 4.6.13 |
| d. Functional, After Valve Separation | 4.6.3 |
| e. Disassembly and Inspection | 4.6.15 |

NOTE: One each specimen subjected to shear and one to tension load.

4.4.3 Rejection and Retest - Production Lots: Failure of any representative sample shall be cause for the rejection of the lot represented. Valve assemblies which have been rejected may be reworked to correct the defects and resubmitted for acceptance. Before resubmitting, full particulars concerning previous rejection and the action taken to correct the defects found in the original rejection shall be furnished the Procuring Activity. Valve assemblies rejected after retest shall not be submitted without the specific approval of the Procuring Activity.

4.5 Test Conditions:

Unless otherwise specified, the following test conditions shall apply during the tests performed in accordance with this specification.

- 4.5.1 Cleaning: Prior to testing any valve assemblies, all lubricants and preservative compounds, except permanent protective coatings such as paint, shall be removed from the external parts of the unit and from all internal parts which are normally wetted with fuel.
- 4.5.2 Test Fluid: Unless otherwise specified, the test fluid shall be in accordance with TT-S-735; P-D-680 Type II; or MIL-C-7024 Type II.
- 4.5.3 Room Temperature and Pressure: Unless otherwise specified, all tests shall be conducted at temperatures of 60 to 90°F and at local barometric pressure.
- 4.5.4 Temperature Tolerance: Unless otherwise specified, the temperature tolerances in Table 3 shall be maintained:

TABLE 3 - Temperature Tolerances

Specified Temperature	Tolerance
Above 100°F	± 10°F
Below 100°F	± 5°F

SAE ARP1616 Revision A

- 4.5.5 Attitude: Unless otherwise specified, all tests shall be conducted with the valve assembly mounted in the attitude specified by the procuring activity.
- 4.5.6 Test Equipment Calibration: Test equipment required to perform the testing described herein shall be calibrated within the specified periods established by MIL-STD-45662. Ranges and accuracy of instrumentation shall be capable of providing test data within the specified tolerances.
- 4.6 Test Methods:
- 4.6.1 Examination of Product: Each valve assembly submitted for acceptance shall be carefully examined to determine its conformance to the requirements of the specification and the procuring activity requirements. This examination should include, but not necessarily be limited to, envelope dimensions, weight, materials, and finishes.
- 4.6.2 Functional, Prior to Valve Separation:
- 4.6.2.1 Bonding: The valve assembly shall meet the requirements of 3.8.4.
- 4.6.2.2 Proof and External Leakage Test: The valve assembly with the valves open shall be pressurized to 2 psig for 1 min, at operating pressure for 1 min and at proof pressure (twice operating) for 1 min. There shall be no evidence of leakage at any pressure, failure, malfunction, or permanent distortion at proof pressure.
- This test shall be extended to 5 min at each pressure for qualification testing.
- 4.6.2.3 Negative Pressure Leakage (as applicable): The valve shall be installed in a minimum volume test system and an internal pressure of -5 psi locked in for a period of 5 min. Temperatures shall be maintained constant within $\pm 2^\circ\text{F}$ and the pressure observed during this period. There shall be no measurable leakage (reduction in pressure reading in excess of 0.5 psig) during this period. This is a qualification test requirement only.
- 4.6.2.4 Pressure Loss: With the valves in the valve assembly open, test for pressure loss in accordance with SAE ARP868. Sufficient data shall be recorded to permit the plotting of curves. The pressure loss graph shall show the net pressure loss versus flow rate of the valve assembly using test fluids as specified by the procuring activity. The pressure loss shall not exceed the pressure loss specified in Table 1 or as specified by the procuring activity.
- 4.6.3 Functional, After Valve Separation: Each valve section with the self-sealing mechanisms closed shall be pressurized at 2 psig for 5 min then gradually increased to proof pressure and held for 5 min. No external valve leakage in excess of 1 drop per minute is allowed. There shall be no failure, malfunction or permanent distortion at proof pressure.

SAE ARP1616 Revision A

- 4.6.4 **Surge Flow:** A complete valve shall be subjected to a flow of two times the rated flow in the normal flow direction for 5 s minimum. This surge flow pattern shall be repeated 20 times; 10 in each direction. The valve shall be examined for evidence of flow blockage, internal damage, and then subjected to the leakage test of 4.6.2.2 and the pressure drop test of 4.6.2.4.
- 4.6.5 **Fungus:** A valve assembly shall be subjected to the fungus test of MIL-STD-810, Method 508.3. If there are no fungus-supporting nutrients, this requirement may be satisfied by certification.
- 4.6.6 **Corrosion Resistance:** The complete valve shall be subjected to the corrosion resistance test of MIL-F-8615.
- 4.6.7 **Contaminated Fuel Endurance:** A test fluid in accordance with TT-S-735, Type I, containing contaminants at the concentration specified in MIL-F-8615 shall be circulated through the unit for a period of 2.5 h. Flow shall be approximately one half the rate specified in Table 1. Upon completion of the tests, the unit shall be subjected to the leakage tests of 4.6.2.2 herein.
- 4.6.8 **Fuel Resistance and Extreme Temperature:** The valve shall be subjected to the fuel resistance and extreme temperature test as shown in Table 4.

The tests shall be conducted in a continuous manner and each period shall follow the preceding one in the order listed. The soak period for each phase shall be conducted with the connected couplings totally immersed continuously in the specified fluid with the ports open. For the dry periods, the coupled couplings shall be drained, without disconnecting, and blown dry with the ports open and placed in a test chamber having air at specified temperature (160°F) continuously circulating around the test specimen.

At the conclusion of each soak and dry period the coupling shall be subjected to the proof and leak test of 4.6.2.2. The tests following Phase I and II shall be conducted at room temperature using the fluids shown in Table 4. The tests following Phase III shall be conducted at the soak temperature, then repeated at room temperature.

- 4.6.9 **Vibration Test:** The vibration test shall be performed in accordance with the applicable vibration tests of MIL-STD-810, Method 514.3 or as specified by the procuring activity. The valve shall be subjected to the functional tests of 4.6.2 upon completion of the vibration tests. There shall be no evidence of structural failure or loosening of parts.