

I. PURPOSE: This Aeronautical Recommended Practice has been prepared in an attempt to effect a standard method of numbering aircraft engine cylinders.

II. DEFINITIONS:

A. ROW

A group of cylinders arranged in a common plane at right angles to the axis of the crankshaft.

B. BANK

A group of cylinders arranged in a common plane parallel to the axis of the crankshaft.

C. BLOCK

A more or less integral group of cylinders constituting an entire bank or a part of a bank of cylinders.

D. PROP END

That end of the engine to which the propeller is attached or the end from which the power is applied either directly or indirectly to the propeller or other points of application, also known as the front of the engine.

E. ANTI-PROP END

The end of the engine opposite the prop end, also known as the rear of the engine.

F. CLOCKWISE

Comparable to the direction of rotation of the hands of a clock as viewed from the anti-prop end.

G. COUNTER-CLOCKWISE

The opposite direction of clockwise as viewed from the anti-prop end.

III. DESIGNATIONS OF ENGINES:

A. SINGLE BANK IN-LINE ENGINE

A multi-cylinder engine consisting of a bank of cylinders mounted in line along a common crankcase.

B. MULTI-BANK IN-LINE ENGINE

An engine basically similar to a single bank in-line engine except for additional banks.

REAFFIRMED

Page 2 of 3 pages

C. SINGLE-ROW RADIAL ENGINE

An engine having three or more cylinders arranged radially in one row at substantially equal angular intervals operating on a common crankpin.

D. MULTI-ROW RADIAL ENGINE

An engine basically similar to single row radial engines except having additional rows of cylinders.

IV. NUMBERING OF ENGINE CYLINDERS:

A. NUMBERING SINGLE BANK IN-LINE ENGINES

The cylinders are numbered consecutively beginning with number one for the cylinder at the anti-propeller end.

B. NUMBERING MULTI-BANK IN-LINE ENGINES

The banks are given letters in a clockwise direction starting with A beginning with the bank at top vertical center, or beginning with the bank nearest to top center moving in a clockwise direction. The cylinders are numbered consecutively beginning with number one for the cylinder at the anti-propeller end of each bank.

C. NUMBERING SINGLE-ROW RADIAL ENGINES

The cylinders are numbered consecutively in a clockwise direction beginning with the cylinder at top vertical center, or beginning with the cylinder nearest to top center moving in a clockwise direction.

D. NUMBERING MULTI-ROW RADIAL ENGINES

When the succeeding rows of such engines are staggered they will be considered as a series of single row radial engines and numbered in the same manner, and rows given letters as A, B, C, D, E, beginning with A at anti-propeller end or rear of engine. When the succeeding rows are not staggered they will be considered as an In-Line Engine and cylinders and banks designated accordingly.

THE NUMBERING OF CYLINDERS AND DESIGNATION OF BANKS IS IRRESPECTIVE OF CRANKSHAFT ROTATION.