

Issued 1988-07
Revised 2000-04
Reaffirmed 2007-07

Superseding ARP4102/14A

Full-Format Printer

RATIONALE

This document has been reaffirmed to comply with the SAE 5-Year Review policy.

1. SCOPE:

This document recommends criteria for the installation and operation of a printer intended for use by flight crew members on the flight deck. The printer is used to supply the flight crew with hard copies of information that originates from data sources such as FMS, EDMS, ACMS, CMS, and data link.

These criteria are in addition to the specifications of the referenced ARINC Characteristic 744A.

2. REFERENCES:

2.1 Documentation:

This annex should be used in conjunction with ARP4102 core document. In addition, the following documents are applicable:

SAE ARP4101, Flight Deck Layout and Facilities
SAE ARP4102/13, Data Link
SAE ARP4102/15, Electronic Library System
SAE ARP4103, Flight Deck Lighting
SAE ARP4105, Nomenclature and Acronyms
SAE S-7 Draft ARP, Electronic Data Management System (EDMS)
ARINC Characteristic 744A

3. OPERATIONAL REQUIREMENTS:

3.1 The printer's controls, output and means of loading output medium should be accessible to both pilots, flight deck space and lay-out permitting.

3.2 The printer should have the capability to print in multiple colors if it is intended to print charts.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2007 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: http://www.sae.org

SAE ARP4102/14 Revision B

- 3.3 It should be possible for the crew easily to obtain an undamaged printout. To achieve this requirement, it may be necessary for the printer to incorporate a cutting, perforating, or tearing device. The printout should be easy to tear off from any angle.
 - 3.4 The printer should recognize and respond to a crew request to print multiple copies.
 - 3.5 If an automatic printing facility is provided, any annunciation of this function should be inhibited during takeoff and landing phases. Automatic printer activation may be inhibited during takeoff and landing.
 - 3.6 It should be possible to cancel individual printing tasks.
 - 3.7 The print resolution should support comfortable reading of the printout by the flight crew under the full range of lighting conditions anticipated for normal operations on the flight deck. This should be no worse than that provided by existing printed materials.
 - 3.8 Adequate warning of expiry of consumable media such as paper or ink should be given, such that the possibility of being unable to obtain printed output during a flight is precluded.
 - 3.9 The crew should be able to replace any consumable media with a minimum of effort. It is suggested that the paper roll, for example, needs only to be inserted into the printer and an automatic feature will properly thread the paper, rather than the crew having to perform this task.
 - 3.10 The possibility of printer jams should be minimized, due to safety criticality of the printed output. If and when a jam occurs, it must be easy to open and reload.
4. PANELS:
- 4.1 Panel placement and output direction should not cause normal amounts of output medium to obscure any flight critical controls or displays.
5. CONTROLS:
- 5.1 The print command control(s) should be on the control panel of the originating data display(s) and should be accessible to both pilots.
 - 5.2 Controls should be provided to carry out at least the following tasks: stop, re-task, and resume printing.
6. DISPLAYS:
- 6.1 If the response from an initial request for printing is not essentially immediate (e.g., within 3 s) then an indication that the print request has been accepted must be provided.