

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE RECOMMENDED PRACTICE

SAE ARP4768

Issued 1993-04-07

Submitted for recognition as an American National Standard

AUTOMATIC TEST EQUIPMENT, RELAYS NOT FULLY RATED 25 AMPERES OR BELOW, AEROSPACE RECOMMENDED PRACTICE FOR

1. SCOPE:

This SAE Aerospace Recommended Practice (ARP) is intended to be a guide for defining automatic test equipment (ATE) methods to be used in performing electrical acceptance tests to ensure repeatability and compatibility of results between manufacturers and between manufacturer and user.

2. APPLICABLE DOCUMENTS:

2.1 SAE Publications:

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

ARD50031 General Specification for 270 V DC Relays

2.2 Military Specifications:

Available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

MIL-R-5757	Relays, Electromagnetic, General Specification for
MIL-R-6106	Relays, Electromagnetic, General Specification for
MIL-R-28776	Relays, Hybrid, Established Reliability, General Specification for
MIL-R-39016	Relays, Electromagnetic, Established Reliability, General Specification for
MIL-R-83536	Relays, Electromagnetic, Established Reliability, General Specification for
MIL-R-83725	Relays, Vacuum, General Specification for
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts
MIL-STD-704	Aircraft Electric Power Characteristics
MIL-STD-45662	Calibration Systems Requirements

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAE ARP4768

2.3 ANSI Publications:

Available from American National Standards Institute, 11 West 42nd Street, New York, NY 10036.

ANSI Y10.19 Letter Symbols for Units Used in Science and Technology
ANSI/IEEE STD 100 IEEE Standard Dictionary of Electrical and Electronic Terms

2.4 Other Documents:

Relay Engineer's Handbook

2.5 Definitions:

The definitions as stated in the Relay Engineer's Handbook shall apply unless otherwise stated herein.

3. PERFORMANCE REQUIREMENTS:

3.1 Pickup Voltage (Nonlatching Type Relays):

Pickup voltage shall be measured on the ATE by either linear ramp or step voltage methods as follows.

3.1.1 Linear Ramp Method:

3.1.1.1 Procedure: Apply the coil voltage in a steady, linear increasing manner until all contacts transfer, i.e., when all NC contacts open and/or all NO contacts close (pickup voltage).

NOTE: The coil voltage ramp may be started at a value other than zero (programmed value) in order to facilitate the testing time, and must end by the maximum rated coil voltage as a safety feature.

3.1.1.2 ATE Details: The ATE shall be capable of providing a programmable value of slope rate equal to $25\% \pm 5\%$ of rated volts/second. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC maximum open circuit voltage. The data returned from this test shall be the value at which all contacts transfer and pass/fail indication.

3.1.2 Step Method:

3.1.2.1 Procedure: Step the coil voltage directly to the specified pickup voltage value, checking for pickup voltage completion, i.e., when all NO contacts open and/or all NO contacts close.

SAE ARP4768

3.1.2.2 ATE Details: The ATE shall be capable of providing a single drive value. Any subsequent stepping must end by the maximum rated coil voltage as a safety feature. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC open circuit voltage maximum. The data returned from this test shall be a pass/fail indication only.

3.2 Latch and Reset Voltage (Latching Type Relays):

Latch or reset voltage shall be measured on the ATE by either linear ramp or step voltage methods as follows.

3.2.1 Linear Ramp Method:

3.2.1.1 Procedure: Apply rated coil voltage to establish the last energized (or reset) position of the contacts. Apply voltage to the latch coil as in 3.1.1. At the completion of the measurement apply rated coil voltage to the latch coil. Apply voltage to the reset coil as in 3.1.1. At the completion of the measurement apply rated coil voltage to the reset coil.

3.2.1.2 ATE Details: Same as in 3.1.1.

3.2.2 Step Method:

3.2.2.1 Procedure: Apply rated coil voltage to establish the last energized (or reset) position of the contacts. Apply voltage to the latch coil as in 3.1.2. At the completion of the measurement apply rated coil voltage to the latch coil. Apply voltage to the reset coil as in 3.1.2. At the completion of the measurement apply rated coil voltage to the reset coil.

3.2.2.2 ATE Details: Same as in 3.1.2.

3.3 Hold Voltage (Not Applicable to Latching Type Relays):

Hold voltage shall be tested on the ATE by either linear ramp or step voltage methods as follows.

3.3.1 Linear Ramp Method:

3.3.1.1 Procedure: Rated voltage shall be applied to the coil then ramped toward zero until the first indication of change of state of any contact occurs.

3.3.1.2 ATE Details: The ATE shall be capable of providing a programmable slope rate equal to $25\% \pm 5\%$ of rated volts/second. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC maximum open circuit voltage. The data returned from this test shall be the value of voltage at which the first indication of change of state of any contact occurs and pass/fail indications.

SAE ARP4768

3.3.2 Step Method:

3.3.2.1 Procedure: Rated voltage shall be applied to the coil, then stepped directly to the specified hold voltage, at which point no change of state of any contact shall have occurred.

3.3.2.2 ATE Details: The ATE shall be capable of providing a minimum of one drive value. The voltage stepping must include the rated or maximum rated (programmed value) as a safety feature. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC maximum open circuit voltage. The data returned from this test shall be a pass/fail indication only.

3.4 Dropout Voltage (Not Applicable to Latching Type Relays):

Dropout voltage shall be tested on the ATE by either linear ramp or step voltage methods as follows.

3.4.1 Linear Ramp Method:

3.4.1.1 Procedure: Rated voltage shall be applied to the coil, then ramped toward zero until all contacts transfer, i.e., when all NC contacts close and/or all NO contacts open.

3.4.1.2 ATE Details: The ATE shall be capable of providing a programmable slope rate equal to $25\% \pm 5\%$ of rated volts/second. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC maximum open circuit voltage. The data returned from this test shall be the value of voltage at which all the contacts transfer and pass/fail indication.

3.4.2 Step Method:

3.4.2.1 Procedure: Rated voltage shall be applied to the coil, then stepped directly to the specified dropout voltage at which point all contacts shall have transferred.

3.4.2.2 ATE Details: The ATE shall be capable of providing a minimum of one drive value. The voltage stepping must include the rated or maximum rated (programmed value) as a safety feature. The ATE shall provide programmable values of contact loading no greater than 10 mA maximum, 6 V DC maximum open circuit voltage. The data returned from this test shall be a pass/fail indication only.

3.5 Coil Resistance (Applicable to Coils of DC Rated Relays without Steering Diodes):

Coil resistance shall be measured on the ATE. This test shall typically be the first performed to assure the measurement is made at the ambient temperature condition.

SAE ARP4768

3.5.1 Procedure: A test current shall be applied through the relay coil or coils (for latching relays); the voltage drop measured and resistance calculated.

3.5.2 ATE Details: The ATE shall be capable of providing test currents of 10 mdc (for coil resistance up to 5K ohms) and 1 mdc (for coil resistance over 5K ohms). The duration of application of test current shall be the minimum necessary to effect an accurate measurement, without unnecessary heating of the coil. The data returned from this test shall be the resistance value calculated from the test currents and voltages and pass/fail indication.

3.6 KAC Coil Current (Applicable to Coils of AC Rated Relays):

AC coil current shall be measured on the ATE. This test shall typically be the first performed to assure the measurement is made at the ambient temperature condition.

3.6.1 Procedure: An AC test voltage shall be applied across the relay coil or coils (for latching relays); and the current measured.

3.6.2 ATE Details: The ATE shall be capable of programming the rated AC coil voltage. The duration of voltage application shall be the minimum necessary to effect an accurate measurement, without unnecessary heating of the coil. The data returned from this test shall be rms current measured and pass/fail indication.

3.7 DC Coil Current (Applicable to Coils with Steering Diodes):

DC coil current shall be measured on the ATE. This test shall typically be the first performed to assure the measurement is made at the ambient temperature condition.

3.7.1 Procedure: An AC test voltage shall be applied across the relay coil or coils (for latching relays); and the current measured.

3.7.2 ATE Details: The ATE shall be capable of programming the rated DC coil voltage. The duration of voltage application shall be the minimum necessary to effect an accurate measurement, without unnecessary heating of the coil. The data returned from this test shall be current measured and pass/fail indication.

3.8 Contact Voltage Drop:

Contact voltage drop shall be measured on NO and NC contacts on the ATE.

3.8.1 Procedure: A DC test current shall be applied to each contact, in turn, through a four wire (Kelvin) socket connection and the resulting voltage drop measured.

SAE ARP4768

3.8.2 ATE Details: The ATE shall be capable of providing currents and voltages over the range required by the applicable specification, either internally or externally (but controlled by the ATE). The contacts shall be switched "dry", i.e., contact current shall be off until the contacts are closed and stabilized. The ATE shall be programmable for the following:

- a. The number of contacts of the relay under test.
- b. The test current and voltage.
- c. The delay time between the time current is applied and voltage drop measured (the settings range shall be sufficient to enable the current supply to reach the programmed value before the voltage measurement is effected).
- d. The voltage drop range.

The ATE shall be capable of repeating this test consecutively any number of times. The data returned from this test shall be the measured value of voltage drop at the relay terminals of each contact and pass/fail indication.

3.9 Contact Resistance:

Contact resistance shall be measured on NO and NC contacts on the ATE.

3.9.1 Procedure: A DC test current shall be applied to each contact, in turn, and the resulting voltage drop across each contact's terminals measured.

3.9.2 ATE Details: The ATE shall be capable of providing currents and voltages at the specified value per the applicable specification, either internally or externally (but controlled by the ATE). The contacts shall be switched "dry", i.e., contact current shall be off until the contacts are closed and stabilized. The ATE shall be programmable for the following:

- a. The number of contacts of the relay under test.
- b. The test current and voltage.
- c. The delay time between the time current is applied and voltage drop measured (the settings range shall be sufficient to enable the current supply to reach the programmed value before the voltage measurement is effected).
- d. The voltage drop range.

The ATE shall be capable of repeating this test consecutively any number of times. The data returned from this test shall be the calculated value of resistance through the terminals of each contact and pass/fail indication.

3.10 Operate (Latch and Reset) Time:

Operate (latch and reset) time shall be measured on the ATE on each pole individually. The contact simultaneous operation requirement associated with operate (latch and reset) time shall be determined by way of ATE software.

SAE ARP4768

- 3.10.1 Procedure: Rated voltage shall be applied to the coil, or each coil of a latching type relay, in turn, and the time interval between this application and contact transfer, i.e., when all NO movable contacts transfer to the NO fixed contacts, exclusive of any contact bouncing.
- 3.10.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage; contact load levels; number of measurements, including a selection of either maximum, average, or peak reading, and the highest value of simultaneous operation. The data returned from this test shall be the measured value of time of each contact pole, exclusive of bounce, and pass/fail indication for timing and simultaneously.
- 3.11 Release Time (Not Applicable to Latching Type Relays):
- Release time shall be measured on the ATE on each pole individually. The contact simultaneous operation requirement associated with release time shall be determined by way of ATE software.
- 3.11.1 Procedure: Rated voltage shall be applied to the coil, then removed, and the time interval between this removal and contact transfer, i.e., when all NC movable contacts transfer to the NC fixed contacts, exclusive of any contact bouncing.
- 3.11.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage; contact load levels; number of measurements, including a selection of either maximum, average, or peak reading, and the highest value of simultaneous operation. The data returned from this test shall be the measured value of time of each contact pole, exclusive of bounce, and pass/fail indication for timing and simultaneously.
- 3.12 Contact Bounce Time (During Make):
- Contact bounce time shall be measured on the ATE on all contacts, individually.
- 3.12.1 Procedure: Rated voltage shall be applied to the coil, or each of the latch and reset coils of a latching type relay, in turn, and the time interval between the first make of the operating contact and last make measured; the last make being defined as the last opening greater than 90% of the open circuit voltage with a pulse width of 10 μ s or greater.
- 3.12.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage, contact load levels, and number of measurements - including a selection of either average, maximum, or peak readings. The data returned from this test shall be the measured value of time of each contact and pass/fail indication.
- 3.13 Contact Break Bounce Time (Not Applicable to Latching Type Relays):
- Break bounce time shall be measured on the ATE for all normally open contacts, individually.

SAE ARP4768

3.13.1 Procedure: Rated voltage shall be applied to the coil, then removed, and the interval between the first break of the operating contact and the last break of the same contact measured; the last break being defined as the last opening greater than 90% of the open circuit voltage with a pulse width of 10 μ s or greater.

3.13.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage; contact load levels; and number of measurements - including a selection of average, maximum, or peak readings. The data returned from this test shall be the measured value of time of each contact and pass/fail indication.

3.14 Contact Stabilization Time:

Contact stabilization time shall be measured on the ATE on all contacts, individually.

3.14.1 Procedure: Rated voltage shall be applied to the coil, or each of the coils of a latching type relay, in turn, and the time interval between the first make of the operating contact and the point wherein a specified contact resistance has been reached, measured (the sum of contact bounce and dynamic contact resistance above a specified value).

3.14.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage and contact load levels. The data returned from this test shall be the measured value of time of each contact and pass/fail indication.

3.15 Coil Transient Suppression:

Coil transient suppression shall be measured on the ATE on all applicable sets of coil terminals.

3.15.1 Procedure: Rated coil voltage shall be applied to all applicable sets of coil terminals in turn, immediately removed, and the resultant maximum induced voltage measured.

3.15.2 ATE Details: The ATE shall be capable of providing programmable values of applied coil voltage. The data returned from this test shall be the measured value of voltage at each set of coil terminals and pass/fail indication.

3.16 Contact Bridging:

Contact bridging shall be tested on the ATE for the normally open and normally closed contacts. For relays not designated as make-before-break, bridging is the condition where, during an operation, a contact makes on one side before all contacts break from the opposite side.

3.16.1 Procedure: Rated coil voltage shall be applied to the coil, then removed, or applied to each coil of a latching type relay, in turn.