

Issued 1942-11
Revised 1960-03
Noncurrent 1995-07
Reaf. Noncur. 2006-05

Superseding AS107B

Surface Finish (RMS)

RATIONALE

This document has been reaffirmed to comply with the SAE 5-year Review policy.

1. SCOPE:

This standard provides a method for the application of surface finish control primarily to aircraft engine and propeller parts. Recommendations for a Surface Roughness Standard are contained in A.S.A. publication B46 and this S.A.E. Aeronautical Standard contains a summary of information therein plus other information which has been compiled from current manufacturing practice.

2. DEFINITIONS:

2.1 Surface:

The surface of an object is the boundary which separates that object from another substance or object.

2.2 Nominal Surface:

A two-dimensional boundary of separation which is absolutely true and smooth and whose shape and extent is defined by a drawing or descriptive specification.

2.3 Surface Qualities:

The physical characteristics of a surface, such as roughness, waviness, lay, flaws, etc.

2.4 Roughness:

That deviation from nominal surface evidenced by minute contiguous irregularities occurring on the nominal surface. Roughness in itself does not alter the trueness of a surface.

2.5 Waviness:

That deviation from nominal surface evidenced by recurrent irregularities having the form of waves. These deviations are of greater magnitude than surface roughness which may be superimposed on waviness.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2006 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org

SAE WEB ADDRESS:

<http://www.sae.org>

SAE AS107 Revision D

2.6 Flaws:

Irregularities of any sort which occur at only one place or at relatively infrequent and widely varying random intervals in a surface. A flaw may be a scratch, a ridge, a hole, a peak, a crack or a check, etc.

2.7 Microinch (Mu In.):

One millionth (.000001) part of the U.S. Standard linear inch.

2.8 RMS:

A linear unit of measurement which represents the square root of the mean of the sum of the squares of the height (in microinches) of the roughness irregularities. RMS values shall be taken from a meter of an instrument made for measuring surface roughness. The meter shall read the average roughness height in RMS over a distance, or cut-off of .030.

2.9 Roughness Scale:

A series of index numbers of varying magnitude from zero upward as indicated in this Standard.

2.10 Roughness Height (Roughness Number):

A physical measurement in RMS microinches which represents the maximum permissible degree of roughness of the surface to which it is applied except that, where two numbers are used, the larger shall be the maximum and the smaller the minimum permissible degree of roughness. The physical measurement shall be the maximum sustained reading of a series of readings, taken normal to the surface and in the direction giving the greater value (usually across the lay).

2.11 Roughness Width:

The distance between the successive ridges which constitutes the predominant pattern of the surface roughness.

2.12 Waviness Scale:

A series of numerical values from zero upward as indicated in this Standard.

2.13 Waviness Height Value:

A physical measurement in inches which represents the maximum vertical distance from peak to valley of the waves.

2.14 Waviness Width Value:

A physical measurement in inches of the distance from peak to peak of the waves.

2.15 Lay:


The direction of tool marks, or grain, of surface roughness.

2.16 Lay Designation:


A series of symbols as indicated in this Standard.

3. SURFACE FINISH SYMBOL:


3.1 The symbol to be used to designate surface finish shall be the check mark and extension as shown.




3.2 Dimensions of the symbol, as follows, are basic and may be proportionately smaller or larger as drawing requirements dictate.




3.3 On drawings, or in specifications, this symbol shall be referred only to the profile of a surface.

3.4 The point of  shall be either on the line depicting the surface, on the witness line, or on an arrow pointing to the surface as shown. The long leg and extension shall be to the right as the drawing is read.




SAE AS107 Revision D


3.5 The maximum roughness number shall be placed adjacent to and on the inside of the long leg, as shown. Ref. Paragraph 2.10




3.5.1 The maximum and minimum roughness numbers shall be placed as shown. Ref. Paragraph 2.10




3.6 The maximum waviness height value when used, shall be placed above the extension line.




3.7 The maximum waviness width value, when required, shall be placed to the right of the waviness height value.



3.8 To control contact area, when required, the percentage value shall be placed above the extension line. Ref. Paragraph 4.3




3.9 The lay designation, when used, shall be placed below the extension line adjacent to and on the outside of the long leg.



SAE AS107 Revision D

3.10 The maximum roughness width value, when required, shall be placed to the right of the lay symbol.



4. SCALES:

4.1 Roughness Scale Numbers (Microinches - RMS):

1	5	13	32	80	200	500
2	6	16	40	100	250	
3	8	20	50	125	320	
4	10	25	63	160	400	

4.2 Waviness Height Value (Inches):

.00002	.0001	.0005	.0020	.0100
.00005	.0002	.0010	.0050	

4.3 Contact Area:

To control the contact area, when required, the value shall be specified in percentage of the contact area (90% - 75% - 50% preferred); thus, 90% blue indicates that the surface shall show 90% with a mating bluing gage.

4.4 Standards have not been established for waviness width and roughness width numbers.

5. LAY DESIGNATION:

- =** Parallel to the line of the surface indicated.
- ⊥** Perpendicular to the line of the surface indicated.
- X** Angular in both directions to the line of the surface indicated.
- M** Multi-directional.
- C** Approximately circular relative to the center of the surface indicated.
- R** Approximately radial relative to the center of the surface indicated.