



AEROSPACE STANDARD

AS 1097

Society of Automotive Engineers, Inc.

400 COMMONWEALTH DRIVE, WARRENDALE, PA. 15096

Issued 1-15-76

Revised

SEAL RING, 37 DEGREE FLARED TUBE FITTING END.




TABLE I
(INCHES)

PART NO.	TUBE SIZE OD	A ±.001	B (REF)	C ±.0015	D ±.001	E ±.001
AS 1097- 4	1/4	.210	.250	.0364	.052	.020
- 6	3/8	.326	.392	.0345	.067	.033
- 8	1/2	.440	.506			
-10	5/8	.545	.611			
-12	3/4	.670	.736			
-16	1	.953	1.019	.0345	.067	.033
-20	1-1/4	1.180	1.260	.0256	.070	.040
AS 1097-24	1-1/2	1.430	1.510	.0256	.070	.040

I DESIGN INFORMATION

A CHARACTERISTICS

1. Material: Tetrafluoroethylene Resin (Teflon - TFE) per MIL-R-8791
2. Finish: Per MIL-R-8791

B APPLICATION NOTES

1. Use in AS1098 and AS1099 seal ring groove.
2. Material is inert except in molten alkali metals, fluorine under pressure, and chlorine trifluoride.
3. Should not be used under long exposure to radiation.
4. Used in systems with temperatures ranging from -320°F to +500°F (-196°C to +260°C)

SAE Technical Board rules provide that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against liability for infringement of patents."