



AEROSPACE STANDARD	AS1159	REV. C
	Issued 1970-01 Revised 1973-09 Noncurrent 1979-10 Reaf. Noncur. 2006-10 Stabilized 2014-07 Superseding AS1159B	
Wrenching Configuration, 12 Lobed, For Threaded Fasteners		

RATIONALE

This document has been determined to contain basic and stable technology which is not dynamic in nature.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE E-25 General Standards for Aerospace and Propulsion Systems Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAENORM.COM : Click to view the full PDF of AS1159C

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.


Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS1159C>



VARIATIONS IN SIZE, FORM, AND POSITION OF THE 12 LOBES ARE PERMITTED WITHIN THE WRENCHING LENGTH, PROVIDING THE ACTUAL PROFILE FALLS WITHIN THE MAXIMUM AND MINIMUM MATERIAL CONDITIONS SHOWN.

DIMENSIONS ARE PRIOR TO DEFORMATION OF THE LOCKING ELEMENT ON SELF LOCKING NUTS, DEFORMATION SHALL NOT PREVENT THE ASSEMBLY OF THE WRENCH ON THE PRODUCT.

APPLICABLE WRENCHING TOOL SHALL HAVE AN INTERNAL WRENCHING CONFIGURATION PER AS 1325.

TABLE I
(U.S. CUSTOMARY UNITS)

DASH NO.	NOMINAL WRENCHING SIZE SEE NOTE	MAXIMUM MATERIAL CONDITION				MINIMUM MATERIAL CONDITION			
		A DIA. MAX.	B DIA. MAX.	C RAD. MIN.	D RAD. MIN.	A DIA. MIN.	B DIA. MIN.	C RAD. MAX.	D RAD. MAX.
06	.1875	.223	.197	.020	.005	.219	.193	.025	.010
07	.2188	.259	.229	.023	.005	.255	.225	.028	.010
08	.2500	.295	.261	.025	.005	.291	.257	.030	.010
10	.3125	.368	.327	.030	.009	.363	.322	.035	.015
12	.3750	.439	.391	.035	.009	.434	.386	.040	.015
14	.4375	.512	.456	.040	.014	.507	.451	.045	.020
16	.5000	.585	.522	.045	.014	.580	.517	.050	.020
18	.5625	.656	.586	.050	.019	.650	.580	.055	.025
20	.6250	.733	.652	.055	.019	.727	.646	.060	.025
22	.6875	.806	.717	.060	.024	.800	.711	.065	.030
24	.7500	.879	.783	.065	.024	.873	.777	.070	.030
26	.8125	.951	.849	.070	.029	.944	.842	.075	.035
28	.8750	1.023	.913	.075	.029	1.016	.906	.080	.035
30	.9375	1.097	.979	.080	.034	1.090	.972	.085	.040
32	1.0000	1.168	1.044	.085	.034	1.161	1.037	.090	.040
34	1.0625	1.239	1.108	.090	.039	1.232	1.101	.095	.045
36	1.1250	1.319	1.175	.095	.039	1.311	1.167	.100	.045
38	1.1875	1.391	1.240	.100	.044	1.383	1.232	.105	.050
40	1.2500	1.463	1.305	.105	.044	1.455	1.297	.110	.050
42	1.3125	1.536	1.370	.110	.049	1.528	1.362	.115	.055
44	1.3750	1.609	1.437	.115	.049	1.601	1.429	.120	.055
46	1.4375	1.681	1.502	.120	.054	1.672	1.493	.125	.060
48	1.5000	1.753	1.566	.125	.054	1.744	1.557	.130	.060
50	1.5625	1.825	1.631	.130	.059	1.816	1.622	.135	.065
52	1.6250	1.899	1.698	.135	.059	1.890	1.689	.140	.065
54	1.6875	1.970	1.762	.140	.064	1.961	1.753	.145	.070
56	1.7500	2.044	1.828	.145	.064	2.035	1.819	.150	.070

NOMINAL WRENCHING SIZE VALUES INDICATE NOMINAL WIDTH ACROSS FLATS OF CORRESPONDING HEXAGON OR DOUBLE HEXAGON (12 POINT) WRENCHING CONFIGURATIONS.