

AS115

SAE Technical Board rules provide that: "All technical reports, including standards approved and practices recommended, are advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. There is no agreement to adhere to any SAE standard or recommended practice, and no commitment to conform to or be guided by any technical report. In formulating and approving technical reports, the Board and its Committees will not investigate or consider patents which may apply to the subject matter. Prospective users of the report are responsible for protecting themselves against infringement of patents."




FIGURE 1

TABLE I

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSEMBLY SIZE REF	THREAD T PER MIL-S-8879 REF	I.D. MIN	A MAX	B GAGE DIA BASIC	C 10/ DRILL DIA MIN	E 11/ DIA MAX WITHOUT SLEEVING	F HEX REF
AS115-04	1/4	.4375-20 UNJF-3B	.212	1.56	.2930	.135	.69	.56
AS115-06	3/8	.5625-18 UNJF-3B	.298	1.75	.4120	.240	.80	.69
AS115-08	1/2	.7500-16 UNJF-3B	.391	2.00	.5600	.340	.97	.88
AS115-10	5/8	.8750-14 UNJF-3B	.485	2.25	.6730	.410	1.11	1.00
AS115-12	3/4	1.0625-12 UNJ -3B	.602	2.50	.8100	.510	1.38	1.25
AS115-16	1	1.3125-12 UNJ -3B	.852	3.00	1.0620	.760	1.66	1.50

TABLE II

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) .125 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) .250 INCH	(PLUS OR MINUS) .250 INCH
36 TO 50 INCHES	(NOT LESS THAN) .500 INCH	(PLUS OR MINUS) .500 INCH
OVER 50 INCHES	(NOT LESS THAN) 1.000 INCH	(PLUS OR MINUS) 1 PERCENT

TABLE III

SLEEVING CODE OR HOSE	TYPE OF SLEEVING OR HOSE	HOSE OR SLEEVE O.D. MAX						TEMP LIMIT °F
		HOSE SIZE						
		1/4	3/8	1/2	5/8	3/4	1	
NONE	HOSE ONLY	.410	.540	.640	.745	.990	1.270	400
A	TUBULAR ABRASION (TFE)	.580	.678	.800	.850	1.184	1.514	400
B	SPIRAL ABRASION	.508	.612	.754	.847	1.080	1.375	275
C	FIRE SLEEVE 9/	.875	1.032	1.152	1.230	1.480	1.840	400
D	INTEGRAL ABRASION	.500	.625	.708	.832	1.112	1.390	350
E	SHRINK ABRASION (FEP)	.470	.600	.700	.813	1.050	1.350	400
F	SHRINK ABRASION (POLYOLEFIN)	.480	.632	.722	.837	1.050	1.375	275
G	FIRE SLEEVE 8/	.875	1.032	1.152	1.230	1.480	1.840	400
H	INTEGRAL FIRE COVER-SILICONE 9/	.781	.891	1.016	1.141	1.328	1.593	400
J	INTEGRAL FIRE COVER-SILICONE 8/	.656	.766	.905	1.016	1.206	1.500	400
K	BRAIDED ABRASION (POLYESTER)	.490	.565	.680	.800	.959	—	300

Prepared by SAE Committee G-3, Aerospace Fittings, Hose and Tubing Assemblies

Society of Automotive Engineers, Inc.
400 COMMONWEALTH DRIVE WARRENDALE, PA 15096

AEROSPACE STANDARD

HOSE ASSEMBLY, NONMETALLIC--3000 PSI, TFE, FLARELESS,
STRAIGHT TO STRAIGHT, LIGHTWEIGHT

AS115

SH 1 OF 3

TABLE IV

HOSE, SLEEVING, HOSE WITH PROTECTIVE COVER OR END FITTING.	UNITS	MAXIMUM WEIGHT					
		HOSE SIZE					
		1/4	3/8	1/2	5/8	3/4	1
HOSE ONLY	LBS/IN.	.010	.015	.021	.028	.055	.089
TUBULAR ABRASION (TFE)	LBS/IN.	.003	.003	.004	.004	.006	.009
SPIRAL ABRASION	LBS/IN.	.001	.002	.003	.003	.004	.005
FIRE SLEEVE 9/	LBS/IN.	.010	.014	.016	.017	.022	.026
INTEGRAL ABRASION WITH HOSE	LBS/IN.	.014	.021	.026	.035	.067	.104
SHRINK ABRASION (FEP) ONLY	LBS/IN.	.001	.003	.003	.004	.005	.006
SHRINK ABRASION (POLYOLEFIN) ONLY	LBS/IN.	.002	.003	.003	.004	.005	.006
FIRE SLEEVE 8/	LBS/IN.	.010	.014	.016	.017	.022	.026
INTEGRAL FIRE COVER WITH HOSE 9/	LBS/IN.	.030	.037	.046	.060	.091	.130
INTEGRAL FIRE COVER WITH HOSE 8/	LBS/IN.	.020	.030	.037	.048	.080	.117
BRAIDED ABRASION WITH HOSE	LBS/IN.	.012	.017	.023	.027	.040	—
FIRE SLEEVE CLAMP	LBS EA	.025	.025	.025	.026	.026	.033
STD END FITTING-STRAIGHT	LBS EA	.064	.110	.182	.274	.467	.735

TABLE V

HOSE SIZE	LENGTH (INCHES)
04 06	2.00 ±.25
08 10	2.50 ±.25
12 16	3.00 ±.25




FIGURE 2

TABLE VI

HOSE SIZE (REF)	SPHERICAL BALL SIZE FOR DETERMINING MIN THRU DIAMETER 10/	
	MS19059 DASH NO.	OIA IN
04	1007	.109
06	1012	.188
08	1016	.313
10	1018	.375
12	1021	.469
16	1029	.719

TABLE VII - LENGTH CORRECTION FACTORS

HOSE SIZE (REF)	END FITTING CONF.
	STRAIGHT
04	.16
06	.16
08	.19
10	.20
12	.23
16	.30

CONSTRUCTION AND PERFORMANCE: THESE HOSE ASSEMBLIES SHALL MEET THE CONSTRUCTION AND PERFORMANCE REQUIREMENTS OF AS 1339. FITTINGS SHALL BE PERMANENTLY ATTACHED TO THE HOSE.

RATED OPERATING CHARACTERISTICS: See AS 1339.

MATERIALS: HOSE AND FITTINGS - PER AS 1339.
 TUBULAR ABRASION SLEEVE (TFE) - BLACK, EXTRUDED SEAMLESS TFE TUBING PER AS 1291.
 SPIRAL ABRASION SLEEVE - BLACK, NYLON COIL PER AS 1294.
 FIRE SLEEVE - ASBESTOS, IMPREGNATED WITH SILICONE RUBBER PER AS 1072 "SIL" CODED.
 INTEGRAL ABRASION SLEEVE - BLACK, INTEGRALLY BONDED SILICONE/TFE COMPOSITE.
 SHRINK ABRASION SLEEVE (FEP) - TRANSLUCENT, SHRINKABLE FEP TUBING PER MIL-I-23053/11
 SHRINK ABRASION SLEEVE (POLYOLEFIN) - BLACK, SHRINKABLE POLYOLEFIN TUBING PER AMS 3587 OR MIL-R-46846 TYPE 5.
 INTEGRAL FIRE COVER - EXTRUDED SILICONE
 BRAIDED ABRASION (POLYESTER)

MARKING: THE HOSE ASSEMBLIES SHALL HAVE ALL IDENTIFICATION MARKING, AS REQUIRED BY AS 1339, PERMANENTLY MARKED ON A PERMANENT STAINLESS STEEL BAND, NOT MORE THAN 1.0 INCH WIDE, OR ON THE END FITTING. THE CHARACTERS SHALL BE A MINIMUM OF 1/16 INCH HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE HOSE TO PREVENT RELATIVE MOVEMENT AND RESULTANT CHAFING AND OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND. VARIABLE DATA, SUCH AS MANUFACTURING DATE AND "PT" SYMBOL, MAY BE ELECTROETCHED ON ONE END FITTING OR FIRE SLEEVE CLAMP.