

AS116925 THRU
AS116960

RATIONALE

THIS DOCUMENT HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE 5-YEAR REVIEW POLICY.

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION AN116925 THRU AN116960 REV. 1, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE AN116925 THRU AN116960 REV. 1, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

SAENORM.COM : Click to view the full PDF of AS116925

THIRD ANGLE PROJECTION



ISSUED 1998-10 REAFFIRMED 2007-06

PREPARED BY COMMITTEE E-25




AEROSPACE STANDARD





SCREW - OVAL FILLISTER HEAD, .138-32

AS116925 THRU
AS116960
SHEET 1 OF 3

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



OPTIONAL METHOD OF SLOTTING



PART NO.	L	K +.000 -.060	PART NO.	L	K +.000 -.060	PART NO.	L	K +.000 -.060
AN116926	.250	(a)	AN116937	.938	(a)	AN116952	2.750	1.500
AN116927	.312	(a)	AN116938	1.000	(a)	AN116954	3.000	1.750
AN116928	.375	(a)	AN116939	1.125	(a)			
AN116929	.438	(a)	AN116940	1.250	(a)			
AN116930	.500	(a)	AN116941	1.375	.125			
AN116931	.562	(a)	AN116942	1.500	.250			
AN116932	.625	(a)	AN116943	1.625	.375			
AN116933	.688	(a)	AN116944	1.750	.500			
AN116934	.750	(a)	AN116945	1.875	.625			
AN116935	.812	(a)	AN116946	2.000	.750			
AN116936	.875	(a)	AN116948	2.250	1.000			
			AN116950	2.500	1.250			

(a) THREAD TO HEAD, MAX TWO IMPERFECT THREADS.