

SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

**REV. C**  
**AS1474™**

FEDERAL SUPPLY CLASS

**RATIONALE**


THIS TECHNICAL REPORT IS BEING STABILIZED BECAUSE IT COVERS TECHNOLOGY, PRODUCTS, OR PROCESSES WHICH ARE MATURE AND NOT LIKELY TO CHANGE IN THE FORESEEABLE FUTURE.

**STABILIZED NOTICE**

THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.

SAENORM.COM : Click to view the full PDF of as1474c

**For more information on this standard, visit**  
<https://www.sae.org/standards/content/AS1474C/>



CUSTODIAN: G-3		PROCUREMENT SPECIFICATION:	
	<b>AEROSPACE STANDARD</b>		<b>AS1474™</b>
	HOSE ASSEMBLY, FLEXIBLE, LOW PRESSURE, FLARELESS, POTABLE WATER, STRAIGHT TO 45°		

ISSUED 1979-04 REVISED 1983-03 NONCURRENT 1994-10 REAFFIRMED NONCURRENT 2014-11 STABILIZED 2024-01




TABLE I  
BASIC HOSE AND END FITTING DIMENSIONS

HOSE ASSEMBLY NO. AND SIZE CODE	HOSE ASSY. SIZE (REF)	THREAD T PER MIL-S-8879 (REF)	A <sub>1</sub> MAX.	A <sub>2</sub> MAX.	B GAGE DIA. BASIC	C MIN. DIA. THRU	D		E MAX.	F HEX ACROSS FLATS (REF)	HOSE I.D. MIN.	HOSE O.D.	
							MIN.	MAX.				MIN.	MAX.
AS1474-04	1/4	.4375-20 UNJF-3B	1.42	1.80	.2930	.174	.33	.39	.67	.56	.235	.35	.39
AS1474-06	3/8	.5625-18 UNJF-3B	1.52	2.16	.4120	.291	.42	.48	.82	.69	.360	.54	.57
AS1474-08	1/2	.7500-16 UNJF-3B	1.87	2.51	.5600	.409	.47	.53	1.03	.88	.485	.68	.73
AS1474-10	5/8	.8750-14 UNJF-3B	1.95	2.84	.6730	.495	.57	.63	1.18	1.00	.610	.81	.86
AS1474-12	3/4	1.0625-12 UNJ-3B	1.99	3.17	.8100	.646	.62	.68	1.47	1.25	.735	.93	.98
AS1474-16	1	1.3125-12 UNJ-3B	2.30	3.80	1.0620	.898	.76	.82	1.75	1.50	.985	1.20	1.24

TABLE II  
LENGTH INCREMENTS AND TOLERANCE

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) .125 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) .250 INCH	(PLUS OR MINUS) .250 INCH
36 TO 100 INCHES	(NOT LESS THAN) .250 INCH	(PLUS OR MINUS) .375 INCH
100 TO 500 INCHES	(NOT LESS THAN) .500 INCH	(PLUS OR MINUS) 1/2 PERCENT
OVER 500 INCHES	(NOT LESS THAN) 1.000 INCH	(PLUS OR MINUS) 1 PERCENT

TABLE III  
HOSE ASSEMBLY WEIGHT INFORMATION

HOSE SIZE (REF)	HOSE LBS/INCH	MAXIMUM WEIGHTS						HOSE LENGTH CORRECTION FACTOR INCH	
		STANDARD END FITTING (LBS) EACH							
		STRAIGHT			45°			ST	45°
		CODE "D"	CODE "S"	CODE "J"	CODE "D"	CODE "S"	CODE "J"		
04	.004	.027		.051	.027		.048	.49	.71
06	.008	.041		.077	.046		.079	.58	.88
08	.011	.068		.123	.076		.122	.59	.95
10	.014	.105		.182	.116		.181	.69	1.13
12	.018	.130		.251	.169		.281	.69	1.33
16	.024	.201		.372	.260		.420	.73	1.56



**AEROSPACE STANDARD**  
HOSE ASSEMBLY, FLEXIBLE, LOW PRESSURE,  
FLARELESS, POTABLE WATER,  
STRAIGHT TO 45°

**AS1474™**  
SHEET 1 OF 2

**REV. C**