


REV. C

SAE AS1506

FEDERAL SUPPLY CLASS
4720

RATIONALE

AS1506C HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.



BEADED ENDS IN ACCORDANCE WITH AS1501 APPLICABLE TO GRADES "A" AND "B"



VIEW 1

FIGURE 1

TABLE 1 – TABULATION OF OPERATING PRESSURE AND PART NUMBER GRADES

GRADE	TYPE (OPERATING TEMPERATURE)	OPERATING PRESSURE RATING (PSI) ("0" PSI TO PRESSURE LISTED BELOW) /4/											
		HOSE INSIDE DIAMETER (INCHES)											
		01	02	03	04	05	06	07	08	09	10	11	12
A /5/	I	40	34	28	22	16	12	8	6	4	3	3	2
B /6/	II												
C /7/	I	20	17	14	11	8	6	4	3	2	2	1	1
D /7/	II												

TABLE 2 – TABULATION OF HOSE LENGTH SPECIFICATIONS


HOSE INSIDE DIAMETER (INCH)	L - HOSE LENGTH (INCHES)		
	GRADES "A" AND "B" MINIMUM /8/	GRADES "C" AND "D" MINIMUM /8/	ALL GRADES MAXIMUM
.50 TO 4.00	3.50	2.75	6.00
4.25 TO 12.00	3.75	3.00	

TABLE 3 – TABULATION OF AVAILABLE HOSE LENGTH INCREMENTS AND TOLERANCES

L - HOSE LENGTH (INCHES)	AVAILABLE LENGTH INCREMENT (INCH)	L - LENGTH TOLERANCE (INCH)
2.00 TO 6.00	.25	±.12

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS1506C>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: AS1501

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

HOSE, AIR DUCT, SEMIFLEXIBLE, SLEEVE SECTION, UNREINFORCED, SELF EXTINGUISHING

SAE AS1506
SHEET 1 OF 3

REV. C

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1978-11 REVISED 1998-12 REAFFIRMED 2013-01

FLAG NOTES:

- /1/ LENGTH "L" IS A TWO DIGIT NUMBER OF WHICH THE FIRST DIGIT DESCRIBES THE HOSE ASSEMBLY LENGTH IN WHOLE INCHES, AND THE SECOND DIGIT, THE FRACTION OF AN INCH IN FOURTHS. SEE TABLE 2 AND 3 FOR LENGTH SPECIFICATION AND TOLERANCES.
- /2/ DIAMETERS ARE IN .25 INCH INCREMENTS. MINIMUM INSIDE DIAMETER (ID) IS .50 INCH AND MAXIMUM INSIDE DIAMETER (ID) IS 12.00 INCHES. INSIDE DIAMETER TOLERANCE IS -.01 TO +.03 INCH.
- /3/ HOSE WALL THICKNESS VARIES FROM .040 TO .080 INCH FOR GRADES "A" AND "B" AND .020 TO .050 INCH FOR GRADES "C" AND "D".
- /4/ FOR FRACTIONAL DIAMETER HOSE OPERATING PRESSURE, USE PRESSURE LISTED FOR NEXT LARGEST HOSE DIAMETER.
- /5/ GRADES "A" - MAXIMUM HOSE WEIGHT: .10 LB/FT (LENGTH)/INCH DIAMETER
MAXIMUM HOSE LEAKAGE: .01 SCFM/FT (LENGTH)/INCH DIAMETER
TOTAL JOINT LEAKAGE: .10 SCFM/INCH DIAMETER
- /6/ GRADE "B" - MAXIMUM HOSE WEIGHT: .12 LB/FT (LENGTH)/INCH DIAMETER
MAXIMUM HOSE LEAKAGE: .01 SCFM/FT (LENGTH)/INCH DIAMETER
TOTAL JOINT LEAKAGE: .10 SCFM/INCH (DIAMETER)
- /7/ GRADES "C" AND "D" - MAXIMUM HOSE WEIGHT: .075 LB/FT (LENGTH)/INCH DIAMETER
MAXIMUM HOSE LEAKAGE: .02 SCFM/FT (LENGTH)/INCH DIAMETER
TOTAL JOINT LEAKAGE: .10 SCFM/INCH DIAMETER
- /8/ MINIMUM HOSE LENGTH MAY BE REDUCED BY .75 WHEN USING NAS 1922 CLAMP.

PROCUREMENT SPECIFICATION: AS1501, FORM 4, TYPES I AND II

MATERIAL: IN ACCORDANCE WITH AS1501

FINISH: AS MANUFACTURED

MARKING: IN ACCORDANCE WITH AS1501

OPERATING TEMPERATURE: TYPE I, -65 °F TO +250 °F (-54 °C TO +121 °C)
TYPE II, -65 °F TO +500 °F (-54 °C TO +260 °C)

GENERAL NOTES:

- A. HOSE SOFT ENDS SHALL BE SUITABLE FOR INSTALLATION OVER A RIGID TUBE END WITH MS33660, TYPE "A" BEAD, OR AS5131.
- B. HOSE CLAMP AND TORQUE REQUIREMENTS SHOULD BE SPECIFIED ON INSTALLATION DRAWING. ALLOWABLE HOSE PRESSURE AND HOSE END LEAKAGE ARE DEPENDENT ON TYPE CLAMP USED, CLAMP TORQUE AND STIFFNESS AND CONFIGURATION OF RIGID HOSE END.
- C. DO NOT USE UNASSIGNED DIAMETER AND LENGTH CODES.
- D. THE CHANGE BAR (I) LOCATED IN THE LEFT MARGIN IS FOR THE CONVENIENCE OF THE USER IN LOCATING AREAS WHERE TECHNICAL REVISIONS, NOT EDITORIAL CHANGES, HAVE BEEN MADE TO THE PREVIOUS ISSUE OF THIS DOCUMENT. AN (R) SYMBOL TO THE LEFT OF THE DOCUMENT TITLE INDICATES A COMPLETE REVISION OF THE DOCUMENT.

 An SAE International Group	AEROSPACE STANDARD	SAE AS1506 SHEET 2 OF 3	REV. C
	HOSE, AIR DUCT, SEMIFLEXIBLE, SLEEVE SECTION, UNREINFORCED, SELF EXTINGUISHING		