

REV.
B

AS1732





FIGURE 1

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and the applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

CUSTODIAN: SAE G-3/G-3A

PROCUREMENT SPECIFICATION: AS1730

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

BODY, COUPLING, RIGID,
FIXED CAVITY, THREADED, FERRULE
TYPE TUBE ENDS, TYPE I

AS1732

SHEET 1 OF 4

REV.

B

ISSUED 1984-01 REVISED 1991-10-30

TABLE 1 - COUPLING BODY DIMENSIONS

AS1732 DASH NUMBER	TUBE SIZE (REF)	THREAD T PER H28/2	ϕA +.005/- .000	ϕB +.005/- .000	ϕC +.010/- .000	ϕD +.000/- .010	ϕE +.005/- .000	ϕF +.005/- .000	ϕG TOL	H
04	.250	.687-12 UN-2A	.680	.529	.480	.298	.228	.375	.254	+.005/- .000 .645
05	.312	.750-12 UN-2A	.743	.580	.535	.353	.290	.437	.316	+.005/- .000 .645
06	.375	.812-12 UN-2A	.805	.635	.590	.408	.353	.500	.379	+.005/- .000 .645
08	.500	.937-12 UN-2A	.930	.762	.716	.534	.479	.625	.504	+.005/- .000 .645
10	.625	1.062-12 UN-2A	1.055	.900	.850	.668	.604	.750	.630	+.005/- .000 .675
12	.750	1.250-12 UNF-2A	1.243	1.033	.984	.802	.729	.890	.755	+.005/- .000 .675
16	1.000	1.500-12 UNF-2A	1.493	1.284	1.235	1.053	.980	1.142	1.005	+.005/- .000 .675
20	1.250	1.750-12 UN-2A	1.743	1.534	1.485	1.303	1.230	1.392	1.256	+.005/- .000 .675
24	1.500	2.000-12 UN-2A	1.993	1.783	1.735	1.553	1.480	1.642	1.506	+.005/- .000 .760
28	1.750	2.250-12 UN-2A	2.243	2.045	1.965	1.783	1.730	1.895	1.756	+.005/- .000 .760
32	2.000	2.500-12 UN-2A	2.493	2.292	2.235	2.053	1.981	2.145	2.006	+.005/- .000 .760
36	2.250	2.750-12 UN-2A	2.743	2.545	2.485	2.283	2.231	2.395	2.257	+.005/- .000 .760
40	2.500	3.000-12 UN-2A	2.993	2.800	2.713	2.531	2.481	2.645	2.507	+.005/- .000 .760
44	2.750	3.250-12 UN-2A	3.249	3.045	2.961	2.781	2.731	2.895	2.757	+.005/- .000 .755
48	3.000	3.625-12 UN-2A	3.618	3.395	3.340	3.158	2.979	3.145	3.007	+.005/- .000 .705
56	3.500	4.125-12 UN-2A	4.118	3.895	3.840	3.658	3.479	3.645	3.509	+.005/- .000 .705
64	4.000	4.625-12 /4/	4.603	4.395	4.340	4.158	3.979	4.155	4.009	+.005/- .000 .705
72	4.500	5.125-12 /4/	5.103	4.895	4.840	4.658	4.479	4.655	4.509	+.006/- .000 .884
80	5.000	5.625-12 /4/	5.602	5.378	5.325	5.143	4.979	5.155	5.009	+.006/- .000 .868

TABLE 2 - COUPLING BODY DIMENSIONS AND DESIGN INFORMATION

AS1732 DASH NUMBER	J	K LENGTH	K TOL	M	N PLACES	P PLACES	S LENGTH	S TOL	W	O-RING DASH NO (REF) /S/	WEIGHT MAX LB
04	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/.010	012	.007
05	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/.010	013	.008
06	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/.010	014	.010
08	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/.010	016	.013
10	.250	.100	±.010	.045	4	5	.150	±.015	.008/.010	018	.016
12	.250	.100	±.010	.045	4	5	.150	±.015	.008/.010	020	.021
16	.250	.100	±.010	.045	4	5	.150	±.015	.008/.010	024	.027
20	.250	.100	±.010	.045	4	5	.150	±.015	.008/.010	028	.033
24	.250	.100	±.010	.045	5	6	.150	±.015	.008/.010	030	.041
28	.250	.100	±.010	.075	5	6	.125	+.020/- .010	.008/.010	032	.045
32	.250	.105	±.010	.075	5	6	.125	+.020/- .010	.008/.010	034	.050
36	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/.010	036	.064
40	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/.010	038	.072
44	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/.010	040	.081
48	.309	.060	±.010	.075	5	6	.125	+.020/- .010	.008/.010	042	.089
56	.309	.060	±.010	.075	5	6	.125	+.020/- .010	.014/.016	044	.101
64	.309	.100	±.010	.075	4	5	.142	±.015	.014/.016	046	.116
72	.409	.100	±.010	.075	6	7	.151	+.020/- .010	.020/.024	048	.177
80	.409	.100	±.010	.075	6	7	.135	+.020/- .010	.020/.024	050	.195