



REV.  
C

AS1732

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



ENLARGED VIEW A

ENLARGED VIEW B

FIGURE 1 - BODY

CUSTODIAN: SAE G-3/G-3A

PROCUREMENT SPECIFICATION: /3/ AS1730

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space  
**INTERNATIONAL**

400 Commonwealth Drive, Warrendale, PA 15096-0001

**AEROSPACE STANDARD**

BODY, COUPLING, RIGID,  
FIXED CAVITY, THREADED, FERRULE  
TYPE TUBE ENDS, TYPE I

**AS1732**

SHEET 1 OF 4

**REV.**

**C**

TABLE 1 - COUPLING BODY DIMENSIONS

BASIC NO. AS1732 SIZE CODE	TUBE SIZE	THREAD T PER H28/2	A	B	C	D	E	F	G	H
			+ .005/- .000	+ .005/- .000	+ .010/- .000	+ .000/- .010	+ .005/- .000	+ .005/- .000	G	TOL
04	.250	.687-12 UN-2A	.680	.529	.480	.298	.233	.375	.254	+ .005/- .000 .645
05	.312	.750-12 UN-2A	.743	.580	.535	.353	.295	.437	.316	+ .005/- .000 .645
06	.375	.812-12 UN-2A	.805	.635	.590	.408	.358	.500	.379	+ .005/- .000 .645
08	.500	.937-12 UN-2A	.930	.762	.716	.534	.483	.625	.504	+ .005/- .000 .645
10	.625	1.062-12 UN-2A	1.055	.900	.850	.668	.609	.750	.630	+ .005/- .000 .675
12	.750	1.250-12 UNF-2A	1.243	1.033	.984	.802	.734	.890	.755	+ .005/- .000 .675
16	1.000	1.500-12 UNF-2A	1.493	1.284	1.235	1.053	.984	1.142	1.005	+ .005/- .000 .675
20	1.250	1.750-12 UN-2A	1.743	1.534	1.485	1.303	1.235	1.392	1.256	+ .005/- .000 .675
24	1.500	2.000-12 UN-2A	1.993	1.783	1.735	1.553	1.480	1.642	1.506	+ .005/- .000 .760
28	1.750	2.250-12 UN-2A	2.243	2.045	1.965	1.783	1.730	1.895	1.756	+ .005/- .000 .760
32	2.000	2.500-12 UN-2A	2.493	2.292	2.235	2.053	1.981	2.145	2.006	+ .005/- .000 .760
36	2.250	2.750-12 UN-2A	2.743	2.545	2.485	2.283	2.231	2.395	2.257	+ .005/- .000 .760
40	2.500	3.000-12 UN-2A	2.993	2.800	2.713	2.531	2.481	2.645	2.507	+ .005/- .000 .760
44	2.750	3.250-12 UN-2A	3.243	3.045	2.961	2.781	2.731	2.895	2.757	+ .005/- .000 .760
48	3.000	3.625-12 UN-2A	3.618	3.395	3.340	3.158	2.979	3.145	3.007	+ .005/- .000 .705
56	3.500	4.125-12 UN-2A	4.118	3.895	3.840	3.658	3.479	3.645	3.509	+ .005/- .000 .705
64	4.000	4.625-12 / / /	4.603	4.395	4.340	4.158	3.979	4.155	4.009	+ .005/- .000 .705
72	4.500	5.125-12 / / /	5.103	4.895	4.840	4.658	4.479	4.655	4.509	+ .006/- .000 .884
80	5.000	5.625-12 / / /	5.602	5.378	5.325	5.143	4.979	5.155	5.009	+ .006/- .000 .868

AS1732

REV.  
C

TABLE 2 - COUPLING BODY DIMENSIONS AND DESIGN INFORMATION

BASIC NO. AS1732 SIZE CODE	J	K LENGTH	K TOL	M	N PLACES	P PLACES	S LENGTH	S TOL	W	O-RING OASH NO (REF) /B/	WEIGHT MAX LB
04	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/ .010	012	.007
05	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/ .010	013	.008
06	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/ .010	014	.010
08	.234	.090	+.005/- .000	.045	4	5	.127	+.020/- .010	.008/ .010	016	.013
10	.250	.100	±.010	.045	4	5	.150	±.015	.008/ .010	018	.016
12	.250	.100	±.010	.045	4	5	.150	±.015	.008/ .010	020	.021
16	.250	.100	±.010	.045	4	5	.150	±.015	.008/ .010	024	.027
20	.250	.100	±.010	.045	4	5	.150	±.015	.008/ .010	028	.033
24	.250	.100	±.010	.045	5	6	.150	±.015	.008/ .010	030	.041
28	.250	.100	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	032	.045
32	.250	.105	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	034	.050
36	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	036	.064
40	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	038	.072
44	.279	.110	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	040	.081
48	.309	.060	±.010	.075	5	6	.125	+.020/- .010	.008/ .010	042	.089
56	.309	.060	±.010	.075	5	6	.125	+.020/- .010	.014/ .016	044	.101
64	.309	.100	±.010	.075	4	5	.142	±.015	.014/ .016	046	.116
72	.409	.100	±.010	.075	6	7	.151	+.020/- .010	.020/ .024	048	.177
80	.409	.100	±.010	.075	6	7	.135	+.020/- .010	.020/ .024	050	.195