

# AS1912

AN AMERICAN NATIONAL STANDARD

FEDERAL SUPPLY CLASS  
4720




FIGURE 1

TABLE I

HOSE ASSY NO. CODE	HOSE SIZE	THREAD T PER MIL-S-8879	I.D. MIN	B DIA MIN <sup>1</sup>	C HEX REF	D DIA MAX <sup>2</sup>
AS1912E	1/4	.4375-24 UNJS-3B	.212	.109	.56	.690
AS1912G	3/8	.5625-20 UNJS-3B	.298	.188	.69	.800
AS1912H	1/2	.7188-20 UNJS-3B	.391	.313	.88	.970
AS1912J	5/8	.8438-18 UNJS-3B	.485	.375	1.00	1.100
AS1912K	3/4	1.0000-16 UNJ-3B	.602	.469	1.25	1.380
AS1912M	1	1.2500-14 UNJS-3B	.852	.719	1.50	1.660

TABLE I (CONT'D)

HOSE ASSEMBLY NO. CODE	HOSE SIZE	E MAX	F	
			MIN	MAX
AS1912E	1/4	1.90	.450	.550
AS1912G	3/8	2.35	.517	.600
AS1912H	1/2	2.50	.513	.675
AS1912J	5/8	2.70	.620	.765
AS1912K	3/4	3.15	.760	.874
AS1912M	1	3.50	.890	.950

<sup>1</sup> A TRUE CIRCULAR CROSS SECTION IS NOT REQUIRED THROUGH THE END FITTING. HOWEVER, THE BALL DIAMETER B LISTED IN TABLE I SHALL PASS THROUGH THE END FITTING AFTER THE END FITTING IS ATTACHED TO THE HOSE ASSEMBLY.

<sup>2</sup> DISTANCE ACROSS CORNERS OF THE COUPLING NUT MAY EXCEED THIS DIMENSION.

CUSTODIAN: SAE G-3/G-3D

PROCUREMENT: AS1339

**SAE** The Engineering Society  
For Advancing Mobility  
Land Sea Air and Space

400 Commonwealth Drive  
Warrendale, PA 15096

## AEROSPACE STANDARD

HOSE ASSEMBLY, NONMETALLIC, 3000 PSI, TFE  
LIGHTWEIGHT, BEAM SEAL, 45° TO 45°

# AS1912

SHEET 1 OF 5

ISSUED 8-85 REVISED

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

AS1912

FEDERAL SUPPLY CLASS  
4720

TABLE II

HOSE ASSEMBLY LENGTH	AVAILABLE INCREMENTS	TOLERANCE
UNDER 18 INCHES	(NOT LESS THAN) 1/8 INCH	(PLUS OR MINUS) .125 INCH
18 TO 36 INCHES	(NOT LESS THAN) 1/4 INCH	(PLUS OR MINUS) .250 INCH
36 TO 50 INCHES	(NOT LESS THAN) 1/2 INCH	(PLUS OR MINUS) .500 INCH
OVER 50 INCHES	(NOT LESS THAN) 1 INCH	(PLUS OR MINUS) 1 PERCENT

TABLE III

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	TEMP LIMIT °F	HOSE OR SLEEVE ASSEMBLED OUTSIDE DIAMETER						
			TOLERANCE	HOSE SIZE (REF)					
				1/4	3/8	1/2	5/8	3/4	1
-	HOSE ONLY (AS1624)	400	MAX MIN	.390 .360	.490 .455	.615 .585	.730 .690	.990 .950	1.270 1.230
A	ABRASION SLEEVE TUBULAR (TFE-AS1291-B)	400	↑	.500 .440	.600 .540	.730 .670	.840 .780	1.110 1.050	1.400 1.340
B	ABRASION SLEEVE COIL (NYLON AS1294)	275	↑	.450 .390	.550 .490	.695 .635	.810 .750	1.080 1.020	1.350 1.300
C	FIRE SLEEVE (15 MIN) <sup>3</sup>	400	↑	.625 .500	.750 .625	.875 .750	1.000 .875	1.250 1.125	1.500 1.375
E	SHRINK ABRASION SLEEVE (FEP)	350	↑	.424 .374	.540 .480	.665 .615	.790 .730	1.070 1.010	1.350 1.290
F	SHRINK ABRASION SLEEVE (POLYOLEFIN)	275	↑	.450 .400	.560 .505	.695 .645	.810 .750	1.080 1.020	1.360 1.300
H	INTEGRAL FIRE SLEEVE (15 MIN)	400	↑	.660 .600	.745 .685	.895 .835	1.005 .945	1.220 1.160	1.515 1.455
K	INTEGRAL ABRASION SLEEVE (BRAIDED POLYESTER)	300	↓	.490 .444	.570 .535	.695 .650	.800 .760	1.070 1.030	1.350 1.310
L	ABRASION SLEEVE COIL (PTFE-AS1293)	400	MAX MIN	.550 .440	.600 .540	.730 .670	.862 .802	1.110 1.050	1.400 1.340

<sup>3</sup> THE SLEEVE DIAMETERS FOR AS1072 SLEEVES APPLY WHEN THE SLEEVE IS COMPRESSED, OR CLAMPED, TO CONTACT THE HOSE. IN THIS CASE A WRINKLE MAY OCCUR OVER APPROXIMATELY 10% OF THE SLEEVE CIRCUMFERENCE.

SAENOR.COM · Click to view the PDF

ISSUED 8-85 REVISED

AS1912

FEDERAL SUPPLY CLASS  
4720

TABLE IV

HOSE OR SLEEVE CODE	HOSE OR TYPE SLEEVE	UNITS	MAXIMUM WEIGHT					
			HOSE SIZE					
			1/4	3/8	1/2	5/8	3/4	1
-	HOSE ONLY	LBS/IN	.009	.015	.020	.027	.055	.085
A	ABRASION SLEEVE (TFE)	↑	.003	.004	.004	.005	.007	.009
B	ABRASION SLEEVE (NYLON)		.001	.002	.003	.003	.004	.005
C	FIRE SLEEVE (15 MIN)		.007	.009	.011	.012	.017	.021
E	SHRINK ABRASION (FEP)	↓	.002	.003	.003	.005	.006	.007
F	SHRINK ABRASION (POLYOLEFIN)		.002	.003	.003	.004	.005	.006
H	INTEGRAL FIRE SLEEVE (15 MIN) WITH HOSE		.019	.027	.035	.047	.099	.117
K	INTEGRAL ABRASION SLEEVE (BRAIDED POLYESTER) W/HOSE	↓	.012	.016	.022	.030	.060	.090
L	COIL ABRASION (PTFE)		LBS/IN	.003	.004	.005	.005	.006
NONE	FIRE SLEEVE CLAMP	LBS EA	.025	.025	.025	.026	.026	.033
NONE	FITTING END (HOSE SIZE - 45°)	LBS EA	.065	.095	.160	.240	.420	.700




FIGURE 2

HEAT SHRINKABLE SLEEVES REQUIRED FOR COIL AND TUBULAR ABRASION SLEEVES (SEE NOTES 3 & 4)

TABLE V

HOSE SIZE	LENGTH (INCHES)
1/4 3/8	2.00 ± .25
1/2 5/8	2.50 ± .25
3/4 1	3.00 ± .25




FIGURE 3

ISSUED 8-85 REVISED

<b>AEROSPACE STANDARD</b>	<h1>AS1912</h1>
HOSE ASSEMBLY, NONMETALLIC, 3000 PSI, TFE LIGHTWEIGHT, BEAM SEAL, 45° TO 45°	
SHEET 3 OF 5	

AS1912

FEDERAL SUPPLY CLASS

4720

CONSTRUCTION AND PERFORMANCE: THESE HOSE ASSEMBLIES SHALL MEET THE CONSTRUCTION AND PERFORMANCE REQUIREMENTS OF AS1339. FITTINGS SHALL BE PERMANENTLY ATTACHED TO THE HOSE.

RATED OPERATING CHARACTERISTICS: SEE AS1339.

MATERIALS: HOSE AND FITTINGS - PER AS1339

TUBULAR ABRASION SLEEVE - BLACK, EXTRUDED SEAMLESS TFE TUBING PER AS1291.

COIL ABRASION SLEEVE - BLACK, NYLON COIL PER AS1294, OR TFE PER AS1293.

INTEGRAL ABRASION SLEEVE - BRAIDED POLYESTER

INTEGRAL FIRESLEEVE - SILICONE COMPOSITE PER AS1722

FIRESLEEVE - FIBERGLASS, IMPREGNATED WITH SILICONE PER AS1072 "SIL" CODED.

SHRINK ABRASION SLEEVE (FEP) - TRANSLUCENT, SHRINKABLE FEP TUBING PER MIL-I-23053/11

SHRINK ABRASION SLEEVE (POLYOLEFIN) - BLACK, SHRINKABLE POLYOLEFIN TUBING PER AS1073 CODE B

MARKING: THE HOSE ASSEMBLIES SHALL HAVE ALL IDENTIFICATION MARKING AS REQUIRED BY AS1339, PERMANENTLY MARKED ON A PERMANENT STAINLESS STEEL BAND NOT MORE THAN 1.0 INCH WIDE OR ON THE END FITTING. THE CHARACTERS SHALL BE A MINIMUM OF 1/16 INCH HIGH. THE BAND SHALL BE SO DESIGNED AS TO REMAIN TIGHT ON THE HOSE TO PREVENT RELATIVE MOVEMENT AND RESULTANT CHAFING AND OF SUFFICIENT STRENGTH TO PREVENT REMOVAL BY HAND.

NOTES:

1. LENGTH "L" IS A THREE DIGIT NUMBER OF WHICH THE FIRST TWO DIGITS DESCRIBE THE HOSE ASSEMBLY LENGTH IN WHOLE INCHES AND THE THIRD DIGIT, THE FRACTION OF AN INCH IN EIGHTHS, LENGTH "L" IS MEASURED FROM END PT. TO END PT. SEE TABLE II FOR AVAILABLE LENGTH INCREMENTS AND TOLERANCES.
2. THE CUT ENDS OF THE SILICONE/FIBERGLASS FIRESLEEVE SHALL BE COATED WITH RTV SILICONE RUBBER, PRIOR TO INSTALLATION, TO PREVENT WICKING OF FLUIDS. THE FIRESLEEVE ENDS SHALL BE SECURED TO THE HOSE ASSEMBLY END FITTINGS WITH CORROSION RESISTANT STEEL BANDS. AFTER INSTALLATION, CRACKS OR VOIDS IN THE FIRESLEEVE, WHICH EXPOSE THE FIBERGLASS, SHALL BE COATED WITH RTV SILICONE RUBBER. THE ENDS OF THE INTEGRAL FIRESLEEVE SHALL BE COVERED WITH A LENGTH OF SILICONE SLEEVE EXTENDING OVER THE END FITTING SOCKET.

ISSUED 8-85 REVISED

AEROSPACE STANDARD

HOSE ASSEMBLY, NONMETALLIC, 3000 PSI, TFE LIGHTWEIGHT, BEAM SEAL, 45° TO 45°

AS1912

SHEET 4 OF 5