

AEROSPACE STANDARD

SAE AS20708/94

Issued 2004-04

Synchro, 60 and 400 Hz, Size 23

FSC 5990

NOTICE

This document has been taken directly from U.S. Military specification MIL-S-20708/94B(MU), Amendment 2, Notice 2 and contains only minor editorial and format changes required to bring it into conformance with the publishing requirements of SAE Technical Standards. The initial release of this document is intended to replace MIL-S-20708/94B(MU), Amendment 2, Notice 2. Any part numbers established by the original specification remain unchanged.

The original military specification was adopted as an SAE standard under the provisions of the SAE Technical Standards Board (TSB) Rules and Regulations (TSB 001) pertaining to accelerated adoption of government specifications and standards. TSB rules provide for (a) the publication of portions of unrevised government specifications and standards without consensus voting at the SAE committee level, and (b) the use of the existing government specification or standard format.

Under Department of Defense policies and procedures, any qualification requirements and associated qualified products lists are mandatory for DoD contracts. Any requirement relating to qualified products lists (QPL's) has not been adopted by SAE and is not part of this technical report.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)

Tel: 724-776-4970 (outside USA)

Fax: 724-776-0790

Email: custsvc@sae.org

SAE WEB ADDRESS:

<http://www.sae.org>

SAE AS20708/94

1. SCOPE:

1.1 This specification covers the detail requirements for 115 volt, 60 and 400 Hz, size 23 synchros (see 6.1).

2. APPLICABLE DOCUMENTS:

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

TT-I-558 Ink, Marking Stencil, Opaque, for Nonporous Surfaces (Metals, Glass, etc.)

Military

MIL-V-173 Varnish, Moisture-and-fungus resistant (For the Treatment of Communications, Electronic, and Associated Electrical Equipment)

MIL-S-20708 Synchros, General Specification for

STANDARDS

Military

MS 17186 Washer, Drive (Synchro)

MS 17187 Nut, Plain, Hexagon

MS 35275 Screw, Machine-drilled, Fillister Head, Slotted, Corrosion Resisting Steel, Passivated, UNC-2A

MS 35333 Washer, Lock, Flat-Internal Tooth

MS 35338 Washer, Lock-spring, Helical, Regular (Medium) Series (in./mm)

2.1 (Continued):

MS 51972 Nut, Plain, Hexagon-steel, Corrosion Resisting, 300 Series,
Passivated, UNF-2B

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS:

3.1 First article:

Synchros furnished under this specification shall be a product which has been tested and has passed the first article inspection specified in accordance with 4.2.

3.2 Design and construction:

Synchros furnished under this specification shall conform with the design, construction, and physical dimensions specified in Figure 1.

3.2.1 Housings: Not applicable.

3.2.2 Slip rings: Not applicable.

3.3 General requirements:

All requirements shall be in accordance with MIL-S-20708 except as otherwise specified herein. In case of conflict between the requirements of MIL-S-20708 and this specification, the requirements of this specification shall govern.

3.3.1 Altitude: Not applicable.

3.3.2 Vibration: Synchros shall withstand mechanical vibrations of 0.10 ± 0.02 inch amplitude up to 60 Hz perpendicular and parallel to the shaft axis for a period of 8 hours \pm 15 minutes without mechanical damage or loosening of parts, and without degradation in performance to the extent specified in MIL-S-20708 following conformance to the vibration requirement.

3.3.3 Shock: Synchros shall be capable of withstanding shock blows of 100 G in accordance with the low impact shock requirement of MIL-S-20708 where applicable. After testing, there shall be no damage or loosening of parts and synchros shall meet the performance requirements specified in MIL-S-20708 following low impact shock testing.

SAE AS20708/94

3.3.4 Ambient temperature: Synchros shall be capable of storage in ambients ranging from -62°C to 100°C. Synchros shall be capable of operation in ambient temperatures ranging from -55°C to 85°C. Synchros shall meet the applicable requirements in Tables I and II herein at the specified ambient temperatures of MIL-S-20708, except the high ambient temperature shall be 85°C in lieu of 125°C. Hereinafter throughout this specification all requirements specified at the high temperature, shall be made at 85°C.

3.3.5 Endurance: All synchros shall be capable of continuous operation for 1000 ± 10 hours without failure or undue wear. After testing, all synchros shall meet the applicable requirements of MIL-S-20708. The high ambient temperature shall be 85°C in lieu of 125°C.

3.4 Performance requirements:

The performance requirements shall be as specified in Tables I and II as applicable.

3.5 Part number identification:

Synchros listed in Tables I and II shall be identified by the following part numbers (see 6.2).

<u>Part No.</u>	<u>Type</u>	<u>Item Name</u>
7674818	23TX4	Synchro, Transmitter
7674819	23TR4	Synchro, Receiver
7674820	23CDX4	Synchro, Differential Transmitter
7674821	23CT4	Synchro, Control Transformer
7676354	23TX6	Synchro, Transmitter
7676355	23TR6	Synchro, Receiver
7676356	23CDX6	Synchro, Differential Transmitter
7676357	23CT6	Synchro, Control Transformer
7676359	23CX6	Synchro, Transmitter
7676360	23TDX6	Synchro, Differential Transmitter
7676906	23CX4	Synchro, Transmitter
7676963	23TDX4	Synchro, Differential Transmitter
8212762	23TX4A	Synchro, Transmitter
8212766	23TR4A	Synchro, Receiver
8212772	23CDX4A	Synchro, Differential Transmitter
8212775	23CT4A	Synchro, Control Transformer
8212778	23TX6A	Synchro, Transmitter
8212781	23TR6A	Synchro, Receiver
8212786	23CDX6A	Synchro, Differential Transmitter
8212789	23CT6A	Synchro, Control Transformer
8212794	23CX6A	Synchro, Transmitter
8212797	23TDX6A	Synchro, Differential Transmitter
8212801	23CX4A	Synchro, Transmitter
8212807	23TDX4A	Synchro, Differential Transmitter

TABLE I. Synchros, Torque System Types

Requirement	Unit	Tolerance	Types							
			TX6 TX6A	TDX6 TDX6A	TR6 TR6A	TX4 TX4A	TDX4 TDX4A	TR4 TR4A		
1/ Frequency	Hz	Nominal	60	60	60	400	400	400	400	
1/ Primary voltage	Volts	Nominal	115	90	115	115	115	90	115	
Primary current	Milliamps	Maximum	231	420	231	1040	1040	1210	1040	
Primary power	Watts	Maximum	6	13.5	6	9.36	9.36	10.2	9.36	
Transformation ratio		± 1%	0.783	1.154	0.783	0.783	0.783	1.154	0.783	
Electrical error	Minutes	Maximum	8	8	8	8	8	8	8	
Torque gradient	oz-in/deg	Minimum	0.12	0.03	0.12	0.12	0.12	0.16	0.12	
Receiver error	Minutes	Maximum			60				60	
Null voltage	Millivolts	Maximum	160		160	100	100		100	
Total			60		60	75	75		75	
Fundamental			0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Friction torque	oz./in.	Maximum	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Temperature rise	°C	Maximum	65	65	65	65	65	65	65	
Impedance	Ohms	R±15%+ j±10%								
Z _{ro}				100+j210						
Z _{so}				170+j52						
Z _{rs}										
Z _{ss}										
		Nominal	121+j28.3		121+j28.3	121+j28.3	7.3+j6.3	11+j94 9+j10	7.3+j6.3	

1/ See MIL-S-20708, Standard test voltage and frequency.

TABLE II. Synchros, Control System Types

Requirement	Unit	Tolerance	Types							
			CX6 CX6A	CDX6 CDX6A	CT6 CT6A	CX4 CX4A	CDX4 CDX4A	CT4 CT4A		
1/ Frequency	Hz	Nominal	60	60	60	400	400	400	400	
1/ Primary voltage	Volts	Nominal	115	90	90	115	90	90	90	
Primary current	Milliamperes	Maximum	83	112	22	264	297	297	7.7	
Primary power	Watts	Nominal	1.6	2.2	0.5	2.5	2.8	2.8	0.08	
Transformation ratio		$\pm 1\%$	0.783	1.154	0.735	0.783	1.154	1.154	0.735	
Electrical error	Minutes	Maximum	8	8	6	8	8	8	6	
Null voltage	Millivolts	Maximum								
Total			100	100	75	100	100	100	60	
Fundamental			75	75	60	75	50	50	30	
Friction torque	oz/in.	Maximum	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
(@-55°C)			0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Temperature rise	°C	Maximum	45	45	45	45	45	45	45	
Impedance	Ohms	R $\pm 20\%$								
Z _{ro}		j $\pm 15\%$	256+j1510	211+j757	1200+j3920	50.1+j544	41.4+j311	41.4+j311	1495+j11870	
Z _{so}				471+j127	1412+j389		36+j32.7	36+j32.7	675+j741	
Z _{rs}							19.3+j16.4	19.3+j16.4		
Z _{ss}			285+j55.5							

1/ See MIL-S-20708, Standard test voltage and frequency.

SAENORM.COM - Click to view the full PDF of SAE AS20708_94