

AS21220

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21220D AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21220D. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENTS RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

SAENORM.COM : Click to view the full PDF of as21220

THIRD ANGLE PROJECTION



ISSUED 1998-05

PREPARED BY THE AIRFRAME CONTROL BEARINGS GROUP

SAE The Engineering Society
For Advancing Mobility
INTERNATIONAL
Land Sea Air and Space®
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

BEARING, ROLLER, ROD END, INTERNAL THREAD,
SELF-ALIGNING, ANTI-FRICTION, AIRFRAME, HEAVY DUTY,
TYPE II, -67° TO 350°F, SEALED

AS21220
SHEET 1 OF 3

AS21220

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-B-8952.




TABLE I. DIMENSIONS AND LOADS

MS DASH NO.	ØA ±.005	B +.0000 -.0005	ØD +.000 -.050	E UNJF-3B THREAD	F ±.015	H +.000 -.015	J HEX FLATS ±.015	L ±.020	M ±.030	N CORNER CHAMFER ±.005	LIMIT LOAD RATING, LBS		RADIAL DYNAMIC LOAD RATING, LBS	NET WT LBS	
											W +.000 -.005	RADIAL AXIAL			
-4G	.420	.2500	1.080	.375-24	1.660	.360	.500	.810	.562		.500	2730	270	2270	.11
-5G	.560	.3125	1.410	.500-20	2.340	.460	.690	1.310	.750	.015	.687	4970	490	4120	.27
-6G	.660	.3750	1.660	.625-18	3.090	.550	.880	1.750	.938		.812	7910	790	6570	.53

1/ THESE BEARINGS ARE SELF-ALIGNING FOR 10° IN EITHER DIRECTION.

REQUIREMENTS

- MATERIAL: INNER RING AND ROLLERS: STEEL, E52100 PER FED-STD-66.
OUTER RING ROD END: STEEL, AISI/SAE 4620 PER AMS 6294 OR AISI-SAE 8620H PER AMS 6274 OR COMPOSITION III (9310) PER MIL-S-7393 OR E52100 PER FED-STD-66.
- LUBRICANT: MIL-G-81322 OR MIL-G-23827. ALL BEARINGS SHALL BE PACKED WITH GREASE CONFORMING TO MIL-G-81322 UNLESS OTHERWISE SPECIFIED. ALL BEARINGS SHALL BE FILLED 80% MINIMUM WITH GREASE. IF MIL-G-23827 IS REQUIRED, ADD THE LETTER "H" AFTER THE MS21220 DASH NUMBER. IF A LUBRICATION FITTING IS NOT DESIRED, DELETE THE CODE "G" AFTER THE MS21220 DASH NUMBER. MIL-G-23827 SHALL NOT BE USED FOR OPERATION WHERE TEMPERATURES EXCEED 250°F.