

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS
4730

AS21912

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21912G AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21912G. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

ANY MATERIAL RELATING TO QUALIFIED PRODUCT LISTS HAS NOT BEEN ADOPTED BY SAE. THIS MATERIAL WAS PART OF THE ORIGINAL MILITARY SPECIFICATION AND IS REPRINTED HERE FOR HISTORIC REFERENCE ONLY.

SAENORM.COM : Click to view the full PDF of as21912

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1998-03

PREPARED BY COMMITTEE G-3

PROCUREMENT SPECIFICATION MIL-F-18280



AEROSPACE STANDARD

TEE, FLARELESS TUBE WITH BULKHEAD ON RUN

AS21912
SHEET 1 OF 3

Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.


QUESTIONS REGARDING THIS DOCUMENT:
TO PLACE A DOCUMENT ORDER:

(724) 772-8510
(724) 776-4970

FAX: (724) 776-0243
Distributed under license from the IHS Archive

SAE WEB ADDRESS: <http://www.sae.org>

AS21912



DASH NO.	TUBE OD	THREAD T MIL-S-8879	H RAD	M +.047 -0	Q +.047 -0	U RAD	V	W APPROX	X APPROX	WT STEEL	LB ALUM	MAX TI
-2	1/8	.3125-24 UNJF-3A		1.313	.781		.313	.313	.188	.064	.023	.036
-3	3/16	.3750-24 UNJF-3A	.063	1.391	.906		.375	.375	.25C	.074	.026	.042
-4	1/4	.4375-20 UNJF-3A		1.500	.938	.063	.438	.375		.091	.033	.052
-5	5/16	.5000-20 UNJF-3A		1.531	1.031		.500	.469		.126	.048	.072
-6	3/8	.5625-18 UNJF-3A		1.688	1.063		.563	.500	.313	.155	.056	.089
-8	1/2	.7500-16 UNJF-3A	.094	1.969	1.313	.094	.750	.688	.438	.290	.112	.167
-10	5/8	.8750-14 UNJF-3A		2.250	1.500		.875	.781		.455	.166	.262
-12	3/4	1.0625-12 UNJ-3A		2.469	1.625	.125	1.063	.906	.500	.677	.245	.390
-16	1	1.3125-12 UNJ-3A		2.594	1.719		1.313	1.094	.625	.962	.342	.555
-20	1-1/4	1.6250-11 UNJ-3A	.125	2.875	2.000		1.625	1.313	.750	1.600	.635	.923
-24	1-1/2	1.8750-12 UNJ-3A		3.156	2.188	.188	1.875	1.500	.875			
-32	2	2.5000-13 UNJ-3A		3.750	2.375		2.563	2.031	1.094			

REQUIREMENTS:

- MATERIAL: CARBON STEEL - FORGINGS
ALUMINUM ALLOY - FORGINGS
CORROSION RESISTANT STEEL - FORGINGS
TITANIUM ALLOY - FORGINGS

SEE PROCUREMENT SPECIFICATION.

- FINISH: SEE PROCUREMENT SPECIFICATION.

NOTES:

- BREAK ALL SHARP EDGES AND REMOVE ALL BURRS AND SLIVERS.
- DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.016, ANGLES ±1/2°
- PART NUMBERS:
NO CODE LETTER IN PART NUMBER FOR CARBON STEEL.
ADD "D" IN PLACE OF DASH FOR ALUMINUM ALLOY (2014).
ADD "W" IN PLACE OF DASH FOR ALUMINUM ALLOY (7075).
ADD "J" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 304.
ADD "K" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 316.
ADD "T" AFTER DASH FOR TITANIUM ALLOY (6AL-4V).
ADD "R" AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 321.