

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS
4730

AS21914

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21914M AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21914M. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

ANY MATERIAL RELATING TO QUALIFIED PRODUCT LISTS HAS NOT BEEN ADOPTED BY SAE. THIS MATERIAL WAS PART OF THE ORIGINAL MILITARY SPECIFICATION AND IS REPRINTED HERE FOR HISTORIC REFERENCE ONLY.

SAENORM.COM : Click to view the full PDF of as21914

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1998-03

PREPARED BY COMMITTEE G-3

AEROSPACE STANDARD



CAP, PRESSURE SEAL, FLARELESS TUBE FITTING

AS21914
SHEET 1 OF 3

Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.

QUESTIONS REGARDING THIS DOCUMENT:
TO PLACE A DOCUMENT ORDER:


(724) 772-8510
(724) 776-4970

FAX: (724) 776-0243
Distributed under license from the IHS Archive


SAE WEB ADDRESS: <http://www.sae.org>

AS21914

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-F-18280.



CAP ASSEMBLY



DASH NO.	TUBING O.D.	T THREAD PER MIL-S-8879	A ±.010	B (REF)	C DIA ±.005	G DIA ±.010	H ±.010	L (REF)	P DIA	R	W DIA MIN
-2	1/8	.3125-24UNJF-3B	.600	.375	.256	-	-	.720	.047	.065	.033
-3	3/16	.3750-24UNJF-3B	.672	.438	.318	-	-	.767			
-4	1/4	.4375-20UNJF-3B	.745	.562	.371	.187	.600	.893		.087	
-5	5/16	.5000-20UNJF-3B	.845	.625	.434	.234	.700	.977	.078	.101	.055
-6	3/8	.5625-18UNJF-3B	.885	.688	.490	.297	.740	.965			
-8	1/2	.7500-16UNJF-3B	.935	.875	.670	.406	.790	1.077			
-10	5/8	.8750-14UNJF-3B	1.062	1.000	.786	.500	.917	1.210	.093	.101	.066
-12	3/4	1.0625-12UNJ-3B	1.082	1.250	.960	.656	.937	1.208			
-16	1	1.3125-12UNJ-3B	1.218	1.500	1.210	.906	1.073	1.189			
-20	1-1/4	1.6250-12UNJ-3B	1.193	2.000	1.470	1.093	1.048	1.288	.093	.101	.066
-24	1-1/2	1.8750-12UNJ-3B	1.271	2.250	1.719	1.343	1.125	1.305			