

SAE-AS21923

ADOPTION NOTICE

SAE-AS21923, "Adapter, Flareless Tube, Bulkhead and Universal to Flared Tube", was adopted on 14 August 1998, for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, Naval Air Warfare Center Aircraft Division, Code 414100B120-3, Highway 547, Lakehurst, NJ 08733-5100. DoD activities may obtain copies of this standard from the DODSSP, Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094. The private sector and other government agencies may purchase copies from SAE, 400 Commonwealth Drive, Warrendale, PA 15096.

SAE-AS21923 should be used instead of MS21923.

Custodians:

Army - AV
 Navy - AS
 Air Force - 99

Adopting Activity
 Navy - AS

(Project 4730-1019)

SAENORM.COM : Click to view the full PDF of as21923

FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Submitted for recognition as an American National Standard

FEDERAL SUPPLY CLASS
4730

AS21923

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21923C, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21923C, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.


THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

SAENORM.COM : Click to view the full PDF of as21923

THIRD ANGLE PROJECTION



ISSUED 1998-08

PREPARED BY SAE COMMITTEE G-3

PROCUREMENT SPECIFICATION: MIL-F-18280

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

ADAPTER, FLARELESS TUBE, BULKHEAD AND UNIVERSAL
TO FLARED TUBE

AS21923
SHEET 1 OF 3


Copyright 1998 Society of Automotive Engineers, Inc.
All rights reserved.

Printed in the U.S.A.

QUESTIONS REGARDING THIS DOCUMENT: (724) 772-8510
TO PLACE A DOCUMENT ORDER: (724) 776-4970

SAE WEB ADDRESS: <http://www.sae.org>
Distributed under license from the IHS Archive
FAX: (724) 776-0730

AS21923



DASH NO.	TUBE OD	THREAD T MIL-S-8879	H	(a) E REF	D ±1/32	WT LB MAX		
						STEEL	ALUMINUM ALLOY	TI ALLOY
-2	1/8	.3125-24 UNJF-3A	1-17/32	9/16	15/16	.032	.012	.018
-3	3/16	.3750-24 UNJF-3A	1- 5/8	5/8	THRU	.047	.017	.027
-4	1/4	.4375-20 UNJF-3A	1- 3/4	11/16	1-3/32	.062	.023	.035
-5	5/16	.5000-20 UNJF-3A	1-25/32	3/4	THRU	.082	.031	.047
-6	3/8	.5625-18 UNJF-3A	1-57/64	13/16		.094	.036	.054
-8	1/2	.7500-16 UNJF-3A	2-1/8	1	1-11/32	.172	.063	.099
-10	5/8	.8750-14 UNJF-3A	2-3/8	1-1/8	1-15/32	.244	.089	.140
-12	3/4	1.0625-12 UNJ-3A	2-21/32	1-3/8		.391	.143	.225
-16	1	1.3125-12 UNJ-3A	2-11/16	1-5/8		.533	.195	.307
-20	1-1/4	1.6250-12 UNJ-3A	2-47/64	1-7/8	1-19/32	.784	.288	.452
-24	1-1/2	1.8750-12 UNJ-3A	2-7/8	2-1/8		.972	.356	.560
-32	2	2.5000-12 UNJ-3A	3-9/16	2-3/4	2			

(a) FOR HEX DIMENSIONS AND TOLERANCES, USE MS33515, STYLE E.
 (b) C'DRILL IS ONLY FROM THE END OF THE LARGER DRILL. AT THE OPTION OF THE MANUFACTURER, THE SMALLER DIA MAY BE DRILLED THROUGH THE FITTING FROM END TO END.
 (c) PARTS WITH THREADS IN ACCORDANCE WITH MIL-S-8879 OF THE SAME THREAD SIZE, PITCH AND TOLERANCE CLASS ARE ACCEPTABLE FOR PROCUREMENT UNTIL 1 JULY 1991. BUT PARTS WITH MIL-S-8879 THREADS WILL NOT BE PROCURED THEREAFTER. EXISTING STOCKS ARE TO BE USED UNTIL EXHAUSTED.

1. MATERIAL: CARBON STEEL - BARS
 ALUMINUM ALLOY - BARS
 CORROSION RESISTANT STEEL - BARS
 TITANIUM ALLOY - BARS
- } SEE PROCUREMENT SPECIFICATION

2. FINISH: SEE PROCUREMENT SPECIFICATION.
3. BREAK ALL SHARP EDGES AND REMOVE ALL BURRS AND SLIVERS.
4. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/64, ANGLES ±1/2°.
5. PART NUMBERS:

NO CODE LETTER IN PART NUMBER FOR CARBON STEEL.
 ADD D IN PLACE OF DASH FOR ALUMINUM ALLOY (2024)
 ADD W IN PLACE OF DASH FOR ALUMINUM ALLOY (7075)
 ADD C AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 302, 303, 304, 316 OR 321.
 ADD J IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 304.
 ADD K IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 316.
 ADD S AFTER DASH NUMBER FOR CORROSION RESISTANT STEEL, TYPE 304L AND 347. PARTS ARE NOT TO BE MANUFACTURED FROM TYPE 304L AFTER 27 JUNE 1969.
 ADD T AFTER DASH NUMBER FOR TITANIUM ALLOY (6AL-4V)



AEROSPACE STANDARD

ADAPTER, FLARELESS TUBE, BULKHEAD AND UNIVERSAL TO FLARED TUBE

AS21923
SHEET 2 OF 3