

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS21938D AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS21938D. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

ANY MATERIAL RELATING TO QUALIFIED PRODUCT LISTS HAS NOT BEEN ADOPTED BY SAE. THIS MATERIAL WAS PART OF THE ORIGINAL MILITARY SPECIFICATION AND IS REPRINTED HERE FOR HISTORIC REFERENCE ONLY.

SAENORM.COM : Click to view the full PDF of as21938

THIRD ANGLE PROJECTION



ISSUED 1998-05 REAFFIRMED 2004-04

AS21938

SAE Technical Standards Board Rules provide that: This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user. SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

PREPARED BY COMMITTEE G-3

SAE Aerospace
An SAE International Group


AEROSPACE STANDARD

BOLT, CLUSTER FITTING, SINGLE PORT
FLARELESS

AS21938
SHEET 1 OF 3

AS21938

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL-F-18280.



LOW FLOW SIZE DASH NUMBER	TUBE OD	THREAD S MIL-S-8879	THREAD T MIL-S-8879	A REF	B	C ±.062	D +.000 -.015	E ±.062	F ±.003	H HEX	LB	WT MAX
-3L	3/16	.3750-24 UNJF-3A	.4375-20 UNJF-3A	1.438	2.172	-----	.621	1.568	.125	.621 .628		.012
-4L	1/4	.4375-20 UNJF-3A	.4375-20 UNJF-3A	1.438	2.235	-----	.684	1.653	.187	.684 .691		.014
-5L	5/16	.5000-20 UNJF-3A	.4375-20 UNJF-3A	1.438	2.297	-----	.746	1.715	.234	.746 .753		.015
-6L	3/8	.5625-18 UNJF-3A	.4375-20 UNJF-3A	1.438	2.344	.663	.871	1.750	.234	.871 .878		.018
-8L	1/2	.7500-16 UNJF-3A	.4375-20 UNJF-3A	1.438	2.437	.656	.996	1.844	.234	.996 1.003		.023
HIGH FLOW SIZE DASH NUMBER	TUBE OD	THREAD S MIL-S-8879	THREAD T MIL-S-8879	A REF	B	C ±.062	D +.000 -.015	E ±.062	F ±.003	H HEX	LB	WT MAX
-6H	3/8	.5625-18 UNJF-3A	.5625-18 UNJF-3A	1.688	2.594	-----	.871	1.913	.297	.871 .878		.016
-8H	1/2	.7500-16 UNJF-3A	.5625-18 UNJF-3A	1.688	2.687	-----	.996	2.030	.422	.996 1.003		.025
-10H	5/8	.8750-14 UNJF-3A	.5625-18 UNJF-3A	1.688	2.750	.812	1.121	2.055	.422	1.121 1.128		.040

INACTIVE FOR NEW DESIGN AFTER 31 DEC: 1990

REQUIREMENTS:

1. MATERIAL: ALUMINUM ALLOY - BARS. SEE PROCUREMENT SPECIFICATION.
2. FINISH: SEE PROCUREMENT SPECIFICATION. SURFACE FINISH IN ACCORDANCE WITH ANSI B46.1. UNLESS OTHERWISE NOTED, ALL OUTSIDE MACHINED SURFACES SHALL BE 125 MICROINCHES Ra, AND ALL INSIDE SURFACES SHALL BE 250 MICROINCHES Ra PER ANSI B46.1.

NOTES:

1. FITTINGS SHALL BE FREE FROM ALL HANGING BURRS AND SLIVERS.
2. DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS -.010, ANGLES -1/2.