

REV.  
A

AS24405


FEDERAL SUPPLY CLASS  
4730

RATIONALE

CHANGED THE PROCUREMENT SPECIFICATION FROM MIL-F-18280 TO AS18280, DELETED THE PREAMBLE NOTICE ON PAGE 1, ADDED PRI-QPL REQUIREMENT, ADDED TABLE 2 AND UPDATED FORMAT.

NOTICE


THE INITIAL PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS24405.



- (b) FOR HEX DIMENSIONS AND TOLERANCES, SEE AS4395 DESIGN STANDARD STYLE E.
- (c) MARK ON TWO OPPOSITE HEX FLATS WITH AN EQUILATERAL TRIANGLE TO DENOTE PRECISION TYPE AND MARKING SHALL BE DEPRESSED .025 + .010.

FIGURE 1 - ADAPTER, FLARELESS TUBE TO FLARED TUBE, PRECISION TYPE

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS24405A>



CUSTODIAN: G-3/G-3B

PROCUREMENT SPECIFICATION: AS18280 /9/



AEROSPACE STANDARD

(R) ADAPTER, FLARELESS TUBE TO FLARED TUBE PRECISION TYPE

AS24405  
SHEET 1 OF 3

REV.  
A

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1999-07 REAFFIRMED 2004-04 REVISED 2014-06

TABLE 1 - DIMENSIONS

DASH NO. /5/ TUBE OD	THREAD T AS8879 CLASS 3A	E (REF) (b)	N ±.016	S ±.031	Q +.010 -.000	WT LB/EA APPROX			
						CRES	AL ALLOY	TI ALLOY	
-3	.188	.3750-24 UNJF	.625	1.156	thru	.093	.044	.015	.025
-4	.250	.4375-20 UNJF	.688	1.266	.563	.109	.053	.019	.030
-5	.313	.5000-20 UNJF	.750	1.266	thru	.109	.060	.021	.034
-6	.375	.5625-18 UNJF	.813	1.281	thru	.125	.073	.026	.042
-8	.500	.7500-16 UNJF	1.000	1.469	.688	.140	.133	.046	.076
-10	.625	.8750-14 UNJF	1.125	1.688	.781	.140	.182	.065	.105
-12	.750	1.0625-12 UNJ	1.375	1.938	.875	.156	.305	.109	.175
-16	1.000	1.3125-12 UNJ	1.625	1.969	.844	.156	.414	.145	.328
-20	1.250	1.6250-12 UNJ	1.875	2.000	.875	.156	.625	.209	.360
-24	1.500	1.8750-12 UNF	2.125	2.156	.875	.156	.820	.280	.473
-32	2.000	2.5000-12 UNJ	2.750	2.469	.906	.156	1.596	.510	.920

NOTES:

NOTICE

THIS DOCUMENT REFERENCES A PART WHICH CONTAINS CADMIUM AS PLATING MATERIAL. CONSULT LOCAL OFFICIALS IF YOU HAVE QUESTIONS CONCERNING CADMIUM USE.

1. MATERIALS: SEE PROCUREMENT SPECIFICATION.

- ALLOY STEEL
- ALUMINUM ALLOY
- CORROSION RESISTANT STEEL
- TITANIUM ALLOY

2. FINISH: SEE PROCUREMENT SPECIFICATION.

3. DIMENSIONS ARE IN INCHES. UNLESS OTHERWISE SPECIFIED TOLERANCES: DECIMALS ±.015, ANGLES ±0°30'.

4. BREAK EDGES .003 TO .015 UNLESS OTHERWISE SPECIFIED.

/5/ PART NUMBERS:

CODE LETTER "-" IN PART NUMBER FOR 4130 ALLOY STEEL IS REPLACED BY CODE LETTER "F" SEE TABLE 2 /A/  
 ADD "F" IN PLACE OF "-" FOR 4130 ALLOY STEEL IS REPLACEMENT FOR CODE "-"  
 ADD "V(SIZE)P" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (15-5PH), CADMIUM PLATED  
 ADD "V" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (15-5PH), NOT CADMIUM PLATED  
 ADD "D" IN PLACE OF DASH FOR ALUMINUM ALLOY (2024) IS INACTIVE FOR NEW DESIGN SEE TABLE 2 /C/  
 ADD "W" IN PLACE OF DASH FOR ALUMINUM ALLOY (7075)  
 ADD "J" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (TYPE 304)  
 ADD "K" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (TYPE 316)  
 ADD "R" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (TYPE 321)  
 ADD "S" IN PLACE OF DASH FOR CORROSION RESISTANT STEEL (TYPE 347) IS REPLACED BY CODE "R" (TYPE 321) SEE TABLE 2 /D/  
 ADD "T" AFTER DASH NUMBER FOR TITANIUM ALLY (6AL-4V)

EXAMPLES OF PART NUMBERS:

- MS24405-4 ADAPTER, .250 TUBING, "-" CODE FOR 4130 ALLOY STEEL IS REPLACED SEE TABLE 2 /A/
- MS24405F4 ADAPTER, .250 TUBING, 4130 ALLOY STEEL
- MS24405V4P ADAPTER, .250 TUBING, CRES (15-5PH), CADMIUM PLATED
- MS24405V4 ADAPTER, .250 TUBING, CRES (15-5PH), NOT CADMIUM PLATED
- MS24405D4 ADAPTER, .250 TUBING, ALUMINUM ALLOY (2024) IS REPLACED SEE TABLE 2 /C/
- MS24405W4 ADAPTER, .250 TUBING, ALUMINUM ALLOY (7075)
- MS24405J4 ADAPTER, .250 TUBING, (TYPE 304)
- MS24405K4 ADAPTER, .250 TUBING, (TYPE 316)
- MS24405R4 ADAPTER, .250 TUBING, (TYPE 321)
- MS24405S4 ADAPTER, .250 TUBING, (TYPE 347) IS REPLACED BY CODE "R" SEE TABLE 2 /D/
- MS24405-4T ADAPTER, .250 TUBING, TITANIUM ALLOY (6AL-4V)

	<b>AEROSPACE STANDARD</b>	<b>AS24405</b> SHEET 2 OF 3	<b>REV.</b> <b>A</b>
	(R) ADAPTER, FLARELESS TUBE TO FLARED TUBE PRECISION TYPE		