

REV.
B

AS3074

FEDERAL SUPPLY CLASS





TABLE 1A

AS IDENT NUMBER	NOM TUBE OD in	NOM TUBE OD (mm)	A in	A (mm)	B in	B (mm)	C in	C (mm)
AS3074-02	.125	3.18	.025-.085	0.64-2.15	.083-.113	2.11- 2.87	.257- .267	6.53- 6.78
AS3074-03	.188	4.76	.020-.080	0.51-2.03	.146- .176	3.71- 4.47	.320- .330	8.13- 8.38
AS3074-04	.250	6.35	.045-.105	1.15-2.66	.193- .223	4.91- 5.66	.373- .383	9.48- 9.72
AS3074-05	.312	7.92	.045-.105	1.15-2.66	.255- .285	6.48- 7.23	.436- .446	11.08-11.32
AS3074-06	.375	9.52	.055-.115	1.40-2.92	.318- .348	8.08- 8.83	.492- .502	12.50-12.75
AS3074-07	.438	11.11	.045-.105	1.15-2.66	.380- .410	9.66-10.41	.554- .564	14.08-14.32
AS3074-08	.500	12.70	.065-.125	1.66-3.17	.426- .456	10.83-11.58	.672- .682	17.07-17.32
AS3074-09	.562	14.29	.070-.130	1.78-3.30	.473- .503	12.02-12.77	.734- .744	18.65-18.89
AS3074-10	.625	15.88	.075-.135	1.91-3.42	.539- .569	13.70-14.45	.788- .798	20.02-20.26
AS3074-11	.688	17.46	.095-.155	2.42-3.93	.602- .632	15.30-16.05	.896- .906	22.76-23.01
AS3074-12	.750	19.05	.095-.155	2.42-3.93	.664- .694	16.87-17.62	.962- .972	24.44-24.68
AS3074-14	.875	22.23	.095-.155	2.42-3.93	.787- .817	19.99-20.75	1.087-1.097	27.61-27.86
AS3074-16	1.000	25.40	.095-.155	2.42-3.93	.913- .943	23.20-23.95	1.212-1.222	30.79-31.03
AS3074-18	1.125	28.58	.095-.155	2.42-3.93	1.022-1.052	25.96-26.72	1.402-1.412	35.62-35.86
AS3074-20	1.250	31.75	.095-.155	2.42-3.93	1.147-1.177	29.14-29.89	1.525-1.535	38.74-38.98
AS3074-24	1.500	38.10	.095-.155	2.42-3.93	1.381-1.411	35.08-35.83	1.775-1.785	45.09-45.33
AS3074-28	1.750	44.45	.095-.155	2.42-3.93	1.646-1.676	41.81-42.57	2.150-2.160	54.61-54.86
AS3074-32	2.000	50.80	.095-.155	2.42-3.93	1.880-1.910	47.76-48.51	2.400-2.410	60.96-61.21

INACTIVE - See Note 8.

THIRD ANGLE PROJECTION



PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD
(R) GASKET - 37° FLARED TUBE FITTING,
NICKEL, AMS 5553

AS3074
SHEET 1 OF 3

REV. B

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

ISSUED 1974-04 REVISED 1997-11 NONCURRENT 1998-02 REAFFIRMED NONCURRENT 2003-10

REV.
B

AS3074

TABLE 1B

AS IDENT NUMBER	D in	D (mm)	E in	E (mm)	F MAX REF in	F MAX REF (mm)
AS3074-02	.025-.055	0.64-1.39	.245- .255	6.23- 6.47	.184	4.67
AS3074-03	.020-.050	0.51-1.27	.307- .317	7.80- 8.05	.173	4.39
AS3074-04	.045-.075	1.15-1.90	.359- .369	9.12- 9.37	.203	5.15
AS3074-05	.045-.075	1.15-1.90	.421- .431	10.70-10.94	.203	5.15
AS3074-06	.055-.085	1.40-2.15	.476- .486	12.10-12.34	.207	5.25
AS3074-07	.045-.075	1.15-1.90	.539- .549	13.70-13.94	.189	4.80
AS3074-08	.065-.095	1.66-2.41	.654- .664	16.62-16.86	.262	6.65
AS3074-09	.070-.100	1.78-2.54	.716- .726	18.19-18.44	.262	6.65
AS3074-10	.075-.105	1.91-2.66	.767- .777	19.49-19.73	.262	6.65
AS3074-11	.095-.125	2.42-3.17	.875- .885	22.23-22.47	.325	8.25
AS3074-12	.095-.125	2.42-3.17	.938- .948	23.83-24.07	.325	8.25
AS3074-14	.095-.125	2.42-3.17	1.062-1.072	26.98-27.22	.325	8.25
AS3074-16	.095-.125	2.42-3.17	1.188-1.198	30.18-30.42	.325	8.25
AS3074-18	.095-.125	2.42-3.17	1.375-1.385	34.93-35.17	.351	8.91
AS3074-20	.095-.125	2.42-3.17	1.501-1.511	38.13-38.37	.376	9.55
AS3074-24	.095-.125	2.42-3.17	1.750-1.760	44.45-44.70	.387	9.82
AS3074-28	.095-.125	2.42-3.17	2.125-2.135	53.98-54.22	.460	11.68
AS3074-32	.095-.125	2.42-3.17	2.375-2.385	60.33-60.57	.463	11.76

TABLE 1C

AS IDENT NUMBER	R in	R (mm)	APPROX MASS lb/100	APPROX MASS kg/100	VENDOR NUMBER
AS3074-02	.345- .405	8.77-10.28	.033	0.015	APSON-02
AS3074-03	.345- .405	8.77-10.28	.042	0.019	APSON-03
AS3074-04	.370- .430	9.40-10.92	.059	0.027	APSON-04
AS3074-05	.370- .430	9.40-10.92	.083	0.038	APSON-05
AS3074-06	.370- .430	9.40-10.92	.115	0.052	APSON-06
AS3074-07	.370- .430	9.40-10.92	.102	0.047	APSON-07
AS3074-08	.470- .530	11.94-13.46	.184	0.083	APSON-08
AS3074-09	.470- .530	11.94-13.46	.260	0.119	APSON-09
AS3074-10	.470- .530	11.94-13.46	.349	0.158	APSON-10
AS3074-11	.520- .580	13.21-14.73	.425	0.194	APSON-11
AS3074-12	.570- .630	14.48-16.00	.534	0.242	APSON-12
AS3074-14	.620- .680	15.75-17.27	.612	0.280	APSON-14
AS3074-16	.720- .780	18.29-19.81	.652	0.296	APSON-16
AS3074-18	.720- .780	18.29-19.81	.817	0.373	APSON-18
AS3074-20	.720- .780	18.29-19.81	.971	0.440	APSON-20
AS3074-24	.844- .904	21.44-22.96	1.151	0.522	APSON-24
AS3074-28	1.470-1.530	37.34-38.86	1.790	0.812	APSON-28
AS3074-32	1.470-1.530	37.34-38.86	2.129	0.966	APSON-32

NOTES:



SAE Aerospace
An SAE International Group

AEROSPACE STANDARD
(R) GASKET - 37° FLARED TUBE FITTING,
NICKEL, AMS 5553

AS3074
SHEET 2 OF 3

REV.
B