

RATIONALE

DOCUMENT COMPLETELY REVISED THREAD SPEC CALLOUT CORRECTED AND DOCUMENT BROUGHT UP TO DATE.

REV.
A

AS3104

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1 - BOLT

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS3104A>



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7477



AEROSPACE STANDARD

(R) BOLT, MACHINE - HEXAGON HEAD, PD SHANK, CRES AMS5731, .5000-20 UNJF-3A

AS3104
SHEET 1 OF 3

REV. A

TABLE 1 - DIMENSIONS

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3104 -14	1.438	.030	.188	10.44
AS3104 -15	1.500	.090	.250	10.75
AS3104 -16	1.562	.152	.312	11.06
AS3104 -17	1.625	.215	.375	11.37
AS3104 -18	1.688	.278	.438	11.67
AS3104 -19	1.750	.340	.500	11.98
AS3104 -20	1.812	.402	.562	12.29
AS3104 -21	1.875	.465	.625	12.59
AS3104 -22	1.938	.528	.688	12.90
AS3104 -23	2.000	.590	.750	13.21
AS3104 -24	2.125	.715	.875	13.82
AS3104 -25	2.250	.840	1.000	14.44
AS3104 -26	2.375	.965	1.125	15.05
AS3104 -27	2.500	1.090	1.250	15.67
AS3104 -28	2.625	1.215	1.375	16.28
AS3104 -29	2.750	1.340	1.500	16.90
AS3104 -30	2.875	1.465	1.625	17.51
AS3104 -31	3.000	1.590	1.750	18.12
AS3104 -32	3.125	1.715	1.875	18.74
AS3104 -33	3.250	1.840	2.000	19.35
AS3104 -34	3.375	1.965	2.125	19.97
AS3104 -35	3.500	2.090	2.250	20.58
AS3104 -36	3.625	2.215	2.375	21.20
AS3104 -37	3.750	2.340	2.500	21.81
AS3104 -38	3.875	2.465	2.625	22.43
AS3104 -39	4.000	2.590	2.750	23.04
AS3104 -40	4.125	2.715	2.875	23.66
AS3104 -41	4.250	2.840	3.000	24.27
AS3104 -42	4.375	2.965	3.125	24.88
AS3104 -43	4.500	3.090	3.250	22.50
AS3104 -44	4.625	3.125	3.375	26.11
AS3104 -45	4.750	3.340	3.500	26.73
AS3104 -46	4.875	3.465	3.625	27.34
AS3104 -47	5.000	3.590	3.750	27.96
AS3104 -48	5.125	3.715	3.875	28.57
AS3104 -49	5.250	3.840	4.000	29.19
AS3104 -50	5.375	3.965	4.125	29.80
AS3104 -51	5.500	4.090	4.250	30.42
AS3104 -52	5.625	4.215	4.375	31.03
AS3104 -53	5.750	4.340	4.500	31.65
AS3104 -54	5.785	4.465	4.625	32.26
AS3104 -55	6.000	4.590	4.750	32.88

FOR SHORT SCREWS THREADED TO HEAD SEE AS9434.

	AEROSPACE STANDARD	AS3104 SHEET 2 OF 3	REV. A
	(R) BOLT, MACHINE - HEXAGON HEAD, PD SHANK, CRES AMS5731, .5000-20 UNJF-3A		