



**TABLE 1**

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3114 - 11	.802 - .822	.100	.182	1.08
AS3114 - 12	.865 - .885	.163	.245	1.12
AS3114 - 13	.928 - .948	.286	.308	1.16
AS3114 - 14	.990 - 1.010	.288	.370	1.20
AS3114 - 15	1.052 - 1.072	.350	.432	1.24
AS3114 - 16	1.115 - 1.135	.413	.495	1.28
AS3114 - 17	1.178 - 1.198	.476	.558	1.32
AS3114 - 18	1.240 - 1.260	.538	.620	1.36
AS3114 - 19	1.302 - 1.322	.600	.682	1.40
AS3114 - 20	1.365 - 1.385	.663	.745	1.44
AS3114 - 21	1.428 - 1.448	.726	.808	1.48
AS3114 - 22	1.490 - 1.510	.788	.870	1.53
AS3114 - 23	1.552 - 1.572	.850	.932	1.57
AS3114 - 24	1.615 - 1.635	.913	.995	1.61
AS3114 - 25	1.678 - 1.698	.976	1.058	1.65
AS3114 - 26	1.740 - 1.760	1.038	1.120	1.69
AS3114 - 27	1.802 - 1.822	1.100	1.182	1.73
AS3114 - 28	1.865 - 1.885	1.163	1.245	1.77
AS3114 - 29	1.928 - 1.948	1.226	1.308	1.81
AS3114 - 30	1.990 - 2.010	1.288	1.370	1.85
AS3114 - 31	2.115 - 2.135	1.413	1.495	1.93
AS3114 - 32	2.240 - 2.260	1.538	1.620	2.01
AS3114 - 33	2.365 - 2.385	1.663	1.745	2.10
AS3114 - 34	2.490 - 2.510	1.788	1.870	2.18
AS3114 - 35	2.615 - 2.635	1.913	1.995	2.26
AS3114 - 36	2.740 - 2.760	2.038	2.120	2.34
AS3114 - 37	2.865 - 2.885	2.163	2.245	2.42
AS3114 - 38	2.990 - 3.010	2.288	2.370	2.50
AS3114 - 39	3.115 - 3.135	2.413	2.495	2.58
AS3114 - 40	3.240 - 3.260	2.538	2.620	2.67
AS3114 - 41	3.365 - 3.385	2.663	2.745	2.75
AS3114 - 42	3.490 - 3.510	2.788	2.870	2.83
AS3114 - 43	3.615 - 3.635	2.913	2.995	2.91
AS3114 - 44	3.740 - 3.760	3.038	3.120	2.99
AS3114 - 45	3.865 - 3.885	3.163	3.245	3.07

FOR SHORT BOLTS THREADED TO HEAD SEE AS9583.

SAENORM.COM - Click to view the PDF of AS3114a