

AS31481

FEDERAL SUPPLY CLASS
5935

NOTICE


THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS3148D, NOTICE 2, AMENDMENT 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS3148D, NOTICE 2, AMENDMENT 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

SAENORM.COM : Click to view the full PDF of as31481

THIRD ANGLE PROJECTION



CUSTODIAN: SAE AE-8/AE-8C1

PROCUREMENT SPECIFICATION: MIL-C-81703

SAEAerospace
An SAE International Group

AEROSPACE STANDARD

CONNECTOR, PLUG, ELECTRIC,
CRIMP TYPE, LANYARD, PUSH-PULL COUPLING,
SERIES 2 (CLASS E AND J)

AS31481
SHEET 1 OF 3

ISSUED 2004-06

Copyright 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

CONNECTOR, PLUG, ELECTRIC,
CRIMP TYPE, LANYARD, PUSH-PULL COUPLING,
SERIES 2 (CLASS E AND J)

DEVIATIONS IN PITCH
LESS THAN 1/2 INCH. TOLERANCE: 1/2 INCH.
TOLERANCE: 1/2 INCH.

12072

COUPLING RODS AND BALLS ARE SHOWN IN THE ENLARGED POSITION FOR CLARITY THIS POSITION SHALL ONLY BE POSSIBLE WHEN EXHIBITED TO THE RECFRPLC.

THE NORMAL DIMENSIONED POSITION THE FOLLOWING IS TRUE

A. THE VISUAL LOCK INDICATOR IS NOT IN VIEW

B. THE BALLS ARE RELEASED WHEN "E" MEAS. EQUALS "C".

9. THE DAILY ARE RELEASED WHEN "E" WITH COMMA "E".

EXAMPLE OF PART NO.

工部局

[illegible]

LAWYARD DETAIL

