

ADOPTION NOTICE

SAE-AS3232, "BOLT, TEE HEAD - AMS 5708, CHAMFERED, .1900-32 UNJF-3A", was adopted on 11-JUL-84 for use by the Department of Defense (DoD). Proposed changes by DoD activities must be submitted to the DoD Adopting Activity: Commander, Defense Supply Center Philadelphia, ATTN: DSCP-ITAA, 700 Robbins Avenue, Philadelphia, PA 19111-5096. Copies of this document may be purchased from the Society of Automotive Engineers 400 Commonwealth Drive Warrendale, Pennsylvania, United States, 15096-0001. <http://www.sae.org/>

Custodians:

Navy - AS
Air Force - 11
DLA - IS

Adopting Activity:

DLA - IS

SAENORM.COM : Click to view the full PDF of SAE-AS3232

FSC 5306

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

AS3232

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."
SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.





FIGURE 1

SAENORM.COM : Click to view the full PDF of AS3232

THIRD ANGLE PROJECTION



PREPARED BY SAE COMMITTEE E-25, GENERAL STANDARDS FOR AEROSPACE PROPULSION SYSTEMS

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space
INTERNATIONAL
400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE STANDARD

BOLT, TEE HEAD - AMS 5708, CHAMFERED,
.1900-32 UNJF-3A

AS3232
SHEET 1 OF 3

ISSUED 1980-07 REAFFIRMED 1999-03

TABLE 1

PART NUMBER	L		G MIN		K MAX		APPROX MASS	
	INCH	mm	INCH	mm	INCH	mm	LB/100	kg/100
AS3232-12	.865-.885	21.98-22.47	.123	3.13	.245	6.22	.97	0.440
AS3232-13	.928-.948	23.58-24.07	.186	4.73	.308	7.82	1.01	0.450
AS3232-14	.990-1.010	25.15-25.65	.248	6.30	.370	9.39	1.06	0.481
AS3232-15	1.052-1.072	26.73-27.22	.310	7.88	.432	10.97	1.10	0.499
AS3232-16	1.115-1.135	28.33-28.82	.373	9.48	.495	12.57	1.14	0.517
AS3232-17	1.178-1.198	29.93-30.42	.436	11.08	.558	14.17	1.16	0.535
AS3232-18	1.240-1.260	31.50-32.00	.498	12.65	.620	15.74	1.23	0.558
AS3232-19	1.302-1.322	33.08-33.57	.560	14.23	.682	17.32	1.27	0.576
AS3232-20	1.365-1.385	34.68-35.17	.623	15.83	.745	18.92	1.31	0.594
AS3232-21	1.428-1.448	36.28-36.77	.686	17.43	.808	20.52	1.35	0.612
AS3232-22	1.490-1.510	37.85-38.35	.748	19.00	.870	22.09	1.39	0.630
AS3232-23	1.552-1.572	39.43-39.92	.810	20.58	.932	23.67	1.43	0.649
AS3232-24	1.615-1.635	41.03-41.52	.873	22.18	.995	25.27	1.47	0.667
AS3232-25	1.678-1.698	42.63-43.12	.936	23.78	1.058	26.87	1.52	0.689
AS3232-26	1.740-1.760	44.20-44.70	.998	25.35	1.120	28.44	1.56	0.708
AS3232-27	1.802-1.822	45.78-46.27	1.060	26.93	1.182	30.02	1.60	0.726
AS3232-28	1.865-1.885	47.38-47.87	1.123	28.53	1.245	31.62	1.64	0.744
AS3232-29	1.928-1.948	48.98-49.47	1.186	30.13	1.308	33.22	1.68	0.762
AS3232-30	1.990-2.010	50.55-51.05	1.248	31.70	1.370	34.79	1.72	0.780
AS3232-31	2.115-2.135	53.73-54.22	1.373	34.88	1.495	37.97	1.80	0.816
AS3232-32	2.240-2.260	56.90-57.40	1.498	38.05	1.620	41.14	1.88	0.853
AS3232-33	2.365-2.385	60.08-60.57	1.623	41.23	1.745	44.32	1.97	0.894
AS3232-34	2.490-2.510	63.25-63.75	1.748	44.40	1.870	47.49	2.05	0.930
AS3232-35	2.615-2.635	66.43-66.92	1.873	47.58	1.995	50.67	2.13	0.996
AS3232-36	2.740-2.760	69.60-70.10	1.998	50.75	2.120	53.84	2.22	1.007
AS3232-37	2.865-2.885	72.78-73.27	2.123	53.93	2.245	57.02	2.31	1.048
AS3232-38	2.990-3.010	75.95-76.45	2.248	57.10	2.370	60.19	2.39	1.084
AS3232-39	3.115-3.135	79.13-79.62	2.373	60.28	2.495	63.37	2.48	1.125
AS3232-40	3.240-3.260	82.30-82.80	2.498	63.45	2.620	66.54	2.56	1.161
AS3232-41	3.365-3.385	85.48-85.97	2.623	66.63	2.745	69.72	2.64	1.197
AS3232-42	3.490-3.510	88.65-89.15	2.748	69.80	2.870	72.89	2.73	1.238
AS3232-43	3.615-3.635	91.83-92.32	2.873	72.98	2.995	76.07	2.81	1.275
AS3232-44	3.740-3.760	95.00-95.50	2.998	76.15	3.120	79.24	2.89	1.311
AS3232-45	3.865-3.885	98.18-98.67	3.123	79.33	3.245	82.42	2.97	1.347

AS3232