

REV.
C

AS3415™

RATIONALE

UPDATE TO ASME Y14.5-2018. REVISE ACROSS POINTS TO AS1132. UPDATE LEAD THREAD CHAMFER TO AS1132. REVISE HEAD TO SHANK FILLET TO CR. IN NOTE 2, ADD "COMPOSITION SIMILAR TO" TO UNS. IN TITLE BLOCK, CORRECT UNS FROM "UNS NO7718" TO "UNS N07718."





FIGURE 1 - BOLT

For more information on this standard, visit
<https://www.sae.org/standards/content/AS3415C/>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7467 /3/



AEROSPACE STANDARD

BOLT, MACHINE - HEXAGON HEAD, PD SHANK
UNS N07718, 185 KSI MIN, .3125-24 UNJF-3A
(STRESS RUPTURE RESISTANT)

AS3415™
SHEET 1 OF 3

REV.
C

SAE Executive Standards Committee Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

TABLE 1 - DIMENSIONS L, G, K, AND APPROX MASS

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3415-04	.490-.510	.025	.108	1.94
AS3415-05	.552-.572	.025	.108	2.06
AS3415-06	.615-.635	.025	.108	2.17
AS3415-07	.678-.698	.025	.108	2.29
AS3415-08	.740-.760	.025	.108	2.40
AS3415-09	.802-.822	.025	.108	2.51
AS3415-10	.865-.885	.025	.108	2.63
AS3415-11	.928-.948	.025	.108	2.74
AS3415-12	.990-1.010	.025	.125	2.86
AS3415-13	1.052-1.072	.044	.188	2.97
AS3415-14	1.115-1.135	.107	.250	3.08
AS3415-15	1.178-1.198	.170	.312	3.21
AS3415-16	1.240-1.260	.232	.375	3.32
AS3415-17	1.302-1.322	.294	.438	3.45
AS3415-18	1.365-1.385	.357	.500	3.56
AS3415-19	1.428-1.448	.420	.562	3.68
AS3415-20	1.490-1.510	.482	.625	3.80
AS3415-21	1.552-1.572	.544	.688	3.92
AS3415-22	1.615-1.635	.607	.750	4.04
AS3415-23	1.678-1.698	.670	.812	4.15
AS3415-24	1.740-1.760	.732	.875	4.27
AS3415-25	1.802-1.822	.794	.938	4.39
AS3415-26	1.865-1.885	.857	1.000	4.51
AS3415-27	1.928-1.948	.920	1.062	4.63
AS3415-28	1.990-2.010	.982	1.125	4.75
AS3415-29	2.115-2.135	1.107	1.250	4.99
AS3415-30	2.240-2.260	1.232	1.375	5.22
AS3415-31	2.365-2.385	1.357	1.500	5.45
AS3415-32	2.490-2.510	1.482	1.625	5.69
AS3415-33	2.615-2.635	1.607	1.750	5.93
AS3415-34	2.740-2.760	1.732	1.875	6.17
AS3415-35	2.865-2.885	1.857	2.000	6.41
AS3415-36	2.990-3.010	1.982	2.125	6.64
AS3415-37	3.115-3.135	2.107	2.250	6.88
AS3415-38	3.240-3.260	2.232	2.375	7.12
AS3415-39	3.365-3.385	2.357	2.500	7.35
AS3415-40	3.490-3.510	2.482	2.625	7.59
AS3415-41	3.615-3.635	2.607	2.750	7.82
AS3415-42	3.740-3.760	2.732	2.875	8.06
AS3415-43	3.865-3.885	2.857	3.000	8.30
AS3415-44	3.990-4.010	2.982	3.125	8.54
AS3415-45	4.115-4.135	3.107	3.250	8.78
AS3415-46	4.240-4.260	3.232	3.375	9.01
AS3415-47	4.365-4.385	3.357	3.500	9.25
AS3415-48	4.490-4.510	3.482	3.625	9.48
AS3415-49	4.615-4.635	3.607	3.750	9.72
AS3415-50	4.740-4.760	3.732	3.875	9.96
AS3415-51	4.865-4.885	3.857	4.000	10.19
AS3415-52	4.990-5.010	3.982	4.125	10.43
AS3415-53	5.115-5.135	4.107	4.250	10.67

SAENORM.COM - Click to view the full PDF of as3415c