

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user." SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

**REV.
A**

SAE AS39029/104

FEDERAL SUPPLY CLASS
5935

RATIONALE


CANCELLATION IS REQUIRED BASED ON NO KNOWN USAGE OF THIS PRODUCT AND THE PREPARING ACTIVITY FOR THE APPLICABLE CONNECTORS HAS REQUESTED THIS DETAIL SHEET BE CANCELLED.

CANCELLATION NOTICE

THIS DOCUMENT HAS BEEN DECLARED "CANCELLED" AS OF AUGUST 2011. BY THIS ACTION, THIS DOCUMENT WILL REMAIN LISTED IN THE NUMERICAL SECTION OF THE AEROSPACE STANDARDS INDEX.

SAENORM.COM : Click to view the full PDF of as39029_104a

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS39029/104A>



CUSTODIAN: AE-8C1

ISSUED 2000-07 CANCELLED 2011-08

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD
CONTACTS, ELECTRICAL CONNECTOR,
CONCENTRIC TWINAX, PIN, SHIELDED, SIZE 8
(FOR MIL-C-28840)

SAE AS39029/104
SHEET 1 OF 8

**REV.
A**

NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-39029/104 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-39029/104. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

SAENORM.COM : Click to view the full PDF of as39029_104a

 An SAE International Group	AEROSPACE STANDARD	SAE AS39029/104 SHEET 2 OF 8	REV. A
	CONTACTS, ELECTRICAL CONNECTOR, CONCENTRIC TWINAX, PIN, SHIELDED, SIZE 8 (FOR MIL-C-28840)		

REQUIREMENTS:

Qualification:

Contacts shall comply with the reliability assurance provisions of MIL-STD-790 as specified in MIL-C-28840.

Design and construction:

Dimensions and configurations: See figures 1 through 3 and table I.

TABLE I. DESIGN CHARACTERISTICS.

BIN code	Color bands			Contact cavity size	Cable accommodated	Type	Class
	1st	2nd	3rd				
556	Green	Green	Blue	8	M17/176-00002	D	B

Assembly procedure: Manufacturer's recommended assembly instructions shall be shipped with unit package.

Electrical:

Low signal level contact resistance (center and intermediate contacts only): See table II.

Contact resistance: See table III.

Frequency: 0 to 20 MHz (operating frequency range).

Voltage rating: 500 volts rms maximum; working voltage at sea level, 125 volts rms maximum at 70,000 feet.

TABLE II. LOW SIGNAL LEVEL CONTACT, RESISTANCE (CENTER AND INTERMEDIATE CONTACTS ONLY).

BIN code	Cable accommodated	Maximum contact resistance (milliohms)	
		Initial	After conditioning
556	M17/176-00002	55	66

TABLE III. CONTACT RESISTANCE.

BIN code	Contact	Cable accommodated	Test current (amperes)	Maximum voltage drop (millivolts)		
				+25°C, +3°C, 0°C		+175°C, +3°C, 0°C
				Initial	After conditioning	After conditioning
556	Center	M17/176-00002	1.0	55	66	94
556	Intermediate	M17/176-00002	1.0	55	66	94
556	Outer	M17/176-00002	12.0	75	90	128

Dielectric withstanding voltage: Shall be as specified in table IV.

TABLE IV. DIELECTRIC WITHSTANDING VOLTAGE.

Contacts	Altitude	Test voltages ac rms
Center to intermediate	Sea level	1,000
Intermediate to outer	Sea level	500

Mating contact: Shall be in accordance with MIL-C-39029/105.

Mechanical:

Contact engagement and separation force (socket contacts only): The engagement depth shall be a minimum of 0.7 of the minimum socket bored depth. The test pins shall be in accordance with MS3197, except the diameters shall be as specified in table V. Provision for clearance hole on outer contact. Test pins shall be provided.

TABLE V. CONTACT ENGAGEMENT AND SEPARATION FORCE.

Test pin diameter (inch)	Minimum separation force (ounces)		Maximum engagement force (ounces)		Maximum average engagement force
	Initial	After conditioning	Initial	After conditioning	
.1090 +.0000 -.0001	NA	NA	18	22	NA
.1110 +.0001 -.0000	0.5	0.4	NA	NA	NA

Crimp tensile strength (center, intermediate, and outer contact crimp joint): See table VI.

TABLE VI. CRIMP TENSILE STRENGTH (AT AMBIENT).

BIN code	Cable accommodated	Axial load (pounds, minimum)		
		Center contact	Intermediate contact	Outer contact
556	M17/176-00002	8	8	25

Vibration: Method 2005 of MIL-STD-1344, test condition V. The following details shall apply:

- Use the vibration envelope shown on figure 4.
- Vibration: To be conducted at standard test conditions.
- Duration: Eight hours in the longitudinal direction and 8 hours in a perpendicular direction (16 hours).