

Contacts, Electrical Connector, Pin,  
Crimp Removable (for MIL-DTL-26482 Series 1,  
MIL-DTL-26500 and MIL-DTL-26518 Connectors)

THIS AMENDMENT FORMS A PART OF AS39029/31A, DATED 2007-11

1. PRESENT REQUIREMENT: (TABLE 4, PART NUMBERS, PAGE 4)

AS39029 Part Number	BIN Code	Superseding Part Number(s)	AS39029 Part Number	BIN Code	Superseding Part Number(s)
M39029/31-223	223	MS3192-20-20A	M39029/31-234	234	MS3192-12-12A
M39029/31-224	224	MS3192-20-20C4	M39029/31-235	235	MS24254-12P
M39029/31-225	225	MS3192-20-20C1	M39029/31-236	236	MS3192-12-12C4
M39029/31-226	226	MS3192-20-20C2	M39029/31-237	237	MS3192-12-12C1
M39029/31-227	227	MS3192-20-20C3	M39029/31-238	238	MS3192-12-12C2
M39029/31-228	228	MS3192-16-16A	M39029/31-239	239	MS3192-12-12C3
M39029/31-229	229	MS24254-16P	M39029/31-240	240	MS3192A20-20A
M39029/31-230	230	MS3192-16-16C4	M39029/31-448	448	MS39029/31-20-20
M39029/31-231	231	MS3192-16-16C1	M39029/31-627	627	M39029/31-241 MS24254-20P
M39029/31-232	232	MS3192-16-16C2			
M39029/31-233	233	MS3192-16-16C3			
M39029/31-234	234	MS3192-12-12A			

CHANGE REQUIREMENT: (TABLE 4, PART NUMBERS, PAGE 4)

AS39029 Part Number	BIN Code	Superseded Part Number(s)	AS39029 Part Number	BIN Code	Superseded Part Number(s)
M39029/31-223	223	MS3192-20-20A	M39029/31-234	234	MS3192-12-12A
M39029/31-224	224	MS3192-20-20C4	M39029/31-235	235	MS24254-12P
M39029/31-225	225	MS3192-20-20C1	M39029/31-236	236	MS3192-12-12C4
M39029/31-226	226	MS3192-20-20C2	M39029/31-237	237	MS3192-12-12C1
M39029/31-227	227	MS3192-20-20C3	M39029/31-238	238	MS3192-12-12C2
M39029/31-228	228	MS3192-16-16A	M39029/31-239	239	MS3192-12-12C3
M39029/31-229	229	MS24254-16P	M39029/31-240	240	MS3192A20-20A
M39029/31-230	230	MS3192-16-16C4	M39029/31-448	448	M39029/31-20-20
M39029/31-231	231	MS3192-16-16C1	M39029/31-627	627	M39029/31-241 MS24254-20P
M39029/31-232	232	MS3192-16-16C2			
M39029/31-233	233	MS3192-16-16C3			
M39029/31-234	234	MS3192-12-12A			

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2009 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: CustomerService@sae.org  
SAE WEB ADDRESS: http://www.sae.org

**SAE values your input. To provide feedback on this Technical Report, please visit**  
[http://www.sae.org/technical/standards/AS39029/31A\\_A2](http://www.sae.org/technical/standards/AS39029/31A_A2)